

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Butyl acetate (when possessing a flashpoint at or below 80° F.).	Colorless limpid liquid with fruity odor. Flashpoint variable. Vapors heavier than air. Immiscible with water. Lighter than water.	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pta. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Butyraldehyde.....	<i>Colorless liquid. Flashpoint 80° F. Boiling point 169° F. Vapors about 2½ times heavier than air. Immiscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC (ICC-12A, 12B) not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-5) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Carbon disulfide (disulfide).	<i>A heavy, clear, colorless to yellow liquid having a very offensive odor. Highly inflammable. Protect from all sources of heat. Vapor is capable of igniting without presence of naked light, as from the temperature of a warm steam pipe. Mixtures of vapor and air are highly explosive over a range of 1% to 80% in air. Self-ignition occurs at about 215° F. in air. Boiling point about 115° F. Vapor is poisonous. Immiscible with water. Keep cool. Stow well away from oxygen and oxidizing materials (yellow label).</i>	Red.....	Stowage: "On deck protected." Outside containers: Steel barrels or drums: (ICC-5, 5A) not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A) not over 8 gal. cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Case oil.....			See under proper shipping name as: "Benzene," "Benzine," "Gasoline," etc.
Cement, leather..... (When possessing a flashpoint at or below 80° F.)	<i>These cements are chemical compounds of various ingredients such as: Asphalt with petroleum distillate; cellulose nitrate in acetone; bituminous asphalt and mineral oil; raw rubber solution and gasoline; etc., all possessing similar characteristics and hazards. Vapors highly inflammable and explosive when mixed in correct proportions with air. Sustained inhalation of vapors in unventilated compartments is dangerous.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D), WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Authorized for stowage "On deck in open" only. Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below." Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC not over 55 gal. cap. Wooden boxes, WIMO (ICC-16X) not over 10 gal. cap. Authorized only for viscous liquids: Portable tank (ICC-62 aluminum), not over 500 gal. cap.
Cement, adhesive, N.O.S.		Red	
Cement, container, liquid		Red	
Cement, linoleum		Red	
Cement, liquid, N. O. S.		Red	
Cement, pyroxylin		Red	
Cement, roofing, liquid		Red	
Cement, rubber		Red	
(When possessing a flashpoint at or below 80° F.)			
Cement, tile		Red	
Cement, wallboard		Red	
Coating solution		Red	

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
See under proper shipping name as: "Benzene," "Benzine," "Gasoline," etc.	See under proper shipping name as: "Benzene," "Benzine," "Gasoline," etc.	See under proper shipping name as: "Benzene," "Benzine," "Gasoline," etc.
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible."	Ferry stowage (AA)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC not over 55 gal. cap. Wooden boxes, WIMO (ICC-16X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Cigar and cigarette lighter fluid.	A mixture of several of the lighter constituents of petroleum. Flashpoint variable depending on mixture used, but less than 80° F. Immiscible with water.	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Coal tar distillate----- Coal tar oil. (When possessing a flashpoint at or below 80° F.)	Distillates of coal tar. The lighter distillates are highly inflammable and will consist of benzene, toluene and xylene. Properties and hazards similar to "Coal tar naphtha," which see below.	Red-----	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STO, not over 55 gal. cap. Wooden boxes, WIMC (ICC-16X) not over 10 gal. cap.
Coal tar naphtha----- Naphtha solvent. (When possessing a flashpoint at or below 80° F., but not less than 20° F.)	Immiscible with water. Mixtures of small amounts of benzene and toluene with xylene. The crude is a dark straw colored liquid and the refined is a water white liquid. Flashpoint ranges between 60° F. and 77° F. Mixtures of vapor in air are explosive over a range of 1.3% to 8%. Vapors are heavier than air. Vapors are poisonous and suffocating. Immiscible with water.	Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-6M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-6M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G), not over 110 gal. cap. (ICC-6M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STO not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STO, not over 55 gal. cap. Wooden boxes, WIMC (ICC-16X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Collodion.....	<i>Solution of tetranitrocellulose in ether, alcohol or other solvent. Pale yellow liquid. Flashpoint approximately 0° F. Immiscible with water. Keep cool.</i>	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside container: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below". Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Compounds, cleaning, liquid.	<i>May consist of volatile inflammable solvents having low flashpoints.</i>	Red-----	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible."
Carbon remover, liquid.		Red.	"Under deck away from heat."
Cleaning fluid or liquid.		Red.	Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap.
Compounds, type-cleaning, liquid.		Red.	Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap.
Compounds, vulcanizing, liquid.		Red.	Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap.
Eradicators, paint or grease, liquid. (When possessing a flashpoint at or below 50° F.)			Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Compounds, lacquer, paint, or varnish, etc., removing, reducing or thinning, liquid. (When possessing a flashpoint at or below 80° F.)	Compounds which through solvent or detergent action remove old paint from surfaces. Exceptionally slow-drying thinners used with pyroxylin base lacquer or enamels to retard speed of drying. Clear liquid solvents and diluents for the reduction of primers, surfacers, and enamels to proper working consistencies.	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from beat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIO (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIO (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-61) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for liquids having a flashpoint above 20° F.: Steel barrels or drums: (ICC-17E, 17H) STC, not over 55 gal. cap. (ICC-37E) STC, not over 8½ gal. cap. Wooden barrels or kegs (ICC-10A, 10B, 10C) not over 50 gal. cap. Fiberboard boxes (ICC-12E), WIMC, not over 110 lb. gr. wt. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.
Compounds, enamel		Red.	
Lacquer removing, reducing and thinning compounds.		Red.	
Paint, lacquer and varnish removing, reducing or thinning compounds.		Red.	
Varnish remover or reducer.		Red.	
Varnish thinning compounds. (When possessing a flashpoint at or below 80° F.)		Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-1 A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for liquids having a flashpoint above 20° F.: Steel barrels or drums: (ICC-17E, 17H) STC, not over 55 gal. cap. (ICC-37E) STC, not over 8½ gal. cap. Wooden barrels or kegs (ICC-10A, 10B, 10C) not over 50 gal. cap. Fiberboard boxes (ICC-12E) WIMC, not over 110 lb. gr. wt. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Compounds, polishing, liquid (when possessing a flashpoint at or below 80° F.).	Flashpoint variable	Red	See: "Polishes, metal, stove, furniture and wood, liquid."
Compounds, tree or weed killing, liquid.			Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums: (ICC-17X) STC not over 55 gal. cap. Wooden boxes: (ICC-15X) WIMC not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
See: "Polishes, metal, stove, furniture and wood, liquid."	See: "Polishes, metal, stove, furniture and wood, liquid."	See: "Polishes, metal, stove, furniture and wood, liquid."
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 5M, 6A, 6B, 6C) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 30 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 30 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes: (ICC-15A, 15B, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Authorized only for export shipments: Steel barrels or drums: (ICC-17X) STC not over 55 gal. cap. Wooden boxes: (ICC-15X) WIMC not over 10 gal. can.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Crotonaldehyde.....	<i>This material is in the form of a clear and almost colorless liquid, having a vapor extremely irritating to the eyes, nose and throat. Easily detected odor. Flashpoint about 55° F. Vapors about 2½ times heavier than air. Immiscible with water.</i>	Red.....	Stowage: "On deck in open." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 10 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B), not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Crude oil, petroleum (when possessing a flashpoint at or below 80° F.).	Crude petroleum in its natural state or which has been subject only to natural weathering or settling and not blended with any other product. A heavy, oily liquid, having color varying from green to almost black. It usually has a disagreeable odor, and varies in inflammability according to percentage of more volatile ingredients. Immiscible with water.	Red-----	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMO (ICC-15X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted-----	Not permitted-----	Ferry stowage (BB). Outside containers: Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden boxes, WIMO (ICC-15X) not over 10 gal. cap. Fiber drum (ICC-21B) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Cyclohexane.....	<i>A clear, volatile liquid having a pungent odor. Flashpoint below 80° F. Forms inflammable or explosive mixtures with air. Immiscible with water. Stow well away from all sources of heat.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Cyclopentane.....	<i>Colorless liquid having organic odor. Moderately volatile. Flashpoint below 80° F. Forms inflammable and explosive mixture with air. Immiscible with water. Stow well away from all sources of heat.</i>	Red.	
Cyclopentane, methyl...	<i>Colorless liquid having organic odor. Moderately volatile. Flashpoint below 80° F. Forms inflammable or explosive mixtures with air. Immiscible with water. Stow well away from all sources of heat.</i>	Red.	

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Diethylamine.....	<i>Clear, colorless liquid.</i> <i>Flashpoint below 0° F.</i> <i>Miscible with water.</i>	Red.....	Stowage: "On deck in open." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized or stowage "On deck" and "First deck below"; Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes WIMC (ICC-15X) not over 10 gal. cap.
Dimethyl sulfide.....	<i>A clear, volatile liquid having an offensive disagreeable odor.</i> <i>Will evolve sulfur dioxide gas in a fire.</i> <i>Boils at approximately 97° F.</i> <i>Immiscible with water.</i>	Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Dimethylamine aqueous solution.	An aqueous solution of an inflammable gas having a fishy, ammoniacal odor. Flashpoint of 25% solution 32° F. Boiling point 45° F. Properties similar to above.	Red	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Monomethylamine aqueous solution.		Red.	
Trimethylamine aqueous solution.		Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard Boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Drugs, chemicals, medicines, or cosmetics, N. O. S. A unit substance or a compound classified as an inflammable liquid in accordance with the definition contained herein, when prepared, packed and offered to the trade as drugs, chemicals, medicines, or cosmetics. In quantity exceeding 1 pint or 16 ounces by weight, in glass or earthenware containers, or 1 quart or 32 ounces by weight in inside metal containers. The following substances shall not be shipped under this designation: Acrolein. Carbon bisulfide (disulfide). Ethyl chloride. Ethyl trichlorosilane. Ethylene oxide. Inflammable liquids (flammable liquids) which are also corrosive liquids or oxidizing materials under these regulations. Lithium aluminum hydride (ethereal). Nickel carbonyl. Pentaborane. Spirits of nitroglycerin in excess of 1 percent by weight. Trichlorosilane. Zinc ethyl. Ethylene imine, inhibited. Zirconium, metallic, solutions or mixtures thereof, liquid. Amyl mercaptan. Butyl mercaptan. Ethyl mercaptan. Aliphatic mercaptan mixtures. Isopropyl mercaptan. Propyl mercaptan. Vinyl trichlorosilane.		Red.	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 10 gal. cap. Wooden boxes WIC, (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC, (ICC-12A, 12B) not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-61) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMO (ICC-15X) not over 10 gal. cap. Containers authorized only for liquids having a flashpoint above 20° F. Steel barrels or drums (ICC-17E, 17H) STC, not over 55 gal. cap. Wooden barrels or kegs (ICC-10B) not over 50 gal. cap. Fiberboard boxes, WIMO (ICC-12E) not over 110 lb. gr. wt.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: (Authorized only for liquids having a flashpoint above 20° F.) Steel barrels or drums: (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC, not over 10 gal. cap. Wooden boxes WIC, (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC, (ICC-12A, 12B) not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA). Outside containers: (Authorized only for liquids having a flashpoint above 20° F.) Steel barrels or drums: (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC, not over 10 gal. cap. Wooden boxes WIC, (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC, (ICC-12A, 12B) not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 10 gal. cap. Wooden boxes WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC, (ICC-12A, 12B) not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes WIMO (ICC-15X) not over 10 gal. cap. Containers authorized only for liquids having a flashpoint above 20° F. Steel barrels or drums (ICC-17E, 17H) STC, not over 55 gal. cap. Wooden barrels or kegs (ICC-10B) not over 50 gal. cap. Fiberboard boxes, WIMO (ICC-12E) not over 110 lb. gr. wt.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ether	Colorless, volatile liquid, pleasant aromatic odor. Suffocating and poisonous. The vapor of ether mixed with air is explosive over a very wide range of 1.8% to 18%. Vapor is 2.5 times heavier than air and will ignite at a considerable distance from the source of leakage. Flashpoint: -42° F. Boiling point about 96° F. Immiscible with water. Keep cool.	Red	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 5 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Ether, ethyl (sulfuric)	Characteristic properties and cautions similar to "Ether," see above.	Red.	
Ethyl methyl ether	Characteristic properties and cautions similar to "Ether," see above.	Red.	

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5B) not over 30 lb. net wt. (ICC-17C, 17E) STC, not over 30 lb. net wt. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Fiber drum (ICC-21B) WIC ICC-2S, ICC-2SL, not over 5 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. NOTE: Total number of one or both type packages shall not exceed ten (10) on any voyage.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5B) not over 30 lb. net wt. (ICC-17C, 17E) STC, not over 30 lb. net wt. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Fiber drum (ICC-21B) WIC ICC-2S, ICC-2SL, not over 5 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. NOTE: Total number of one or both type packages shall not exceed ten (10) on any voyage.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5B) not over 30 lb. net wt. (ICC-17C, 17E) STC, not over 30 lb. net wt. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Fiber drum (ICC-21B) WIC ICC-2S, ICC-2SL, not over 5 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. NOTE: Total number of one or both type packages shall not exceed ten (10) on any voyage.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethyl acetate.....	<i>Colorless, volatile liquid having a characteristic fruity odor. Vapors are 3 times heavier than air and form an explosive mixture within a range of 2½% to 11% in air. Flashpoint at or about 24° F. Boiling point 170° F. Immiscible with water. Keep cool.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 16C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMO not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethyl chloride	Colorless, volatile liquid. Gas at temperatures above 54° F. Anesthetic. Vapors in low concentrations will be suffocating. Flashpoint about -37° F. Boiling point about 54° F. Vapors when mixed with air are explosive over a range of 3.5% to 18%. Immiscible with water. Keep cool.	Red	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums (ICC-5A) not over 33 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A) not over 16 gal. cap. Fiberboard boxes, WIC (ICC-12B) not over 65 lb. gr. wt. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Ethyl formate	Colorless inflammable liquid. Vapors when mixed with air are explosive over a range of 3.5% to 16.5%, and are about 2½ times heavier than air. Flashpoint about 10° F. Boiling point 130° F. Soluble in water. Keep cool.	Red	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums, (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 16 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted	Not permitted	Not permitted.
Not permitted	Not permitted	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethyl methyl ketone. Methyl ethyl ketone. Methyl vinyl ketone, inhibited. NOTE: Methyl vinyl ketone, inhibited, in a glass or metal container not over 4 fluid ounces each, packed in a strong wooden or fiberboard box, is exempt from specification packaging, marking other than name of contents, and labeling requirements. Ethyl nitrate (nitric ether).	Colorless liquid, acetone-like odor. Sustained inhalation of vapors in unventilated compartments is dangerous. Vapors are about $2\frac{1}{2}$ times heavier than air and form an explosive mixture within a range of 2% to 12% in air. Flashpoint approximately 30° F. Miscible with water. Colorless, inflammable liquid, pleasant odor and sweet taste. Vapors are more than 3 times heavier than air and will form an explosive mixture with a lower limit of 3.8% in air. Sustained inhalation of vapors in unventilated compartments is dangerous. Flashpoint approximately 50° F. Immiscible with water.	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.	Not permitted.	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethyl nitrite (Nitrous ether).	Yellowish liquid, aromatic odor... Exceedingly volatile. Vapors are about 3 times heavier than air and form an explosive mixture within a range of 5% to 60% in air. Flashpoint about -31° F. Boiling point 61.6° F. Spontaneously decomposes at 194° F. Immiscible with water. Keep cool. Stow well away from all sources of heat.	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5Q, 5M) not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-28, not over 55 gal. cap. Aluminum barrels or drums (ICC-42B, 42C, 42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Ethyl trichlorosilane. Methyl trichlorosilane. Vinyl trichlorosilane. Dimethyl dichlorosilane. Ethyl dichlorosilane. Trimethyl chlorosilane.	Colorless liquids with acrid odor... Evokes white fumes when exposed to moist air. React violently with water to evolve heat and white, acrid fumes. Fumes extremely corrosive. May form explosive mixtures with air. Flashpoints below 80° F. Handle carefully to avoid damage to containers and exposure of contents to air.	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C) not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-5F) not over 11 gal. cap. (ICC-17H, 37A) STC, with inside glass containers not over 1 gal. cap., not over 55 gal. total cap. Wooden boxes, WIC (ICC-15A, 15B) not over 65 lb. gr. wt. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethylene dichloride.....	Colorless, oily liquid, pleasant chloroform-like color. Anesthetic vapors in low concentrations will be suffocating. Vapors are $3\frac{1}{2}$ times heavier than air and form an explosive mixture within a range of 8% to 16% in air. Flashpoint 70°F . Immiscible with water.	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-61) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Dichlorethylene.....		Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ethylene imine, inhibited.	<i>Oily volatile liquid, strongly alkaline. Vapors very irritating to the eyes. Vapors heavier than air. Flash point below 80° F. Miscible with water. Keep cool.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Wooden boxes (ICC-15A, 15B) WIC not exceeding 5 pints cap. Wooden boxes (ICC-15A, 15B, 15C) WIC ICC-37B metal drum not over 5 gal. cap. Metal barrels or drums (ICC-6A, 6B, 6C, 6J) WIC ICC-17E metal drum not over 30 gal. cap. Authorized only for ethylene imine, inhibited, stowage "On deck" and "First deck below": Tank cars complying with ICC regulations (trainships only).
Propylene imine, inhibited	Similar characteristics and hazards as given for ethylene imine.	Red.	
Ethylene oxide.....	<i>A colorless, highly volatile liquid with ether-like odor. Anesthetic vapors even in low concentrations will be suffocating. Vapors are 1½ times heavier than air and form an explosive mixture within a range of 3% to 30% in air. Flashpoint below 20° F. Boiling point, 51° F. Miscible with water. Keep cool.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums (ICC-5F) lagged, not over 61 gal. cap. Drums marked "Keep this end up." Wooden boxes (ICC-15A, 15B, 15C, 16A) WIC, not over 9 lb. net wt. Fiberboard boxes (ICC-12B) WIC, not over 9 lb. net wt. Cylinders as prescribed for any compressed gas except acetylene. NOTE: Ethylene oxide may also be carried in strong incombustible nonspecification outside containers. WIC complying with ICC regulations, not over 100 grams net wt.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Gas drips, hydrocarbon--	Liquid condensate of gas----- Has odor of illuminating gas. Flashpoint variable but usually low. Immiscible with water.	Red-----	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat."
Gasoline----- Permitted shipping names for export only: Essence. Gasoline. Motor fuel. Motor spirit. Petrol. Benzine. Gasolina. Nafta.	Derivative of crude petroleum--- Vapor is 3 to 4 times heavier than air and when mixed with air is explosive over a range of 1.4% to 8%. Flashpoint less than 0° F. Immiscible with water and will float on surface.	Red.	Outside containers: Steel barrels or drums: ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. ICC-5M) not over 55 gal. cap. ICC-17C) STC, not over 55 gal. cap. ICC-17E) STC, not over 55 gal. cap. ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: ICC-42B, 42C) not over 110 gal. cap. ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC ICC-11A, 11B) not over 10 gal. cap. Wooden boxes, WIC ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes: ICC-12A, 12B) WIC not over 65 lb. gr. wt. ICC-12B) WIC ICC-2F not over 5 gal. total cap. Fiber or plywood drums ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks ICC-51) not over 20, 01 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC ICC-15X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
NOTE: Shall not be accepted for transportation on board passenger vessels or passenger-carrying ferry vessels except such fuel as is contained within the fuel tanks of motor vehicles for use as a source of motive power for their own propulsion on and off the vessel, or for auxiliary equipment when such motor vehicles are being transported on board such vessels.		

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Heptane.....	<i>Colorless, volatile liquid having organic odor. Forms inflammable or explosive mixtures with air. Flashpoint about 55° F. Boiling point about 208° F. Immiscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37F) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Hexane.....	<i>Colorless, extremely volatile liquid having organic odor. Forms inflammable or explosive mixtures with air. Flashpoint below 0° F. Boiling point about 166° F. Immiscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-28, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Inflammable liquids, N. O. S. Flammable liquids, N. O. S.	May be any liquid classifying as an inflammable liquid in accordance with the definitions contained in these regulations, provided such inflammable liquid is not otherwise specified by name in these regulations. Flashpoint variable, may be less than 0° F.	Red	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: (a) Flammable liquids with flashpoint 20° F. or below and having vapor pressure (Reid test) not over 16 p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass not over 9 pts. cap. each, not over 480 lbs. gr. wt. Aluminum barrels or drums (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B), WIC not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lbs. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC not over 10 gal. cap. (b) Flammable liquids with flashpoint above 20° F. to 80° F. and having vapor pressure (Reid test) not over 16 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6K) stainless steel not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: (a) Flammable liquids with flashpoint above 20° F. to 80° F. and having vapor pressure (Reid test) not over 16 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H) STC not over 55 gal. cap. (ICC-17K) stainless steel not over 55 gal. cap. (ICC-17H, 37A) WIC of glass not over 9 pts. cap. each, not over 480 lbs. gr. wt. (ICC-37P) NRC not over 5 gal. cap. (ICC-6D, 37M (NRC)) WIC ICC-2SL not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC not over 65 lbs. gr. wt. Fiber or plywood drums, (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum, (ICC-21C) WIC ICC-2S, 2SL not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA).----- Outside containers: (a) Flammable liquids with flashpoint above 20° F. to 80° F. and having vapor pressure (Reid test) not over 16 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H) STC not over 55 gal. cap. (ICC-17K) stainless steel not over 55 gal. cap. (ICC-17H, 37A) WIC of glass not over 9 pts. cap. each, not over 480 lbs. gr. wt. (ICC-37P) NRC not over 5 gal. cap. (ICC-6D, 37M (NRC)) WIC ICC-2SL not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes, (ICC-12A, 12B) WIC not over 65 lbs. gr. wt. Fiber or plywood drums, (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum, (ICC-21C) WIC ICC-2S, 2SL not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB).----- Outside containers: (a) Flammable liquids with flashpoint 20° F. or below and having vapor pressure (Reid test) not over 16 p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. (ICC-17E) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass not over 9 pts. cap. each, not over 480 lbs. gr. wt. Aluminum barrels or drums (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC not over 65 lbs. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC not over 10 gal. cap. (b) Flammable liquids with flashpoint above 20° F. to 80° F. and having vapor pressure (Reid test) not over 16 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-17H) STC not over 55 gal. cap. (ICC-6K) stainless steel not over 55 gal. cap. (ICC-37P) NRC not over 5 gal. cap. (ICC-6D, 37M (NRC)) WIC ICC-2SL not over 55 gal. cap. Wooden barrels or kegs: (ICC-10B) not over 50 gal. cap. Fiberboard boxes: (ICC-12E) WIMC not over 65 lbs. gr. wt. Fiber drum: (ICC-21C) WIC ICC-2S, 2SL not over 55 gal. cap. (c) Inflammable liquids the vapor pressure of which exceeds 16 p.s.i.a. at 100° F., but does not exceed 27 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-17C) STC not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Fiberboard boxes: (ICC-12B) WIC not over 65 lbs. gross weight.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Inflammable liquids, N. O. S.—Continued Flammable liquids, N. O. S.—Continued			Steel barrels or drums—Con. (ICC-17H, 37A) WIC of glass not over 9 pts. cap. each, not over 480 lbs. gr. wt. (ICC-17H) not over 55 gal. cap. (ICC-37P) NRC not over 5 gal. cap. (ICC-6D, 37M) NRC, WIC ICC-28L, not over 55 gal. cap. Aluminum barrels or drums (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC not over 65 lb. gr. wt. (ICC-12E) WIMC not over 65 lb. gr. wt. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. (ICC-21C) WIC ICC-28, 28L not over 30 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lbs. gr. wt. Authorized for stowage "On deck deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC not over 10 gal. cap. (e) Inflammable liquids the vapor pressure of which exceeds 16 lbs. p.s.i.a. at 100° F., but does not exceed 27 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC not over 55 gal. cap. Wooden barrels or kegs: (ICC-11A, 11B) WIC not over 16 gal. cap. Fiberboard boxes: (ICC-12B) WIC not over 65 lbs. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC not over 10 gal. total cap. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
		Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. (d) Inflammable liquids the vapor pressure of which exceeds 27 lbs. p.s.i.a. at 100° F., but does not exceed 40 lbs. p.s.i.a. at 100° F.: Steel barrels or drums: (ICC-5, 5A) not over 110 gal. cap. (ICC-5P) lagged, not over 61 gal. cap. (e) Viscous inflammable liquids having a vapor pressure which does not exceed 16 lbs. p.s.i.a. at 100° F.: All containers listed in (a) and (b) irrespective of flashpoint. Steel barrels or drums: (ICC-6A, 6B, 6C) not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. Aluminum barrels or drums (ICC-42F) not over 50 gal. cap. (f) Viscous inflammable liquids with flashpoint above 20° F. to 80° F. and having a vapor pressure which does not exceed 18 lbs. p.s.i.a. at 100° F.: All containers listed in (c) and (d). Steel barrels or drums (ICC-17E, 17H) STC not over 55 gal. cap. (g) Flammable liquids which are also oxidizing materials or corrosive liquids as defined in §§ 146.22-1 and 146.23-1: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 17C, (STC), 17E (STC)) not over 16 gal. cap. (ICC-37P) WIL polyethylene not over 5 gal. cap. Fiberboard boxes: (ICC-12B) WIC polyethylene not over 65 lbs. gross weight. (ICC-12P) WIC ICC-2U not over 65 lbs. gross weight. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A) WIC not over 1 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Inflammable liquids, N. O. S.—Continued Flammable liquids, N. O. S.—Continued			Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lbs. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). (d) Inflammable liquids the vapor pressure of which exceeds 27 lbs. p.s.i.a., at 100° F., but does not exceed 40 lbs. p.s.i.a., at 100° F.: Steel barrels or drums: (ICC-5, 5A) not over 110 gal. cap. (ICC-5P) lagged, not over 61 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lbs. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). (e) Viscous inflammable liquids having a vapor pressure which does not exceed 16 lbs. p.s.i.a., at 100° F. All containers listed in (a) and (b), irrespective of flashpoint. Steel barrels or drums: (ICC-6A, 6B, 6C) not over 55 gal. cap. (ICC-37A, 37B) STC not over 5 gal. cap. Aluminum barrels or drums (ICC-42F) not over 50 gal. cap. (f) Viscous inflammable liquids with flashpoint above 20° F. to 80° F., and having a vapor pressure which does not exceed 18 lbs. p.s.i.a., at 100° F.: All containers listed in (c) and (d). Steel barrels or drums (ICC-17E, 17H) STC not over 55 gal. cap. (g) Flammable liquids which are also oxidizing materials or corrosive liquids as defined in §§146.22-1 and 146.23-1: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 17C, (STC) 17E (STC)) not over 16 gal. cap. (ICC-37P) WIL polyethylene, not over 5 gal. cap. Fiberboard boxes: (ICC-12B) WIC polyethylene not over 65 lbs. gr. wt. (ICC-12P) WIC ICC-2U not over 65 lbs. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 16A) WIC not over 1 gal. cap. (See note in columns 5, 6, and 7.)

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle

Note: Specification containers shall be of a design and constructed of materials that will not react dangerously with nor be decomposed by the chemical packed therein

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Ink (when possessing a flashpoint at or below 80° F.).	<i>A fluid or viscous material containing coloring matter in solution or suspension. Flashpoint variable.</i>	Red-----	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for ink with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for ink with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for ink with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for ink with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Insecticide, liquid (<i>germin exterminator</i>) (when possessing a flashpoint at or below 80° F.). NOTE: Insecticides having a flashpoint at or below 20° F. shall not be offered for transportation or be transported on board passenger-carrying vessels.	<i>Insecticides frequently contain petroleum or coal tar distillates or other inflammable liquids.</i> <i>Flashpoint variable.</i> <i>Immiscible with water.</i>	Red	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. for liquids with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. for liquids with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. for liquids with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB)----- Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. for liquids with a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Isooctane.....	<i>Clear, colorless, slightly volatile liquid having an organic odor. Vapors much heavier than air. Flashpoint below 80° F. Immiscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat."
Isooctane.....	<i>Clear, colorless liquid having an organic odor. Vapors heavier than air. Flashpoint below 80° F. Immiscible with water.</i>	Red.	Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 65 gal. cap. gal. cap. (ICC-17E) STC, not over 65 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-28, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Isopentane.....	<i>Clear, colorless, very volatile liquid having an organic odor. Vapors heavier than air. Flashpoint below -60° F. Boiling point about 81° F. Immiscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-28, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Isoprene.....	<i>Clear, colorless, very volatile liquid having an organic odor. Vapors form inflammable or explosive mixture with air. Flashpoint below -0° F. Boiling point about 98° F. Immiscible with water.</i>	Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Isopropyl acetate.....	Colorless, aromatic liquid..... Slightly miscible with water. Flashpoint 36° F.	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M (NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A) WIC, not over 16 gal. cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Lacquer base or lacquer chips, plastic (wet with alcohol or solvent). Wet with at least 20% by weight of alcohol or solvent with a flashpoint not lower than 30° F. (When possessing a flashpoint at or below 8° F.)	Lacquer chips are composed of nitrocellulose incorporated with a plasticizer and pigments. They are the film-forming part of lacquer which remains after the solvents or thinners have evaporated. Involved in fire will give off nitrous fumes which are deep orange in color and extremely poisonous. Flashpoint is variable depending upon the solvent used to wet the chips. Immiscible with water.	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5M) not over 490 lb. gr. wt. (ICC-6A, 6B, 6C, 6J, 6K) not over 490 lb. gr. wt. (ICC-17C, 17E, 17H) STC not over 490 lb. gr. wt. (ICC-37A, 37B) STC not over 490 lb. gr. wt. for 37A; 490 lb. gr. wt. for 37B. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 490 lb. gr. wt. (ICC-42H) not over 490 lb. gr. wt. Wooden barrels or kegs: (ICC-10A, 10B) not over 490 lb. gr. wt. (ICC-11A, 11B) WIC, not over 490 lb. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B, 12E) WIC, not over 65 lb. gr. wt. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.
Lithium aluminum hydride, ethereal.	Clear, water-white liquid with odor resembling ether. Reacts quickly with water to evolve an inflammable gas. Solvent very volatile. If spilled, the ether evaporates to leave a residue which is easily ignited by spark or mild friction.	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-6A, 6B, 6C, or 17H) (STC) with not more than one inside glass container not exceeding 2 gal. cap. Wooden boxes (ICC-15A) with inside glass or earthenware containers not over 1 quart each enclosed in airtight metal cans. Outside container not over 16 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5M) not over 490 lb. gr. wt. (ICC-6A, 6B, 6C, 6J, 6K) not over 490 lb. gr. wt. (ICC-17C, 17E, 17H) STC not over 490 lb. gr. wt. (ICC-37A, 37B) STC not over 490 lb. gr. wt. for 37A; 490 lb. gr. wt. for 37B. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 490 lb. gr. wt. (ICC-42H) not over 490 lb. gr. wt. Wooden barrels or kegs: (ICC-10A, 10B) not over 490 lb. gr. wt. (ICC-11A, 11B) WIC, not over 490 lb. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B, 12E) WIC, not over 65 lb. gr. wt. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC, not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5M) not over 490 lb. gr. wt. (ICC-6A, 6B, 6C, 6J, 6K) not over 490 lb. gr. wt. (ICC-17C, 17E, 17H) STC not over 490 lb. gr. wt. (ICC-37A, 37B) STC not over 490 lb. gr. wt. for 37A; 490 lb. gr. wt. for 37B. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 490 lb. gr. wt. (ICC-42H) not over 490 lb. gr. wt. Wooden barrels or kegs: (ICC-10A, 10B) not over 490 lb. gr. wt. (ICC-11A, 11B) WIC, not over 490 lb. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B, 12E) WIC, not over 65 lb. gr. wt. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC, not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5M) not over 490 lb. gr. wt. (ICC-6A, 6B, 6C, 6J, 6K) not over 490 lb. gr. wt. (ICC-17C, 17E, 17H) STC not over 490 lb. gr. wt. (ICC-37A, 37B) STC not over 490 lb. gr. wt. for 37A; 490 lb. gr. wt. for 37B. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 490 lb. gr. wt. (ICC-42H) not over 490 lb. gr. wt. Wooden barrels or kegs: (ICC-10A, 10B) not over 490 lb. gr. wt. (ICC-11A, 11B) WIC, not over 490 lb. gr. wt. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 13 gal. total cap. Fiberboard boxes: (ICC-12A, 12B, 12E) WIC, not over 65 lb. gr. wt. Fiber or plywood drums: (ICC-21C, 22A, 22B) WIC, not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.
Not permitted.....	Not permitted.....	Not permitted.....

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Mercaptans: Amyl mercaptan. Butyl mercaptan. Ethyl mercaptan. Isopropyl mercaptan. Propyl mercaptan. Mercaptan mixtures, aliphatic. (When possessing a flash point at or below 50° F.) Warning or odorizing devices containing not more than one ounce of a mercaptan or mixture in a hermetically sealed container or sealed portion of the device are not subject to the regulations in this part.	<i>Water-white to yellow liquids. Strong offensive garlic-like odor. Butyl mercaptan highly toxic, others are toxic to lesser degree. Do not breathe vapors from these substances or allow in contact with eyes.</i> <i>Flashpoints variable (ethyl—lowest; amyl—highest). Immiscible with water.</i> Keep cool. Stow well away from living quarters.	Red.....	Stowage: “On deck protected.” “On deck under cover.” “Tween decks readily accessible.” Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C) not over 110 gal. cap. (ICC-17C, STC, not over 55 gal. cap. (ICC-17E) STC, not over 5 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 16A, 16B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12B) WIC, not over 65 lb. gr. wt. Specification cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage “On deck” and “First deck below.” Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for mercaptans having a flash point above 20° F. Steel barrels or drums: (ICC-17E) STC, not over 55 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methyl acetate	<i>A clear, colorless, volatile liquid with fragrant odor. Vapors are 2½ times heavier than air and form an explosive mixture within a range of 4% to 14% in air. Flashpoint about 20° F. Boiling point about 138° F. Slightly miscible with water.</i>	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) 8TC, not over 55 gal. cap. (ICC-17E) 8TC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 15 gal. cap. Wooden boxes, (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes, (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-61) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below". Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Methylacetone	<i>A water-white, anhydrous liquid consisting of acetone with methanol. Flashpoint variable, may be as low as 4° F. Miscible with water.</i>	Red.	

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger, or vehicle
Not permitted	Not permitted	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methylchloromethylether, anhydrous.	Clear, colorless liquid. Gives off fumes which are irritating to the eyes. Flashpoint about 6° F. Keep cool.	Red.	Stowage: "On deck protected." "On deck under cover." Outside containers: Nickel barrels or drums (ICC-5K) not over 55 gal. cap.
Methyl dichlorosilane.	Clear volatile liquid Fumes strongly, in moist air. Fumes are irritating and corrosive. Flashpoint below 80° F. Keep dry and cool.	Red.	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5A, 5B, 5C) not over 55 gal. cap. (ICC-5F) not over 11 gal. cap. (ICC-17H, 37A) STC, with inside glass containers not over 1 qt. cap. each, not over 55 gal. total cap. Wooden boxes (ICC-15A, 16B) WIC not over 1 qt. cap. each, not over 65 lb. gr. wt. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.	Not permitted.	Not permitted.
Not permitted.	Not permitted.	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methyl formate	<i>Colorless liquid, agreeable odor. Vapor pressure 18 lbs. at 100° F. Vapors 3 times heavier than air and form an explosive mixture within a range of 4 1/4% to 25% in air. Sustained inhalation of vapors in an unventilated compartment is dangerous. Flashpoint -25° F. Boiling point 28° F. Slightly miscible with water.</i>	Red	Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over a gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Methylhydrazine	<i>A colorless liquid with an ammonia like odor. Corrosive. Vapors may be explosive when exposed to high temperature. Stow well away from corrosive liquids and organic materials.</i>	Red	Stowage: "On deck protected." "On deck under cover." Outside containers: Carboys, boxed, glass (ICC-1D) not over 6 1/4 gal. cap. Metal barrels or drums: (Stainless steel): (ICC-5, 5A, 5C) not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. Wooden boxes: (ICC-15A, 15B, 15C) WIC, not over 200 lb. gr. wt. Authorized only for dimethylhydrazine, unsymmetrical: Metal barrels or drums: (ICC-17C) STC, not over 55 gal. cap. (ICC-42B) aluminum, not over 55 gal. cap. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Dimethylhydrazine, unsymmetrical.			

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted	Not permitted	Not permitted.
Not permitted	Not permitted	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methyl iso-propenyl ketone, inhibited.	Nearly colorless, inflammable liquid, with a pleasant odor and sweet taste. Sustained inhalation of vapors in unventilated spaces is dangerous.	Red-----	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42E) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes: (ICC-15A, 15B, 15C, 16A, 16A, 16B) WIC, not over 10 gal. total cap. Fiberboard boxes: (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. (ICC-12E) WIMO, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable Liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted-----	Not permitted-----	Not permitted;

Table D—Classification.

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methyl magnesium bromide in ethyl ether in concentrations not over 40%.	<i>Highly inflammable.</i> <i>Takes fire on contact with air.</i> Keep cool.	Red	Stowage: "On deck protected." Outside containers: Steel barrels or drums: (ICC-17C) STC, not over 55 gal. cap. (ICC-37A) STC, WIMC not over 1 gal. cap. each, not over 5 gal. total cap. Wooden boxes (ICC-15A, 15B, 15C), WIMC ICC-2A WIC glass or metal not over 1 qt. cap. each, not over 1 gal. net contents. Fiberboard boxes (ICC-12A) WIMC ICC-2A WIC glass or metal not over 1 qt. cap. each, not over 1 gal. net contents. (ICC-12B), WIC glass not over 1 qt. cap. each, not over 65 lb. gr. wt. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailer-ships and train-ships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.	Not permitted.	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Methyl methacrylate monomer.	<i>A water white liquid of low viscosity. Flashpoint about 55° F. May polymerize spontaneously without addition of an inhibitor.</i>	Red-----	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C) not over 110 gal. cap. (ICC-6M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37F) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipment: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37F) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)----- Outside containers: Steel barrels or drums: (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37F) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37F) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipment: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes (ICC-15X) WIMC, not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Monoethylamine (ethylamine).	<i>A colorless liquid having a strong ammoniacal odor. Flashpoint below 0° F. Can react vigorously with oxidizing materials. Keep cool. Keep away from heat and open flame.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Metal barrels or drums: (ICC-5, 5A) not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).
Motor fuel, N. O. S. (when possessing a flashpoint at or below 80° F.)	<i>Any fuel for internal combustion motors not otherwise specified by name in these regulations. Vapors when mixed with air may be explosive over a wide range. Flashpoint variable. May or may not be miscible with water.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMO (ICC-15X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.
Not permitted.....	Not permitted.....	Not permitted.

NOTE: Shall not be accepted for transportation on board passenger vessels or passenger-carrying ferry vessels except such fuel as is contained within the fuel tanks of motor vehicles for use as a source of motive power for their own propulsion on and off the vessel, or for auxiliary equipment when such motor vehicles are being transported on board such vessels.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Neohexane	<i>Clear, water-white, rather volatile liquid. Vapors form inflammable or explosive mixtures with air. Flashpoint below 0° F. Immiscible with water. Boiling point about 120° F.</i>	Red	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 10 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.
Nickel carbonyl	<i>Colorless, volatile liquid. Poisonous. Vapors explode in air at about 140° F. Vapors heavier than air. Boiling point approximately 110° F. Immiscible with water.</i>	Red	Stowage: "On deck protected." "On deck under cover." Outside containers: Cylinders as prescribed for any compressed gas except acetylene.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted	Not permitted	Not permitted
Not permitted	Not permitted	Not permitted

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Oil. Oil, N. O. S. Petroleum oil. Petroleum oil, N. O. S. (When possessing a flashpoint at or below 80° F. but not less than 20° F.) Note: For these liquids when possessing a flashpoint at or below 20° F., see "Petroleum distillate."	May include any oil product derived from crude petroleum, except oils properly described by name within these regulations. Flashpoint variable. Immiscible with water.	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. capacity each. (ICC-37P) STC, not over gal. cap. for liquid having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) STC, not over 5 gal. cap. for liquid having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) STC, not over 5 gal. cap. for liquid having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) STC, not over 5 gal. cap. for liquid having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Paint, enamel, lacquer, stain, shellac, varnish, aluminum, bronze, gold, wood filler, liquid, and lacquer base liquid.	Flashpoint variable. May or may not be miscible with water.	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat."
Aluminum liquid (or paint).		Red.	Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap.
Bronze liquid (or paint).		Red.	(ICC-17C, 17E), STC, not over 55 gal. cap.
Driers, paint, varnish, enamel, etc.		Red.	(ICC-37A, 37B) STC, not over 5 gal. cap.
Enamel.		Red.	(ICC-37P) NRC, not over 5 gal. cap. for liquids having a flashpoint exceeding 20° F.
Furniture or wood stain, liquid.		Red.	Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap.
Gold paint.		Red.	(ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap.
Lacquer.		Red.	Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap.
Lacquer base liquid.		Red.	(ICC-42H) not over 55 gal. cap.
Leather bleach.		Red.	Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap.
Leather dressing.		Red.	Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap.
Mortar stain, liquid.		Red.	Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt.
Paint driers, liquid.		Red.	Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap.
Shellac.		Red.	Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.
Shellac, liquid.		Red.	Cylinders as prescribed for any compressed gas except acetylene.
Stain.		Red.	Portable tanks (ICC-52 aluminum or magnesium) not over 500 gal. cap.
Varnish.		Red.	Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt.
Varnish driers.		Red.	Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only).
Wood filler.		Red.	Tank cars complying with ICC regulations (trainships only).
Wood stains, liquid.		Red.	Authorized only for liquids having a flashpoint above 20° F.: Steel barrels or drums: (ICC-17E, 17H) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap.
(When possessing a flashpoint at or below 80° F.)			Wooden barrels or kegs (ICC-10A, 10B, 10C) not over 50 gal. cap.
When the flashpoint of a liquid shipped under this descriptive name is 20° F. or below, the bill of lading or other shipping paper shall bear the following certification: "This liquid possesses a flashpoint of 20° F. or less."			Fiberboard boxes (ICC-12E), WIMC, not over 110 lb. gr. wt.
When the flashpoint is above 20° F. and not more than 80° F. the following certification shall appear hereon: "This liquid possesses a flashpoint of above 20° F. but not more than 80° F."			Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-16X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible."	Ferry stowage (AA). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap.
Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap.	(ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flashpoint exceeding 20° F.	(ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flashpoint exceeding 20° F.
(ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flashpoint exceeding 20° F.	Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap.	Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap.
Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap.	Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap.	Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap.
Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap.	Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap.	Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap.
Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap.	Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap.	Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap.
Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap.	Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt.	Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt.
Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt.	Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap.	Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap.
Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap.	Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.	Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.
Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap.	Cylinders as prescribed for any compressed gas except acetylene.	Cylinders as prescribed for any compressed gas except acetylene.
Cylinders as prescribed for any compressed gas except acetylene.		

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Pentaborane.....	<i>A colorless liquid with a disagreeable odor. Poisonous. Boiling point 58.4° C. Decomposed by water yielding Hydrogen gas which is inflammable and forms explosive mixtures with air. Keep cool. Stow well away from all sources of artificial heat.</i>	Red.....	Stowage: "On deck protected." "On deck under cover." Outside containers: Cylinders as prescribed for any compressed gas except acetylene.
Pentane.....	<i>A clear colorless, volatile liquid obtained from petroleum. Vapors when mixed with air are explosive over a range of approximately 1.4% to 8.0% in air. Flashpoint below 0° F. Boiling point 88° F. to 104° F. Immiscible with water. Keep cool.</i>	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap.
Pentane methyl.....	<i>A clear, colorless, volatile liquid having an organic odor. Vapors form inflammable or explosive mixtures with air. Flashpoint below 0° F. Boiling point about 135° F. Immiscible with water. Keep cool.</i>	Red.	Aluminum barrels or drums: (ICC-42B, 42C, 42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap.
Petroleum distillate..... Naphtha distillate. (When possessing a flashpoint at or below 80° F.)	<i>Any petroleum distillate not otherwise named in these regulations that is not used as motor fuel for internal combustion engines. Flashpoint variable. Vapors when mixed with air are explosive over a wide range. Immiscible with water.</i>	Red.	Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for export shipments of petroleum distillate or naphtha distillate: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-18X) not over 10 gal. cap.

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Peroxides, organic, liquids or solutions, N. O. S. (When possessing a flashpoint at or below 80° F.)	Colorless, oxidizing liquid having a sharp penetrating odor. Readily ignitable and burns rapidly, with acceleration. Flashpoint variable. Immiscible with water. Keep cool.	Red-----	Stowage: "On deck protected." "On deck under cover." Outside containers: Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A) not over 150 lb. gr. wt. Fiberboard boxes, WIC (ICC-12B) not over 65 lb. gr. wt. Authorized for materials which will not react dangerously with the drum metal or be decomposed by contact with it: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 16 gal. cap. (ICC-17C, 17E) STC, not over 16 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted-----	Not permitted-----	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Polishes, metal, stove, furniture and wood, liquid. (When possessing a flashpoint at or below 80° F.)	<i>Liquid preparations used to remove film from surfaces and restore and protect polish and finish of such surface. Flashpoint variable. May or may not be miscible with water.</i>	Red.	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E, 17F) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only). Authorized only for liquids having a flashpoint above 20° F.: Steel barrels or drums (ICC-17E, 17H) STC, not over 55 gal. cap. Wooden barrels or kegs (ICC-10A, 10B) not over 50 gal. cap. Fiberboard boxes (ICC-12E) WIMC, not over 110 lb. gr. wt. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.
Compounds, polishing, liquid.		Red.	
Furniture polish.		Red.	
Metal polish, liquid.		Red.	
Stove polish, liquid.		Red.	
Wood polish, liquid.		Red.	
(When possessing a flashpoint at or below 80° F.)			

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB). Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G, 6B, 6C) not over 110 gal. cap. (ICC-5M, 6A) not over 55 gal. cap. (ICC-17C, 17E) STC, not over 55 gal. cap. (ICC-37A, 37B) STC, not over 5 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. for liquids having a flash point exceeding 20° F. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC 2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42F) not over 50 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs, WIC (ICC-11A, 11B) not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized only for liquids having a flashpoint above 20° F.: Steel barrels or drums (ICC-17E, 17H) STC, not over 55 gal. cap. Wooden barrels or kegs (ICC-10A, 10B) not over 50 gal. cap. Fiberboard boxes (ICC-12E) WIMC, not over 110 lb. gr. wt. Authorized only for export shipments: Steel barrels or drums (ICC-17X) STC, not over 55 gal. cap. Wooden boxes, WIMC (ICC-15X) not over 10 gal. cap.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Propylene oxide.....	Colorless liquid, ethereal odor. Explosive range: 3 to 15% in air. Flashpoint below 0° F. Miscible with water.	Red.....	Stowage: "On deck protected." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C) STC, not over 55 gal. cap. (ICC-17E) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. Cylindrical steel overpack: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes (ICC-15A, 15B, 15C, 16A, 19A, 19B) WIC, not over 10 gal. total cap. Fiberboard boxes (ICC-12A, 12B) WIC, not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Not permitted.....	Not permitted.....	Not permitted.

Table D—Classification:

Descriptive name of article	Characteristic properties, cautions, markings required	Label required	Required conditions for transportation
			Cargo vessel
Pyridine..... (When possessing a flashpoint at or below 80° F.).	<i>A slightly yellow or colorless liquid having a penetrating and offensive odor. Vapors are 2.76 times heavier than air and form an explosive mixture within a range of 1.8 to 12.4% in air. Vapors are poisonous and suffocating. Flashpoint 68° F. Miscible with water.</i>	Red.....	Stowage: "On deck in open." "On deck under cover." "Tween decks readily accessible." "Under deck away from heat." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pts. cap. each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Authorized for stowage "On deck in open" only: Portable tanks (ICC-51) not over 20,000 lb. gr. wt. Authorized for stowage "On deck" and "First deck below": Motor vehicle tank trucks complying with ICC regulations (trailerships and trainships only). Tank cars complying with ICC regulations (trainships only).

Inflammable liquids—Continued

Required conditions for transportation—Continued		
Passenger vessel	Ferry vessel, passenger or vehicle	R. R. car ferry, passenger or vehicle
Stowage: "On deck protected." "On deck under cover." Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Wooden barrels or kegs (ICC-11A, 11B) WIC, not over 16 gal. cap. Wooden boxes, WIC (ICC-15, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC (ICC-12A, 12B) not over 65 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (AA)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene.	Ferry stowage (BB)..... Outside containers: Steel barrels or drums: (ICC-5, 5A, 5B, 5C, 5G) not over 110 gal. cap. (ICC-5M) not over 55 gal. cap. (ICC-17C, 17E, 17H) STC, not over 55 gal. cap. (ICC-17H, 37A) WIC of glass, not over 9 pints capacity each. (ICC-37P) NRC, not over 5 gal. cap. Cylindrical steel overpacks: (ICC-6D) WIC ICC-2S, not over 55 gal. cap. (ICC-6D, 37M(NRC)), WIC ICC-2SL, not over 55 gal. cap. Aluminum barrels or drums: (ICC-42B, 42C) not over 110 gal. cap. (ICC-42H) not over 55 gal. cap. Wooden barrels or kegs: (ICC-10A, 10B) not over 50 gal. cap. (ICC-11A, 11B) WIC not over 16 gal. cap. Wooden boxes, WIC (ICC-15A, 15B, 15C, 16A, 19A, 19B) not over 10 gal. total cap. Fiberboard boxes, WIC: (ICC-12A, 12B) not over 65 lb. gr. wt. (ICC-12E) WIMC, not over 110 lb. gr. wt. Fiber or plywood drums (ICC-21C, 22A, 22B) WIC not over 1 gal. cap. Fiber drum (ICC-21C) WIC ICC-2S, ICC-2SL, not over 55 gal. cap. Cylinders as prescribed for any compressed gas except acetylene. Tank cars complying with ICC regulations.