

MILITARY SEA TRANSPORTATION SERVICE, PACIFIC
NAVAL SUPPLY CENTER
OAKLAND, CALIFORNIA 94625

SPECIFICATION NUMBER: MSTSP 70-75

16 March 1970

ADDITION NUMBER 1

To

S P E C I F I C A T I O N S

For

DRYDOCKING - INACTIVATION

USNS GEN. JOHN POPE (T-AP 110)

These specifications consist of the following pages:

Pages 905-2 and 914-1 (A total of 2 pages)

CATEGORY "A" ITEMS

ITEM 905 - FORE PEAK, AFT PEAK AND DISTILLED WATER TANKS: (ADDENDUM 1) (MAC)

Add the following to Item 905 on page 905-1, in the basic specifications.

After the fourth paragraph insert the following paragraph.

"Install and connect Government furnished float switches, two (2) in each tank, and D/H air ducting in the fore and after peak.

Hook-up D/H air ducting after installation of expanded metal manhole covers."

USMRS PGPE (T-AP 110)
MSTSP 70-74

CATEGORY "A" ITEMS

ITEM 914 - BILGES CLEANING AND DRYING OF: (MAC)

Remove all oil, water, dirt and debris from all bilge areas which become soiled as a result of work in these specifications.

Bilges shall be cleaned and thoroughly dried to the satisfaction of the MSTSP Inspector prior to the ship leaving the Contractor's plant.