

USNS POPE

JO 80-710

LIFEBOAT DAVITS, ANNUAL INSPECTION AND TEST

SHOP X72

NO. 1 AND 2 LIFEBOAT STATION. RENEW THE DAMAGED FALLS AND THE AFT LEAD BLOCK AT BOTH LIFE BOAT STATIONS WITH MATERIAL EQUAL TO ORIGINAL WHEN NEW. PULL SHEAVE PINS FROM ALL OTHER SHEAVES, IDLERS AND FLOATING BLOCKS INWAY OF THESE FALLS, CLEAN AND PREPARE FOR DETAILED EXAMINATION OF BEARINGS, PINS, BUSHINGS, 35: BY THE USCG AND MSTs INSPECTORS. UPON COMPLETION OF EXAMINATION, REASSEMBLE AND REINSTALL AS ORIGINAL.

PULL SHEAVE PINS FROM A TOTAL OF TWENTY (20) ADDITIONAL SHEAVES, AS DIRECTED BY USCG AND MSTs INSPECTORS, FOR DETAILED EXAMINATION.

RENEW TWENTY (20) SHEAVE BEARINGS WITH MARLIN ROCKWELL

CORPORATION (MAXIMUM DRAG SEAL) BALL BEARINGS WITH NEOPRENE SEALS.

MRC NO. 398-~~XXXXXX~~ SZZ OR EQUIV AS APPROVED. RENEW TEN ~~XXXX~~ BRONZE SHEAVE PINS. ALSO RENEW TEN (10) SHEAVE BUSHINGS USING BRONZE BUSHING

MATERIAL. ~~DESIGN XXXX XXXX XXXX XXXX XXXX~~ SIZE TO FIT NEW SEALED BALL BEARINGS. BUSHINGS DESIGN SHALL BE SAME AS THOSE REMOVED. UPON COMPLETION OF RENEWALS AND EXAMINATION, CLEAN ALL PARTS, ~~XXXXXX~~ REASSEMBLE AND REINSTALL AS ORIGINAL.

~~XXXXXX/XXX/XXXXXX/XXXXX/+X/XXX+XX/XXXX/XX/+X~~

LUBRICATE ALL, SHEAVE, IDLER AND FLOATING BLOCK PINS AND BUSHINGS. FLUSH ALL DAVIT TRUNION ROLLERS FREE OF ALL GREASE AND DEBRIS, THOROUGHLY ~~XXXX~~ LUBRICATE AND PROVE FREE AND ROLLING.

FREE-UP AND ADJUST THE HAND BRAKE LINKAGE FOR ALL LIFEBOAT DAVIT ~~XXXX~~ WINCHES.

~~WEIGHT AND OPERATIONALLY TEST THE SHIPS FOURTEEN 1-XXXXXX/XX/~~

~~XXXXXX/~~ LIFEBOAT STATIONS DAVITS AND HANDLING ASSEMBLIES IN ACCORDANCE

WITH USCG RULES AND REGULATIONS AS LAST AMENDED. TEST SHALL BE WITNESSED BY THE MSTs INSPECTOR, USCG, INSPECTOR AND COGNIZ, SHIPS OFFICER.

RESULTS OF TEST SHALL BE FORWARDED, ~~XXXXXX/XX/XX~~ TRIPLICATE TO MSTSPAC VIA THE MSTs INSPECTOR.

OBSERVE SAFETY PRECAUTIONS.

SIGNED: DAVIS/CASSIDY/CATRON