

REMARKS

1200-1600 WATCH

@ Rockside Tacoma Mach. - Machinery in operation as of Noon: B-2, M-1, MC-2, ME-2, F.O., INDO. A-1, AC-1, AE-2, AEG, D-2, P-1, F-1, C-1, W-1, L-1, LS-1, - Main unit on jacking gear -
 F.W.E. @ 1217 - Following Work Done: Shovel in Relief Valve #1 Fuel Pump -
 New Jacket #1 Fuel Pump L.O. Strainer - Added Packing #1 Fuel Pump, W'str. End - Put
 clamp on Leaking Main Return Line below 58th Station - Transferred Fuel oil from
 Outboard Settler - Bilge @ Safe Level -

WATCH ENGR'S SIGNATURE.

M. F. F.

1600-2000 WATCH

@ Rockside Tacoma Mach. Machinery as before. Main unit on jacking gear - Vacuum on main unit. Bilges Eng room fwd and aft. Check aft engine room speed and boilers.

WATCH ENGR'S SIGNATURE.

S. H. Burk

2000-2400 WATCH

Moved C Tacoma dock. Machinery as before. Main unit jacking gear with vacuum 61-62 carrying load. Bilge C safe level. See taking on fresh to P & S No 1 Tanker C 2315 made routine rounds of full AFT engine room space.

WATCH ENGR'S SIGNATURE.

R. P. Adams

2400-0400 WATCH

F.W.T. - Sargent Oil - Bella
 Sat. Machinery as before, except: - Dumped #1 Boiler - Replaced Hi & Low Gauge #1 Boiler - Refilled Boiler from Fuel Bottom - Made Routine Inspection Rounds of all Machinery Space - Bilge @ Safe Level - Changed to Outboard Settler @ 0330 - #2 Boiler on Lost. Blow to Sink - Shovel, Elct. Report that Cargo Tank Secured @ 0300 -

WATCH ENGR'S SIGNATURE.

M. F. F.

0400-0800 WATCH

Oil - Manning F/H/T - Bennett
 Machinery as before. Main unit jacking gear engaged. Inspected machinery spaces. Pumped bilges. Made rounds fwd. and aft engine rooms.

WATCH ENGR'S SIGNATURE.

S. H. Burk

0800-1200 WATCH

F.W.T. - Wenner Sargent
 moved C Tacoma dock, machinery as before, main unit jacking gear over with vacuum, sec 1st stage to main air ejector C 0825. circulate fuel oil to No 1 Boiler C 0830, put fire in STB'D Boiler C 0900, open 150" line to AFT Eng. C 0935 - Blow down STB'D boiler C 0955 - see fire in STB'D Boiler C 1010 at 300th made routine inspection of space

WATCH ENGR'S SIGNATURE.

R. P. Adams

CHIEF ENGINEER

2 BOILER /

8.18 P. ALK S
 11.10 T. ALK L
 9.53 CHLO C
 PH. 4
 SO. 3
 PH. 4

42 06 WS. HRS. 4088
 1558 FS. HRS. 1548

CHIEF ENGR'S SIGNATURE.

J. P. Halloran

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME							60 MIN	240	260	260	260	240	
DETENTION TIME													
REVOLUTION COUNTER (END OF WATCH)							0488 1930	0490 4925	0492 9550	0495 3140	0497 6610		
TOTAL REVOLUTIONS (FOR WATCH)							29530	12415	24630	24540	23470		
AVERAGE RPM							98.4	88.4	94.7	94.6	98.3		
F.O. METER (END OF WATCH)							8764740 6034 740	8767 350	8769 940	8772 500	8776 210	8777 580	
F.O. CONSUMED							1260	3610	2590	2560	2710	2370	
PRESSURES	THROTTLE	420	445	440	440	450	440						
	H.P. AHEAD	400	415	420	420	425	420						
	L.P. AHEAD	26	24	19.5	23	21	19						
	VACUUM	29"	29"	29"	29"	29"	29"						
	L.O. TO TURBINES	15	15	13.8	14	14	14						
	AUX. STEAM	135	135	145	140	130	140						
	BACK PRESSURE	9	9	9	9	9	9						
	GLAND STEAM	4	4	3	—	2	2						
	H.P. BLEEDER		80	80	80	64	80						
	I.P. BLEEDER		-10	10	70	-10	6						
	L.P. BLEEDER		6	6	10"	6	-11						
TEMPERATURES	STEAM AT THROTTLE	620	685	665	660	655	675						
	L. P. EXHAUST	48	90	88	96	94	95						
	CONDENSATE	88	82	78	88	88	88						
	CIRC. WATER IN	56	55	54	62	65	63						
	CIRC. WATER OUT	72	64	64	74	73	74						
	L.O. TO COOLERS	130	126	130	130	126	130						
	L.O. FROM COOLERS	112	106	112	110	107	110						
	TEMPERATURE THRUST BEARING	120	117	118	120	117	118						
	FORWARD H.P. ROTOR BEARING	123	123	126	126	123	125						
	AFT. H.P. ROTOR BEARING	140	135	140	140	135	138						
	FORWARD L.P. ROTOR BEARING		131	135	135	132	136						
AFT. L.P. ROTOR BEARING		127	133	133	128	132							
HOTTEST GEAR BEARING FORWARD									157	157	155	156	
HOTTEST GEAR BEARING AFT									151	151	145	147	
AUX. COND. CONDENSATE							80 82	80 82	78 75	90 82	95 85	90	
1ST STAGE FEED WATER HEATER							96	148	148	150	151	154	
D. C. FEED WATER HEATER							236	235	238	240	240	238	
3RD STAGE FEED WATER HEATER													
SUPER HEAT							P 770	800	790	790	780	800	
							S 770	800	790	780	800	620	
F.O. TO BURNERS							180	180	180	180	180	180	
AIR TO FURNACE							P 128	126	123	127	128	126	
							S 128	126	123	127	128	124	
F.O. TEMP. IN SETTLING TANKS							P 104	106	110	108	104	116	
							S 98	116	114	114	110	118	
PORT BOILER UPTAKE							320	341	310	310	305	290	
STBD. BOILER UPTAKE							310	315	305	305	330	290	
F. O. BACK PRESSURE							12	14	12	12	10	11	
MAIN STEAM							440	450	440	460	460	440	
F.O. TO BURNERS							240	240	200	190	250	190	
MAIN COND. SALINITY							.4	1.2	.4	.4	1.6	.4	
ENGINE ROOM TEMPERATURE							78	71	69	73	73	73	
FIRE ROOM TEMPERATURE							78	71	69	73	73	73	
NOZZLES IN USE							16	16	16	16	16	16	
NO. OF BURNERS IN USE							P 3	3	3	3	3	3	
							S 3	3	3	3	3	3	
BURNER TIP SIZE							P 53 70	53 70	53 70	53 70	53 70	53 70	
							S 53 70	53 70	53 70	53 70	53 70	53 70	
CO ₂ % PORT BOILER								12.5	12.0	13.5	14.5		
CO ₂ % STBD. BOILER								12.5	12.0	13.5	13.5		
OIL LEVEL MAIN SUMP								1.1		1.2"	1.0"	1"	
DOUBLE BOTTOM							.4	.4		.4	.4		

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL																																		
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	METER AT NOON	METER PRE-VIDUS NOON	CONSUMED BY METER	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND	CONSUMED	RECEIVED DURING DAY	EXPENDED DURING DAY	REMAINING ON BOARD	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND	CONSUMED	RECEIVED	EXPENDED	RECEIVED	CONSUMED																	
1200 TO 1600	1	1200	440		9	120	110		62	10 LINE		240	74.860	45.320	29.540	17.156	—	703	16.453	1280	155	1255	180	ON HAND AT START OF DAY	4300	—	5295	5																			
1600 TO 2000	2	1200	440		7	130	120		73	1200	1200	240																																			
2000 TO 2400	1	Idling			9	120	110		62			240																																			
2400 TO 0400	2	1200	450		7	132	120		73	1400	1350	240																																			
0400 TO 0800	1	1200	440		9	116	105		62	0	0	240																																			
0800 TO 1200	2	1200	440		7	132	120		73	1100	1100	240																																			
	1	1200	440		9	120	110		62	10 LINE		240																																			
	2	1200	440		7	130	120		73	1200	1200	240																																			
	1	1200			9				62	Idling		240																																			
	2	1200	440		7	134	120		73	1300	1300	240																																			
	2	1200	440			135	120		73	1500	1500	240																																			
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)												W 2 4 1/2																																			
L.O. CENTRIFUGE (HOURS OPERATED)												4						4						4 1/2						4 1/2						4 1/3						2 1/2					
SUMMARY												RUNNING TIME						1320						PROPELLER SLIP (%)						14.31																	
												DETENTION TIME						✓						BBL FUEL/MI																							
												TOTAL REVOLUTIONS						119.960						WIND DIRECTION						270°-15' Kt																	
												AVERAGE R.P.M.						90.8						STATE OF SEA						270°-4 ft																	
												TOTAL MILES BY ENGINE						447						STATE OF WEATHER						B-Cloud																	
												TOTAL MILES BY OBSERVATION						383						S=17.4						H=59																	

1200-1600 WATCH

Preparing Plant for Sea: Elect. Load shifted aft. & Plants split @ 1225 #1
 Ekn. Idling - Tested Telegraph @ 1227 Synch. Clock @ 1245 - #1 Boiler on line @ 1215
 off-jacking Ekn & Rolling with steam @ 1320 - S.F.E. @ 1347 - S.FOM-2725120 P.FOM-6038720
 TACH. - 04852400 SHAFT. CTR - Bells as per Bell Book - Dpt. @ 1520 - 16 No. 2 3/4
 S.FOM-2725360 P.FOM-6038920 TACH. - 04854970 - SHAFT. CTR - Blue Tubes #1 & 2 Boiler 1525-1535

Bilges @ Safe Level - Filled Bilge - Empty #1 Fuel Pump tank 40 oil
 1600-2000 WATCH

Machinery as before except - changed allboard to inboard f.o. settler @
 1600. 1640 Electrician called out to work on No. 1 feed pump controller - call again
 @ 1810. Lte of Ekn at 1810. Story 1920 - 60 RPM - Bells as per Bell Book

7 wt Stagg

2000-2400 WATCH

underway on 16 No. 2 @ 1955 G-2 carrying load G-1 idling
 sec No. 1 Ekn @ 2030 back on line @ 2130 No. 1 feed pump trip out
 four times between 2035 & 2135 F.P. trip out again @ 2145 back
 on line @ 2155 changed & cleaned port fuel oil strainer @ 2245 -
 Retard clock 20 min @ 2300 - checked steering gear made routine rounds
 and inspection of machinery

2400-0400 WATCH

Machinery as before, except: - changed & cleaned fuel oil P.P.
 Burner - changed & cleaned fuel oil Section Strainer - Set clock back
 20 minutes @ 0100 - changed to outboard settle @ 0230 - Pumped fog
 Spray Rig - Second #1 fog @

0400-0800 WATCH

Machinery as before, except. Called out Electrician @ 0500 to 0700
 work on Evap pump motor. Lte of Ekn, evap @ 0500. Retard clock @
 0500. 20 min. changed engine room bilges. Cleaned discharge
 hot strainer on Port fuel oil to boiler. Made routine rounds and
 checked machinery spaces. Cleaned L.O. Strainers. FW switched to No. 1 & 5.

0800-1200 WATCH

underway on 16 No. 2 - Machinery as before G-2 carrying
 load Blue Tubes P15 @ 0800 - sec No. 1 Turbo Generator @ 0840 - sec
 Comp circulator @ 0900 - changed & clean center burner @ 0905 - sec
 heating steam to compartments @ 0910. Abandon ship Drill & standing by
 @ 1015 sec @ 1029 - sec L.O. Purifier @ 1030 Made routine rounds
 and inspection of machinery - Cleaned Lube oil Purifier

CHIEF ENGINEER

BOILER

✓ P. ALK
 T. ALK
 CHLO
 PH. 4
 SO. 3
 PH

4236 WS. HRS. 4091
 1582 FS. HRS. 1551

CHIEF ENGR'S SIGNATURE-

J. P. Adami

A 6025

Dept @ 1500-S-C-TR 04861630 - T-CTR-04854970 FOM S-2725368

REMARKS

1200-1600 WATCH

Underway on 16 Nozzle - Machinery in operation as of 7:00. Main Unit, B-1, B-2, G-1, H-1, MC-2, ME-R, AC-1, AE-R, D-1, D-2, P-1, P-2, F-1, F-2, C-1, W-1, L-1, S-1, - Single Plant by securing AE-R, & AC-1, Let off Lube oil Centrifuge @ 1230 - Blow Tubes #1 & 2 - 1315-1325 - Pumped by Spec Bilge -

F.O. OUTBD
F.W.
MUP DB/15
MU-U 6.4
EVAP 142
GAL-D 820

WATCH ENGR'S SIGNATURE - M. Fox

1600-2000 WATCH

Machinery as before except: checked and pumped bilges, made routine rounds, changed L.O. strainers, changed fuel oil strainers, changed and cleaned bottom burner P's. Turned heat on at 1800.

F.O. OUTBD
F.W. 34
MUP DB/15
MU-U 5.7
EVAP 142
GAL-D 8750

WATCH ENGR'S SIGNATURE - Sub. Park

2000-2400 WATCH

Underway on 16 Nozzle - Machinery in operation as before close water tight doors @ 2025 - changed & clean main L.O. strainers - check steering gear @ 2130 - pumped engine room bilges - retard clock 20 minutes @ 2300 - made routine rounds & inspection of machinery.

Hypoc. 101
No SE
DB/15
6.8
2 P45
9200

WATCH ENGR'S SIGNATURE - R. P. Adams

2400-0400 WATCH

Machinery as before, except; changed to Inboard Letter @ 0030 - Let Clock Back 20 minutes @ 0038 - changed & cleaned Upper Fuel oil Burners & Fuel oil Suction Strainers - Pumped by Spec Bilge - Electric Steering Failure @ 0330 & Steering by Repeater.

F.O. INBD
F.W. 34
MUP DB/15
MU-U 6.4
EVAP 142
GAL-D 9200

WATCH ENGR'S SIGNATURE - M. Fox

0400-0800 WATCH

Machinery as before except: retarded clock @ 0500. changed and cleaned bottom fuel oil burners. cleaned L.O. strainers. Pumped bilges. checked machinery in engine space. made routine rounds. Small leak on F.W. discharge line from tank to pumps - line giving way.

F.O. INBD
F.W. 34
MUP DB/15
MU-U
EVAP 142
GAL-D 9200

WATCH ENGR'S SIGNATURE - R. P. Adams

0800-1200 WATCH

Underway on 16 Nozzle - Machinery in operation as before - Blow Tubes P's Boilers @ 0810 to 0828 - see air compressor Utility man working on same @ 0854 - cross over open from AFT ENG. AIR COMP. tested fire alarm @ 0853 - changed & clean center Burners @ 0910 - changed to out B'D seat @ 1100 - checked steering gear - made routine rounds & inspection of machinery

F.O. OUTBD
F.W. 34
MUP DB/15
MU-U 8.6
EVAP 34
GAL-D 8600

WATCH ENGR'S SIGNATURE - R. P. Adams

CHIEF ENGINEER

2 BOILER /

5.16 P. ALK 2.9
7.01 T. ALK 4.67
7.97 GHLO 2.07
25 PH. 4.5
55 SO. 3.5
PH
4254 WS. HRS. 4105
1606 FS. HRS. 1570

CHIEF ENGR'S SIGNATURE - R. P. Adams

USS *John Pope* *DD-110* VOYAGE NO. *4B* FROM *Pacoma Hash* TO *Opa, Okinawa* TYPE OF VESSEL *DD-110* DATE *JULY 25-26-1966*

		WATCH								WATCH																	
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200												
RUNNING TIME		240	240	240	240	240	240	MACH. PARTICULARS (CONT'D)		TEMPERATURES (CONT'D)		HOTTEST GEAR BEARING FORWARD						157	156	156	157	155	157				
DETENTION TIME												HOTTEST GEAR BEARING AFT						153	148	148	148	148	148				
REVOLUTION COUNTER (END OF WATCH)		0514 0360	0516 3000	0518 5698	0520 8470	0523 1200	0525 3869					AUX. COND. CONDENSATE						90	95	92	96	98	97				
TOTAL REVOLUTIONS (FOR WATCH)		22600	22630	22678	22780	22730	22669					1ST STAGE FEED WATER HEATER						148	153	154	150	151	152				
AVERAGE RPM		94.1	94.2	94.5	94.9	94.7	94.5					D. C. FEED WATER HEATER						240	238	240	240	240	240				
F.O. METER (END OF WATCH)		8795 080	8797 510	8799 910	8802 350	8804 790	8807 160					3RD STAGE FEED WATER HEATER															
F.O. CONSUMED		2430	2430	2400	2440	2440	2370					BOILER PARTICULARS		TEMPERATURES		SUPER HEAT						P 770	795	790	790	780	815
PRESSURES		THROTTLE		445	445	445	445									445	440	S 770						745	630	790	780
		H.P. AHEAD		425	425	425	425	425	420	F.O. TO BURNERS						180	180	180	180	190	184						
		L.P. AHEAD		19	19	19	19	18	18.5	AIR TO FURNACE						P 130	127	126	128	126	129						
		VACUUM		29"	29"	29"	29"	29"	27.4	S 130						127	126	128	126	127							
		L.O. TO TURBINES		14	14.5	14.4	14	14	14.4	F.O. TEMP. IN SETTLING TANKS						P 104	100	100	98	100	104						
		AUX. STEAM		140	135	135	140	135	135	S 102						102	98	102	104	104							
		BACK PRESSURE		9	9	9	9	9	9	PORT BOILER UPTAKE						315	294	315	320	331	295						
		GLAND STEAM		2	2	2	2	2	2	STBD. BOILER UPTAKE						300	295	300	300	308	295						
		H.P. BLEEDER		80	80	80	80	75	85	F. O. BACK PRESSURE						12	12	11	12	10	11						
		L.P. BLEEDER		6	6	6	6	6	6	MAIN STEAM						460	460	465	460	460	465						
		L.P. BLEEDER		12"	12"	12	12"	12	12	F.O. TO BURNERS						175	185	190	180	190	185						
TEMPERATURES		STEAM AT THROTTLE		690	670	655	655	675	685	MISCELLANEOUS		MAIN COND. SALINITY						.4	.8	.4	.4	.5	.4				
		L. P. EXHAUST		90	94	95	95	95	97			ENGINE ROOM TEMPERATURE						76	73	72	72	72	76				
		CONDENSATE		85	88	87	88	90	91			FIRE ROOM TEMPERATURE						76	73	72	72	72	76				
		CIRC. WATER IN		61	62	64	65	65	66			NOZZLES IN USE						16	16	16	16	16	16				
		CIRC. WATER OUT		71	74	74	74	75	76			NO. OF BURNERS IN USE						P 3	3	3	3	3	3				
		L.O. TO COOLERS		130	130	130	130	130	130			S 3						3	3	3	3	3					
		L.O. FROM COOLERS		110	110	110	110	110	110			BURNER TIP SIZE						P 5370	5370	5370	5370	5370	5370				
		TEMPERATURE THRUST BEARING		120	120	118	120	120	120			S 5370						5370	5370	5370	5370	5370					
		FORWARD H.P. ROTOR BEARING		126	124	125	126	125	125			CO ₂ % PORT BOILER						13.5	13.5	14	13	13.5	14				
		AFT. H.P. ROTOR BEARING		138	138	136	136	136	136			CO ₂ % STBD. BOILER						13.5	13.5	14	14	13.5	14				
		FORWARD L.P. ROTOR BEARING		135	132	133	134	131	133			OIL LEVEL MAIN SUMP						12"	12"	1'	12"	12"	1'				
AFT. L.P. ROTOR BEARING		132	130	131	132	130	131	POWDER BOTTOM SAL.						14	4		4	4									

GENERATORS											FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	METER AT NOON	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND
1200 TO 1600	2	1200	445	770	7	132	120	77	1400	1400	290		37.710	82	69	113
													METER PREVIOUS NOON			
													30.860			
													CONSUMED BY METER			
													ON HAND AT START OF DAY			
													15.690			
													RECEIVED DURING DAY			
													EXPENDED DURING DAY			
													14.955			
													REMAINING ON BOARD			
1600 TO 2000	2	1200	445		7	134	120	73	1250	1250	240		ON HAND AT START OF DAY			
													1030			
													EVAPORATED OR RECEIVED			
													120			
													ON HAND			
													950			
													CONSUMED			
													200			
2000 TO 2400	2	1200	445		7	134	120	73	1250	1200	240		LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)			
													4 hrs.			
2400 TO 0400	2	1200	445		7	132	120	73	1200	1200	240		L.O. CENTRIFUGE HOURS OPERATED			
													1200 TO 1600			
													1600 TO 2000			
													2000 TO 2400			
													2400 TO 0400			
													0400 TO 0800			
													0800 TO 1200			
													4	4	4	4
0400 TO 0800	2	1200	445		7	134	120	73	1150	1150	240		SUMMARY			
													RUNNING TIME	1440	PROPELLER SLIP (%)	14.20
													DETENTION TIME	✓	BBL FUEL/MI	1.47-1.71
													TOTAL REVOLUTIONS	134,260	WIND DIRECTION	320°-5Kt
													AVERAGE R.P.M.	93.2	STATE OF SEA	320°-1 ft
													TOTAL MILES BY ENGINE	500	STATE OF WEATHER	pt-Cloudy
													TOTAL MILES BY OBSERVATION	429	S=17.87	A=61°
0800 TO 1200	2	1200	440		7	134	122	73	1200	1200	240					

REMARKS

1200-1600 WATCH

Underway on 16 nozzle - Machinery in operation as of Noon. Main Unit, B-1, B-2, E.O. OUTB.D.
 G-2, H-1, MC-2, ME-2, D-1, D-2, P-1, P-2, F-1, F-2, W-1, L-1, S-1, LC-1, - Found Bay Box Check Valve Installed W. way on M.U. F. & L. Line, changed around & ran Bottom Blow from #2 Boiler 1230-1430 - S. B. E. @ 1257, F.W. 32
 Poor Visibility - LH @ 1402 $\frac{1}{2}$ - Ship's Force Working on Main Air Comp. & Air Cond. Unit - Blew, MUF 08/15
 Suber #1 & 2 Boilers 1515-1530 - Pumped Eng. Space Bilges - S. B. E. @ 1535, MU-U 7.1
 Poor Visibility - changed to Inland Settle @ 1540, EVAP #142
 GAL-D 8600

WATCH ENGR'S SIGNATURE-

M. Fox

1600-2000 WATCH

Machinery as before except, cleaned generator strainer, cleaned, F.O. 4600
 suction fuel oil strainer, pumped engine bilges. Inspected machinery, F.W. 34
 and spaces, made routine rounds. Oil checked reefers and, MUF 08/15
 recorded temperature readings. Day workers working on air compressors, MU-U 5.7
 air conditioner, and F.W. pump line leak. on stby all watches, EVAP #142
 GAL-D 8600

WATCH ENGR'S SIGNATURE-

J. H. Burk

2000-2400 WATCH

Underway on 16 nozzle - machinery operating as before - F.W. F.O. 4600
 pump shut off - Air compressor sec - Relieved watch on standby, F.W. 34
 oiler checked reeper flat @ 2000 - full ahead from Standby @ 2159, MUF 08/15
 clean & changed L.O. strainer on G-2 - oiler checked reeper flat @ 2200, MU-U 6.0
 Standby because of fog - Leak in cold F.W. pipe over light fixture sec, EVAP 15
 with through line @ 2245 - pumped Bilges - checked steering Eng. R.M. sec, GAL-D 7900
 Standby @ 2321 $\frac{1}{2}$, 2-130-1-L

WATCH ENGR'S SIGNATURE-

R. P. Adams

2400-0400 WATCH

Machinery as before, except: - changed & cleaned fuel oil upper burner, F.O. OUTB.D.
 Section of Port Hot Strainer - changed to Outboard Settle @ 0230 - Oiler checked Reeper, F.W. 34
 Machinery as before - Pumped fog space Bilges - MUF 08/15
 MU-U 6.4
 EVAP #142
 GAL-D 8600

WATCH ENGR'S SIGNATURE-

M. Fox

0400-0800 WATCH

Machinery as before except - added 3 gal L.O. to P-2, Oiler made F.O. 4600
 round and checked reefers. Checked steering engine room, checked, F.W. 34
 machinery spaces and pumped bilges. @ 0615 2nd mate reported leak, MUF 08/15
 in wheel - still steering engine. Mr. Eng. reports everything normal. Chief in S.B. @ 0720, MU-U 4.9
 GAL-D 8600

WATCH ENGR'S SIGNATURE-

J. H. Burk

0800-1200 WATCH

Underway on 16 nozzle - machinery operating as before - sec standby @ 0812, F.O. 4600
 Blew tubes from 0755 to 0815 - changed to m.B.D. sett @ 0848 - Electrician cleaning, F.W. 34
 G-1 from 0815 to 1000 - tested fire alarm @ 0915 - changed & clean center, MUF 08/15
 Burner @ 0930 - Disregarded alarm test as ordered by bridge @ 0932 - MU-U 7.4
 checked steering Eng. @ 1010 - tested L.O. standby pump works satisfactory, EVAP 34
 Chief in Eng. R.M. @ 1040 - Clean P.F.O. discharge strainer @ 0835 - Clean Bilge, GAL-D 8800
 Pump strainer - HP - 1049 LP - 089

WATCH ENGR'S SIGNATURE-

R. P. Adams

CHIEF ENGINEER

2 BOILER /

8.18 P. ALK 6.42

11.68 T. ALK 8.76

6.21 CHLO 2.9

30.11.4.25

SO. 3

10.5 PH 10.5

4278 WS. HRS. 4139

1630 FS. HRS. 1579

CHIEF ENGR'S SIGNATURE-

J. H. Burk

DATE July 26-27 1966

USNS	VOYAGE NO.	FROM	TO	TYPE OF VESSEL	DATE
Gen John Pope TAB-110	43	Pacoma, Wash.	Paha, Okinawa	B-2 S-2 R-2	July 26-27, 1966
WATCH		WATCH		WATCH	

		WATCH								WATCH					
		1200 TO 1800	1800 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME		240	240	240	260	260	240								
DETENTION TIME															
REVOLUTION COUNTER (END OF WATCH)		0527 6630	0529 9270	0532 3859	0534 8460	0537 3020	0539 5682								
TOTAL REVOLUTIONS (FOR WATCH)		22770	22640	24589	24610	24560	22662								
AVERAGE RPM		94.8	94.3	94.5	94.6	94.4	94.4								
F.O. METER (END OF WATCH)		8809 570	8811 970	8814 610	8817 240	8819 890	8822 330								
F.O. CONSUMED		2410	2400	2640	2630	2650	2440								
PRESSURES	THROTTLE	440	445	440	440	445	445								
	H.P. AHEAD	420	425	420	420	425	425								
	L.P. AHEAD	19	19	19.5	19.5	19.5	20								
	VACUUM	29"	29"	29"	29"	29	29"								
	L.O. TO TURBINES	14	14.5	14.4	14	14	15								
	AUX. STEAM	140	135	135	140	135	137								
	BACK PRESSURE	9	9	9	9	9	9								
	GLAND STEAM	✓	1	2	2	1	2								
	H.P. BLEEDER	80	80	80	80	80	80								
	I.P. BLEEDER	6	6	6	6	6	6								
	L.P. BLEEDER	11"	12	12	12"	12	12								
	TEMPERATURES	STEAM AT THROTTLE	670	675	665	660	660	670							
L. P. EXHAUST		98	100	100	98	100	102								
CONDENSATE		90	94	93	93	95	97								
CIRC. WATER IN		68	70	68	68	70	72								
CIRC. WATER OUT		78	80	80	80	80	82								
L.O. TO COOLERS		128	129	128	130	128	129								
L.O. FROM COOLERS		110	110	110	110	110	110								
TEMPERATURE THRUST BEARING		120	120	120	120	120	120								
FORWARD H.P. ROTOR BEARING		140	136	125	125	125	125								
AFT. H.P. ROTOR BEARING		136	136	136	136	136	137								
FORWARD L.P. ROTOR BEARING		132	133	133	132	132	134								
AFT. L.P. ROTOR BEARING		130	131	131	131	131	130								
HOTTEST GEAR BEARING FORWARD		157	156	156	156	156	157								
HOTTEST GEAR BEARING AFT		146	148	148	148	147	147								
AUX. COND. CONDENSATE		160	102	95	100	102	102								
1ST STAGE FEED WATER HEATER		153	154	155	152	154	156								
D. C. FEED WATER HEATER		240	240	238	240	242	238								
3RD STAGE FEED WATER HEATER															
TEMPERATURES	SUPER HEAT	P 820	810	765	770	785	800								
		S 820	810	620	770	785	610								
	F.O. TO BURNERS		180	180	180	180	185								
	AIR TO FURNACE	P 130	131	129	132	134	132								
		S 130	131	129	132	134	132								
	F.O. TEMP. IN SETTLING TANKS	P 180	102	102	102	98	116								

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL																									
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL				BOILER WATER		LUBE OIL		DOMESTIC WATER		DIESEL OIL															
1200 TO 1600	2	1208	440		7	134	122		72	1250	1250	241	METER AT NOON	69.820		ON HAND AT START OF DAY	113	EVAPORATED OR RECEIVED	17	ON HAND	96	CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	—		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
1600 TO 2000	2	1200	440		7	136	124		73	1250	1250	240	RECEIVED DURING DAY	—		ON HAND AT START OF DAY	950	EVAPORATED OR RECEIVED	190	ON HAND		CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	765		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
2000 TO 2400	2	1200	440		7	136	124		72	1100	1100	240	RECEIVED DURING DAY	—		ON HAND AT START OF DAY	950	EVAPORATED OR RECEIVED	190	ON HAND		CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	765		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
2400 TO 0400	2	1200	440		7	134	122		72	1150	1150	240	RECEIVED DURING DAY	—		ON HAND AT START OF DAY	950	EVAPORATED OR RECEIVED	190	ON HAND		CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	765		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
0400 TO 0800	2	1200	445		7	136	124		72	1200	1150	240	RECEIVED DURING DAY	—		ON HAND AT START OF DAY	950	EVAPORATED OR RECEIVED	190	ON HAND		CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	765		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
0800 TO 1200	2	1200	445		7	136	124		72	1350	1350	210	RECEIVED DURING DAY	—		ON HAND AT START OF DAY	950	EVAPORATED OR RECEIVED	190	ON HAND		CONSUMED BY METER	32.110		ON HAND AT START OF DAY	14.955		RECEIVED DURING DAY	765		ON HAND AT START OF DAY	3285		EXPENDED DURING DAY	765		RECEIVED	—
														LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)																								
														1-2 4Hrs. 142 4Hrs.																								
														L.O. CENTRIFUGE HOURS OPERATED																								
														1200 TO 1600 1600 TO 2000 2000 TO 2400 2400 TO 0400 0400 TO 0800 0800 TO 1200																								
														4 4 4 1/3 4 1/3 4 1/3 4																								
														SUMMARY																								
														RUNNING TIME		1500		PROPELLER SLIP (%)		13.71																		
														DETENTION TIME		✓		BBL FUEL/MI		1.45 - 1.68																		
														TOTAL REVOLUTIONS		140.820		WIND DIRECTION		150° - 5 kts																		
														AVERAGE R.P.M.		93.88		STATE OF SEA		150° - 4'																		
														TOTAL MILES BY ENGINE		52.5		STATE OF WEATHER		Clear																		
														TOTAL MILES BY OBSERVATION		45.3		S=18.12		A=71°																		

1200-1600 WATCH

Underway on 16 nozzles - Machinery in operation as of Norm: Main unit, B-1, B-2, E-2, H-1, H-2, HE-R, AE-R, D-1, D-2, P-1, P-2, F-1, F-2, L-1, S-1, LC-1, - Shaking on M.W.P. & Fuel Controller - Ship's Force Shaking on Main Air Compressor - Blow down Surge Blower #1 & #2 - Blow Tube #1 & #2 Blower @ 1515-1530 - Second Heating Blower B/C Chief Engr. - Fresh Water Second 1200 for Repair; on @ 1420 - Pumped Eng. from Bilge - changed from S-1 to S-2 @ 1300 -

F.O. INRD
F.W. 3 1/5
MUF 15/15
MU-U 6.4
EVAP 142
GAL 1 8900

WATCH ENGR'S SIGNATURE-

J. H. Fox

1600-2000 WATCH

Underway on 16 nozzles. Machinery as before. Pumped E.R. Bilges. Cleaned L.O. strainers main engine cleaned L.O. strainers on E-2. Made routine rounds and checked machinery spaces. Changed lower burner. Oiler checked reeper spaces and obtained readings. Stby @ 1910 - Full ahead @ 1915. Steam leak on return from fuel heater for bulkhead. Stby @ 1945. Standing Valve open.

F.O. outboard
F.W. 3 1/5
MUF 15/15
MU-U 5.7
EVAP 142
GAL-D 4,000

WATCH ENGR'S SIGNATURE-

S. H. Burk

2000-2400 WATCH

Underway on 16 nozzles - machinery as before - full ahead from standby @ 1959 - oil leak in compartment 2-62-0-L (seepage from sounding tube) @ 2045 - Clean M.L.O. strainer & changed over @ 2145 C & C L.O. strainer on G-2 - oiler made rounds & inspection of upper plot @ 2000 & 2200 - pumped E.R. Bilges - Retard clock 20 min. @ 2300 - made routine rounds & inspection of spaces.

F.O. outboard
F.W. 3 1/5
MUF 15/15
MU-U 6.0
EVAP 3 1/2
GAL-D 10,000

WATCH ENGR'S SIGNATURE-

R. P. Calamini

2400-0400 WATCH

Machinery as before, exact: - changed & cleaned upper fuel oil Burners & Suction Strainer - Set clock back 20 minutes @ 0046 - changed to Inboard Settler @ 0055 - oiler made Refr. Rounds - Pumped Eng. Space Bilges - added 2 Sals Lube oil #1 Red Pump -

F.O. INRD
F.W. 3 1/5
MUF 15/15
MU-U 5.7
EVAP 142
GAL-D 9900

WATCH ENGR'S SIGNATURE-

M. Fox

0400-0800 WATCH

Underway 16 nozzles. Machinery as before. Made temporary repairs on fuel oil return line on fuel bulkhead. Retarded clock 20 min. @ 0500. Cleaned bottom burners. Oiler made reeper rounds. Pumped E.R. Bilges. Carried out Standing orders.

F.O. INRD
F.W. 3 1/5
MUF 15/15
MU-U 7.5
EVAP 142
GAL-D 9,800

WATCH ENGR'S SIGNATURE-

S. H. Burk

0800-1200 WATCH

Underway on 16 nozzles - machinery as before - Blow tubes from 0805 - 0820 F.W. sec from 0845 - 0900 - pump No. 1 P/S hold @ 0900 - C & C Center Burners @ 0930 - Test fire alarm @ 1002 1/2 - pump E.R. Bilges - sec F.W. pumps @ 1035 steam pumps on line - C & C P.F.O. strainers - changed to old B.O. cell - made routine rounds & inspection of machinery -

F.O. outboard
F.W. 3 1/5
MUF 15/15
MU-U 6.8
EVAP 3 1/2
GAL-D 8600

WATCH ENGR'S SIGNATURE-

R. P. Calamini

CHIEF ENGINEER

V BOILER /

8.18 P. ALK 9.34
11.69 T. ALK 12.26
4.16 CHLO 3.31
40 PH. 4 45
3030. 3 50
10.5 PH 10.5
430 W3. HRS. 4163
1654 W3. HRS. 1603

CHIEF ENGR'S SIGNATURE-

J. H. Fox

USNS Gen. John Pope 200-110 VOYAGE NO. 4B FROM Reina Luch TO Naha Okinawa 29-28-1966

WATCH							WATCH																
1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200		1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200	
MACHINERY PARTICULARS																							
TEMPERATURES																							
PRESSURES																							
MISCELLANEOUS																							
FUEL - WATER AND LUBE OIL																							
L.O. CENTRIFUGE - HOURS OPERATED																							
SUMMARY																							

1200-1600 WATCH

Underway on 16 Nozzles: Machinery in operation as of 2000. Main Dist. B-1, B-2, E-1, H-1, MC-1, MC-2, ME-R, AE-R, D-1, D-2, P-1, P-2, F-1, F-2, L-1, S-2, LC-1, - Blow Down Storage Tanks #1 & 2. Bites - Blow Tanks #1 & 2 Bites 1515-1530 - Demand 50 lb. Steam & opened X-over from aft. Eng. Room, Ship Force Working on Leach in Line - Pumped Eng. Space Bilges. S.B.R. @ 1300 Collision Drill #1 @ 1321

WATCH ENGR'S SIGNATURE - M. Fox

1600-2000 WATCH

Machinery as before except - air compressor casualty. @ 1740. Plant back on line @ 1755 - 18 Nozzles B/O of Chief Engineer in Engine room 1740 - 1755. Made routine round and inspection of machinery spaces. Checked steering engine room. Pumped bilges. Read depth gauge and checked reefers. Day workers working on West return line and compressor in F.W.E.R.

WATCH ENGR'S SIGNATURE - J.H. Brink

2000-2400 WATCH

Underway on 18 Nozzles - machinery as before - started L.O.P. pump to pump C 2045 - C & C 6-2 - C & C M.L.O. Strainers C 2130 - fr. Eng. investigated ventilation blower 186-5 in compartment 2-7 because says could not be started by controller button or reset button call out electrician C 2130 - pumped Eng. Bilges - main air compressor sec - close over from AFT E.R. - retard clock 20 min C 2301 - made routine rounds & inspection -

WATCH ENGR'S SIGNATURE - R.P. Adams

2400-0400 WATCH

Machinery as before, except: - Set clock back 20 minutes @ 0039 - Added 2 1/2 Gal. Fuel oil #2 Fuel Pump - changed & cleaned upper fuel oil Burners & Suct. Strainers - changed to outboard Settler C 0230 - Steam on 3 1/2 & 4 1/2 Fuel oil Tank ht. coils @ 0100 - Blow Down Storage Tanks #1 & 2 Bites - Pumped Eng. Space Bilges -

WATCH ENGR'S SIGNATURE - M. Fox

0400-0800 WATCH

Machinery as before, Except. Retarded clock 20 minutes @ 0500. Checked steering engine room - pumped up main. Checked reefers and reported readings. Pumped bilges in E.R. Changed lower burners and cleaned. Cleaned secondary strainer on #2. Air compressor back on - cross over open - there seems to be trouble looking or kicking in. Chief Eng in E.R. @ 0730 - 140.

WATCH ENGR'S SIGNATURE - J.H. Brink

0800-1200 WATCH

Underway on 18 nozzles - machinery as before - Blow Tanks from 0800 to 0820 - STB'D F.P. Trip out C 0810 Reset on line C 0812 - Test fire alarm C 0836 - changed to INB'D at C 0850 - C & C center Burners @ 0900 - Chief in E.R. - fr. Towed Tugs through Eng space 1000 to 1100 - C & C P.F.O. strainers - 18 & Utility men working on air compressor - Air compressor on line close over after supplying AFT E.R. @ 1130 -

WATCH ENGR'S SIGNATURE - R.P. Adams

CHIEF ENGINEER

Chief Elect. Completed Weekly Check of All Safety devices as per check off list - Everything in satisfactory condition - P/H.

1.40 P. ALK 8.18
9.34 T. ALK 12.46
4.14 CHLO 5.31
40. PH. 4 42
53. SO. 3.50
10.5 PH 10.5

4326 WS. HRS. 14187
1678 FS. HRS. 1617

CHIEF ENGR'S SIGNATURE - J. Halloran

1200-1600 WATCH

Underway on 18 Nozzles: Machinery in operation as of Noon. Main Unit, B-1, B-2, G-2, M-4, MC-2, ME-3, E-1, E-2, D-1, D-2, P-1, P-2, F-1, F-2, C-1, L-1, S-2, LC-1. Blew down Storage Blower #4 - Bilge - Blew Tank #1/2 Bilge 1515-1530 - Pumped Eng. Spec Bilge -

F.O. INBD
F.W. 32
MUF DB/15
MU-U 6.4
EVAP 32
GAL-D 5400

WATCH ENGR'S SIGNATURE-

M. Fox

1600-2000 WATCH

Underway on 18 Nozzles. Machinery as before excepts changed and cleaned L.O. Strainers on Q-2. Strainer clean. Cleaned and changed lower burner. Cleaned and changed main L.O. discharge strainer. Pumped E.R. bilges. Made routine rounds and inspections.

F.O. outbd
F.W. 36
MUF DB/15
MU-U 5.7
Evap 32
GAL-D 6900

WATCH ENGR'S SIGNATURE-

J. H. Burk

2000-2400 WATCH

Underway on 18 nozzles - Machinery as before - C & C M.L.O. Strainer C & C G-2 Strainer - Held casualty drill E-1 four men present Low Water in bilge; loss of feed water pressure @ 2030 to 2045 - Check steering Engine R.M. @ 2200 - Lower bilge @ 2-149 2nd deck left of gangway @ 2220 - Start clock 20 min @ 2300 - Pumped Eng. R.M. Bilge - made routine rounds & inspection of machinery -

F.O. outbd
F.W. 32
MUF DB/15
MU-U 7
EVAP 35
GAL-D 9200

WATCH ENGR'S SIGNATURE-

R. P. Ahlani

2400-0400 WATCH

Machinery as before, except - changed to Inboard Litter @ 0015 - Set Clock Back 20 minutes @ 0042 - changed & cleaned upper fuel oil Burners & suction strainer - Conducted Eng. Casualty Drill "E-1" - 0200-0220 4 men present, Notified Bridge - Pumped Eng. Spec Bilge -

F.O. INBD
F.W. 32
MUF DB/15
MU-U 6.4
EVAP 32
GAL-D 8200

WATCH ENGR'S SIGNATURE-

M. Fox

0400-0800 WATCH

Machinery as before except - cleaned bottom burners, pumped E.R. bilges. Retarded clock @ 0440. Checked steering E.R. Held Engine casualty drill "E-1" 0500 - 0530. 4 men present, Notified Bridge. 0510 Purifier exhausted oil to bilge out water drain. Gauge dropped about 3 feet. Condensate pump, kicked out, slowed down, put no/ and pump down @ 0520 to 0550. Oil wiped off deck plate. In. Engineer check out toaster malfunction @ 0605 checked oil from storage to sump - 062. Purifier secure

F.O. outbd
F.W. 32
MUF DB/15
MU-U 6.4
EVAP 32
GAL-D 8400

WATCH ENGR'S SIGNATURE-

J. H. Burk

0800-1200 WATCH

Underway on 18 nozzles - Machinery as before - Blew tank from 0810 to 0827 - Test fire alarm 0845 1/2 - changed & clean center Burner @ 0900 - changed to outbd sett @ 0847 - upon test to compartment @ 0855 - shut fuel @ 1110 - C & C P.F.O. strainer - Chief Elect reported #2 M. Condensate pump ready for use - C & put L.O.P. on line @ 1105 - made routine rounds & inspt. of machinery -

F.O. outbd
F.W. 34
MUF DB/15
MU-U 7.5
EVAP 35
GAL-D 4000

WATCH ENGR'S SIGNATURE-

R. P. Ahlani

CHIEF ENGINEER

0400-0800 - Ch. Eng in engine 0520 - 0550. Electrician checking main condensate noz. 0725 Eng no/ being secured by Eng man.

✓ BOILER 1

10.51 P. ALK 7.29
14.60 T. ALK 11.68
4.14 CHLO 3.31
35 PH. 4 50
60 SO. 3 50
10.5 PH 10.5
4350 WS. HRS. 4211
1690 FS. HRS. 1651
1704

CHIEF ENGR'S SIGNATURE-

J. H. Burk

REMARKS

1200-1600 WATCH

Underway on 18 nozzles. Machinery in op. as of 200. Main unit, B-1, B-2, F.O., INBD, F.W. 32, MUF DB/17, MU-U 6.7, EVAP 3.5, GAL-D 3.6.

G-2, H-1, MC-1, ME-R, E-2, D-1, D-2, P-1, P-2, F-1, F-2, C-1, L-1, S-2, LC-1. Second LC-1 @ 1330 -
 Blow 1st 1/2 Boiler @ 1515-1530 - Pumped Eng. Space Bilge -

WATCH ENGR'S SIGNATURE - M. Fox

1600-2000 WATCH

Underway on 18 nozzles. Machinery as before, except: Pumped 70. - Inboard E.R. bilges, cleaned main L.O. discharge strainers. Made routine 7.4 43 Q. sounds and inspections. Checked and pumped up reservoir on MUF DB-1/2. steering engine. Cleaned D-2 L.O. Strainers. MU-U 5.7, 2nd sound, EVAP. 2.2, 2.35, GAL-D 3700

WATCH ENGR'S SIGNATURE - S. H. Burk

2000-2400 WATCH

Underway on 18 nozzles - machinery as before - sounded L.O. storage 7K F.O., & set 7K by gage, storage 7', set 4' - H.P. Thrust .049 - LP .087 - checked F.W. MUF, MU-U, EVAP, GAL-D
 steering gear @ 2100 - C & C M.L.O. strainer @ 2105 - put L.O.P. on line @ 2200 - C & C G-2 strainer - made routine sounds & inspect. of machinery -

WATCH ENGR'S SIGNATURE - R. P. Adams

2400-0400 WATCH

Machinery as before, except: - changed & cleaned Fuel oil Section F.O., OUTBD, F.W. 3P, MUF DB/15, MU-U 6.4, EVAP 3.5, GAL-D 3700
 Strainer & Lower Upper Burner - changed to out-board sett @ 0245 -
 Added 2 Hds. Fuel oil #2 Fuel Pump - Pumped Eng. Space Bilge -

WATCH ENGR'S SIGNATURE - M. Fox

0400-0800 WATCH

Machinery as before, except. Added 3 gal L.O. to P-2. made routine sounds and checked machinery spaces. Checked steering engine room oil. Pumped E.R. bilges. Changed and cleaned lower burners. H/E exp. distilling to bilges - tested 10 grains. Ch. Eng. in Engine room @ 0735 - 0745 F.O., OUTBD, F.W. 3E, MUF DB/15, MU-U 6.0, EVAP 3.5, GAL-D 2300

WATCH ENGR'S SIGNATURE - S. H. Burk

0800-1200 WATCH

Underway on 18 nozzles - machinery as before - Blow tubes from 0810 to 0829 - STBD feed pump Trip out @ 0825 back on line immediately - C & C Center Burner @ 0900 - C & C P.F.O. strainer - Re-set L.O.P. @ 0950 - oil King running with - checked steering E.R. - made routine sounds & inspections - changed to salt water @ 1125 - F.O., INBD, F.W. 3P, MUF DB/15, MU-U 7.5, EVAP 3.5, GAL-D 7200

WATCH ENGR'S SIGNATURE - R. P. Adams

CHIEF ENGINEER

1730-1800 - Held Engineering Casualty Drill E-2 - Boiler tube failure. Four men present. Notified bridge. 2030-2045 - Held Casualty Drill E-2 Boiler tube failure. Four men present. Notified bridge.

2 BOILER 1

9.93P. ALK 7.01
 14.02P. ALK 11.10
 4.14CHLO 3.31
 3.5PH. 4 4.5
 2.5SO. 3 5.0
 10.5PH 10.5
 4374 WS. HRS. 4235
 1726 FS. HRS. 1645

Conducted Eng. Casualty Drill "E-2" 0200-0220 4 men Present
 Notified Bridge -

CHIEF ENGR'S SIGNATURE - J. A. Halleran

USS *Gen. John Pope* *DD-110* VOYAGE NO. *4 B* FROM *Panama, Canal* TO *Naha, Okinawa* *22-23-24 July 31-Aug 1, 1966*

91.500

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE					
John Cope PAB-110		4 B		Tacoma, Wash.		Naha, Okinawa		P22-2A-2		July 31-Aug					
		WATCH								WATCH					
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME		140	240	260				MACH. PARTICULARS (CONT'D) TEMPERATURES (CONT'D)	HOTTEST GEAR BEARING FORWARD	160	160	161			
DETENTION TIME									HOTTEST GEAR BEARING AFT	150	150	148			
REVOLUTION COUNTER (END OF WATCH)		0584 5580	0586 8360	0589 3230					AUX. COND. CONDENSATE	110	110	108			
TOTAL REVOLUTIONS (FOR WATCH)		23020	22780	24870					1ST STAGE FEED WATER HEATER	160	156	163			
AVERAGE RPM		95.9	94.9	95.7					D. C. FEED WATER HEATER	240	240	238			
F.O. METER (END OF WATCH)		8871 460	8874 118	8876 900					3RD STAGE FEED WATER HEATER						
F.O. CONSUMED		2520	2650	2790				BOILER PARTICULARS TEMPERATURES	SUPER HEAT	P	790	800	800		
PRESSURES	THROTTLE	445	445	440					S	790	800	625			
	H.P. AHEAD	425	225	420					F.O. TO BURNERS		180	180	185		
	L.P. AHEAD	22	19	23					AIR TO FURNACE	P	136	135	134		
	VACUUM	28"	28"	28"					S	136	175	134			
	L.O. TO TURBINES	16	16	16					F.O. TEMP. IN SETTLING TANKS	P	102	104	96		
	AUX. STEAM	140	140	140					S	100	114	126			
	BACK PRESSURE	9	9	9					PORT BOILER UPTAKE	2.7	295 42	244	300		
	GLAND STEAM	2	2	2					STBD. BOILER UPTAKE		310	302	315		
	H.P. BLEEDER	80	80	80					F. O. BACK PRESSURE		12	12	11		
	L.P. BLEEDER	6	6	6				MAIN STEAM		460	460	465			
L.P. BLEEDER	10"	11"	10					F.O. TO BURNERS		190	190	190			
TEMPERATURES	STEAM AT THROTTLE	680	675	680				MISCELLANEOUS	MAIN COND. SALINITY		.4	.4	.4		
	L. P. EXHAUST	105	107	110					ENGINE ROOM TEMPERATURE		90	90	91		
	CONDENSATE	102	104	108					FIRE ROOM TEMPERATURE		90	90	91		
	CIRC. WATER IN	76	80	77					NOZZLES IN USE		18	18	18		
	CIRC. WATER OUT	87	90	92					NO. OF BURNERS IN USE	P	3	3	3		
	L.O. TO COOLERS	128	128	130					S	3	3	3			
	L.O. FROM COOLERS	110	110	111					BURNER TIP SIZE	P	5370	5370	5370		
	TEMPERATURE THRUST BEARING	120	120	119					S	5370	5340	5370			
	FORWARD H.P. ROTOR BEARING	128	125	127					CO. % PORT BOILER		13	13.0	12.5		
	AFT. H.P. ROTOR BEARING	138	136	137					CO. % STBD. BOILER		12.5	13.5	12.5		
FORWARD L.P. ROTOR BEARING	135	133	135				OIL LEVEL MAIN SUMP		10"	10"	10"				
AFT. L.P. ROTOR BEARING	131	130	131					DOUBLE BOTTOM		.4	.4				

WATCH	GENERATORS											FUEL - WATER AND LUBE OIL																					
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL		DIESEL OIL														
1200 TO 1600	✓	1200	445	680	7	142	130		70	1500	1500	240	METER AT NOON	83350	ON HAND AT START OF DAY	68	METER PRE- VIOUS NOON	66.730	EVAPORATED OR RECEIVED	53	CONSUMED BY METER	16.620	ON HAND	98	ON HAND AT START OF DAY	5265	RECEIVED	-	ON HAND	5260	CONSUMED	23	
1600 TO 2000	2	1200	445	675	7	144	132		71	1350	1350	240	ON HAND AT START OF DAY	11.883	ON HAND AT START OF DAY	5265	RECEIVED DURING DAY	-	EXPENDED DURING DAY	396	REMAINING ON BOARD	11.487	ON HAND	5260	CONSUMED	5	ON HAND		RECEIVED		CONSUMED		
2000 TO 2400	2	1200	440	680	7	144	132		70	1400	1350	240	ON HAND AT START OF DAY	607	ON HAND AT START OF DAY		EVAPORATED OR RECEIVED	67	ON HAND	626	CONSUMED	48	ON HAND		ON HAND		RECEIVED		CONSUMED		CONSUMED		
2400 TO 0400													LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)																				
0400 TO 0800													L.O. CENTRIFUGE - HOURS OPERATED																				
0800 TO 1200													SUMMARY																				
													RUNNING TIME		740	PROPELLER SLIP (%)		13.46															
													DETENTION TIME		✓	BBL FUEL/MI		1.52-1.76															
													TOTAL REVOLUTIONS		69.650	WIND DIRECTION		100°-20 kts															
													AVERAGE R.P.M.		94.12	STATE OF SEA		100°-5 ft															
													TOTAL MILES BY ENGINE		260	STATE OF WEATHER		Clear															
													TOTAL MILES BY OBSERVATION		225	A=79° S=18 kts																	

REMARKS

1200-1600 WATCH

Underway on 18 nozzles: machining in op. as of noon: Main Unit, B-1, B-2, G-1, H-1, MC-1, ME-R, E-1, E-2, D-1, D-2, P-1, P-2, F-1, F-2, C-1, L-1, S-2, LC-1, #1 Feed Pump Drifted out @ 1415 - Back on Line Immediately - added 2 Hds. Lub. Oil #1 Feed Pump - Blow Tube #1 & 2 Back on 1515-1530 - Pumped Eng. Space Bilge - Che

F.O. INBD
F.W. 3²
MUF
MU-U DB 1.5
EVAP #1/2-3
GA

WATCH ENGR'S SIGNATURE-

M. Fox

1600-2000 WATCH

Machining as before, except: Purifier lost seal @ 1605 back on @ 1610 Chief electrician called out @ 1730 to check fluid supply in compartment 2-3. Checked steering engine room - pumped up reservoir: Pumped engine room bilges, make routine rounds and inspection. Cleaned and changed bottom burner.

F.O. - Inboard
F.W. - 2154P
MUF - DB-15
MU-U 5.3
EVAP #1-2-3-38
GA - D, 9.600

WATCH ENGR'S SIGNATURE-

J.H. Burk

2000-2400 WATCH

Underway on 18 nozzles - machining as before - close water tight door @ 2000 - C & C M.L.O.S and G-2 - checked steering E.R. - pumped Eng Bilge - Visual on 3-216 over - planning checked & sec. - made routine rounds and inspection of engine spaces - Retard clock 20 min @ 2300 - set steam heat to in 60, set @ 2335 -

F.O. Inboard
F.W. 2145
MUF DB 1P
MU-U 4.5
EVAP 30+15
GA 1066

WATCH ENGR'S SIGNATURE-

R.P. Adams

2400-0400 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GA - D

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GA - D

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GA - D

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

1830-1900 Held Engineering Casualty drill E-3. High Salinity in Boiler or Boilers. 7 crew men present. Notified bridge. Held casualty drill E-3 - High Salinity in Boiler or Boilers - Four crew present. Notified Bridge @ 2145 to 2200

9.34P ALK 10.51
13.43 T. ALK 14.02
7.04 CHLO 7.46
48 PH. 4 45
55 SO. 3 50
10.2 PH 10.5
4398 WS. HRS. 1259
1750 PS. HRS. 1699

CHIEF ENGR'S SIGNATURE-

J.A. O'Halloran

LOW PRESSURE DISTILLING PLANT OPERATING RECORD

UNDERWAY _____

U. S. #15. *Gen John Pope T-AP-110*

PLANT NO. _____

AT ANCHOR _____

TIME: ZONE DESCRIPTION

SET CLOCKS AHEAD OR BACK

20 min

MINUTES AT 2300-0100-0500

DATE 7-1

1966

DISTILLED WATER RECORD			
HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS*	FEED TANKS*
0000			
0100			
0200			
0300	06344900	5900	23
0400			23
0500			23
0600			23
0700	06350700	1400	4400 = 4 Hr 20 min.
0800			
0900			
1000			
1100	06321400		
1200	06356100	5400	
1300			
1400			
1500	06327000	5600	
1600			
1700			
1800			
1900	06332800	134	5800
2000			
2100			
2200			
2300	06339000	6200	
2400			

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD			
	EFFECT		
	NO. 1	NO. 2	NO. 3
DATE LAST SCALED	7-30-66	7-30-66	7-30-66
HOURS BROUGHT FORWARD	675	4	4
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	6000		
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			
APPROVED			
(Engineer Officer, U. S. N.)			

8-1-66
#1 Unit dist. to #3 stbd.
Refilled #1 Haza Vap tank.
SIGNED *H.M. Guinan*

0400-0800
#1 Unit Dist. to #3 stbd
0400 #1 port & stbd Test 2 drops
0500 shifted Dist to #1 port-Feed
pumped Bilges in Eucp & Refr Flat
0600 shifted Dist to #3
#1 port & stbd. Test 2 Drops 0730
SIGNED *R. Shppard*

0800-1200
#1 UNIT DIST TO
#3 CENTER LINE
SIGNED *E. J. Magallanes*

7-31-66
REMARKS
1255 - Dist to #3-Port.
1310 - 1335 - Dist to Bilge - Salt.
1335 - Dist to #3 Port.
Filled Haza Vap Tank
SIGNED *H.M. Guinan*

1200-1600
#1 Eucp. Dist. to #3 port
01600 shifted. Dist. to #1 stbd - Feed
#1 port & stbd Test 2 Drops.
pumped Bilges in Eucp & Refr Flats.
SIGNED *R. Shppard*

2000-2400
#1 UNIT DIST. TO #
3 STBD.
Added 802 @ HORINE
PER 1000 GALS.
SIGNED *E. J. Magallanes*

LOW PRESSURE DISTILLING PLANT OPERATING RECORD

UNDERWAY _____

U.S. NS Gen John Pope T-AP-110 PLANT NO. 2

AT ANCHOR _____

TIME: ZONE DESCRIPTION

SET CLOCKS ~~ON~~ **AHEAD** BACK 20 min

MINUTES AT 2300-0100-0500 DATE 7-1 19 66

#2-

DISTILLED WATER RECORD

HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS*	FEED TANKS*
0000			
0100			
0200			
0300	02225600		4400
0400			
0500			
0600			
0700	02229900	1000	3300 = 44 hr. 420 min
0800			
0900			
1000			
1100	02209400	3000	
1200	02233700	3800	
1300			
1400			
1500	02213000	3000	
1600			
1700			
1800			
1900	02216800	3800	
2000			
2100			
2200			
2300	02221200		4400
2400			

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD

	EFFECT		
	NO. 1	NO. 2	NO. 3
DATE LAST SCALED	6-6-66	6-6-66	6-6-66
HOURS BROUGHT FORWARD	850		
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	898600		
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			
APPROVED			
(Engineer Officer, U. S. N.)			

NAVSHIPS 3675 (REV. 11-50) BACK

REMARKS

8-1-66
#2 - Set dist to #1 - Stbd Feed TK.
44 hr. 420 min
SIGNED *H.M. Lurians*

0400-0800
#2 unit dist. to #3 stbd
20400 #1 port & stbd Test 2 drops.
20500 shifted dist to #1 port - Feed
Filled #2 Evap Tank
pumped B. 465 in Evap & Refr Flts
20700 shifted dist to #3
20730 #1 port & stbd Test 2 drops

SIGNED *R. Sheppard*

0800-1200
#2 Unit Dist to
#3 CENTER LINE

SIGNED *E. J. Magallanes*

Stocked in CDS

7-31-66
1255 - dist to #3. Port.
Added 8 g chlorine to 1000 gal water dist.
SIGNED *H.M. Lurians*

1200-1600
#2 Evap Dist to #3 port
#1 port & stbd Test 2 drops.
Added chlorine 8 g to each 1000 gals
Fresh water Dist

SIGNED *R. Sheppard*

2000-2400
#2 Unit Dist to
#1 STBD FEED.

SIGNED *E. J. Magallanes*

For disposal of this record see current Records Disposal Instructions for Vessels of the U. S. Navy.

7-23-66

#1

DISTILLED WATER RECORD

REMARKS

7-23-66

HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS *	FEED TANKS *
0000			
0100			
0200			
* 0300	06188700		
0400			
0500			
0600			
* 0700	06190400	1500	
0800			
0900			
1000			
SVN 1100	06194800	4400	
1200			
1300			
1400			
1500			
1600			
1700			
1800			
1900			
2000			
2100			
✓ 2200	06185700		
2300	06187100	1400	
2400			

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD

	EFFECT		
	NO. 1	NO. 2	NO. 3
DATE LAST SCALED	6-6-66	6-6-66	6-6-66
HOURS BROUGHT FORWARD	519		
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	782400	856000	
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			

APPROVED

(Engineer Officer, U. S. N.)

0000-0400

DOH 5 #1 - Brine outlet Pump
Stopped. Could not get started.
0050 - Sec #1 set of Evaps

SIGNED

H.M. Guinan

1200-1600

SIGNED

0400-0800

0415 called chief Elec. To start
#1 Brine pump. Burned out fuse.
0430 hit off #1 set of Evaps
0500 #1 set dist to #3 &
0500 set clocks back 20 min.

SIGNED

R. Sheppard

1600-2000

1900 hit off #1 set of Evaps
1930 #1 set of Evaps dist to
#2 port & stbd.

SIGNED

R. Sheppard

0800-1200

#1 UNIT DIST. TO #3
CENTER LINE
WASHED FLOOR PLATE w/
Soap & WATER.

SIGNED

E. J. Magallanes

2000-2400

#1 EVAP DIST. TO #2 PORT
& STBD. @ 2000 #1 BRINE
PUMP KICKED OFF. SECURED
PLANT. CALLED ELECT. STARTED
@ 2100. FRESH WATER METER
OUT OF ORDER.

SIGNED

E. J. Magallanes

LOW PRESSURE DISTILLING PLANT OPERATING RECORD

UNDERWAY ☒AT ANCHOR ☐USS. John N. POPE A-T-110PLANT NO. 2

TIME: ZONE DESCRIPTION

AHEAD
OR
BACK25 Min
1 hrMINUTES AT 2300-0100-0500 DATE 7-24

19

66

	7-24-66												7-25-66											
	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
STEAM TO REG. VALVE, PRESSURE #G	8	8	8	8	8	8	8	8	8	8	8						7	7	7	7	7	7	8	8
STEAM FROM REG. VALVE, PRESSURE #G	1	0	0	0	0	0	0	0	0	0	0						0	0	0	0	0	0	0	0
STEAM TO 1ST EFFECT, PRESSURE, #G OR #G	1	0	0	0	0	0	0	0	0	0	0						0	0	0	0	0	0	0	0
STEAM TO 1ST EFFECT, TEMPERATURE, °F	275	275	275	275	275	275	275	285	285	275	275						275	275	275	275	275	275	285	285
1ST EFFECT COIL DRAIN, TEMPERATURE, °F	180	186	186	186	180	180	180	185	185	185	185						170	170	170	170	170	170	180	180
1ST EFFECT SHELL PRESSURE, #G	12	10	10	10	12	12	12	12	12	12	12						14	14	14	14	14	14	12	12
2D EFFECT COIL DRAIN, TEMPERATURE, °F																								
2D EFFECT SHELL PRESSURE, #G	20	20	19	19	20	20	20	20	20	20	20						22	22	22	22	22	22	21	21
3D EFFECT COIL DRAIN, TEMPERATURE, °F	150	156	156	156	150	150	150	150	150	152	152						138	136	136	136	136	136	148	148
3D EFFECT SHELL PRESSURE, #G	24	23	22	22	23	23	23	23	23	23	23						24	24	24	24	24	24	26	26
CONDENSATE TO COOLER, TEMPERATURE, °F	139	146	146	146	138	138	138	142	142	142	142						128	128	128	128	128	128	138	138
CONDENSATE FROM COOLER, TEMPERATURE, °F	88	92	92	98	88	88	88	88	92	92	92						78	80	78	78	78	78	88	88
BRINE OVERBOARD, TEMPERATURE, °F	124	136	138	142	120	120	120	136	136	136	136						120	120	120	120	120	120	129	134
STEAM TO AIR EJECTOR, PRESSURE, #G	96	86	86	86	86	86	86	86	86	86	86						98	98	98	98	98	98	94	94
AIR EJECTOR DRAINS, TEMPERATURE, °F																								
CIRC. WATER INJECTION, TEMPERATURE, °F	60	60	60	60	60	60	60	62	62	62	62						60	60	54	54	54	54	60	60
CIRC. WATER TO CONDENSATE COOLER, TEMPERATURE, °F	60	60	60	60	60	60	60	62	62	62	62						60	60	54	54	54	54	60	60
CIRC. WATER TO DISTILLER CONDENSER, TEMPERATURE, °F																								
FEED TO AIR EJECTOR CONDENSER, TEMPERATURE, °F																								
FEED TO 2D EFFECT VAP. FD. HEATER, TEMPERATURE, °F	104	120	120	120	110	110	110	110	110	110	110						90	90	90	90	90	90	102	102
FEED TO 1ST EFFECT VAP. FD. HEATER, TEMPERATURE, °F	126	130	130	130	120	120	120	122	122	122	122						104	104	104	104	104	104	118	118
FEED TO 1ST EFFECT, TEMPERATURE, °F	140	148	148	148	134	134	134	135	135	135	138						120	120	120	120	120	120	132	132
CIRC. WATER OVERBOARD, TEMPERATURE, °F	108	108	108	108	100	100	100	104	104	104	104						82	82	82	82	82	82	94	94
CIRC. PUMP SUCTION PRESSURE, #G	7	6	6	6	6	6	6	6	6	6	6						5	5	5	5	5	5	6	6
CIRC. PUMP DISCHARGE PRESSURE, #G	22	22	22	22	22	22	22	22	22	22	22						21	21	21	21	21	21	22	22
BRINE PUMP SUCTION PRESSURE, #G	-16	-15	-15	-15	17	17	17	15	15	15	15						17	17	17	17	17	17	-16	-16
BRINE PUMP DISCHARGE PRESSURE, #G	16	19	19	18	17	17	17	17	17	17	17						16	16	16	16	16	16	17	17
FEED PUMP SUCTION PRESSURE, #G	20	21	21	21	20	20	20	20	20	20	20						18	18	18	18	18	18	19	19
FEED PUMP DISCHARGE PRESSURE, #G	39	40	38	38	36	36	36	37	37	37	37						33	33	33	33	33	33	37	37
1ST EFFECT DRAIN PUMP SUCTION PRESSURE, #G	-4	-1	-1	-1	5	5	5	4	4	4	4						12	12	12	12	12	12	-5	-5
1ST EFFECT DRAIN PUMP DISCHARGE PRESSURE, #G	45	46	45	45	45	45	45	40	40	40	40						41	41	41	41	41	41	45	45
F. W. PUMP DISCHARGE PRESSURE	10	12	10	10	14	14	14	14	14	14	14						10	10	10	10	10	10	10	10
FEED DENSITY, 32NDS																								
BRINE OVERBOARD DENSITY, 32NDS	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5						1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
F.W. TEST	.2	.2	.2	.2	.2	.2	.2	.2	.2	.2	.2						.2	.2	.2	.2	.2	.2	.2	.2
AIR EJECTOR DRAINS, SALINITY-E. P.					.06	.06	.06	.01	.01	.01	.01						.05	.05	.01	.01	.01	.01	.1	.1
1ST EFFECT DRAINS, SALINITY-E. P.	.1	.1	.1	.1	.05	.05	.05	.01	.01	.01	.01						.05	.05	.01	.01	.01	.01	.1	.1
CONDENSATE FROM COOLER, SALINITY-E. P.	.1	.1	.1	.1													.05	.05	.01	.01	.01	.01	.1	.1

DISTILLED WATER RECORD			
HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS*	FEED TANKS*
0000			
0100			
0200			
0300	02046600		
0400			
0500			
0600			
0700	02051700		4100
0800			
0900			
1000	02056100		4400
1100			
1200			
1300			
1400			
1500			
1600			
1700			
1800			
1900	02037000		
2000			
2100			
2200			
2300	02041600	4600	
2400			

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD			
	EFFECT		
	NO. 1	NO. 2	NO. 3
DATE LAST SCALED	6-66-66	6-6-66	6-6-66
HOURS BROUGHT FORWARD	686		
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	732600		
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			
APPROVED			
(Engineer Officer, U. S. N.)			

NAVSHIPS 3676 (REV. 11-50) BACK

7-24-66		REMARKS	7-23-66
0000-0400		#2 - Evap dist to #2-P & #2 Stbd. 0240- Dist. to #1-Stbd-	1200-1600
SIGNED			SIGNED

0400-0800	#2 Evaps Dist to #1 Stbd. Feed #1 Stbd. Test 2 drops - #1 port Test 4 Drops 00415. Filled Hageevap Tank @ 0300 0500 set clocks back 20 min	1600-2000	1600 hit off #2 set of Evaps 1700 #2 set of Evaps Dist to #2 port & Stbd
SIGNED <u>R. Shppard</u>		SIGNED <u>R. Shppard</u>	

0800-1200	#2 UNIT Dist. to #1 Stbd. FEED TEST @ 1145 = 2 DROPS	2000-2400	#2 EVAP Dist. to #2 Port & 2 Stbd. Filled HAGE EVAP TR Pump Bilge in EVAP Flat
SIGNED <u>E. J. Magallanes</u>		SIGNED <u>E. J. Magallanes</u>	

Stocked in CDS

For disposal of this record see current Records Disposal Instructions for Vessels of the U. S. Navy.

CENTRIFUGAL AIR CONDITIONING COMPRESSOR LOG

DATE 8-2-66

REMARKS 8-3-66

TIME	STEAM TO THROTTLE	STEAM TO NOZZLE	STEAM TO EXHAUST	STEAM & LUBE OIL	PURGE UNIT	PRESSURE				LUBE OIL TEMP	TEMPERATURE										DAMPER SETTING	SPEED RPM		
						COMPRESSOR LUBE OIL	SUCTION	DISCHARGE	COND WATER		CHILLED WATER	FREON IN COOLER	FREON IN CONDENSER	COND WATER		CHILLED WATER		BEARING		ROOM				
														IN	OUT	IN	OUT	IN	OUT				LINE	THRUST
0100	440	340	12	11	ON	16	18	9	118		5	14	26	46	102		84	88	47	43	136	78		3800
0200	440	330	12	11	"	14	15	10	120		5	14	26	46	104		84	88	57	53	124	80		2500
0300	440	340	11	11	"	15	18	9.5	120		5	14	26	46	104		84	88	47	43	134	78		3800
0400	440	340	12	11	"	16	21	9	120		5	14	26	46	104		84	88	46	43	136	79		3800
0500	440	340	12	11	"	16	21	9	116		5	14	26	46	104		84	88	46	43	136	79		3800
0600	440	340	12	10	"	16	21	9	115		5	14	26	46	102		84	88	46	46	138	79		3800
0700	440	340	12	10		16	21	7.5	115		5	14	26	43	103		84	88	48	44	138	80		3800
0800	440	330	12	10		15	18	8.5	120		5	14	26	46	102		83	87	49	45	135	79		3750
0900	430	320	12	10		15	18	9	120		5	14	26	46	102		84	88	51	47	135	80		3650
1000																								
1100																								
1200																								
1300																								
1400																								
1500																								
1600																								
1700																								
1800																								
1900																								
2000	440	350	13	11	ON	15	17	9.5	115		6	14	26	46	102		84	88	52	47	130	80		3700
2100	450	340	13	11	"	16	17	9	115		5	14	26	45	102		84	88	48	45	130	78		3750
2200	450	340	13	11	"	16	18	9	117		5	14	26	44	102		84	88	48	44	130	78		3800
2300	450	340	11	11	"	16	18	9	118		5	14	26	46	102		84	88	47	43	130	78		3800
2400	450	340	12	11	"	16	18	9	118		5	14	26	45	102		84	88	47	43	136	78		3800

0600-0400
20100
0100 Refill oil. 40 gals. with
0445 Turning back out on low
0400-0800
0400-0800

0800-1200

1200-1600

1200 Commence lighting
off A/C unit.
Chl. water 30 gals.

1600-2000

1900 let off A/C unit.

2000-2400

Routine work

Mann

8/3/66

8/2/66

TIME	CIRC WATER	COMPRESSOR 1			COMPRESSOR 2			COMPRESSOR 3			COMPRESSOR 4			COMPRESSOR 5		
	INLET TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP
0100	83				0	115	88	20	110	98	5	105	92	0	115	95
0200	83				0	115	88	10	115	98	—	—	—	0	115	95
0400	83				0	115	87	20	115	98	10	105	91	0	115	97
0600	83				0	115	88	20	115	99	9	105	91	0	115	94
0800	83				0	120	87	0	110	98	7	105	92	0	115	95
1000	81				0	115	87	5	115	99	13	110	92	0	115	95
1200	81				0	115	86	5	115	98	5	105	92	0	115	94
1400	82				0	115	86	20	105	98	10	110	92	0	115	94
1600	83				0	115	88	—	—	—	14	110	93	0	115	92
1800	82				0	115	90	10	115	98	15	110	93	0	115	95
2000	83				0	115	89	15	115	99	12	110	92	0	115	96
2200	83				0	115	90	—	—	99	7	110	92	0	115	96
2400	83				0	115	88	20	115	98	10	110	93	0	115	95

MAIN REEFER LOG: USNS GEN JOHN POPE (T-AP110)

DATE 8/2/66 + 8/3/66

COLD STORAGE BOX TEMPERATURES												REMARKS	
	ICE CREAM	DAIRY	MEAT	FROZ FOOD	THAW	MEAT	THAW	MEAT	VEG.	BUTT. EGGS	FRUIT		
TIME	1	2	3	4	5	6	7	8	9	10	11		
8/3/66 0100	-4	34	-1	2	23	-1	34	-3	35	34	37	0000-0400 0100 Retard all clocks one hour	
0200	-4	34	-1	2	23	-1	34	-3	35	34	37		
0400	-4	36	-2	2	18	-2	34	-2	35	34	37		
0600	-4	37	-2	2	25	-3	37	-4	35	36	38		
0800	2	37	0	2	39	-3	34	1	34	37	40	0400-0800 <i>Herigstad</i>	
8/2/66 1000	-1	42	0	6	44	-3	33	6	35	34	41	... <i>Beans</i>	
1200	-3	36	-1	6	34	-4	34	-2	35	34	40	0800-1200	
1400	-4	36	5	2	35	-3	34	-2	36	34	39	<i>Maroon</i>	
1600	-4	37	-1	4	34	-1	34	5	36	34	40	1200-1600	
1800	-4	37	-2	6	39	0	35	-3	36	34	-	1600-2000 <i>Herigstad</i>	
2000	-4	36	-1	4	32	1	34	-5	34	35	44		
2200	-4	35	0	4	26	-1	33	-4	35	34	37		
2400	-4	35	0	3	27	-1	34	-4	35	34	37		
CHIEF ENGINEER												2000-2400 2015 Secured defrosting #11 box.	
												<i>Maroon</i>	

21 July

TIME	CIRC WATER	COMPRESSOR 1			COMPRESSOR 2			COMPRESSOR 3			COMPRESSOR 4			COMPRESSOR 5		
	INLET TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP
9200	60	0	105	—	0	110	86				20	105	86			
0400	60	0	—	—	0	110	82				15	105	84			
0600	60	0	105	80	0	110	82				20	105	83			
0800	58	0	110	94	0	105	86				20	105	88			
1000	54	0	105	88	0	110	87				20	105	88			
1200	53	0	105	90	0	105	86				20	105	90			
1400	55	0	105	88	0	105	86				15	110	88			
1600	60	0	115	92	0	110	84				15	110	83			
1800	62	0	110	90	0	110	83				10	110	84			
2000	62	0	110	91	0	110	86				8	105	87			
2200	62	0	110	91	0	110	86				12	110	87			
2400	60	0	110	90	—	—	—				15	105	88			

20 July

MAIN REEFER LOG: USNS GEN JOHN POPE (T-AP110)

DATE

COLD STORAGE BOX TEMPERATURES

	ICE CREAM	DAIRY	MEAT	FROZ FOOD	THAW	MEAT	THAW	MEAT	VEG.	BUTT. EGGS	FRUIT
TIME	1	2	3	4	5	6	7	8	9	10	11
21 July 0200	-5	37	-4	-1	8	-3	34	-2	38	34	37
0400	-5	37	-5	-2	8	-2	34	-3	38	33	36
0600	-5	36	-5	0	25	0	36	-2	38	33	37
0800	-5	37	-5	-1	14	2	37	-5	38	33	38
1000	-5	39	-5	-1	24	-2	34	-1	38	33	37
1200	-6	37	-3	0	20	-2	34	-5	38	33	37
20 July 1400	-6	36	-3	0	20	0	35	15	38	38	36
1600	-5	37	-5	0	17	-2	34	-5	38	33	35
1800	-5	37	-5	-1	14	-2	34	-2	37	33	35
2000	-5	38	-5	-1	11	-3	34	-5	37	33	35
2200	-5	37	-5	-2	10	-3	34	-1	38	34	36
2400	-6	37	-5	-1	9	-3	34	-3	38	34	36

REMARKS

0000-0400

Harigstad

0400-0800

Beans

0800-1200

Murphy

1200-1600

Harigstad

1600-2000

Beans

2000-2400

Murphy

CHIEF ENGINEER

19 July

TIME	CIRC WATER	COMPRESSOR 1			COMPRESSOR 2			COMPRESSOR 3			COMPRESSOR 4			COMPRESSOR 5		
	INLET TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP
0200	65	0	110	90	0	110	84				15	105	84			
0400	65	0	105	90	0	105	84				25	110	88			
0600	65	0	105	90	0	105	84				15	110	90			
0800	65	0	110	90	0	115	84				15	115	84			
1000	65	0	110	90	0	110	84				15	110	84			
1200	65	0	—	—	0	105	84				15	110	88			
1400	65	0	115	90	0	110	84				13	110	84			
1600	65	0	115	90	0	110	84				—	—	—			
1800	65	0	115	90	0	110	84				15	110	84			
2000	65	0	115	90	0	110	84				20	110	84			
2200	65	0	115	90	0	110	84				15	—	—			
2400	65	0	115	90	0	110	86				5	110	84			

18 July

MAIN REEFER LOG: USNS GEN JOHN POPE (T-AP110)

DATE 18 July 1971

COLD STORAGE BOX TEMPERATURES											
	ICE CREAM	DAIRY	MEAT	FROZ FOOD	THAW	MEAT	THAW	MEAT	VEG.	BUTT. EGGS	FRUIT
19 July TIME	1	2	3	4	5	6	7	8	9	10	11
0200	-5	37	-5	0	5	-3	35	-2	-	33	37
0400	-6	35	-5	0	5	-3	34	-2	-	33	35
0600	-6	37	-5	0	5	-3	34	-5	45	33	36
0800	-5	37	-5	-1	4	-4	35	-2	43	33	35
1000	-6	37	-5	0	20	-4	34	-5	42	34	45
1200	-4	36	-4	0	13	-3	34	-2	42	34	38
1400	-6	34	-5	0	12	-3	34	-3	33	34	34
1600	-6	34	-5	0	10	-3	34	-3	36	34	36
1800	-6	38	-5	0	7	-3	34	-3	35	34	35
2000	-6	38	-5	0	7	-3	34	-3	35	34	35
2200	-6	38	-5	0	6	-3	34	-3	36	34	36
2400	-6	37	-5	0	5	-3	34	-1	-	33	37

REMARKS

0000-0400

Herigstad

0400-0800

0430 #9 walkin box on line

Herigstad

0800-1200

Bram

1200-1600

Hamy

1600-2000

Hordy

2000-2400

No #9 Box Secured 10300
Loading Stores.

Hordy

CHIEF ENGINEER

25 July

July 24

24 July 66

(25-July)

TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1. L.P. EXHAUST TEMP	93	92	92	92	92	92	92	92	93	93	94	95	95	95	94	93	94	92	92	93	93	93	93	93
2. MN COND STE TEMP	84	84	84	87	86	87	86	84	85	85	85	88	88	86	86	88	88	86	86	84	84	83	74	84
3. MN INJ TEMP	60	60	60	60	60	60	60	60	61	61	62	62	64	64	60	60	60	60	60	60	60	60	60	60
4. MN OVBD TEMP	71	71	71	71	71	71	71	71	71	71	72	72	72	72	72	72	72	71	71	72	71	71	71	71
5. L.O. TO COOLERS	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	128	126	125	125	125	125	125	125
6. L.O. FROM COOLERS	110	110	116	110	110	110	110	110	110	110	110	108	108	110	110	110	109	106	105	105	105	105	105	105
7. THRUST BRG TEMP	120	126	120	120	120	120	120	120	118	118	118	118	118	118	120	120	118	116	115	118	118	118	120	118
8. FWD H.P. ROTOR BRG	122	122	122	124	124	124	124	124	124	124	125	125	125	126	126	125	124	120	120	122	121	121	122	122
9. AFT H.P. ROTOR BRG	134	134	134	136	136	136	136	136	136	136	138	138	138	138	138	136	135	135	134	134	134	134	134	134
10. FWD L.P. ROTOR BRG	128	128	128	131	134	133	133	134	133	133	135	135	135	135	135	133	132	130	128	126	128	127	127	127
11. AFT L.P. ROTOR BRG	128	130	130	131	130	131	131	131	131	131	132	132	132	132	132	130	130	127	127	127	127	127	127	128
12. HOT GEAR BRG FWD	155	155	155	155	155	155	155	155	155	155	157	156	156	156	156	156	155	155	155	155	155	155	155	155
13. HOT GEAR BRG AFT	146	146	146	147	147	148	148	148	148	148	150	147	147	147	147	146	145	145	145	145	145	145	145	145
14. AUX COND STE TEMP	90	90	90	90	90	90	90	90	90	90	92	90	90	95	95	95	90	90	92	87	88	90	90	90
15. 1ST STAGE AIR TEMP	150	150	150	148	150	151	150	151	150	151	154	152	152	150	150	152	152	150	152	152	150	148	150	150
16. D.C. HEATER TEMP	237	238	238	238	235	245	238	238	238	238	240	235	240	238	240	240	232	238	242	240	240	240	240	240
17. SUPRHT TEMP PORT	800	800	800	765	765	770	770	770	770	765	770	800	800	800	800	800	800	800	800	800	800	800	800	800
18. SUPRHT TEMP STBD	630	630	630	615	620	610	615	630	620	625	630	630	630	630	630	630	630	620	625	630	630	625	625	630
19. F.O. SETT TEMP P	110	110	110	108	104	104	104	104	104	104	104	124	124	120	120	118	110	110	110	112	112	112	110	110
20. F.O. SETT TEMP S	102	102	102	106	108	104	104	104	104	104	104	116	116	114	114	112	116	112	108	104	104	104	102	102
21. UPTAKE PORT	300	305	305	315	318	336	336	385	285	295	300	290	290	295	295	295	290	295	290	290	285	285	285	285
22. UPTAKE STBD	285	290	290	290	296	300	303	300	285	295	300	290	290	290	290	291	285	293	293	290	285	285	285	285
23. F.O. PUMP SUCT TEMP	120	120	120	120	118	116	115	116	116	116	116	136	136	134	134	134	122	122	120	122	122	122	120	120
24. MN FD PMP L.O PORT	32	32	32	31	32	32	32	32	32	32	32	34	34	34	34	32	32	32	29	31	31	31	31	31
25. MN FD PMP L.O STBD	30	30	30	25	25	30	25	30	30	30	26	31	31	31	31	25	25	25	30	30	30	25	30	30
26. L.O. TO GEARS	114	114	114	114	114	114	114	114	114	114	114	114	114	114	114	114	114	110	110	110	110	110	110	110
27. AIR CONTR L.O. PRESS	28	28	28	-	-	-	-	27	-	-	-	28	28	28	28	28	-	-	-	-	-	-	-	29

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1					9	9	9	9	9	9	9						-	-	-	-				
28. L.O. PRES #2	10	10	10		10	10	10	10	10	10	10	10	10	10	10		10	10	10	10	10	10	10	10
31. L.O. TO COOLER #1					130	130	130	130	132	132	132						-	-	-	-				
30. L.O. TO COOLER #2	130	130	130		130	130	130	130	130	130	130	130	130	130	130		130	130	130	130	130	130	130	130
33. L.O. FROM COOLER #1					110	110	110	110	110	110	110						-	-	-	-				
32. L.O. FROM COOLER #2	110	110	110		110	110	110	110	110	110	110	110	110	110	110		110	110	110	110	110	110	110	110
35. L.O. GOV PRES #1					62	62	62	60	62	62	62						-	-	-	-				
34. L.O. GOV PRES #2	50	50	50		50	50	50	50	50	50	50	50	50	50	50		50	50	50	50	50	50	50	50
37. AMPS POS #1					-	-	-	-									-	-	-	-				
36. AMPS POS #2	1250	1250	1250		1250	1250	1250	1300	1250	1250	1250	1250	1250	1250	1250		1200	1200	1200	1200	1250	1250	1250	1250
39. AMPS NEG #1					-	-	-	-									-	-	-	-				
38. AMPS NEG #2	1250	1250	1250		1250	1250	1250	1300	1250	1250	1250	1250	1250	1250	1250		1200	1200	1200	1200	1250	1250	1250	1250
41. HP HIGH SPEED PIN. AFT	136	136	136		136	136	136	136									136	136	136	136	136	136	136	136
42. HP INTER SPEED PIN FWD	140	140	140		140	140	142	142									142	142	142	142	142	142	142	142
43. HP INTER SPEED PIN AFT	132	132	132		132	132	132	132									135	135	135	135	135	135	135	135
44. L.P. THRUST BEARING	130	130	130		130	130	130	130									132	132	132	132	132	132	132	132
45. H.P. THRUST BEARING	144	144	144		144	144	144	144									144	144	144	144	144	144	144	144
46. LP HIGH SPEED PIN. FWD	126	126	126		126	126	126	126									128	128	128	128	128	128	128	128
47. LP HIGH SPEED PIN. AFT	124	124	124		124	124	124	124									124	124	124	124	124	124	124	124
48. LP INTER SPEED PIN FWD	142	142	142		142	142	142	142									143	143	143	143	143	143	143	143
49. LP INTER SPEED PIN. AFT	135	135	135		135	135	135	135									135	135	135	135	135	135	135	135
50. MAIN GEAR RCTOR FWD	108	108	108		108	108	108	108									108	108	108	108	108	108	108	108
51. MAIN GEAR RCTOR AFT	105	105	105		105	105	105	105									105	105	105	105	105	105	105	105
52. LP BLEED	12	12	12		12	12	12	12									12	12	12	12	12	12	12	12

	TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	
1.	L.P. EXHAUST TEMP												91	91	89	88	98	94	94	96						
2.	MN COND STE TEMP																74	76	84	84						
3.	MN INJ TEMP												79		100		46	50	54	54						
4.	MN OVBD TEMP																70	70	70	68						
5.	L.O. TO COOLERS																118	125	124	126						
6.	L.O. FROM COOLERS												108		110	110	104	110	110	110						
7.	THRUST BNG TEMP													110	110	110	108	110	110	110						
8.	FWD H.P. ROTOR BNG												131	121	115		115	121	123	125						
9.	AFT H.P. ROTOR BNG												121	115	115		118	120	122	124						
10.	FWD L.P. ROTOR BNG												121	121	115	115	120	125	126	127						
11.	AFT L.P. ROTOR BNG												121	115	115		120	124	126	126						
12.	HOT GEAR BRG FWD												111	111	113		108	112	112	113						
13.	HOT GEAR BRG AFT												115	115	116		113	115	116	117						
14.	AUX COND STE TEMP												100	110	115		74	77	80	80						
15.	1ST STAGE AIR TEMP												100	110	115		160	160	165	165						
16.	D.C. HEATER TEMP												240	240	240		240	240	240	240						
17.	SUPRHT TEMP PORT												710	710	710		720	740	700	730						
18.	SUPRHT TEMP STBD												710	710	710		720	740	700	730						
19.	F.O. SETT TEMP P												95	100	105		95	100	102	103						
20.	F.O. SETT TEMP S												75	75	75		75	78	80	80						
21.	UPTAKE PORT												275	275	275		275	275	275	275						
22.	UPTAKE STBD												265	265	265		265	265	265	265						
23.	F.O. PUMP SUCT TEMP												80	100	110		80	100	110	120						
24.	MN FD PMP L.O PORT																36	31	32	32						
25.	MN FD PMP L.O STBD																34	29	27	27						
26.	L.O. TO GEARS												19	19	19		19	19	19	19						
27.	AIR CONTR L.O. PRESS																32	33	33	33						

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1																8	8	8	8					
28. L.O. PRES #2																10	10	10	10					
31. L.O. TO COOLER #1																134	130	130	128					
30. L.O. TO COOLER #2																128	130	130	130					
33. L.O. FROM COOLER #1																112	110	110	108					
32. L.O. FROM COOLER #2																107	108	110	110					
35. L.O. GOV PRES #1																61	62	62	62					
34. L.O. GOV PRES #2																52	52	52	52					
37. AMPS POS #1																850	850	800	800					
36. AMPS POS #2																850	900	950	900					
39. AMPS NEG #1 3																850	800	800	800					
38. AMPS NEG #2 4																925	900	950	900					
41. HP HIGH SPEED PIN. AFT																130	134	134	134					
42. HP INTER SPEED PIN FWD																138	140	140	142					
43. HP INTER SPEED PIN AFT																130	132	133	135					
44. L.P. THRUST BEARING																124	128	128	130					
45. H.P. THRUST BEARING																138	140	140	142					
46. LP HIGH SPEED PIN. FWD																120	124	124	125					
47. LP HIGH SPEED PIN. AFT																118	124	124	125					
48. LP INTER SPEED PIN FWD																135	140	140	145					
49. LP INTER SPEED PIN. AFT																128	135	135	137					
50. MAIN GEAR RCTOR FWD																104	106	106	108					
51. MAIN GEAR RCTOR AFT																100	105	105	106					
52. LP BLEND																16	13	14	13					

REMARKS

1200-1600 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

F.O.
F.W.
MUF
MU-U
EVAP
GAL-D

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER

P. ALK

P. ALK

CHLO

PH. 4

SO. 3

PH

WS. HRS.

FS. HRS.

CHIEF ENGR'S SIGNATURE-