

USNS		VOYAGE NO.		FROM AT		TO		TYPE OF VESSEL		DATE	
GEN. JOHN POPE T-AP-10				NSC CANTLAND, CA.				P25262		3-15/19-67	
WATCH 1200 TO 1600 1600 TO 2000 2000 TO 2400 2400 TO 0400 0400 TO 0800 0800 TO 1200 WATCH 1200 TO 1600 1600 TO 2000 2000 TO 2400 2400 TO 0400 0400 TO 0800 0800 TO 1200											
MACH. PARTICULARS (CONT'D)											
TEMPERATURES (CONT'D)											
PRESSURES (CONT'D)											
MISCELLANEOUS											
MACHINERY PARTICULARS											
PRESSURES											
TEMPERATURES											
MISCELLANEOUS											
GENERATORS											
FUEL - WATER AND LUBE OIL											
L.O. CENTRIFUGE - HOURS OPERATED											
SUMMARY											

REMARKS

1200-1600 WATCH

PORT RELIEF WATER. Machine. Spent Port Boiler Blower, F.D. Service Pump with
No. 1 Elec. F.D. Pump with 300. Station, Air Fan, Port, No. 2 Galle, a No. 3 Galle, and
Aux. Galle, No. 3 Galle, Pump, F.D. Pump, Aux. Air Fan. Checked machinery and cutting spaces.
Pumped F.D. oil. Checked and cleaned burner and all F.C. Oil. Soot & Soot. All duty
loaders. Oil must be bad. Otherwise condition good.

Ref. Beans, Other Green, F.W. P. Kelly

1600-2000 WATCH

PORT RELIEF WATER. No changes in machinery. Routine checks of machinery
and cutting spaces. Checked and cleaned burner and F.C. Disch. St. Pumped
Exp. F.D. F.D. oil. Satisfactory. Condition Normal.
1935 Tripped No. 1 Gen. off line - idling. Difficult to keep parallel with No. 2.

WATCH ENGR'S SIGNATURE

Oiler - Lovell F.W. - Watkins F.W. - Gault

2000-2400 WATCH

PORT RELIEF WATER. Machinery same except No. 1 Gen. idling. Checked machinery
and cutting spaces. Checked and cleaned burner and F.C. Disch. St. Pumped F.D.
oil. Satisfactory. Condition Normal.

WATCH ENGR'S SIGNATURE

Oiler - Lovell F.W. - Watkins F.W. - Gault

2400-0400 WATCH

PORT BUTLER REMOVED WATER 0007 GALT SAILWORTH REMOVED WATER 0013
VIBR ENGR FLEW TUBES 0125 TO 0140 PENIC FROM AIRLINE PHONO SILEN THAT WIND DIRECTION
WAS FAVORABLE

WATCH ENGR'S SIGNATURE

Routine Port Water Blows At Safe Limit
ROUTINE INSPECTIONS OF ALL MAIN SERVICES.

Oiler - SAILWORTH F.W. - BUTLER

0400-0800 WATCH

Routine Port Water
Blows OK
1940 P.O. TO #1 M/T F.D. PUMP.
Two Exhausters & Cleaned F.C. Disch. Soot & Soot

WATCH ENGR'S SIGNATURE

Oiler - SAILWORTH F.W. - BUTLER

0800-1200 WATCH

Routine Port Water
Blows OK

WATCH ENGR'S SIGNATURE

F.W. - GALT F.W. - P. Kelly

CHIEF ENGINEER

RECEIVED

WATCH ENGR'S SIGNATURE

BOILER WATER READINGS

STB'D PORT

HOURS 779 HOURS SEC.

AKL 9.93 AKL

T-AKL 14.40 T-AKL

SAL. 4.14 SAL.

PEOS. 50 PEOS.

PH 11 R. ph

CHIEF ENGR'S SIGNATURE

USNS	VOYAGE NO.	FROM AT	TO	TYPE OF VESSEL	DATE
SPIN. JELLY POPE FAF 110		NSC OAKLAND, CA.		P232R	3-19-60-67

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME							MACH. PARTICULARS (CONT'D)	HOTTEST GEAR BEARING FORWARD					
DETENTION TIME								HOTTEST GEAR BEARING AFT					
REVOLUTION COUNTER (END OF WATCH)								AUX. COND. CONDENSATE	104 106 115 113 127 110 101				108
TOTAL REVOLUTIONS (FOR WATCH)								1ST STAGE FEED WATER HEATER	135 130 131 130 126 130				130
AVERAGE RPM								D. C. FEED WATER HEATER	240 240 240 270 270 238				
F.O. METER (END OF WATCH)	1130 3120	1130 3260	1130 3860	1136 4320	1136 4790	1136 5320		3RD STAGE FEED WATER HEATER					
F.O. CONSUMED	500 320	320 400	400 460	460 470	470 530	530		SUPER HEAT	P 570 625 630 600 610 650				
								F.O. TO BURNERS	S 100 100 190 200 170 190				
							BOILER PARTICULARS	AIR TO FURNACE	P 1.1 1.1 1.1 1.1 1.1 1.1				
								F.O. TEMP. IN SETTLING TANKS	P 95 95 95 90 90 90				
								PORT BOILER UPTAKE	S 95 95 95 90 90 100				
								STBD. BOILER UPTAKE					
								F. O. BACK PRESSURE	280 280 285 275 280 305				
								MAIN STEAM	10 10 10 10 10 10				
								F.O. TO BURNERS	240 240 240 440 440 440				
									180 180 200 200 200 140				
								MAIN COND. SALINITY					
								ENGINE ROOM TEMPERATURE	70 73 73 65 65 76				
							MISCELLANEOUS	FIRE ROOM TEMPERATURE					
								NOZZLES IN USE					
								NO. OF BURNERS IN USE	P 1 1 1 1 1 2				
								BURNER TIP SIZE	S 53 53 53 53 53 53				
								CO ₂ % PORT BOILER	70 70 70 70 70 70				
								CO ₂ % STBD. BOILER					
								OIL LEVEL MAIN SUMP					

GENERATORS												FUEL - WATER AND LUBE OIL			
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	METER AT NOON	ON HAND AT START OF DAY	
1200 TO 1600	1	1200	440	600	9	118	108		61	-	-	240	11365320	220	
	2	1200	440	590	7	128	110		63	1450	1450	240	11362620	10	
1600 TO 2000	1	1200	440	625	9	120	110		61	-	-	240	2700	220	
	2	1200	440	625	7	120	110		63	1500	1500	240	4419	10	
2000 TO 2400	1	1200	440	630	9	120	110		62	-	-	240	4355	2180	
	2	1200	440	630	7	120	112		62	1500	1500	240	880	0	
2400 TO 0400	1	1200	440	600	9	120	110		62	800	800	270	860	1242	
	2	1200	440	600	7	129	110		62	950	950	270	10	1240	
0400 TO 0800	1	1200	440	610	9	120	110		62	800	800	270		2	
	2	1200	440	610	7	129	110		62	950	950	270			
0800 TO 1200	1	1200	440	650	9	120	110		62	800	800	270			
	2	1200	440	650	7	129	110		62	950	950	270			

L.O. CENTRIFUGE - HOURS OPERATED					
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
SUMMARY					
RUNNING TIME					PROPELLER SLIP (%)
DETENTION TIME					BBL FUEL MI
TOTAL REVOLUTIONS					WIND DIRECTION
AVERAGE R.P.M.					STATE OF SEA
TOTAL MILES BY ENGINE					STATE OF WEATHER
TOTAL MILES BY OBSERVATION					

REMARKS

1200-1600 WATCH

PORT RELIEF WATCH. Machinery in Cold. No. 1 Boiler, Blower, Elec. FC. Suck Pump and Elec. FC. Pump with steam pumps stand-by, Outboard, Sat., Main FC. Mtr., No. 1-2 Gens., No. 2 Oil Line, No. 1 Lifting on VENTAGE, No. 1 Cond. Pump to Aux. Gens., Aux. Cond., Elec. Suck Pump & Main Elec. FC. Pump. Aux. Air Pipes, Reserve 2B. Water Tank Mtr. Lit. off FC. Evap. to save Res. Fu. Pumped ER Bilge, cleaned and changed burner and FC. Suck & Disch. Strs.

CHIEF - QUINN. FWT - FIKLEY. RTR - BOGGS

1600-2000 WATCH

WATCH ENGR'S SIGNATURE

PORT RELIEF WATCH. Machinery as before. Routine checks of machinery and spaces. Changed and cleaned burner & disch. str. Pumped ER Bilge at safe level. Condition Normal.

CHIEF - LEVALL. FWT - WATKINS. RTR - GENTIL

2000-2400 WATCH

WATCH ENGR'S SIGNATURE

PORT RELIEF WATCH. No changes in machinery. Routine checks of machinery and cutting spaces. Changed and cleaned burner & disch. str. Pumped ER Bilge at safe level. Condition Normal.

CHIEF - LEVALL. FWT - WATKINS. RTR - GENTIL

2400-0400 WATCH

WATCH ENGR'S SIGNATURE

CHANGED TO #3 ON INBOARD SETTER @ 2345
ROUTINE PORT WATCH
BILGES AT SAFE LEVEL

CHIEF - STANLEY. FWT - BUTLER

0400-0800 WATCH

WATCH ENGR'S SIGNATURE

CHANGED FC & DISCH. SIZING + BURNER + CLEANED BURN.
ROUTINE PORT WATCH
PWT # 1 OPEN ON TAIL LINE @ 0700

CHIEF - STANLEY. FWT - BUTLER

0800-1200 WATCH

WATCH ENGR'S SIGNATURE

On port mach in operation as before, cleaned & changed burners.
Working as per work list. Made Rounds + Insp of Mach + Eng spaces.

CHIEF ENGINEER

WATCH ENGR'S SIGNATURE

BOILER WATER READINGS

SEA'D PORT

HOURS 803 HOURS 500

AKL 9183 AND

T-AKL 1440 T-AKL

SAL. 4117 SAL.

INHS. 50 INHS.

WIND 11 Rph

CHIEF ENGR'S SIGNATURE

REMARKS

1200-1600 WATCH

Port watch. Mach in operation #1 Boiler, #1 & 2 Blower #1 main feed pump
 #1 & #2 Generators, #1 main Cond pump, #1 aux Circ pump, #1 air Comp.
 #1 fire pump @ 1400 pumped outboard Settles from #6 Dup tps. Make
 Rounds + Insp of Mach + Eng Spaces - Bilge at Safe level.
 Men working as per work list, yard workers on various jobs.

Order Quinn, 7th Morgan,

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

Port Power Watch Machy as left and as before. Checked machy and spaces.
 Changed and cleaned burners and Disch str. Pumped bilge. No cargo work tonight.
 Condition Normal. Evap Flat Bilge satisfactory

Order - Levell FWT - ^{Watkins} ~~Patton~~ R/R - Gentil

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

Port Power Watch Machy same. Changed and cleaned burners and
 Disch str. Checked machy and spaces. Pumped LR bilge & Evap Flat.
 Condition Normal.

Order - Levell FWT - ^{Watkins} ~~Patton~~ R/R - Gentil

WATCH ENGR'S SIGNATURE

2400-0400 WATCH

Routine Port Watch.
 Bilge at Safe Level.
 P.C. Sig. to Settles @ 0315
 Routine inspections of Air & Aux Mach. Spaces made at regular
 intervals

Order Signaworth Port Butler

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

Routine Port Watch Except Dead Tow Shift
 Disconnected F.W. HOSE @ 0530 (Over) B/C Chief Engr Start Car
 L.O. Through #1 & 2 Main Units @ 0600
 Relieved at 0755

Order Signaworth Port Butler

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

Port watch machinery in operation as before changed
 & cleaned F.O. Burner & Disch. Strainer. Started water
 washing Beam. Tubes Port Boiler, cleaning fire side. Evap
 Working as per work list. S.C. L.O. Pump @ 0900.

WATCH ENGR'S SIGNATURE

CHIEF ENGINEER

BOILER WATER READING

F.W.T. F.W.T.

HOLD 827 F.W.T. S.C.

AW 9.34

D-44 14.02

H. 4.14

H. 4.40

H. 4.11

S.C. 45

PH. Cond. 8.0

CHIEF ENGR'S SIGNATURE

A 6025

REMARKS

1200-1600 WATCH

Port watch machinery in operation #1 Boiler & F.D. Blower
 #1 Elect. Bl. F.D. Pump. #1 F.D. Pump #1 + #2 S.S. Cuts. Aux. Circ.
 #1 Main Pumps. #1 Air Pump. #1 Fire Pumps F.W. Pump. Pumped
 inboard suth. Room to deep TH. crew working AS per work list.

WATCH ENGR'S SIGNATURE-

S. Harris

1600-2000 WATCH

Port Relief Watch Machinery above with ML Evap ended. Routine
 checks of machy. and spaces. Changed and cleaned burners and F.D. Disc St.
 Bilge satisfactory.

Chief - Lovell F.W.T. - Watkins R.R. - ?

WATCH ENGR'S SIGNATURE-

S. Harris

2000-2400 WATCH

Port Relief Watch Machinery same. Made routine checks of machy. and spaces.
 Changed & cleaned burners and stc. Pumped bilge. Complied with S/O EN/C.
 Pumping Evap. Flat and 4 P/S

Chief - Lovell F.W.T. - Watkins R.R. - ?

WATCH ENGR'S SIGNATURE-

S. Harris

2400-0400 WATCH

Plant AS BEFORE OPENED #2 Bilge Pump Bilge Main Section
 VALVES (AIR CHAMBER - SPRING CHAMBER) AND PUMPED SHAFT ALLEY
 PORT & STBD & AIR Bilge WELLS.

Over Steamworth Two Boilers

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

W. J. Spring

Dinged to SAGE LEVEL
 Receiving Port Watch

0800-1200 WATCH

Watch AS BEFORE.
 Port watch machinery in operation AS BEFORE finished cleaning
 #2 Boiler fire side started closing some up crew working
 AS per work list Pumped Bilges.

WATCH ENGR'S SIGNATURE-

S. Harris

CHIEF ENGINEER

WATCH ENGR'S SIGNATURE-

S. Harris

BOILER WATER READINGS

STE'D PORT

HOURS 851 HOURS Sec.

AKL 9.34 AKL

T-AKL 4.02 T-AKL

SAL 7.46 SAL.

PHOS. 40 PHOS.

R-ph 11 R-ph

S-3 45

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE-

S. Harris

REMARKS

1200-1600 WATCH

Port watch machinery in operation #1 Boiler & F.D. Blower #1 Elect. Feed Pump #1 F.O. Pump #1 & #2 S.S. Cans. Aux. Circ. Pump #1 M.W. Cond. Pump Air Comp. #1 Fire Pump. F.W. Pump. Crew working as per work list.

WATCH ENGR'S SIGNATURE-

L. Harris

1600-2000 WATCH

First Relief Watch. Machinery as before and as left, except at 1730 tipped No. 2 Gen. off line. Checked mach. and spaces. Changed and cleaned burners and F.O. Disch str. Necessary to have gland seal on tailing No. 2 Gen. 5" on. Bilge at safe level - PP list - some oil. Ream cracked open, return. Evaporator at 25" steam pressure to cell tank all evening. Sky clear, 10" line, looking.

Oiler - Lovell F.W. - Watkins

R/R - Gentil

WATCH ENGR'S SIGNATURE-

J. Lawrence R/R

2000-2400 WATCH

Port Relief Watch. No change in mach. Routine check of mach. and spaces. Changed and cleaned burners and str. Pumped ER bilge 'down'. Complied with S/C & N/C. Condition Normal.

Oiler - Lovell F.W. - Watkins R/R - Gentil

WATCH ENGR'S SIGNATURE-

J. Lawrence R/R

2400-0400 WATCH

Blew tubes stop boiler after receiving permission to blow same from Port Authorities via Night Relief Officer. Routine Port Watch. Bilges at safe level.

Oiler - STANWORTH F.W. BUTLER R/R - HARRIS

WATCH ENGR'S SIGNATURE-

J. Lawrence R/R

0400-0800 WATCH

Routine Port Watch. Bilges at safe level. Changed & cleaned burners & discharge strainer. Put #2 Gen on the line - @ C 710. Changed to #3 (INBD) F.O. Settler at C 717.

WATCH NO. BILGE.

WATCH ENGR'S SIGNATURE-

J. Lawrence R/R

0800-1200 WATCH

Port watch machinery in operation as before changed & cleaned R.O. Burner & Disch. strainers. Crew working as per work list. Pool men & wiper cleaning & painting lower flat Eng. Room. Sec. Air Pump. Elect. Installing new under header Pumped Bilges. & #4 hold. Puzin Wall.

WATCH ENGR'S SIGNATURE-

L. Harris

CHIEF ENGINEER

SEWER WATER READINGS

SEWER PORT

HOURS 8:25 HOURS S.C.

AHL 9.34 AHL

T-AHL 14.02 - AHL

SAL. 4.14 SAL.

PHOS. 4.0 PHOS.

R.ph 11 R.ph

SOS 40

PR. COND. 8.0

CHIEF ENGR'S SIGNATURE-

J. Lawrence R/R

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE			
John Pope TAP-110				AT NSC OAKLAND				P-2-31-R2		3-23-24-67			
		WATCH						WATCH					
		1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200	
RUNNING TIME													
DETENTION TIME													
REVOLUTION COUNTER (END OF WATCH)													
TOTAL REVOLUTIONS (FOR WATCH)													
AVERAGE RPM													
F.O. METER (END OF WATCH)		1137		1187		1137		1137		1137		1137	
F.O. CONSUMED		4930		4620		5030		5760		5910		6430	
		440		390		410		430		450		4520	
PRESSURES													
THROTTLE													
H.P. AHEAD													
L.P. AHEAD													
AUX. VACUUM		28.5		28.5		27		27		27		27	
L.O. TO TURBINES													
AUX. STEAM		150		150		150		150		150		150	
BACK PRESSURE		9		9		9		9		9		9	
GLAND STEAM													
H.P. BLEEDER													
L.P. BLEEDER													
L.P. BLEEDER													
TEMPERATURES													
STEAM AT THROTTLE													
AUX. L.P. EXHAUST		100		95		95		95		95		95	
CONDENSATE													
CIRC. WATER IN		58		58		58		58		58		58	
CIRC. WATER OUT		74.6		70		72		72		72		72	
L.O. TO COOLERS													
L.O. FROM COOLERS													
TEMPERATURE THRUST BEARING													
FORWARD H.P. ROTOR BEARING													
AFT. H.P. ROTOR BEARING													
FORWARD L.P. ROTOR BEARING													
AFT. L.P. ROTOR BEARING													
MISCELLANEOUS													
HOTTEST GEAR BEARING FORWARD													
HOTTEST GEAR BEARING AFT													
AUX. COND. CONDENSATE		94		88		92		92		92		92	
1ST STAGE FEED WATER HEATER		118		115		120		112		114		114	
D. C. FEED WATER HEATER		240		240		240		240		240		240	
3RD STAGE FEED WATER HEATER													
SUPER HEAT		P											
F.O. TO BURNERS		S		630		630		660		630		630	
AIR TO FURNACE		P		100		95		90		90		90	
F.O. TEMP. IN SETTLING TANKS		S		105		100		95		95		105	
PORT BOILER UPTAKE													
STBD. BOILER UPTAKE				270		270		285		275		285	
F.O. BACK PRESSURE													
MAIN STEAM		440		220		220		440		440		440	
F.O. TO BURNERS		160		140		140		140		140		140	
MAIN COND. SALINITY		.41		.02		.02		.02		.02		.41	
ENGINE ROOM TEMPERATURE		75		70		69		69		69		70	
FIRE ROOM TEMPERATURE		75											
NOZZLES IN USE													
NO. OF BURNERS IN USE		P		2		2		2		2		2	
BURNER TIP SIZE		S		53/60		53/60		53/60		53/60		53/60	

REMARKS

1200-1600 WATCH

Port Watch Machinery In operation #1 Bilge + F.D. Blower #1
 Elact. Feed Pump #1 F.D. Pump #1 & #2 S.S. Cans. #1 Air Comp
 #1 Fire Pumps #1 Mr. Cond. Pump Aux. Circ. Pump. Crew working
 as per work list.

WATCH ENGR'S SIGNATURE-

F. Harris

1600-2000 WATCH

Port Relief Watch. Machy. as above with No. 1 Air Compressor added and
 Mr. Brown checked machy. and spaces. Changed and cleaned burners and
 F.D. Disch. Str. Bilge at safe level. At 1830 John Mc^(MERS) and helper removed
 spare Gen. Gen. to shop for reconditioning.

2000-2400 WATCH

Chief - Lovell. Port - Watkins. Relief - Gintel. WATCH ENGR'S SIGNATURE- *[Signature]* R/H
 Port Relief Watch. Machy. same. Checked and changed burners and F.D.
 Disch. Str. Pumped ER bilge down. Complied with S/C E/M/C. Condition Normal.

2400-0400 WATCH

Chief - Lovell. Port - Watkins. Relief - Gintel

WATCH ENGR'S SIGNATURE-

[Signature] R/H

ROUTINE PORT WATCH.

ROUTINE INSPECTIONS MADE OF MAIN + AUX. MACHINERY SPACES

0400-0800 WATCH

Chief - SEAWORTH. Port - BUTLER. Relief - GINTAL

WATCH ENGR'S SIGNATURE-

[Signature] R/H

ROUTINE PORT WATCH.

Bilges at safe level although rising. #1 Bilge Pump
 has signs that it is in suction manifold.

0800-1200 WATCH

Chief - But + Relief as Before

WATCH ENGR'S SIGNATURE-

[Signature]

Port watch machinery For operation as before changed &
 cleaned F.D. Burners & Disch. Strainers. Port main Painting base.
 Flat Eng. Room. Crew working as per work list.

WATCH ENGR'S SIGNATURE-

F. Harris

CHIEF ENGINEER

AIR WATER READINGS

PORT

BARS 899 FURS 500

AIR 9.93 ASD

TEMP 14.60 F ASD

REL. 2.08 ASD

RHOS. 40 PESS.

R.ph 11 R.ph

503 38

PH COND. 800

CHIEF ENGR'S SIGNATURE-

[Signature]

USNS
John Pope TAP-110

VOYAGE NO.
AT NSC OAKLAND

FROM
AT NSC OAKLAND

TO
AT NSC OAKLAND

TYPE OF VESSEL
R2-S2-R2

DATE
3-24/25/67

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME							MACH. PARTICULARS (CONT'D)						
DETENTION TIME													
REVOLUTION COUNTER (END OF WATCH)													
TOTAL REVOLUTIONS (FOR WATCH)													
AVERAGE RPM													
F.O. METER (END OF WATCH)	1137 6910	1137 7310	1137 7740	1137 8170	1137 8640	1137 9070	TEMPERATURES (CONT'D)						
F.O. CONSUMED	480	400	430	450	450	430							
PRESSURES	THROTTLE												
	H.P. AHEAD												
	L.P. AHEAD												
	AUX. VACUUM	29"	29"	29"	29"	25"							
	L.O. TO TURBINES												
	AUX. STEAM	145	120	120	140	140	BOILER PARTICULARS						
	BACK PRESSURE	9	9	9	9	9							
	GLAND STEAM												
	H.P. BLEEDER												
	L.P. BLEEDER												
	STEAM AT THROTTLE												
	AUX. EXHAUST	101/102	100/100	98/98	95/90	76/98							
	CONDENSATE												
	CIRC. WATER IN	60	60	60	60	60							
TEMPERATURES	CIRC. WATER OUT	74/77	68/66	72/66	68/66	69/66							
	L.O. TO COOLERS						MISCELLANEOUS						
	L.O. FROM COOLERS												
	TEMPERATURE THRUST BEARING												
	FORWARD H.P. ROTOR BEARING												
	AFT. H.P. ROTOR BEARING												
	FORWARD L.P. ROTOR BEARING												
	AFT. L.P. ROTOR BEARING												

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL					
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	METER AT NOON	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND		
1200 TO 1600	1	1200	440	630	9	124	115	64	62	950	950	240	11379070	170	15	170		
	2	1200	440	630	7	126	110		64	950	950	240	11376430					
1600 TO 2000	1	1200	440	610	9	120	110		62	800	800	240	2640	170	15	170		
	2	1200	440	610	7	122	110		62	700	700	240	4096					
2000 TO 2400	1	1200	440	630	9	120	110		62	800	800	240	4096	15		15		
	2	1200	440	630	7	122	110		62	700	700	240	4096					
2400 TO 0400	1	1200	440	640	9	118	105		62	1000	1000	240	4096	2145	0	2145		
	2	1200	440	640	7	124	110		62	750	750	240	90					
0400 TO 0800	1	1200	440	640	9	118	110		62	1000	1000	240	4006	2140		2140		
	2	1200	440	640	7	124	110		62	700	700	240	4006					
0800 TO 1200	1	1200	440	620	9	119	109		62	750	750	240	830	5		5		
	2	1200	440	620	7	124	109		62	850	850	240	800	1230		1230		
LOW PRESS. EVAPORATORS (No. of hrs. operated) / (Fresh water made gals.)																		
L.O. CENTRIFUGE - HOURS OPERATED																		
SUMMARY																		
FUEL OIL												BOILER WATER						
RECEIVED DURING DAY												ON HAND AT START OF DAY						
EXPENDED DURING DAY												EVAPORATED OR RECEIVED						
REMAINING ON BOARD												ON HAND						
DOMESTIC WATER												CONSUMED						
ON HAND AT START OF DAY												ON HAND AT START OF DAY						
EVAPORATED OR RECEIVED												RECEIVED						
ON HAND												ON HAND						
CONSUMED												CONSUMED						
DIESEL OIL												CONSUMED						
ON HAND AT START OF DAY												ON HAND						
EVAPORATED OR RECEIVED												RECEIVED						
ON HAND												ON HAND						
CONSUMED												CONSUMED						

REMARKS

1200-1600 WATCH

Port Watch machinery Incorporation #1 Boiler + F.O. Blower #1
 Elbow, Feed Pump, #1 FC Pump #1 + #2 S.S. Cond. MN. Cond. Pump
 #1 Fire Pump Aux. Circ. Pump. Air Comp. Pumped F.O. Salt
 from #6 Pump THS. After Pock Tank Empty.

WATCH ENGR'S SIGNATURE

L. Harris

1600-2000 WATCH

Port Relief Watch. Machinery as left with M.C. Evap. in service, filling double bottom
 tank. Checked machinery and spaces. Changed and cleared burners and FC Disch. Sigs.
 Anchor line (spring) brakes. Sawed lock off door to get to Capstan Switches knife Sw.
 Energized Capstans 1 & 2 for Mate and left 'ON'. Bilge at safe level. Looks like
 sea down in bilge. Did not pump.

Chief - Lovell FWT - Watkins RTR - Allen

2000-2400 WATCH

Port Relief Watch. Machinery same. Changed and cleaned burners and disch.
 2nd. Checked machinery and spaces. Bilge at safe level. Did not pump.
 Complied with S/C & N/C. Condition Normal. Dbl. Bln. Res. about 1-3" to get to F.

WATCH ENGR'S SIGNATURE

L. Harris

Chief - Lovell FWT - Watkins RTR - Allen

2400-0400 WATCH

ROUTINE PORT WATCH

ROUTINE INSPECTIONS OF MAINT. AND MACH. SPACES MADE AT REGULAR
 INTERVALS.

WATCH ENGR'S SIGNATURE

L. Harris

Chief - Lovell FWT - Watkins RTR - Allen

0400-0800 WATCH

SPECIALITY AS BEFORE

CONCERN WITH HANDLING & NIGHT ORDERS.

AT 0700 REC. CALL FROM MR. MC DONALD. HIS INSTRUCTIONS WERE TO CALL
 COT AND SUPPLY FOR DAY WORK.

CHANGED & CLEANED BURNERS & DISCH. SERVICER

ADDED 19th A.C. TO #1 M.C. F.O. PUMP

WATCH ENGR'S SIGNATURE

L. Harris

Chief - Lovell FWT - Watkins RTR - Allen

0800-1200 WATCH

Dbl. Bln. Deton. Tr. FLOW AT 0825

SHOWED M.C. EVAP.

WATCH ENGR'S SIGNATURE

L. Harris

Chief - Lovell FWT - Watkins RTR - Allen

CHIEF ENGINEER

WATCH ENGR'S SIGNATURE

L. Harris

WATER READING

923 FTS. S & C.

4193

14140

2.27

15.40

11 P.M.

5.335

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE

L. Harris

[illegible]

REMARKS

1200-1600 WATCH

PORT RELIEF WATCH. Machinery in Operation: No. 1 Boiler, F.D. Blower, F.W. Pumps (No. 1 & 2), No. 1 F.W. Serv. Pump, No. 1-2 S.S. Grs., Circ. & M. Cond. Pump, No. 1 F.W. Pump, No. 1 F.W. Pump on Standby, M.E. Evap., Labd. Sulf. and No. 3 F.W. Checked machinery and spaces. Changed and cleaned burners and both F.C. disch. and suet str. Bilges at safe level. Paper in ER painting burner stands; EAO in lower ER painting.

1600-2000 WATCH

Ciler - Wanner FWT - Matthews Reiter ^{BEAMS} ~~Wanner~~ WATCH ENGR'S SIGNATURE *Wanner* R/E
PORT RELIEF WATCH. No changes in machinery. Lower deck freshly painted as far as paint lasted. No checks made until paint dries. Ships crew secured. Bilges safe.

2000-2400 WATCH

Ciler - Levell FWT - Matthews R/E - Marvin WATCH ENGR'S SIGNATURE *Levell* R/E
PORT RELIEF WATCH. Machinery same. Spread paper on deck as requested by (D) 2A/B for Ciler needs at 2000. Until paint set, no rounds. Pumped ER bilge down. Changed and cleaned burners and disch. str. Completed with S.S. & M.E. Condition Normal.

2400-0400 WATCH

Ciler - Levell FWT - Matthews R/E - Marvin WATCH ENGR'S SIGNATURE *Levell* R/E
ROUTINE PORT WATCH
Bilges at safe level
ROUTINE INSPECTIONS OF MAIN & AUX MACH. SPACES MADE AT REG. INTERVALS

0400-0800 WATCH

Ciler - Spindes FWT - Matthews R/E - Gentile WATCH ENGR'S SIGNATURE *Spindes* R/E
Machinery is BEFORE
Plant Normal AS BEFORE
Bilges at safe level
Changed & Cleaned Burners & Discharge Strainers

0800-1200 WATCH

Ciler - Spindes FWT - Matthews R/E - Gentile WATCH ENGR'S SIGNATURE *Spindes* R/E
Machinery is BEFORE
Bilges at safe level
ROUTINE INSPECTIONS OF MAIN & AUX MACH. SPACES MADE AT REG. INTERVALS

CHIEF ENGINEER

WILLIAM SPINDES FWT - Matthews R/E - Gentile BEAMS WATCH ENGR'S SIGNATURE *Spindes* R/E
CHIEF ENGINEER

1700-1800
1800-1900
1900-2000

947 S.C.
9.34
14.02
21.07
30
11.17
50330
PL 0046 S.C.

CHIEF ENGR'S SIGNATURE

USNS

GEN. JOHN POPE T-AP 110

VOYAGE NO.

FROM

TO

TYPE OF VESSEL

DATE

		WATCH								WATCH								
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			
RUNNING TIME								MACH. PARTICULARS (CONT'D) TEMPERATURES (CONT'D)		HOTTEST GEAR BEARING FORWARD								
DETENTION TIME										HOTTEST GEAR BEARING AFT								
REVOLUTION COUNTER (END OF WATCH)										AUX. COND. CONDENSATE		88	87	85	87	84	90	
TOTAL REVOLUTIONS (FOR WATCH)										1ST STAGE FEED WATER HEATER		112	112	112	112	112	116	
AVERAGE RPM										D. C. FEED WATER HEATER		240	240	240	240	240	240	
F.O. METER (END OF WATCH)		1138 1910	1135 2310	1138 2700	1138 3120	1138 3530	1138 4070	3RD STAGE FEED WATER HEATER										
F.O. CONSUMED		400	200	390	420	430	520											
PRESSURES	THROTTLE							BOILER PARTICULARS TEMPERATURES		SUPER HEAT		P						
	H.P. AHEAD									S	650	615	615	610	605	630		
	L.P. AHEAD									F.O. TO BURNERS		190	190	190	190	190	190	
	AUX. VACUUM	29"	29"	29"	29"	29"	29"			P	AIR TO FURNACE							
	L.O. TO TURBINES									S	1.2	1.2	1.2	1.4	1.4	1.2		
	AUX. STEAM	125	125	125	145	145	145			P	F.O. TEMP. IN SETTLING TANKS		80	80	85	85	90	85
	BACK PRESSURE	10	10	10	10	10	10			S	97	90	95	95	105	102		
	GLAND STEAM									PORT BOILER UPTAKE								
	H.P. BLEEDER									STBD. BOILER UPTAKE		245	245	240	285		275	
	I.P. BLEEDER									F. O. BACK PRESSURE								
L.P. BLEEDER							MAIN STEAM		220	220	420	440		440				
STEAM AT THROTTLE								F.O. TO BURNERS		120	120	130	140		100			
AUX. H.P. EXHAUST		96/94	95/95	92/94	94/98	96/98	99/110	MAIN COND. SALINITY		.02	.02	.02	.2	.2	.2			
CONDENSATE								ENGINE ROOM TEMPERATURE		72	71	69	69	69	74			
CIRC. WATER IN		59	60	59	58	51	60	FIRE ROOM TEMPERATURE										
AUX. CIRC. WATER OUT		67/65	70/66	68/64	67/64	68/64	70/61	NOZZLES IN USE										
L.O. TO COOLERS								NO. OF BURNERS IN USE		P								
L.O. FROM COOLERS								S	2	2	2	2	2	2				
TEMPERATURE THRUST BEARING								P	BURNER TIP SIZE									
FORWARD H.P. ROTOR BEARING								S	53/60	53/60	53/60	53/60	54/60	54/60				
AFT. H.P. ROTOR BEARING								CO ₂ % PORT BOILER										
FORWARD L.P. ROTOR BEARING								CO ₂ % STBD. BOILER										
AFT. L.P. ROTOR BEARING								OIL LEVEL MAIN SUMP										

GENERATORS												FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	METER AT NOON	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND	CONSUMED
1200 TO 1600	1	1200	440	650	9	115	109		62	550	800	240	11384070	175	20	180	15
	2	1200	440	650	7	125	110		62	450	800	240	11381510				
1600 TO 2000	1	1200	440	615	9	120	110		62	700	600	240	2560	2135		2130	5
	2	1200	440	615	7	122	110		62	700	600	240	3948				
2000 TO 2400	1	1200	440	615	9	120	110		62	700	600	240	50	2135		2130	5
	2	1200	440	615	7	124	110		62	700	600	240	3898				
2400 TO 0400	1	1200	440	610	9	115	100		62	1100	1100	240	780	2135		2130	5
	2	1200	440	610	7	129	110		62	700	700	240	50				
0400 TO 0800	1	1200	440	605	9	115	108		62	800	800	240	3898				
	2	1200	440	605	7	123	110		62	750	750	240	50				
0800 TO 1200	1	1200	440	630	9	124	113		62	800	800	240	780				
	2	1200	440	630	7	124	111		43	750	750	240	50				
													LOW PRESS. EVAPORATORS (No. of hrs. operated / Fresh water made gals.)				
													L.O. CENTRIFUGE - HOURS OPERATED				
													1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800
													SUMMARY				
													RUNNING TIME	PROPELLER SLIP (%)			
													DETENTION TIME	BBL FUEL MI			
													TOTAL REVOLUTIONS	WIND DIRECTION			
													AVERAGE R.P.M.	STATE OF SEA			
													TOTAL MILES BY ENGINE	STATE OF WEATHER			
													TOTAL MILES BY OBSERVATION				

REMARKS

1200-1600 WATCH

PORT RELIEF WATCH. Machinery in Operation - No. 1 Boiler, F.D. Blower, F.D. Pump (Elec), E.V.C. 1450 F.C. Service Pump, Inhd. S.W., No. 1-2 S.S. Gens., Condenser with No. 1 Aux. Cuts and No. 2 Cond. Pump, & Aux. Air Eject, No. 2 F.E.S. Pump, No. 1 F.D. Pump, No. 1 Air Compressor, No. 2 Air Compressor, No. 1 Evap. Changed F.W. Due to 3 P. and 1 P. Relief to Port. Found finally a grease gun and greased No. 1 F.D. Pump. Changed and cleaned burners and F.C. Disch. & S.W. strainers. Bilges safe. Still on S.W.

Oiler - Wanner F.W. - 11' Ginnis P.R. - Booms

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

PORT RELIEF WATCH. Machinery same. Made routine checks of machinery and spaces. Changed and cleaned burners and str. Bilge satisfactory.

Oiler - Lovell F.W. - Watkins P.R. - Marvin

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

PORT RELIEF WATCH. No machinery changes. Routine checks of machinery and spaces. Need adjustment on Evap. float air valve. Sticks occasionally - then does not fill without float tripping. Changed and cleaned disch. str. and burners. Pumped BK bilge down, also Evap. flat. Complied with S.P. & N/C. Condition Normal.

Oiler - Lovell F.W. - Watkins P.R. - Marvin

WATCH ENGR'S SIGNATURE

2400-0400 WATCH

BLOW TUBES #1 BLOWER. BLOW 3 TIMES #8 TO #1 SOOT BLOWER 4 TIMES #1 TO #8 SOOT BLOWER A TOTAL OF 7 BLOWS PER ELEMENT.
NOTE #4 ELEMENT SCAVING AIR LINE BLOW OUT.

LOOK STOWAGE FOR BUTTER, SALT, GENTLE

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

PLANT NO. 400 - AS BEFORE

BILGES AT SOLE LEVEL

ROUTINE INSPECTIONS OF MAIN & FOX, YARD, STAGES, WIDE AT REGULAR INTERVALS

WATCH AS BEFORE

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

Port watch machinery in operation as before. Changed & cleaned F.D. Burner & Disch. strainer. Lit. off Port Boiler for drying S.O.C. same. Crew working on sootblower & cleaning & painting Eng. Room.

WATCH ENGR'S SIGNATURE

CHIEF ENGINEER

BOILER TEMPERATURES

STEAM PRESSURE

HOURS 971 HOURS 500

AKL 9.34

T-W 13.43 P-F 14

S.L. 2107 S.L.

PHOS. 35 PHOS.

R-ph 17 R-ph

50328

CHIEF ENGR'S SIGNATURE

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE	
JOHN POPE TAP-110				AT NSC OAKLAND				P2-52-R2		3/27-28/67	

		WATCH								WATCH					
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME								MACH. PARTICULARS (CONT'D)							
DETENTION TIME								TEMPERATURES (CONT'D)							
REVOLUTION COUNTER (END OF WATCH)								HOTTEST GEAR BEARING FORWARD							
TOTAL REVOLUTIONS (FOR WATCH)								HOTTEST GEAR BEARING AFT							
AVERAGE RPM								AUX. COND. CONDENSATE		87	87	87	88	88	88
F.O. METER (END OF WATCH)		1138	1138	1138	1138	1138	1138	1ST STAGE FEED WATER HEATER		112	112	112	114	114	113
F.O. CONSUMED		400	460	400	420	440	476	D. C. FEED WATER HEATER		240	240	240	240	240	240
								3RD STAGE FEED WATER HEATER							
								SUPER HEAT		P					
								F.O. TO BURNERS		S	630	620	650	650	620
								PRESSURE AIR TO FURNACE		P					
								F.O. TEMP. IN SETTLING TANKS		P	90	90	90	85	85
								PORT BOILER UPTAKE		S	105	115	112	105	105
								STBD. BOILER UPTAKE			275	280	285	280	285
								F. O. BACK PRESSURE							
								MAIN STEAM			440	440	440	440	440
								F.O. TO BURNERS			140	130	130	140	140
								MAIN COND. SALINITY			114	102	103	104	104
								ENGINE ROOM TEMPERATURE			75	74	71	69	70
								FIRE ROOM TEMPERATURE							
								NOZZLES IN USE							
								NO. OF BURNERS IN USE		P					
								BURNER TIP SIZE		S	53/60	53/60	53/60	53/60	53/60
								CO ₂ % PORT BOILER							
								CO ₂ % STBD. BOILER							
								OIL LEVEL MAIN SUMP							

		GENERATORS										FUEL - WATER AND LUBE OIL									
		GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL			
1200 TO 1600		1	1200	440	630	9	134	125		62	850	850	240	METER AT NOON	11386560	ON HAND AT START OF DAY	180	EVAPORATED OR RECEIVED	20		
		2	1200	440	630	7	127	112		63	800	800	240	METER PREVIOUS NOON	11384070	ON HAND	185	CONSUMED	15		
														CONSUMED BY METER	2490	ON HAND AT START OF DAY	3898	RECEIVED DURING DAY	-0-		
														ON HAND AT START OF DAY	-0-	ON HAND AT START OF DAY	2130	RECEIVED DURING DAY	50		
														REMAINING ON BOARD	3848	ON HAND	2125	CONSUMED	5		
1600 TO 2000		1	1200	440	620	9	120	110		62	800	700	240	ON HAND AT START OF DAY	750	ON HAND	1223	RECEIVED	1220		
		2	1200	440	620	7	124	110		62	800	700	240	EVAPORATED OR RECEIVED	242	ON HAND	1223	RECEIVED	1220		
														ON HAND	542	ON HAND	1220	RECEIVED	1220		
														CONSUMED	50	ON HAND	1220	RECEIVED	1220		
2000 TO 2400		1	1200	440	650	9	120	110		62	800	700	240	DOMESTIC WATER		ON HAND	1220	RECEIVED	1220		
		2	1200	440	650	7	122	110		62	800	700	240	CONSUMED	50	ON HAND	1220	RECEIVED	1220		
																ON HAND	1220	RECEIVED	1220		
																ON HAND	1220	RECEIVED	1220		
2400 TO 0400		1	1200	440	650	9	120	110		62	800	800	240	L.O. CENTRIFUGE - HOURS OPERATED							
		2	1200	440	650	7	122	110		62	650	650	240	1200 TO 1600		1600 TO 2000		2000 TO 2400			
																2400 TO 0400		0400 TO 0800			
																		0800 TO 1200			
0400 TO 0800		1	1200	440	650	9	118	110		62	700	700	240	SUMMARY							
		2	1200	440	650	7	123	109		62	350	800	240	RUNNING TIME		PROPELLER SLIP (%)					
														DETENTION TIME		BBL FUEL MI					
														TOTAL REVOLUTIONS		WIND DIRECTION					
0800 TO 1200		1	1200	440		9	119	110		62	700	700	240	AVERAGE R.P.M.		STATE OF SEA					
		2	1200	440		7	126	116		62	850	750	240	TOTAL MILES BY ENGINE		STATE OF WEATHER					
														TOTAL MILES BY OBSERVATION							

REMARKS

1200-1600 WATCH

Port watch machinery in operation #1 Boiler & #1 F.D. Blower #1 Elect. Feed Pump. #1 F.O. Pump #1 M.H. and Pump #1 + #2 S.S. Cais. Aux. Circ. Pump. Air Comp. #1 Fire Pump. even cleaning & painting Eng. Rm.

WATCH ENGR'S SIGNATURE-

L. Harris

1600-2000 WATCH

PORT RELIEF WATCH -- ORDERS ARE: -- "DO NOT PUMP #1 ER TONIGHT!!" -- DEAF. Checked machinery and spaces as 10th. Changed and cleaned burners & str. Filling D.B. Reserve Feed Tank. 1830 Gang way Flood Light started at socket & plug. Fuses out, at affected socket box FC 158 P. Rejoining another light to latter socket box. Also, no keys tonight again.

2000-2400 WATCH

Oilier - Lovell Port - Watkins R/R - Marvin WATCH ENGR'S SIGNATURE- *[Signature]* R/R
PORT RELIEF WATCH. No changes in machy. Checked machinery and spaces. Changed and cleaned burners and F.O. Disch Str. Filling Res. Fed Tank. Bilge not pumped as per orders - 2' down in Stbd Bilge. Complied w/b's & F.O. F.W. Suit - 3 Stbd. List 1' Stbd. 2300 Inbd Sett. 2'-6". Changed to Outbd.

2400-0400 WATCH

Oilier - Lovell Port - Watkins R/R - Marvin WATCH ENGR'S SIGNATURE- *[Signature]* R/R
ROUTINE PORT WATCH
DID NOT PUMP Bilges
ADDED POT WATER TO #3 PORT TO TAKE STBD LIST OFF SHIP

0400-0800 WATCH

Oilier STABLE. PORT BUTALK REEF CENTRE WATCH ENGR'S SIGNATURE- *[Signature]* R/R
ROUTINE PORT WATCH
ROUTINE INSPECTIONS OF M.V. AUX. MACH. SPACE MADE AT REGULAR INTERVALS.
Bilges AT SAFE LEVEL. TRIED TO PUMP SHAFT ALLEY BUT AIR ACTUATED VALVE FROM #2 PUMP TO Bilge MAIN LEAKS COMPROMISED TO SUCTION LINE THEREBY LOSING PUMP SUCTION.

0800-1200 WATCH

WATCH AS BEFORE WATCH ENGR'S SIGNATURE- *[Signature]* R/R
Port watch machinery in operation as before changed & cleaned F.O. Blower & strainer. Pumped shaft alley Bilges, #1 F.O. Pump over. Tacked over Stbd shaft for water. To Check #13 spring bearing. Added compound to stbd Bilge.

WATCH ENGR'S SIGNATURE-

L. Harris

CHIEF ENGINEER

BOILER WATER READINGS

STEAM PORT

HOURS 995 1000 SEC. 0

AKI 8.76

F.W. 11.68

S.L. 2.07

T.M. 40 100.

T.M. 10 100.

S.O. 40 S.O. 3

PH COND. 7.6

CHIEF ENGR'S SIGNATURE-

[Signature]

REMARKS

1200-1600 WATCH

Port watch machinery In operation #1 Bailou & F.D. Blower #1 Elect. Food Pump. #1 F.O. Pump #1 & #2 S.S. C.W.S. #1 main and Pump. Aux. Circ. Pump. #1 Fire Pump Air Comp. F.W. Pump. Pumped F.O. Satt. from #6 Deep TK.

WATCH ENGR'S SIGNATURE-

L. Harris

1600-2000 WATCH

PORT RELIEF WATCH. Machinery as above and as left. Checked machinery and spaces. 1600 F.W. Suct. to P. list 2000 Plumber filling 33 fire in shore. 1745 Ship shifted to Stbd. Secured F.W. on Deck. F.W. Suct. to Stbd. Changed and cleaned burners and Stc. 2 1/2" water in Stbd. bilge. N/C - no pumping. 1930 Put heat to Port Gang's Quarters by request. Return trap stopped up.

Oiler - Lovell F.W.T. Watkins Rtr. - Martin

2000-2400 WATCH

WATCH ENGR'S SIGNATURE-

L. Harris

PORT RELIEF WATCH. No changes in machinery. Routine checks of machinery and spaces. Routine changing of burners and cleaning, also discharge. Complied with S/O & N/C. 2230 Complied with heat to Port Gang. Trap not working in bilge pump. Told Rtr. to stop blower, and secure steam leave door open; take heat from passage way.

Oiler - Lovell F.W.T. Watkins Rtr. - Martin

2400-0400 WATCH

WATCH ENGR'S SIGNATURE-

L. Harris

Routine Port Watch

Bilges at safe level. Except for shaft alley. On order to pump down. Complied with Night & Landing orders. Took on water to #30' Port Tank. To trim ship.

Oiler - Lovell F.W.T. Watkins Rtr. - Martin

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

L. Harris

WATER TO PUMP SHAFT ALLEY. Bilges. Due to inoperative Bilge Chain Air-actuated Suction Valve.

Pumped down Bilges 2000. But did not pump down Bilge due to Night orders.

Watch As Before

0800-1200 WATCH

WATCH ENGR'S SIGNATURE-

L. Harris

Port watch machinery in operation as before. Changed & cleaned F.O. Bunker & strainer. Pumped shaft alley Bilges. Annual Inspection of machinery & spaces by Port Navy Captain. Sec. Fire & sanitary system @ 0930. Same on line @ 1100.

WATCH ENGR'S SIGNATURE-

L. Harris

CHIEF ENGINEER

BOILER WATER READINGS

STEAM 100

HOURS 1019 - 1025 S.C. 0

AIR 18.74

WATER 11.48

FAL 2.07

FECS. 40 PHOS.

LASH 10 B. 22

SOS 35 SOS

1st. Ph. Cond. 8.0

CHIEF ENGR'S SIGNATURE-

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE			
John POPE TAP-110				AT NSE ONKLAND				PR-52-R2		3-29/30/67			
		WATCH						WATCH					
		1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200	
RUNNING TIME													
DETENTION TIME		Port		Boiler running		new bearings		4555		7170			
REVOLUTION COUNTER (END OF WATCH)		1138		1139		1139		1139		1139		1139	
TOTAL REVOLUTIONS (FOR WATCH)		9580		0090		0530		0150		1320		1810	
AVERAGE RPM		1138		1139		1139		1139		1139		1139	
F.O. METER (END OF WATCH)		440		510		440		420		420		440	
F.O. CONSUMED		440		510		440		420		420		440	
MACH. PARTICULARS (CONT'D)													
HOTTEST GEAR BEARING FORWARD													
HOTTEST GEAR BEARING AFT													
AUX. COND. CONDENSATE		88						86 85 87 87 87					
1ST STAGE FEED WATER HEATER		113						112 110 112 112 128					
O. C. FEED WATER HEATER		240						240 240 240 240 238					
3RD STAGE FEED WATER HEATER													
SUPER HEAT		P											
F.O. TO BURNERS		S						630 635 600 600 600 640					
AIR TO FURNACE		P											
F.O. TEMP. IN SETTLING TANKS		S						110 110 110 95 95 95					
PORT BOILER UPTAKE													
STBD. BOILER UPTAKE		305						290 295 295 300 300					
F. O. BACK PRESSURE													
MAIN STEAM		440						440 440 440 440 440					
F.O. TO BURNERS		160						160 130 130 140					
MAIN COND. SALINITY		.1						.01 .01 .01 .01 .01					
ENGINE ROOM TEMPERATURE		70						70 67 65 66 66					
FIRE ROOM TEMPERATURE													
NOZZLES IN USE													
NO. OF BURNERS IN USE		P											
BURNER TIP SIZE		S						3 2 2 2 2 2					
CO ₂ % PORT BOILER													
CO ₂ % STBD. BOILER													
OIL LEVEL MAIN SUMP													
MISCELLANEOUS													
STEAM AT THROTTLE		17/84						42/42 90/90 80/86 80/86 103					
CONDENSATE													
CIRC. WATER IN		60						60 60 60 60 60					
CIRC. WATER OUT		69/65						65/64 60/62 60/62 60/62 70					
L.O. TO COOLERS													
L.O. FROM COOLERS													
TEMPERATURE THRUST BEARING													
FORWARD H.P. ROTOR BEARING													
AFT. H.P. ROTOR BEARING													
FORWARD L.P. ROTOR BEARING													
AFT. L.P. ROTOR BEARING													
GENERATORS													
WATCH													
GENERATOR NUMBER													
R.P.M.													
STEAM PRESSURE													
STEAM TEMP.													
L.O. PRESSURE													
L.O. TO COOLER													
L.O. FROM COOLER													
TEMP. OF HOTTEST BEARING													
L.O. GOVERNOR PRESSURE													
AMPS POSITIVE													
AMPS NEGATIVE													
VOLTS													
1200 TO 1600		1 1200 440 630 9 120 110 62 800 850 240						2 1200 440 630 7 125 110 62 800 800 240					
1600 TO 2000		1 1200 440 635 9 120 110 62 800 800 240						2 1200 440 635 7 120 110 62 800 800 240					
2000 TO 2400		1 1200 440 600 9 120 110 62 800 800 240						2 1200 440 600 7 120 110 62 800 800 240					
2400 TO 0400		1 1200 440 600 9 120 110 62 800 800 240						2 1200 440 600 7 123 110 62 800 800 240					
0400 TO 0800		1 1200 440 600 9 120 110 62 800 800 240						2 1200 440 600 7 122 110 62 800 800 240					
0800 TO 1200		1 1200 440 600 9 119 110 62 800 800 240						2 1200 440 600 7 122 110 62 800 800 240					
FUEL - WATER AND LUBE OIL													
METER AT NOON		1139/870						ON HAND AT START OF DAY 186					
METER PREVIOUS NOON		11389/40						EVAPORATED OR RECEIVED 25					
CONSUMED BY METER		2730						ON HAND 195					
ON HAND AT START OF DAY		3758						CONSUMED 15					
RECEIVED DURING DAY		-0-						ON HAND AT START OF DAY 2120					
EXPENDED DURING DAY		55						RECEIVED -0-					
REMAINING ON BOARD		3743						ON HAND 2115					
ON HAND AT START OF DAY		900						CONSUMED 5					
EVAPORATED OR RECEIVED		-0-						ON HAND 1218					
ON HAND		880						RECEIVED 1215					
CONSUMED		20						CONSUMED 3					
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)													
L.O. CENTRIFUGE - HOURS OPERATED													
1200 TO 1600													
1600 TO 2000													
2000 TO 2400													
2400 TO 0400													
0400 TO 0800													
0800 TO 1200													
SUMMARY													
RUNNING TIME								PROPELLER SLIP (%)					
DETENTION TIME								BBL FUEL MI					
TOTAL REVOLUTIONS								WIND DIRECTION					
AVERAGE R.P.M.								STATE OF SEA					
TOTAL MILES BY ENGINE								STATE OF WEATHER					
TOTAL MILES BY OBSERVATION													

REMARKS

1200-1600 WATCH

Port Watch machinery in operation as before ^{1st} #1 Boiler & F.D. Blower
 #1 Elect. Feed Pump #1 F.C. Pump #1 & #2 S.S. Cans #1 main Cond. Pump
 #1 Fire Pump Aux. Circ. Pump Air Comp. F.W. Pump.

WATCH ENGR'S SIGNATURE-

L. Harris

1600-2000 WATCH

Port Relief Watch. Machinery as before. R/E Evap. in service. Routine checks
 of machy and spaces. Changed and cleaned burners and FC Disch. Str.
 1800 Mn Galley 3 35°C Faucet over sink stripped open. Secured valves
 underneath. Telephone call of ringing order. F.W. Suct. 3P List 12 P. Cooled Sats.
 Dia'net pump bilge as per N/C.

Ciler-Lovell FWT-Watkins R/E-Martin

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

Port Relief Watch. No changes in machy. Routine checks made.
 Changed and cleaned burners and disch str. Dia'net pump bilge as per N/C.
 Complied with SIC & N/C. Condition Normal.

Ciler-Lovell FWT-Watkins R/E-Martin

WATCH ENGR'S SIGNATURE-

L. Harris

2400-0400 WATCH

ROUTINE PORT WATCH

BILGES AT SAFE LEVEL

ROUTINE INSPECTIONS OF AUX. & MAIN MACH. SPACES
 MADE AT REGULAR INTERVALS.

Ciler-Lovell FWT-Watkins R/E-Martin

WATCH ENGR'S SIGNATURE-

L. Harris

0400-0800 WATCH

CHANGED TO #3 F.W. SETTLER @ 0500

COMPLIED WITH A/SHT & STANDING ORDERS.

MACHINERY AS BEFORE

Changed & cleaned Burners

WATCH AS BEFORE

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

Port Watch machinery in operation as before except Sec.
 #2 M & R Rooms commenced. Changed & cleaned F.C. Burners &
 Disch. Structures.

WATCH ENGR'S SIGNATURE-

L. Harris

CHIEF ENGINEER

PORTER WATER READINGS

1001

1013

8176

11148

2149

110.40 FEET

10010 B.T.

35 35

11000

CHIEF ENGR'S SIGNATURE-

L. Harris

REMARKS

1200-1600 WATCH

Port watch machinery in operation #1 Boiler + F.D. Blower #1 Elect. Feed Pump #1 B.P. Pump #1 S.S. Blower #1 main cond. Pump and Cond. Pump Pumped salt from Aft Eng. Room F.O. salt. Pumped salt Aft. started #2 S.S. Blower 1400 To Check Main Condenser. Test same, it had speed 1230 RPM overspeed 1340 RPM. Same on line

WATCH ENGR'S SIGNATURE

J. H. Hume

1600-2000 WATCH

PORT RELIEF WATCH Machinery as above with M/E Evap. in service. Blandford Pump. Routine checks of mach. and spaces. Changed and cleaned burners and strainers, F.O. Disch. Set 150" Sta. to 150". Gen #2 Gen. functioning properly. Raised gland seal to keep 24" vacuum. Condition Normal. Need some scratch paper in this LR. 1930 Mate notified - "Loading Stores". Need Elec. Found Bricks (Elec) aware and standing by.

Ciler - Lovell FWT-Watkins Rtr-Martin

WATCH ENGR'S SIGNATURE

W. Watkins R/E

2000-2400 WATCH

PORT RELIEF WATCH Machinery same. Routine checks of mach. and spaces. Changed and cleaned burners and str. Bldg pump tagged and "off" on board, so did not pump bilge. Loading stores. Elec available. Leak in AC unit at 3-60 2 3-2 Trip Comp. Mate notified - did not check - reported not bad. FWSect 38. Complied with SIC & N/A. Condition Normal.

Ciler - Lovell FWT-Watkins Rtr-Martin

WATCH ENGR'S SIGNATURE

W. Watkins R/E

2400-0400 WATCH

Routine checks of mach. and spaces. Bldg pump tagged and "off" on board, so did not pump bilge. Loading stores. Elec available. Leak in AC unit at 3-60 2 3-2 Trip Comp. Mate notified - did not check - reported not bad. FWSect 38. Complied with SIC & N/A. Condition Normal.

0400-0800 WATCH

Routine checks of mach. and spaces. Bldg pump tagged and "off" on board, so did not pump bilge. Loading stores. Elec available. Leak in AC unit at 3-60 2 3-2 Trip Comp. Mate notified - did not check - reported not bad. FWSect 38. Complied with SIC & N/A. Condition Normal.

WATCH ENGR'S SIGNATURE

W. Watkins R/E

0800-1200 WATCH

Port watch machinery in operation #1 Boiler + F.D. Blower #1 Elect. Feed Pump #1 B.P. Pump #1 S.S. Blower #1 main cond. Pump and Cond. Pump Pumped salt from Aft Eng. Room F.O. salt. Pumped salt Aft. started #2 S.S. Blower 1400 To Check Main Condenser. Test same, it had speed 1230 RPM overspeed 1340 RPM. Same on line

WATCH ENGR'S SIGNATURE

W. Watkins R/E

CHIEF ENGINEER

1. 10/10
2. 10/10
3. 10/10
4. 10/10
5. 10/10
6. 10/10
7. 10/10
8. 10/10
9. 10/10
10. 10/10

CHIEF ENGR'S SIGNATURE

W. Watkins R/E

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE			
270 LIFE TAP-110				04050 201000				P-33-82		3/3/11-27			
		WATCH						WATCH					
		1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200	
RUNNING TIME													
DETENTION TIME													
REVOLUTION COUNTER (END OF WATCH)													
TOTAL REVOLUTIONS (FOR WATCH)													
AVERAGE RPM													
F.O. METER (END OF WATCH)		1187 4720		1139 5100		1137 5490		1129 5860		1137 6230		1134 6690	
F.O. CONSUMED		440		380		370		390		390		440	
MACH. PARTICULARS (CONT'D)													
TEMPERATURES (CONT'D)													
HOTTEST GEAR BEARING FORWARD													
HOTTEST GEAR BEARING AFT													
AUX. COND. CONDENSATE		87		88		87		87		82		89	
1ST STAGE FEED WATER HEATER		100		108		102		110		102		111	
D. C. FEED WATER HEATER		230		242		240		270		270		270	
3RD STAGE FEED WATER HEATER													
SUPER HEAT		P											
S		630		650		630		600		600		630	
F.O. TO BURNERS		170		190		190		190		190		190	
AIR TO FURNACE		P											
S		1.5		2.0		2.0		1.5		1.5		1.5	
F.O. TEMP. IN SETTLING TANKS		P		90		90		95		95		90	
S		115		115		115		110		110		110	
PORT BOILER UPTAKE													
STBD. BOILER UPTAKE		285		285		280		275		275		270	
F.O. BACK PRESSURE													
MAIN STEAM		470		420		420		440		440		440	
F.O. TO BURNERS		150		150		130		130		130		130	
MAIN COND. SALINITY				0.1		0.9		0.0		0.0		0.0	
ENGINE ROOM TEMPERATURE		48		65		66		67		67		65	
FIRE ROOM TEMPERATURE													
NOZZLES IN USE													
NO. OF BURNERS IN USE		P											
S		2		2		2		2		2		2	
BURNER TIP SIZE		P											
S		5/16		5/16		5/16		5/16		5/16		5/16	
CO ₂ % PORT BOILER													
CO ₂ % STBD. BOILER													
OIL LEVEL MAIN SUMP													
MISCELLANEOUS													
GENERATORS													
WATCH													
GENERATOR NUMBER													
R.P.M.													
STEAM PRESSURE													
STEAM TEMP.													
L.O. PRESSURE													
L.O. TO COOLER													
L.O. FROM COOLER													
TEMP. OF HOTTEST BEARING													
L.O. GOVERNOR PRESSURE													
AMPS POSITIVE													
AMPS NEGATIVE													
VOLTS													
1200 TO 1600		1 1200 440 610 9 110 110 67 62 800 800 240		2 1200 440 630 7 125 110 67 62 800 800 240									
1600 TO 2000		1 1200 440 650 9 120 110 67 62 800 80											

REMARKS

1200-1600 WATCH

Port Relief Watch. Machinery as before with MU Evap filling Reserve Path. DB. Checked machinery and spaces. Changed burners and F.C. Disch. Str. & cleaned. Loading status. Elec Gutierrez available. Bilge satisfactory. Condition Normal. F.W. Suct No 34. F.C. Suct inbd.

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

Port Relief Watch. Machinery as before with MU Evap filling Reserve Path. DB. Checked machinery and spaces. Changed burners and F.C. Disch. Str. & cleaned. Loading status. Elec Gutierrez available. Bilge satisfactory. Condition Normal. F.W. Suct No 34. F.C. Suct inbd.

Oiler - Lovell FWT - Watkins R/R - Marvin

Elect on watch via Gutierrez

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

Port Relief Watch. No changes in machinery. Filling Res Ev Tanks with MU Evap. Routine checks of machinery and spaces. Changed and cleaned burners and F.C. Disch. Str. Pumped ER bilge down. Complied with S/C & N/C. Condition Normal. Oiler cleaned up oil on and around Gens as per N/C. Loading status until 0400.

Oiler - Lovell FWT - Watkins R/R - Marvin

2400-0400 WATCH

ROUTINE PORT WATCH
BILGES AT SAFE LEVEL
CHANGED BURNERS & CLEANED TANK

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

ROUTINE PORT WATCH

BILGES OK

CHANGED & CLEANED F.C. STRAINERS

ADDED 1 GAL LUBE OIL TO #1 MU FEED PUMP

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

AS BEFORE

ROUTINE PORT WATCH

BILGES OK

#2 CLM FILL TO 100% @ 1015

DATA DOWN M. J. 1015

WATCH ENGR'S SIGNATURE

CHIEF ENGINEER

WATCH ENGR'S SIGNATURE

BOILER WATER READINGS

STB'D	PORT
HOURS	HOURS
AKL	AL
T-AKL	T-AKL
SAL.	SAL.
PCS.	PCS.
ph	R. ph

CHIEF ENGR'S SIGNATURE

[illegible]

REMARKS

1200-1600 WATCH

PORT RELIEF WATCH. Mostly in Oper. No. 2 Boiler, F.D. Blower, Elec. FC & F.D. Pump, F.D. Heater, No. 1-2 Guns, Condensers Circ. & No. 1 M. Cond. Pump. No. 1 Aux. Eject, No. 2 Gun idling, M.C. Evap., No. 1 Air Comp. on Stdby, No. 1 Elec. F.W. Pump & F.E.S. Pump. Using Inboard Suct. F.W. Suct. 3". Changed & cleaned burners and both Suct. & Disch. F.C. Strs. 1430 Sizeable leak in Aft Peak manhole cover. Manhole cover loose. Tightened nuts. Stopped leak. Tank not over flowing.

Ciler - Mornish

F.W.T. - Searcas Rte - Brown

WATCH ENGR'S SIGNATURE

2205 Reported

1600-2000 WATCH

PORT RELIEF WATCH. 1600 Noticed water pouring on Fan Tail from Aft Peak over Flow. Checked valves in SP. One cracked open. Secured. C'flow stopped. Routine 'plus' checks. Condition back to normal. Changed & cleaned burners and disch. str. Bilge satisfactory.

Ciler - Levell

F.W.T. - Watkins Rte - Brown

WATCH ENGR'S SIGNATURE

2205 Reported

2000-2400 WATCH

PORT RELIEF WATCH. Mostly same. Routine checks of machinery and spaces. Changed and cleaned burners and disch. strainer. Pumped ER bilge down. Complied with S/O & N/C Condition Normal. Notes - Need rain. F.W.T. & Ciler in need. Will get Steward for sheets tomorrow - Sunday.

Ciler - Levell

F.W.T. - Watkins Rte - Brown

WATCH ENGR'S SIGNATURE

2205 Reported

2400-0400 WATCH

Normal Water Level
Pumped to Safe Level
Pumped & Cleaned Burners

0400-0800 WATCH

After 0400 hours the M.C. Gun & M.C. Gun Drill. WATCH ENGR'S SIGNATURE. Machinery as before. Bilge to safe level. Routine inspection of No. 7 Aux. Mach. Spaces above to regular intervals.

0800-1200 WATCH

Machinery as before. Bilge to safe level. R - STM to STBD INBD & OUTBOARD F.C. SETTLERS BOTH AT 80". TOOK ON FRESH WATER 70 + 30 DLT APPROX 2 1/2 FT. TO AHEAD 9 FEET LEVEL.

CHIEF ENGINEER

W. H. Mornish F.W. Searcas Rte - Brown

WATCH ENGR'S SIGNATURE

2205 Reported

FO. TPC READINGS
SEAL. 400
HOURS. 1000
AIR. 10
FUEL. 10
WATER. 10
FRESH. 10
R. ph.

CHIEF ENGR'S SIGNATURE

2205 Reported

REMARKS

1200-1600 WATCH

PORT RELIEF WATCH. Machinery in Operation: No. 1 Boiler, F.E. Blower, Elec. F.D. & F.O. Serv. Pump w/EC. Htr, Inbd. Satt. 6 1/2, Nos. 1-2 S.S. Gens, Condensers and Aux. Circ, No. 1 Ma. Cond. Pump, No. 2 Gen. idling, Aux. Air Eject, No. 1 Air Comp. on Standby, No. 1 Elec. F-S Pump and F.W. Pump, suet. 3 1/2, 6 mi. Blon. Jern. Mid. Evap. in service. Changed and cleaned burners and both disc. and suction str. Capt. Berlin in ER with guest Mr. Summers and friends visited ER. Over wiped-up Gens.

Over - Harrah FWT - Semons R/R - Brown

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

PORT RELIEF WATCH. Machinery same except Return by pass at aft Satt. is open. Trap is either stopping up or too small. 4 hrs. with very little rise in temp. Made routine checks at machinery and spaces. Changed burners and disc. str. & cleaned. Filled reserve F.D. Tr. 1830 Aft Satt. 100°. Secured str. and closed by pass. Trap valve open thru trap. Bilge satisfactory.

Over - Lovell FWT - Watkins R/R - Marvin

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

PORT RELIEF WATCH. Machinery same. Routine checks made. Changed/cleaned burners and str. 2130 No. 2 Gen. on line. 2200 No. 2 Boiler in readiness. Lit-off. Burning 5 min ON; 20 min OFF for warm-up. Complied with S/C & N/C. Condition Normal. Bilge satisfactory. Mr McDonald pumped Satt. in this ER. Now on Outbd. Str. on both Satt. - ME

Over - Lovell FWT - Watkins R/R - Marvin

WATCH ENGR'S SIGNATURE

2400-0400 WATCH

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

WATCH ENGR'S SIGNATURE

CHIEF ENGINEER

CHIEF ENGR'S SIGNATURE

[illegible]

✓

	TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1.	L.P. EXHAUST TEMP	90	96	96	76	76	75	75	88	92	42		92	94	94	94	94	94	94	94	94	96	98	98	96
2.	MN COND STE TEMP	90	90	90	80	80	82	82	76	72	68	72	90	90	90	90	90	90	90	90	90	90	100	100	90
3.	MN INJ TEMP	56	54	54	56	54	56	56	56	56	56	56	56	56	56	56	56	56	56	56	56	58	58	58	56
4.	MN OVBD TEMP	68	68	68	66	66	56	56	56	56	56		66	66	66	66	66	66	66	66	68	68	68	70	68
5.	L.O. TO COOLERS	126	126	126	126	126	122	122	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126
6.	L.O. FROM COOLERS	110	110	110	110	110	110	110	116	116	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
7.	THRUST BRG TEMP	112	112	112	112	112	108	108	116	108	108	108	110	110	110	110	110	110	110	110	112	112	112	112	112
8.	FWD H.P. ROTOR BRG	120	120	120	122	122	118	118	118	118	118		120	120	120	120	122	122	122	122	122	122	122	122	120
9.	AFT H.P. ROTOR BRG	125	125	125	125	125	120	120	120	120	120		125	125	125	125	126	126	126	126	125	135	135	125	125
10.	FWD L.P. ROTOR BRG	130	130	130	132	132	120	120	120	120	120		125	125	125	125	127	127	127	127	127	130	130	130	130
11.	AFT L.P. ROTOR BRG	125	125	125	125	125	120	120	120	125	125		125	125	125	125	125	125	125	125	125	125	135	125	120
12.	HOT GEAR BRG FWD	146	146	146	148	148	126	126	126	126	126		145	145	145	145	148	148	148	148	142	142	142	142	146
13.	HOT GEAR BRG AFT	138	138	138	140	140	125	125	125	125	125		138	138	138	138	140	140	140	140	138	138	138	138	138
14.	UX COND STE TEMP	86	86	86	80	80	80	80	84	88	88	88	86	86	86	86	86	86	86	86	84	84	86	86	86
15.	1ST STAGE AIR TEMP	165	165	165	165	165	80	80	80	80	80		165	165	165	165	165	165	165	165	165	170	170	165	165
16.	D.C. HEATER TEMP	238	238	238	238	236	236	236	236	234	236		238	238	238	238	238	238	238	238	236	236	238	236	238
17.	SUPRHT TEMP PORT	735	735	735	730	730	655	655	660	660	635		730	730	730	730	730	730	730	730	745	735	740	735	736
18.	SUPRHT TEMP STBD	735	735	735	730	730	655	655	665	660	635		730	730	730	730	730	730	730	730	745	735	740	735	736
19.	F.O. SETT TEMP P	100	100	100	100	100	100	100	100	100	100	106	100	100	100	100	100	100	100	100	104	104	104	104	104
20.	F.O. SETT TEMP S	100	100	100	100	100	100	100	100	100	100	95	100	100	100	100	100	100	100	100	104	104	104	104	104
21.	UPTAKE PORT	310	320	310	310	310	295	295	295	280	270		310	310	310	310	310	310	310	310	305	315	315	315	315
22.	UPTAKE STBD	305	310	310	305	305	290	290	290	270	260		300	300	300	300	300	300	300	300	305	300	305	300	305
23.	F.O. PUMP SUCT TEMP	120	115	110	110	112	112	112	112	112	110	112	120	120	120	115	115	115	115	115	118	118	120	120	120
24.	MN FD PMP L.O PORT	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32	32
25.	MN FD PMP L.O STBD	30	30	30	30	30	30	30	30	30	30	30	28	28	28	28	28	28	28	28	28	28	28	28	30
26.	L.O. TO GEARS	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112
27.	AIR CONTR L.O. PRESS	31	31	31	30	30	30	30	30	30	30	30	31	31	31	31	31	31	31	31	31	31	31	31	31

[illegible]

TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	
1. L.P. EXHAUST TEMP	92	92	92	94	94	92	92	92	92	92	92	90	90	90	92	94	94	94	94	92	92	92	92	92	92
2. MN COND STE TEMP	90	90	90	90	90	90	90	90	90	90	90	88	88	88	86	88	88	88	88	90	90	90	90	90	90
3. MN INJ TEMP	56	56	56	56	56	56	56	56	56	56	56	56	56	56	56	58	58	58	58	58	56	56	56	56	56
4. MN OVBD TEMP	68	68	68	68	68	68	68	68	68	68	68	67	67	67	67	70	70	70	70	70	68	68	68	68	68
5. L.O. TO COOLERS	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126
6. L.O. FROM COOLERS	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
7. THRUST BRG TEMP	110	110	110	110	110	110	110	110	110	112	112	110	110	110	110	110	110	110	110	110	110	110	110	110	110
8. FWD H.P. ROTOR BRG	122	122	122	122	122	122	122	122	122	122	122	120	120	120	120	122	122	122	122	122	122	122	122	122	122
9. AFT H.P. ROTOR BRG	128	128	128	128	128	128	128	128	128	128	128	125	125	125	125	127	127	127	127	127	127	127	127	127	127
10. FWD L.P. ROTOR BRG	128	128	128	128	128	128	128	128	128	128	128	125	125	125	125	127	127	127	127	127	127	127	127	127	127
11. AFT L.P. ROTOR BRG	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125
12. HOT GEAR BRG FWD	146	146	146	148	148	148	148	142	142	142	142	145	145	145	145	150	150	150	150	142	142	142	142	142	142
13. HOT GEAR BRG AFT	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	142	142	142	142	138	138	138	138	138	138
14. AUX COND STE TEMP	86	86	86	88	88	88	88	86	86	86	86	86	86	86	86	86	86	86	86	86	86	86	86	86	86
15. 1ST STAGE AIR TEMP	165	165	165	165	165	165	165	170	170	170	170	165	165	165	165	165	165	165	165	170	170	165	165	165	165
16. D.C. HEATER TEMP	238	238	238	238	238	238	238	238	238	238	238	238	238	238	238	238	238	238	238	236	238	236	238	238	238

Fwd. 3/14-15/67

	TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1.	L.P. EXHAUST TEMP	90	90	90	90	90	90	90	90	90	90	90	90	90	92	90	90	90	90	90	91	91	91	91	90
2.	MN COND STE TEMP	80	80	80	81	82	80	81	82	83	82	83	82	82	82	80	81	81	80	83	83	83	83	82	79
3.	MN INJ TEMP	56	56	56	58	58	58	58	58	55	56	56	57	60	58	58	58	58	58	58	56	56	56	56	56
4.	MN OVBD TEMP	68	70	70	68	68	68	68	68	68	68	68	70	70	70	70	68	68	68	68	68	68	68	68	68
5.	L.O. TO COOLERS	128	129	130	128	128	128	128	129	129	129	129	128	129	129	128	128	129	129	129	129	129	129	129	129
6.	L.O. FROM COOLERS	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
7.	THRUST BRG TEMP	119	119	120	120	120	120	119	119	119	119	119	119	119	130	119	118	120	120	120	119	119	119	119	119
8.	FWD H.P. ROTOR BRG	124	126	127	135	133	125	125	124	124	124	124	120	119	127	124	125	125	125	125	124	124	124	124	124
9.	AFT H.P. ROTOR BRG	136	137	137	135	135	138	138	136	136	136	135	135	136	140	135	135	138	138	135	136	136	136	136	136
10.	FWD L.P. ROTOR BRG	133	134	134	133	133	135	135	131	131	131	131	133	138	135	130	133	133	135	135	132	131	131	131	130
11.	AFT L.P. ROTOR BRG	127	128	130	128	128	128	128	128	128	128	128	127	127	130	127	128	128	128	128	128	128	128	128	126
12.	HOT GEAR BRG FWD	158	158	158	158	158	158	158	156	156	156	155	154	155	162	158	155	158	158	158	157	158	157	157	158
13.	HOT GEAR BRG AFT	145	146	146	145	145	145	145	145	146	146	145	144	144	148	144	145	148	148	148	145	145	145	145	145
14.	AUX COND STE TEMP	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90	90
15.	1ST STAGE AIR TEMP	150	160	150	148	148	148	148	146	152	156	148	150	150	152	152	146	148	148	148	150	148	148	148	150
16.	D.C. HEATER TEMP	241	240	238	238	238	238	238	238	238	238	238	238	240	240	240	237	238	238	238	238	238	238	238	240
17.	SUPRHT TEMP PORT	620	620	620	630	650	670	660	650	660	660	670	660	660	620	620	620	630	650	650	650	650	660	660	650
18.	SUPRHT TEMP STBD	610	610	610	610	660	680	680	670	680	680	690	670	696	620	620	630	650	630	630	620	620	630	630	620
19.	F.O. SETT TEMP P	110	110	110	105	105	105	100	100	100	100	100	100	115	110	110	110	110	105	105	105	105	105	105	105
20.	F.O. SETT TEMP S	115	105	105	95	105	105	100	100	100	100	105	115	110	110	110	110	105	105	110	105	105	105	105	105
21.	UPTAKE PORT	355	355	355	355	365	375	370	345	345	345	345	350	350	355	360	340	340	345	350	350	350	350	350	355
22.	UPTAKE STBD	355	350	350	355	355	365	360	335	335	335	335	340	350	345	345	350	330	335	345	345	345	345	345	350
23.	F.O. PUMP SUCT TEMP	118	116	116	112	112	112	112	112	106	106	106	100	102	112	112	112	112	112	112	112	112	112	112	111
24.	MN FD PMP L.O PORT	34	34	34	34	34	34	34	34	34	34	34	35	33	34	34	34	34	34	34	34	34	34	34	34
25.	MN FD PMP L.O STBD	20	20	20	20	20	20	20	22	22	22	22	25	25	25	25	23	25	25	25	22	22	22	22	20
26.	L.O. TO GEARS	112	111	111	112	112	112	112	114	114	114	114	112	114	114	112	112	112	112	112	114	114	114	114	112
27.	AIR CONTR L.O. PRESS	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
28. L.O. PRES #2	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
31. L.O. TO COOLER #1	120	120	122	120	114	114	120	120	120	120	120	120	120	122	120	115	120	120	120	120	120	120	120	120
30. L.O. TO COOLER #2	126	125	125	126	124	124	124	124	124	124	124	124	124	125	125	126	124	124	126	126	126	126	126	126
33. L.O. FROM COOLER #1	109	110	110	108	108	108	110	110	110	110	110	112	110	110	110	103	110	110	110	110	110	110	110	110
32. L.O. FROM COOLER #2	112	112	112	114	112	112	112	112	110	110	110	110	110	113	113	116	116	114	114	114	114	112	112	112
35. L.O. GOV PRES #1	62	62	62	61	61	61	61	62	62	62	62	62	62	62	62	62	64	64	61	61	62	62	62	62
34. L.O. GOV PRES #2	62	62	62	63	63	63	63	62	62	62	62	62	62	62	62	62	63	63	63	63	62	62	62	62
37. AMPS POS #1	950	900	900	1000	1100	1100	1100	1000	1000	900	800	900	850	800	1100	1050	1000	1000	450	900	900	900	900	900
36. AMPS POS #2	800	750	1050	700	700	700	700	800	1000	1000	1100	1000	1050	900	1150	1100	1050	1000	1000	900	900	900	900	900
39. AMPS NEG #1	900	900	900	1000	1150	1100	1100	1000	1000	900	800	950	850	850	1150	1100	1050	1000	1000	900	900	900	900	900
38. AMPS NEG #2	750	800	1000	700	750	750	750	800	1000	1000	1100	900	950	950	900	750	800	600	850	800	800	800	800	1000
41. HP HIGH SPEED PIN. AFT	146	146	146	145	145	145	145	145	146	146	145	144	144	146	144	145	148	148	145	145	145	145	145	145
42. HP INTER SPEED PIN FWD	146	146	145	145	145	145	146	145	145	144	143	146	147	147	145	145	148	148	145	145	145	145	145	146
43. HP INTER SPEED PIN AFT	146	148	149	148	145	145	148	147	147	146	146	146	146	146	145	145	148	148	145	146	147	147	147	147
44. L.P. THRUST BEARING	130	130	130	130	130	132	132	130	130	130	130	130	130	134	130	130	130	132	132	130	130	130	130	130
45. H.P. THRUST BEARING	146	146	147	145	143	145	145	144	143	143	143	143	142	146	145	145	145	145	145	145	144	145	145	145
46. LP HIGH SPEED PIN. FWD	132	132	134	130	133	133	132	131	132	132	132	130	130	135	130	130	133	133	133	132	131	131	131	130
47. LP HIGH SPEED PIN. AFT	127	127	128	128	124	128	127	128	128	128	128	127	127	128	127	128	128	124	128	128	128	128	128	127
48. LP INTER SPEED PIN FWD	154	155	155	153	153	153	155	153	153	153	153	152	153	154	153	153	153	153	153	153	153	153	153	153
49. LP INTER SPEED PIN. AFT	133	134	135	133	133	133	135	133	133	133	133	132	132	135	130	133	133	133	133	133	133	133	133	132
50. MAIN GEAR ROTOR FWD	114	114	114	115	115	115	115	115	115	115	115	114	114	114	114	115	115	115	115	115	115	115	115	114
51. MAIN GEAR ROTOR AFT	106	107	110	105	108	110	106	108	106	106	105	100	105	100	100	98	98	98	108	106	105	105	106	104
52. LP BLEAD	10	10	10	10	10	10	10	10	10	10	10	11	10	10	10	11	10	10	10	11	11	11	11	10

TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1. L.P. EXHAUST TEMP	92	92	92	92	92	92	92	92	92	92	90	92	92	92	92	92	92	92	92	92	92	92	92	92
2. MN COND STE TEMP	86	86	86	88	88	88	88	86	88	90	90	86	86	86	86	87	87	87	87	86	86	88	88	86
3. MN INJ TEMP	54	54	54	56	56	56	58	56	56	56	56	54	54	54	54	54	54	54	54	56	56	56	58	54
4. MN OVBD TEMP	66	66	66	66	66	66	66	68	68	68	68	64	64	64	64	66	66	66	66	68	68	68	68	66
5. L.O. TO COOLERS	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126	126
6. L.O. FROM COOLERS	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
7. THRUST BRG TEMP	110	110	110	110	110	110	110	110	110	112	110	110	110	110	110	112	112	112	112	110	110	110	110	110
8. FWD H.P. ROTOR BRG	120	120	120	120	120	120	120	120	120	120	120	120	120	120	120	122	122	122	122	122	122	122	122	120
9. AFT H.P. ROTOR BRG	124	124	124	124	124	124	124	124	125	125	125	122	122	122	122	122	122	122	122	125	125	125	125	122
10. FWD L.P. ROTOR BRG	125	125	125	127	127	127	127	127	127	128	128	122	125	125	125	130	130	130	130	130	130	130	130	125
11. AFT L.P. ROTOR BRG	125	125	126	125	125	125	125	125	125	125	125	125	125	125	125	127	127	127	127	125	125	125	125	125
12. HOT GEAR BRG FWD	146	146	146	148	148	148	148	142	142	142	142	146	146	146	146	150	150	150	150	142	142	142	142	146
13. HOT GEAR BRG AFT	136	136	136	140	140	140	140	138	138	138	138	138	138	138	138	140	140	140	140	138	138	138	138	136
14. AUX COND STE TEMP	82	82	82	82	82	84	84	84	84	86	86	82	82	82	82	82	82	82	82	82	84	84	84	82
15. 1ST STAGE AIR TEMP	165	165	165	165	165	165	165	165	165	165	170	165	165	165	165	165	165	165	165	165	165	165	165	165
16. D.C. HEATER TEMP	238	238	238	238	236	236	238	236	236	238	238	238	238	238	238	238	238	238	238	238	238	236	236	238
17. SUPRHT TEMP PORT	740	736	730	730	730	730	730	735	745	740	735	730	730	73										

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1 3	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
28. L.O. PRES #2																								
31. L.O. TO COOLER #1 3	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132
30. L.O. TO COOLER #2																								
33. L.O. FROM COOLER #1 3	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
32. L.O. FROM COOLER #2																								
35. L.O. GOV PRES #1 3	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
34. L.O. GOV PRES #2																								
37. AMPS POS #1 3	750	850	1000	1100	1150	1250	1300	1200	1150	1100	1150	900	1000	1000	1000	1050	1100	1050	1200	1050	1050	1250	1050	1000
36. AMPS POS #2																								
39. AMPS NEG #1 3	750	850	1000	1100	1150	1250	1300	1200	1150	1100	1150	900	1000	1000	1000	1050	1100	1050	1200	1050	1050	1250	1050	1000
38. AMPS NEG #2																								
41. HP HIGH SPEED PIN. AFT	136	136	136	140	140	140	140	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	138	136
42. HP INTER SPEED PIN FWD	140	140	140	142	142	142	142	140	140	140	140	140	140	140	140	140	140	140	140	140	140	140	140	140
43. HP INTER SPEED PIN AFT	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130
44. LP THRUST BEARING	140	140	140	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	140
45. HP THRUST BEARING																								
46. LP HIGH SPEED PIN. FWD	120	120	120	124	124	124	124	124	125	125	125	125	120	120	120	120	120	120	120	120	120	120	120	120
47. LP HIGH SPEED PIN. AFT	122	122	122	125	125	125	125	125	125	125	125	125	120	120	120	120	120	120	120	120	120	120	120	120
48. LP INTER SPEED PIN FWD	146	146	146	148	148	148	148	148	148	148	148	148	146	146	146	146	146	146	146	146	146	146	146	146
49. LP INTER SPEED PIN. AFT	136	136	136	140	140	140	140	140	140	140	140	140	136	136	136	136	136	136	136	136	136	136	136	136
50. MAIN GEAR ROTOR FWD	106	106	106	110	110	110	110	108	108	108	108	108	105	105	105	105	105	105	105	105	105	105	105	105
51. MAIN GEAR ROTOR AFT	108	108	108	110	110	110	110	105	105	105	105	105	108	108	108	108	108	108	108	108	108	108	108	108
52. LP BLEAD	12"	12"	12"	12"	12"	12"	12"	13	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12

1032
5457