

USNS	VOYAGE NO.	FROM	TO	TYPE OF VESSEL	DATE
GEN John POPE TAP-110	8-17	NSC OAKLAND CALIF	OILYANNA	P2-52-R2	4-20-2167

WATCH							WATCH						
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
MACHINERY PARTICULARS (CONT'D)							MACHINERY PARTICULARS (CONT'D)						
PRESSURES							PRESSURES						
TEMPERATURES							TEMPERATURES						
MISCELLANEOUS							MISCELLANEOUS						

WATCH							WATCH						
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
MACHINERY PARTICULARS (CONT'D)							MACHINERY PARTICULARS (CONT'D)						
PRESSURES							PRESSURES						
TEMPERATURES							TEMPERATURES						
MISCELLANEOUS							MISCELLANEOUS						

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												
L.O. GOVERNOR PRESSURE													FUEL OIL												
AMPS POSITIVE													FUEL OIL												
AMPS NEGATIVE													FUEL OIL												
VOLTS													FUEL OIL												

GENERATORS													FUEL - WATER AND LUBE OIL												
WATCH													WATCH												
GENERATOR													FUEL OIL												
R.P.M.													FUEL OIL												
STEAM PRESSURE													FUEL OIL												
STEAM TEMP.													FUEL OIL												
L.O. PRESSURE													FUEL OIL												
L.O. TO COOLER													FUEL OIL												
L.O. FROM COOLER													FUEL OIL												
TEMP. OF HOTTEST BEARING													FUEL OIL												

REMARKS

1200-1600 WATCH

Underway on 18 NOZZ MACH. IN OPERATION #1+2 Boilers. 1+2 F.D. BLANKETS. 1+2 F.W.S. PUMPS. 1+2 M.H.F.D. PUMPS. MAIN AIR COMPRESSOR. MAIN AIR EJECTOR. MIN. CIRC + COND PUMPS. L.O. PURIFIER. L.O.S. PUMP. #1 AUX GENERATOR. AUX AIR EJECTOR. CIRC + COND PUMPS OVER TO MAIN F.W.S. + S.A.D. PUMP. PORT STEERING GEAR. DAILY TEST OF MAIN THRUST. PUMPED UP PORT SETHLERS FROM #2 P.S. DBTS. CHANGED + CLEANED CENTER F.O. BURNERS + P/S DISCH. STRAINERS. CHECKED STEERING ER. GEAR. PUMPED Bilges. Added 1501 Lb to #1 M.H.F.D. PUMP. MADE ROUTINE ROUNDS ON MACH + ENGR SPACES. Complied with standing + COMSTS 4700-7.

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

Underway 18 NOZZLAS machinery IN OPERATION AS BEFORE. Blow tubes on Port + Stbd Boilers @ 1400. Changed + cleaned F.O. BURNERS + Suct. Strainers. Complied with 4700-7. Pumped Bilges. Checked Steering ENGR. Room.

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

Underway, Steaming 18 Nozz, Cleaned + Changed top furnace #1+2 Boilers. Shift + Clean 70 Disch strainers P+S, Shift + Clean L.O. strainer #1 Generator. Pumped bilges, Made Rounds + Insp of Mach + Eng spaces. Complied with Comsts Inst 4700-7.

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

Underway on 18 NOZZ MACH AS BEFORE. CHANGED + CLEANED CENTER F.O. BURNERS. P/S DISCH STRAINERS. SECURED L.O. PURIFIER + BACK IN SERVICE. DAILY TEST OF Stby L.O. PUMP. INSPECTED + CLEANED MAIN L.O. DISCH STRAINERS. PUMPED UP PORT SETHLERS FROM #2 P.S. DBTS + #4 DBTS. PUMPED Bilges. CHECKED STEERING ER. GEAR. MADE ROUTINE ROUNDS ON MACH + ENGR SPACES. Complied with COMSTS INST 4700-7.

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

Underway 18 NOZZLAS machinery IN OPERATION AS BEFORE. CHANGED + CLEANED F.O. BURNERS + Suct. Strainers. Complied with Comsts. 4700-7. Checked Steering ENGR. Room. Pumped Bilges.

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

Underway, Steaming 18 Nozz, 0800 to 0830 flew tubes on #1+2 boilers. Changed + cleaned top furnace P+S, Shift + Clean 70 Disch strainers P+S. Shift + Clean L.O. strainer #1 Generator. Made Rounds + Insp of Mach + Eng spaces, Pumped bilges. Complied with Comsts Inst 4700-7.

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS 1366	HOURS 1267
AKL 9.34	AKL 8.76
T-FW 12.85	T-AKL 12.26
SAL. 3.73	SAL. 3.73
PHOS. 30	PHOS. 30
R.ph 10	R.ph 10
50335	30
Ph Cond. 8.0	

CHIEF ENGR'S SIGNATURE-

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOZZ MACH IN OPERATION #1+2 Boilers 1+2 F.D. Blowers 1+2 F.O.S. PUMPS 1+2 M.D. F.D. PUMPS 17N A.R. COMPRESSOR MAIN A.R. EJECTOR 17N CIRC+COND. PUMPS L.O. PURIFIER L.O.S. PUMP #1 AUX GENERATOR AUX A.R. EJECTOR CIRC+COND PUMPS OVER TO MAIN F.I.R. S.D. PUMP. Port Steering Gear. Daily test of MN Thrst. Pumped up port settlers from #4 & D.B.T. Checked steering ER. Gear. Pumped Bilges. Run & Tested A.C. Unit for 4 hr. Weekly test of EMERGENCY Equipment & Safety Devices. Changed & cleaned center F.C. burners & 1/2 disc strainers. Raised vacuum on #2 Aux Generator. Made routine rounds on mach & eng spaces. Complied with Consts. 4700-7.

WATCH ENGR'S SIGNATURE-

Henry Bunney

1600-2000 WATCH

UNDERWAY 18 NOZZLES machinery IN operation AS Before Except Started #1 S.S. Cond. & S.O.C. #2 S.S. Cond. @ 1615 for cleaning. Sec. Air Comp. Blower Tubes on Port & stbd Boilers @ 1600. Changed & cleaned F.C. Burners & suet. strainer. Complied with Consts. 4700-7. Pumped Bilges. Elect. Cleaning #1 S.S. Cond. Checked Steering Eng. Room.

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

Underway, Steaming 18 Nozz, Cleaned & changed burners #1+2 Boilers Shift & Clean F.O. disc strainers #5, Shift & Clean L.O. strainer #2 Generator. Electricians Working on #1 Generator. Retarded Ships Clock 20 minutes @ 2255. Made Rounds & Insp of Mach & Eng spaces. Comp with Consts Incl 4700-7. Pumped bilges.

WATCH ENGR'S SIGNATURE-

R. Summers

2400-0400 WATCH

UNDERWAY ON 18 NOZZ MACH AS Before. Changed & cleaned center F.C. burners 1/2 disc strainers. Inspected & cleaned main L.O. disc strainers. Daily test of stbd L.O. pump. Retarded Clocks 20 mins @ 0100. Pumped up port settlers from #4 & D.B.T. Pumped Bilges. Checked steering ER. Room. Made routine rounds on mach & eng spaces. Complied with Consts 4700-7.

WATCH ENGR'S SIGNATURE-

Henry Bunney

0400-0800 WATCH

underway 18 Nozzles machinery IN operation AS Before. Changed & cleaned F.C. Burners & suet. strainer. Retarded clock 20 min. @ 0500. Checked steering Eng. Room. Complied with Consts. 4700-7. Pumped Bilges.

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

Underway, steaming 18 Nozz, 0815 to 0845 blew tubes on #1+2 Boilers, Changed & cleaned burners #1+2 Boilers, Shift & Clean F.O. Disc strainers #5, Shift & Clean L.O. strainers #1+2 Generators. 0800 Lit off #1 Generator. 0845 put on line, 0930 put air Cond Unit in service, @ 1015 Secured A.C. Unit. Due to Faulty Coil, @ 1115 put air Cond Unit back in service, Made Rounds & Insp of Mach & Eng spaces, Comp with Consts 4700-7.

WATCH ENGR'S SIGNATURE-

R. Summers

CHIEF ENGINEER

12-16 Cont FIRE drill @ 1510 Sec @ 1520 Tested Relief Valve Piped BOILER WATER READINGS 125" PSI Tested Aft diesel FIRE PUMP Abandon ship drill @ 1535 Sec STB'D PORT @ 1532 Stbd @ 1514 L.H. @ 1532 HOURS 1371 HOURS 292 0800-1200.

AKL 8.76 AKL 8.76 Test Governor speed #1 generator. 1230 R.P.M. No load.

T-1V 11.68 T-AKL 11.68

SAL. 3.73 SAL. 3.73

PHOS. 30 PHOS. 30

R.ph 10 R.ph 10

SO3 30 30

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE-

R. Summers

USNS		VOYAGE NO.		FROM		TO		SUBC BAY		P.I.		TYPE OF VESSEL		DATE		
GEN JOHN POPE T-116		8-A		NSC OAKLAND CALIF		OKLAHOMA						P2-S2-R2		4-22-23-67		
		WATCH								WATCH						
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
RUNNING TIME		240	240	240	240	240	240	MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING		139	140	137	140	138	
DETENTION TIME									FORWARD L. P. ROTOR BEARING		134	130	133	134	134	134
REVOLUTION COUNTER (END OF WATCH)		2691	2693	2696	2698	2700	2703		AFT. L. P. ROTOR BEARING		130	130	128	129	130	130
TOTAL REVOLUTIONS (FOR WATCH)		25380	23460	23250	23350	23310	23360		HOTTEST GEAR BEARING FORWARD		160	140	159	160	160	160
AVERAGE RPM		97.4	97.7	96.8	97.3	97.1	97.3		HOTTEST GEAR BEARING AFT		145	147	144	145	148	145
F.O. METER (END OF WATCH)		1158	1158	1158	1159	1159	1159		AUX. COND. CONDENSATE		109	112	112	110	112	112
F.O. CONSUMED		3020	2840	2950	2980	2860	2940		1ST STAGE FEED WATER HEATER		160	158	162	162	164	164
									O. C. FEED WATER HEATER		240	240	238	240	240	240
									3RD STAGE FEED HP WATER HEATER L.P.		105	105	105	105	105	105
									F.O. TO BURNERS		225	220	220	220	230	230
									F. O. BACK PRESSURE		6.0	6.0	6.0	6.0	6.0	6.0
									AIR TO FURNACE		5.5	6.0	6.0	5.5	6.0	5.5
									SALINITY UPTAKE		.41	.41	.41	.41	.41	.41
									MAIN STEAM		440	440	440	440	440	440
									SUPER HEAT		685	695	690	680	690	700
									F.O. TO BURNERS		190	190	190	190	190	190
									F.O. TEMP. IN SETTLING TANKS		105	105	105	105	105	110
								PORT BOILER UPTAKE		360	345	355	365	380	340	
								STBD. BOILER UPTAKE		355	346	370	370	385	345	
								ENGINE ROOM TEMPERATURE		89	86	86	89	89	91	
								FIRE ROOM TEMPERATURE		89	86	86	89	89	91	
								NOZZLES IN USE		18	18	18	18	18	18	
								NO. OF BURNERS IN USE		6	6	6	6	6	6	
								BURNER TIP SIZE		53/6	53/6	53/6	53/6	53/6	53/6	
								CO2 % PORT BOILER								
								CO2 % STBD. BOILER								
								OIL LEVEL MAIN SUMP		1'2"	1'2"	1'2"	1'2"	1'2"	1'2"	

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL						
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL	WATER	LUBE OIL				
1200 TO 1600	1	1200	440	685	9	123	113		62	850	800	235	METER AT NOON	11596840	ON HAND AT START OF DAY	137			
	2	1200	440	685	7	136	125		63	850	800	235	METER PREVIOUS NOON	11579250	EVAPORATED OR RECEIVED	62			
1600 TO 2000	1	1200	440	695	9	120	110		62	750	700	235	CONSUMED BY METER	17590	ON HAND	128			
	2	1200	440	695	7	134	124		63	750	700	235	ON HAND AT START OF DAY	9223	CONSUMED	71			
2000 TO 2400	1	1200	440	690	9	120	110		62	750	750	235	RECEIVED DURING DAY	-0-	ON HAND AT START OF DAY	1980			
	2	1200	440	690	7	135	124		63	750	750	235	EXPENDED DURING DAY	583	RECEIVED	-0-			
2400 TO 0400	1	1200	440	680	9	121	111		62	650	650	255	REMAINING ON BOARD	8640	ON HAND	1975			
	2	1200	440	680	7	137	124		63	650	650	255	ON HAND AT START OF DAY	584	CONSUMED	5			
0400 TO 0800	1	1200	440	690	9	120	110		62	750	750	235	EVAPORATED OR RECEIVED	120	DIESEL OIL	1160			
	2	1200	440	690	7	137	124		63	800	800	235	ON HAND	458	ON HAND	1158			
0800 TO 1200	1	1200	440	700	9	120	110		62	800	800	235	CONSUMED	246	CONSUMED	2			
	2	1200	440	700	7	138	126		63	900	900	235	LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)						
													4	4	4	4	4	4	
													L.O. CENTRIFUGE - HOURS OPERATED						
													1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
													4	4	4	4	4	4	
													SUMMARY						
													RUNNING TIME	1440	PERCENT OF SLIP	P/S: 10.3			
													DETENTION TIME	-0-	BBL FUEL/MI	1.15 1.28			
													TOTAL REVOLUTIONS ^{P/S}	135,915	WIND DIRECTION	160°			
													AVERAGE R.P.M.	94.3	STATE OF SEA	2'			
													TOTAL MILES BY ENGINE	5.07	STATE OF WEATHER	74°			
													TOTAL MILES BY OBSERVATION	455					

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOZZ MACH IN OPERATION #1+2 BOILERS 1+2 F.W. BLOWERS 1+2 F.W. PUMPS 1+2 MAIN F.D. PUMPS. MAIN AIR COMPRESSOR. MAIN AIR EJECTOR. MAIN CIRC. COND. PUMPS. L.O. PUMPER. L.O. PUMP 1+2 AUX GENERATORS. AUX AIR EJECTOR. CIRC. COND. PUMPS. OVER TO MAIN. A.C. UNIT. F.W. COND. PUMP. PORT STEERING GEAR. DAILY TEST OF MAIN THRUST. PUMPED UP PORT SETTLERS FROM #4 STBD. D.B. T.K. TOOK A DRY. EX ALL 5+6 F.C.T.S. CHANGED + CLEANED CENTER F.C. BURNERS $\frac{1}{2}$ DISCH STRAINERS. CHECKED STEERING GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH + ENGS SPACES. COMPLIED WITH COMSTS 4700-7. Shifted #1 EVAP. AIR EJECTOR DRAINS TO ATMOSPHERE TANK. WATCH ENGR'S SIGNATURE - George Banning

1600-2000 WATCH

UNDERWAY 18 NOZZLES MACHINERY IN OPERATION AS BEFORE BLOW TUBES ON PORT + STBD. BOILERS @ 1600. CHANGED + CLEANED F.C. BURNERS + SUCT. STRAINERS. CHECKED STEERING ENG. ROOM. COMPLIED WITH COMSTS. 4700-7. PUMPED BILGES.

WATCH ENGR'S SIGNATURE - L. Harris

2000-2400 WATCH

UNDERWAY, STEAMING 18 NOZZ, CLEANED + CHANGED TOP FURNERS #1+2 BOILERS. SHIFT + CLEAN F.O. DISCH STRAINERS #4+5, SHIFT + CLEAN L.O. STRAINERS #1+2 GENERATORS. PUMPED BILGES, MADE ROUNDS + INSPECTION OF MACH + ENG SPACES, COMP WITH COMSTS INST 4700-7.

WATCH ENGR'S SIGNATURE - R. Summers

2400-0400 WATCH

UNDERWAY ON 18 NOZZ MACH AS BEFORE CHANGED + CLEANED CENTER F.C. BURNERS + $\frac{1}{2}$ DISCH STRAINERS. INSPECTED + CLEANED MAIN L.O. DISCH STRAINERS. DAILY TEST OF STBY L.O. PUMP. PUMPED UP PORT SETTLERS FROM #4 STBD. D.B. T.K. CHECKED STEERING GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH + ENGS SPACES. COMPLIED WITH COMSTS 4700-7.

WATCH ENGR'S SIGNATURE - George Banning

0400-0800 WATCH

UNDERWAY 18 NOZZLES MACHINERY IN OPERATION AS BEFORE CHANGED + CLEANED F.C. BURNERS + SUCT. STRAINERS. ADDED COMPOUND TO PORT + STBD. BOILERS. COMPLIED WITH COMSTS 4700-7. PUMPED BILGES. CHECKED STEERING ENG. ROOM.

WATCH ENGR'S SIGNATURE - L. Harris

0800-1200 WATCH

UNDERWAY, STEAMING 18 NOZZ, @ 0800-0830 BLOW TUBES #1+2 BOILERS. CHANGED + CLEANED TOP FURNERS IN #1+2 BOILERS, SHIFT + CLEAN F.O. DISCH STRAINERS #4+5, SHIFT + CLEAN L.O. STRAINERS #1+2 GENERATORS. @ 0900 SHIFT TO SUCT. TO INFUSED SETTLER. MADE ROUNDS AND INSPECTION OF MACH + ENG SPACES, PUMPED BILGES. COMPLIED WITH COMSTS INST 4700-7.

WATCH ENGR'S SIGNATURE - R. Summers

CHIEF ENGINEER

REB. ~~0800-1200~~ @ 1045 Collected Chart, Subject For Dumb Starter Trip Battery

BOILER WATER READINGS

STB'D PORT

HOURS 1415 HOURS 316

AKE 16.54 AKE #1+2 10.51

T-AK 11.10 T-AK 15.18

SAL. 3.73 SAL. 3.73

FECS. 40 FECS. 40

R.ph 11 R.ph 11

SO³ 4.0 4.0

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE - [Signature]

USNS GEN JOHN POPE TPR-110 VOYAGE NO. 8-H FROM NSC OAKLAND CALIF TO SUBIC BAY P.I. TYPE OF VESSEL P2-52-R2 DATE 4-23-24-67

		WATCH								WATCH						
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
RUNNING TIME		240	240	260	260	260	240	MACHINERY PARTICULARS (CONT'D)	TEMPERATURES (CONT'D)	AFT. H. P. ROTOR BEARING	138	140	137	139	140	138
DETENTION TIME										FORWARD L. P. ROTOR BEARING	133	133	133	133	130	134
REVOLUTION COUNTER (END OF WATCH)		2705 4900	2707 8150	2710 3490	2712 8870	2715 3900	2717 7470			AFT. L. P. ROTOR BEARING	130	130	130	130	130	129
TOTAL REVOLUTIONS (FOR WATCH)		23360	23250	25240	25320	25380	23576			HOTTEST GEAR BEARING FORWARD	160	160	159	160	161	161
AVERAGE RPM		97.3	96.9	97.0	97.6	96.2	98.2			HOTTEST GEAR BEARING AFT	145	148	144	145	145	145
F.O. METER (END OF WATCH)		1159 9730	1160 2590	1160 5750	1160 8890	1161 1930	1161 4880			AUX. CONO. CONDENSATE	114 110	115	114	115	115	114
F.O. CONSUMED		2890	2860	3160	3140	3060	2930			1ST STAGE FEED WATER HEATER	163	164	164	164	163	164
MACHINERY PARTICULARS	PRESSURES	THROTTLE	440	440	440	440	440	440	TEMPERATURES	O. C. FEED WATER HEATER	240	240	240	240	240	240
		H.P. AHEAD	440	440	440	440	440	440		3RD STAGE FEED H.P. WATER HEATER L.P.	240	240	240	240	240	240
		L.P. AHEAD	27	27	27	27	27	27		F.O. TO BURNERS	220	220	220	220	220	220
		VACUUM	28.5"	28.5"	28.5"	28.5"	28.3"	28.0		F.O. BACK PRESSURE						
		L.O. TO TURBINES	12	12	12	12	12	12		AIR TO FURNACE	5.6	5.4	5.5	5.5	5.5	5.5
		AUX. STEAM	150	150	150	150	150	150		SPLINITY UPTAKE	41	41	41	41	41	41
		BACK PRESSURE	9	9	9	9	9	9		MAIN STEAM	440	440	440	440	440	440
		GLAND STEAM	1.0	1.0	1.0	1.0	1.0	1.0		SUPER HEAT	700	700	695	690	695	700
		H.P. BLEEDER	70	70	70	70	70	70		F.O. TO BURNERS	190	190	190	190	190	190
		L.P. BLEEDER	6	6	6	6	6	6		F.O. TEMP. IN SETTLING TANKS	98	100	100	105	105	100
TEMPERATURES	PRESSURES	L.P. BLEEDER	9"	9"	9"	9"	9"	9"	TEMPERATURES	PORT BOILER UPTAKE	340	340	345	345	350	345
		STEAM AT THROTTLE	700	700	695	690	695	700		STBD. BOILER UPTAKE	355	355	350	355	350	345
		L.P. EXHAUST	110	110	112	112	109	114		ENGINE ROOM TEMPERATURE	92	91	91	91	92	94
		CONDENSATE	105	109	109	109	107	110		FIRE ROOM TEMPERATURE	92	91	91	91	92	94
		CIRC. WATER IN	79	80	81	81	81	83		NOZZLES IN USE	18	18	18	18	18	18
		CIRC. WATER OUT	94	94	94	95	94	95		NO. OF BURNERS IN USE	6	6	6	6	6	6
		L.O. TO COOLERS	128	129	129	128	128	129		BURNER TIP SIZE	53/70	53/70	53/70	53/70	53/70	53/70
		L.O. FROM COOLERS	110	110	110	110	110	110		CO ₂ % PORT BOILER						
		TEMPERATURE THRUST BEARING	118	120	119	119	118	120		CO ₂ % STBD. BOILER						
		FORWARD H.P. ROTOR BEARING	126	125	124	125	124	124		OIL LEVEL MAIN SHIP	1'2"	1'2"	1'2"	1'2"	1'2"	1'2"

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL					
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL	DOMESTIC WATER	BOILER WATER	LUBE OIL		
1200 TO 1600	1	1200	440	700	9	122	111		62	900	900	235	METER AT NOON	11614880	ON HAND AT START OF DAY	128		
	2	1200	440	700	7	137	127		63	850	850	235	METER PREVIOUS NOON	11796840	EVAPORATED OR RECEIVED	49		
1600 TO 2000	1	1200	440	700	9	120	110		62	750	750	235	CONSUMED BY METER	18040	ON HAND	135		
	2	1200	440	700	7	138	127		63	800	800	235	ON HAND AT START OF DAY	8640	CONSUMED	42		
2000 TO 2400	1	1200	440	695	9	120	110		62	700	700	235	RECEIVED DURING DAY	-0-	ON HAND AT START OF DAY	1975		
	2	1200	440	695	7	138	125		63	800	800	235	EXPENDED DURING DAY	600	RECEIVED	-0-		
2400 TO 0400	1	1200	440	690	9	120	110		62	750	750	235	REMAINING ON BOARD	8,040	ON HAND	1920		
	2	1200	440	690	7	138	127		63	750	750	235	ON HAND AT START OF DAY	458	CONSUMED			
0400 TO 0800	1	1200	440	695	9	120	110		62	800	800	235	EVAPORATED OR RECEIVED	130	DIESEL OIL 1158			
	2	1200	440	695	7	138	128		63	750	750	235	ON HAND	400	ON HAND 1155			
0800 TO 1200	1	1200	440	700	9	122	112		62	750	750	235	CONSUMED	188	CONSUMED 3			
	2	1200	440	700	7	139	126		63	750	750	235	LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)					
													4	4	4 1/2	4 1/2	4 1/2	4
													L.O. CENTRIFUGE - HOURS OPERATED					
													1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
													4	4	4 1/2	4 1/2	4 1/2	4
													SUMMARY					
													RUNNING TIME	1500	PERCENT OF SLIP			19.4
													DETENTION TIME	-0-	BBL FUEL/MI			9.32
													TOTAL REVOLUTIONS	141495	WIND DIRECTION			160°
													AVERAGE R.P.M.	94.3	STATE OF SEA			1/4
													TOTAL MILES BY ENGINE	528	STATE OF WEATHER			70°
													TOTAL MILES BY OBSERVATION	452				

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOZZ. MACH IN OPERATION #1+2 Boilers 1+2 F.D. Blowers 1+2 F.O.S. PUMPS 1+2 MAIN F.D. PUMPS. MAIN A.R. COMPRESSOR. MAIN AIR EJECTOR. MAIN FIRE & COND PUMPS. L.O. PURIFIER. L.O.S. PUMP 1+2 AUX GENERATORS. AUX AIR EJECTOR. FIRE & COND PUMPS OVER TO MAIN. A.C. UNIT. FIRE & SAN PUMP. PORT STEERING GEAR. DAILY TEST OF MAIN THRUST. CHECKED STEERING E.R. GEAR. CHANGED & CLEANED CENTER F.O. BURNERS & P.S. DISCH. STRAINERS. PUMPED BILGES. PUMPED UP PORT SETTLERS FROM #6 & DEEP #5 & DEEP #4. CALLED OUT OSBORNE. ENGR. UNTIL 1500. 1st ENGR. 1400 TO INST. MANHOLD COVER TO #4 STB. Complied with Comsts 4700.7

WATCH ENGR'S SIGNATURE-

George Bunney

1600-2000 WATCH

UNDERWAY 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. BLOW TUBES ON PORT & STBD. BOILER. CHANGED & CLEANED F.O. BURNERS & SUCTION STRAINERS. CHECKED STEERING ENGR. ROOM. Complied with Comsts 4700.7. PUMPED BILGES.

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

UNDERWAY, STEAMING 18 NOZZ. CLEANED & CHANGED TOP FURNERS #1+2 BOILERS. SHIFT & CLEAN F.O. DISCH STRAINERS P+S, SHIFT & CLEAN L.O. STRAINERS #1+2 GEN. RETARDED SHIPS CLOCK 20 MIN. AT 2355, MADE ROUNDS & INSPECTION OF MACH & ENGR SPACES, PUMPED BILGES. Complied with Comsts Inst 4700-7.

WATCH ENGR'S SIGNATURE-

R Summers

2400-0400 WATCH

UNDERWAY ON 18 NOZZ. MACH AS BEFORE. CHANGED & CLEANED CENTER F.O. BURNERS & P.S. DISCH STRAINERS. DAILY TEST OF STBY L.O. PUMP. INSPECTED & CLEANED MAIN L.O. DISCH STRAINER. RETARDED CLOCKS 20 MIN. AT 0300. HELD ENGR CASUALTY DRILL B-18. FAILURE OF COMBUSTION CONTROL SYSTEM. WATCH INST. & BRIDGE NOTIFIED. ONE FIRE PUMPED UP PORT SETTLERS FROM #5 & DEEP #4. CHECKED STEERING E.R. GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH & ENGR SPACES. Complied with Comsts Inst 4700.7.

WATCH ENGR'S SIGNATURE-

George Bunney

0400-0800 WATCH

UNDERWAY 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. BURNERS & SUCTION STRAINERS. RETARDED CLOCK 20 MIN @ 0500. HELD ENGR CASUALTY DRILL B-18. PUMPED 0500 TO 0530 & MEN PRESENT BRIDGE NOTIFIED. CHECKED STEERING ENGR ROOM. Complied with Comsts 4700.7. PUMPED BILGES.

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

UNDERWAY, STEAMING 18 NOZZ. 0800 TO 0830 BLOW TUBES ON #1+2 BOILERS. 0830 TO 0900 HELD ENGR CASUALTY DRILL B-18. & MEN PRESENT BRIDGE NOTIFIED. CLEANED & CHANGED TOP FURNERS #1+2 BOILERS. SHIFT & CLEAN F.O. DISCH STRAINERS P+S, SHIFT & CLEAN L.O. STRAINERS #1+2 GENERATORS. MADE ROUNDS & INSPECTION OF MACH & ENGR SPACES, PUMPED BILGES. Complied with Comsts Inst 4700-7. @ 1100 SHIFT TO SUCTION TO OUTBOARD SETTLER.

WATCH ENGR'S SIGNATURE-

R Summers

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS 1440	HOURS 341
AKL 11.10	AKL 9.34
T-FW 15.18	T-AKL 14.02
SAL. 3.73	SAL. 3.73
PHOS. 40	PHOS. 40
R.ph 11	R.ph 19
S03 45	40
PH 40	8.0

CHIEF ENGR'S SIGNATURE-

L. Harris

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOV 22 MACH IN OPERATION #1+2 Boilers 1+2 F.O. BLOWERS 1+2 F.O.S. PUMPS. 1+2 M.H. FB PUMP. M.H. AIR COMPRESSOR. MAIN AIR EJECTOR. M.H. CIRC. & COND PUMPS L.O. PURIFIER. L.O. PUMP. 1+2 AUX GENERATORS. AUX AIR EJECTOR. CIRC. & COND PUMPS OVER TO MAIN. A.C. UNIT. FIRST STN. PUMP. PORT STEERING GEAR. DAILY TEST OF M.H. THROT. PUMPED UP PORT SETTLERS FROM #5 & DEEP TKS. PUMPED BILGES. CHECKED STEERING E.R. GEAR. TEST & ADJ. ON #5 & DB TK. CHANGED & CLEANED CENTER F.O. BURNERS & 1/2 DISCH. STRAINERS. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH COMSTS 4700-7

WATCH ENGR'S SIGNATURE-

George Bunney

1600-2000 WATCH

UNDERWAY 18 NOV 22 MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. BURNERS & SUCT. STRAINERS. CHECKED STEERING ENGR. ROOM. COMPLIED WITH COMSTS 4700-7. PUMPED BILGES.

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

UNDERWAY, STEAMING 18 NOV 22, CLEANED & CHANGED TOP BURNERS #1+2 Boilers. Shift & Clean 70 Disch. strainers #1+5, Shift & Clean L.O. strainers #1+2 Generators. @ 2130 Shift 70 Suct. to Inboard Section. Settles. PUMPED BILGES, MADE ROUNDS & INSPECTION OF MACH & ENGS SPACES. COMPLIED WITH COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

R. Summers

2400-0400 WATCH

UNDERWAY ON 18 NOV 22 MACH AS BEFORE. CHANGED & CLEANED CENTER F.O. BURNERS & 1/2 DISCH. STRAINERS. PUMPED UP PORT SETTLERS FROM #5 & DB. ENGS CASUALTY WATER IN F.O. @ 0105 Chief Engr. + 1st Asst Engr. WITNESS SAME. BRIDGE NOTIFIED. ADJUSTED SPEED TO MAINT STN. PRESSURE. A.C. UNIT FAIL TO TRIP OUT WHEN POWER FAILURE. SECURE #2 MAIN FEED CORRECTED LOOSE NUT ON #3 PUMP. CHECKED STEERING E.R. GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH STANDING ORDERS & COMSTS 4700-7

WATCH ENGR'S SIGNATURE-

George Bunney

0400-0800 WATCH

UNDERWAY 18 NOV 22 MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. BURNERS & SUCT. STRAINERS. ENGS CASUALTY WATER IN F.O. ADJUSTED SPEED TO MAINT STN. PRESSURE. PUMPED F.O. FROM #6 DB. TO INBOARD SUCT. COMPLIED WITH COMSTS 4700-7. PUMPED BILGES. CHECKED STEERING ENGR. ROOM.

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

UNDERWAY, STEAMING 18 NOV 22, 0800 to 2230 flew tubes #1+2 Boilers. Shift & Clean 70 Disch. strainers #1+5, Shift & Clean L.O. strainers #1+2. Cleaned & Changed top burners #1+2 Boilers, made Rounds & Insp of MACH & ENGS spaces. PUMPED BILGES, COMPLIED WITH COMSTS 4700-7

@ 1116 Port steering motor failure, Casually, Bridge notified @ 1116 stop @ 1127 H
@ 1145 start @ 1145-510WV 20 RPM @ 1151 H 18 NOV 22

WATCH ENGR'S SIGNATURE-

R. Summers

CHIEF ENGINEER

BOILER WATER READINGS

STE'D PORT 365.4

HOURS 1464 HOURS 365

AKL 1110 DEL 9.34

T-AND 15.18 T-AKL 13.43

SAL. 4.14 SAL. 4.14

PHOS. 40 PHOS. 40

R-ph 11 R-ph 14

SO 340 35

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE-

W. C. Summers

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE					
Gen John Pope T-110		8-A		NSC OAKLAND CALIF		Subic Bay P.I.		P2-S2-R2		4-25-26-67					
		WATCH								WATCH					
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME		240	240	260	260	260	240	MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING	140	141	139	141	142	138
DETENTION TIME									FORWARD L. P. ROTOR BEARING	135	135	133	134	134	132
REVOLUTION COUNTER (END OF WATCH)		2733 5400	2735 8400	2738 3770	2740 8800	2745 4100	2745 7460		AFT. L.P. ROTOR BEARING	131	131	128	130	131	129
TOTAL REVOLUTIONS (FOR WATCH)		22720	23000	25370	25030	25300	23360		HOTTEST GEAR BEARING FORWARD	153	154	153	153	150	152
AVERAGE RPM		94.9	95.8	97.5	96.0	97.3	97.3	HOTTEST GEAR BEARING AFT	147	150	145	147	148	145	
F.O. METER (END OF WATCH)		1163 5720	1163 8830	1164 2070	1164 5390	1164 8550	1165 1430	AUX. COND. CONDENSATE	118	120	118	118	120	116	
F.O. CONSUMED		3170	3040	3240	3320	3160	2880	1ST STAGE FEED WATER HEATER	164	164	166	164	165	164	
								D. C. FEED WATER HEATER	240	240	240	240	240	240	
								3RD STAGE FEED W.P. WATER HEATER	115	115	115	115	115	115	
								F.O. TO BURNERS	255 250	260 260	250 250	245 240	240 240	240 240	
								F. O. BACK PRESSURE							
								AIR TO FURNACE	5.5 5.5	5.6 6.8	6.0 6.5	6.0 6.4	5.6 6.5	5.6 6.2	
								UP TAKE	41	41	41	41	41	41	
								MAIN STEAM	435	435	440	440	440	440	
								SUPER HEAT	685	700	690	695	700	705	
								F.O. TO BURNERS	190 190	190 190	190 190	190 190	190 190	190 190	
								F.O. TEMP. IN SETTLING TANKS	105 105	105 105	105 105	107 110	110 115	110 115	
								PORT BOILER UPTAKE	350	350	375	375	370	335	
								STBD. BOILER UPTAKE	350	345	345	350	350	335	
								ENGINE ROOM TEMPERATURE	97	96	96	94	96	98	
								FIRE ROOM TEMPERATURE	97	96	96	94	96	98	
								NOZZLES IN USE	18	18	18	18	18	18	
								NO. OF BURNERS IN USE	6	6	6	6	6	6	
								BURNER TIP SIZE	53/10	53/10	53/10	53/10	53/10	53/10	
								CO ₂ % PORT BOILER							
								CO ₂ % STBD. BOILER							
								OIL LEVEL MAIN SUMP	1'2"	1'2"	1'2"	1'2"	1'2"	1'2"	

GENERATORS												FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL	WATER	LUBE OIL	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED
1200 TO 1600	1	1200	435	685	9	125	114		62	800	800	235	METER AT NOON	1165/430	ON HAND	145	
	2	1200	435	685	7	140	139		63	850	850	235	METER PREVIOUS NOON	11632620	EVAPORATED OR RECEIVED	38	
													CONSUMED BY METER	18810	ON HAND	130	
													ON HAND AT START OF DAY	7330	CONSUMED	43	
													RECEIVED DURING DAY	732	ON HAND AT START OF DAY	1960	
													EXPENDED DURING DAY	732	RECEIVED	-0-	
													REMAINING ON BOARD	6598	ON HAND	1950	
													ON HAND AT START OF DAY	345	CONSUMED	10	
1600 TO 2000	1	1200	435	700	9	124	115		62	800	800	235	EVAPORATED OR RECEIVED	144	DIESEL OIL	1152	
	2	1200	435	700	7	140	130		63	900	900	235	ON HAND	260	ON HAND	1150	
													CONSUMED	229	CONSUMED	2	
2000 TO 2400	1	1200	440	690	9	124	114		62	750	750	235	LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gal.)				
	2	1200	440	690	7	140	128		63	750	750	235	4	4	4 1/2	4 1/2	4
													L.O. CENTRIFUGE - HOURS OPERATED				
													1200 TO 1600	1600 TO 2000	2000 TO 2400	0400 TO 0800	0800 TO 1200
													4	4	4 1/2	4 1/2	4
2400 TO 0400	1	1200	440	695	9	125	115		62	750	750	235	SUMMARY				
	2	1200	440	695	7	140	129		63	750	750	235	RUNNING TIME	1500	PERCENT OF SLIP	85.9.16	
													DETENTION TIME	-0-	BBL FUEL/MI	1.40	
													TOTAL REVOLUTIONS	140545	WIND DIRECTION	090°	
													AVERAGE R.P.M.	93.6	STATE OF SEA	Smooth	
													TOTAL MILES BY ENGINE	524	STATE OF WEATHER	80°	
0400 TO 0800	1	1200	440	705	9	122	112		62	700	700	235	TOTAL MILES BY OBSERVATION	476			
	2	1200	440	705	7	138	128		63	700	700	235					

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOZZ MACH IN OPERATION #1+2 Boilers 1+2 F.D. Blowers 1+2 F.O.S. PUMPS. 1+2 M.N. F.V. PUMPS. MAIN A.I.R. COMPRESSOR. MAIN A.I.R. EJECTOR. MAIN FIRE & COND. PUMPS. L.O. PURIFIER. L.V.S. PUMP. 1+2 AUX. GENERATORS. AUX. A.I.R. EJECTOR & FIRE & COND. PUMPS OVER TO MAIN. A.O. UNIT. FIRE & S.A. PUMP. PORT STEERING GEAR. DAILY TEST OF M.N. THRST. PUMPED UP PORT S.O. LACKS FROM #6 & DB. CHANGED CLEANED CENTER F.O. BURNERS & P/S DISCH STRAINERS. PUMPED BILGES. CHECKED STEERING E.R. GEAR. MADE ROUTINE ROUNDS ON MACH & ENG'S SPACES. COMPLIED WITH COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

Henry Banning

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. BLEW TUBES ON PORT & STBD. BOILERS. @ 1600. CHANGED & CLEANED F.O. BURNERS & SUCT. STRAINERS. PUMP F.O. SATT. FROM #6 STBD. F.O. T.H. COMPLIED WITH COMSTS 4700-7. CHECKED STEERING ENG. ROOM. PUMPED BILGES.

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

UNDERWAY, STEAMING 18 NOZZ, CLEANED & CHANGED TOP FURNERS #1+2 BOILERS. SHIFT & CLEAN F.O. DISCH STRAINERS P+5, SHIFT & CLEAN L.O. STRAINERS #1+2 GENERATORS. RETARDED SHIPS CLOCK 20 MINUTES @ 2255, PUMPED BILGES. MADE ROUNDS & INSP OF MACH & ENG SPACES. COMPLIED WITH COMSTS INST. 4700-7. - TOOK DOWN BILGE PRIMING PUMP. -

WATCH ENGR'S SIGNATURE-

R. Summers

2400-0400 WATCH

UNDERWAY ON 18 NOZZ MACH AS BEFORE. CHANGED & CLEANED CENTER F.O. BURNERS & P/S DISCH STRAINERS. INSPECTED & CLEANED MAIN L.O. DISCH STRAINERS. DAILY TEST OF STEERING PUMP. RETARDED CLOCKS 20 MINS @ 0100. PUMPED UP PORT S.O. LACKS FROM #7 & DB. CHECKED STEERING E.R. GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH & ENG'S SPACES. COMPLIED COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

Henry Banning

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. BURNERS & SUCT. STRAINERS. RETARDED CLOCK 20 MINS @ 0500. CHECKED STEERING ENG. ROOM. COMPLIED WITH COMSTS 4700-7. PUMPED BILGES.

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

UNDERWAY, STEAMING 18 NOZZ, 0800 to 0830 BLEW TUBES ON #1+2 BOILERS. SHIFT & CLEAN F.O. DISCH STRAINERS P+5. SHIFT & CLEAN L.O. STRAINERS #1+2 GEN. CHANGED & CLEANED TOP FURNERS #1+2 BOILERS. PUMPED BILGES. MADE ROUNDS & INSP OF MACH & ENG. SPACES @ 0953. SECURED SPECIAL SEA DETAIL. COMPLIED WITH COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

R. Summers

CHIEF ENGINEER

1200-1600

CONT. FIRE DRILL @ 1515 SEC @ 1524 TESTED RELIEF VALVES ON

BOILER WATER READINGS

FIRE PUMPS PORED AT 125" PSI. STBY @ 1515 LT @ 1524 ABANDONED

STB'D

PORT

SHIP DRILL @ 1528 SEC @ 1531. UNABLE TO START FWD DIESEL FIRE PUMP.

HOURS 1487 HOURS 390

AKL 11:10 AKL 9:34

T-APT. 15:18 T-AKL 12:55

SAL. 4.54 SAL. 4.50

PHOS. 30 PHOS. 30

R.ph 11 R.ph 10

SOS 40 SOS 35

PH. COND. 8.0

CHIEF ENGR'S SIGNATURE-

R. Summers

USNS GEN John POPE-TAHU VOYAGE NO. 8-A FROM NSC OAKLAND CALIF TO Subic Bay P.I. TYPE OF VESSEL P2-52-R2 DATE 4-26-27-67

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME	240	240	240	240			AFT. H. P. ROTOR BEARING	141	142	130	131		
DETENTION TIME							FORWARD L. P. ROTOR BEARING	132	133	126	127		
REVOLUTION COUNTER (END OF WATCH)	2747	2750	2751	2753			AFT. L. P. ROTOR BEARING	130	130	124	125		
TOTAL REVOLUTIONS (FOR WATCH)	22190	22610	16700	15470			HOTTEST GEAR BEARING FORWARD	150	152	130	135		
AVERAGE RPM	92.4	92.0	69.5	64.5			HOTTEST GEAR BEARING AFT	146	146	133	735		
F.O. METER (END OF WATCH)	4480	7370	9140	0700	1720	2440	AUX. COND. CONDENSATE	118	121	112	115		120
F.O. CONSUMED	3050	2890	1770	1560	1020	720	1ST STAGE FEED WATER HEATER	165	164	148	110		106
MACHINERY PARTICULARS	THROTTLE	435	440	440	440		D. C. FEED WATER HEATER	240	240	240	240	240	240
	H.P. AHEAD	435	440	280	220		3RD STAGE FEED WATER HEATER	1050					
	L.P. AHEAD	22	23		5		F.O. TO BURNERS	246	230	180	230	140	160
	VACUUM	27.4"	27.4"	28.0	28.0	27.8	F.O. BACK PRESSURE						
	L.O. TO TURBINES	12	12	12	12	13	AIR TO FURNACE	5.5	6.0	4.0	2.0	1.0	1.0
	AUX. STEAM	150	150	150	150	150	MAIN STEAM	435	440	440	440	440	440
	BACK PRESSURE	9	9	9	9	9	SUPER HEAT	700	705	670	620	610	610
	GLAND STEAM	1.0	1.0	2.0	2.5	2.0	F.O. TO BURNERS	190	190	190	190	190	190
	H.P. BLEEDER	70	70				F.O. TEMP. IN SETTLING TANKS	108	110	115	110	105	105
	I.P. BLEEDER	6	6				PORT BOILER UPTAKE	343	335	360	355	275	280
PRESSURES	L.P. BLEEDER	10					STBD. BOILER UPTAKE	337	335	300	300	275	280
	STEAM AT THROTTLE	700	705	670	620	610	ENGINE ROOM TEMPERATURE	97	97	95	94	91	99
	L.P. EXHAUST	115	115	98	100		FIRE ROOM TEMPERATURE	97	97	95	94	91	99
	CONDENSATE	111	110	95	97		NOZZLES IN USE	16	16		Throat		
	CIRC. WATER IN	85	84	83	84	84	NO. OF BURNERS IN USE	6	6	4		2	2
	CIRC. WATER OUT	100	99	88	89		BURNER TIP SIZE	53/76	53/55	53/55	53/55	53/55	53/55
	L.O. TO COOLERS	128	127	122	122		CO2 % PORT BOILER						
	L.O. FROM COOLERS	110	110	110	110		CO2 % STBD. BOILER						
	TEMPERATURE THRUST BEARING	118	118	116	115		OIL LEVEL MAIN SUMP	1'2"	1'2"	1'2"	1'0"	1'0"	1'0"
	FORWARD H.P. ROTOR BEARING	126	124	122	123								
TEMPERATURES													

GENERATORS												FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	FUEL OIL	WATER	LUBE OIL	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	
1200 TO 1600	1	1200	435	700	9	126	116		62	850	850	1162440			130	66	
	2	1200	433	700	7	142	132		63	800	750	11651430			145	51	
1600 TO 2000	1	1200	440	705	9	125	115		62	650	650	11010			1950	-0-	
	2	1200	440	705	7	140	130		63	700	700	6558			1940	06	
2000 TO 2400	1	1200	440	670	9	120	110		62	650	650	11023			1150	1147	
	2	1200	440	670	7	139	126		63	650	650	448			3		
2400 TO 0400	1	1200	440	620	9	123	113		62	700	700	17173					
	2	1200	440	620	7	139	129		63	700	700	260					
0400 TO 0800	1	1200	440	610	9	125	110		62	600	600	823					
	2	1200	440	610	7	136	120		63	600	600	943					
0800 TO 1200	1	1200	440	610	9	123	112		62	750	750	240					
	2	1200	440	610	7	138	128		63	750	750						
SUMMARY												L.O. CENTRIFUGE - HOURS OPERATED					
												1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
												4	4	4	4	4	4
RUNNING TIME												SUMMARY					
DETENTION TIME												RUNNING TIME		PERCENT OF SLIP			
TOTAL REVOLUTIONS												DETENTION TIME		BBL FUEL/MI			
AVERAGE R.P.M.												TOTAL REVOLUTIONS		WIND DIRECTION			
TOTAL MILES BY ENGINE												AVERAGE R.P.M.		STATE OF SEA			
TOTAL MILES BY OBSERVATION												TOTAL MILES BY ENGINE		STATE OF WEATHER			

REMARKS

1200-1600 WATCH

Underway Reduced Speed to 16 Nozz @ 1200 B/o Bridge. Mach 2 operation #1 & 2 Boilers. 1 & 2 F.W. Blowers. 1 & 2 F.C.S. PUMPS. 1 & 2 M.N. F.W. PUMPS. M.N. AIR COMPRESSOR. M.N. AIR EJECTOR. M.N. FIRE & COND PUMPS. L.C. PURIFIER. L.C.S. PUMP. 1 & 2 AUX GENERATORS. AUX AIR EJECTOR. CIRC & COND PUMPS. ~~over~~ to MAIN FIRE & SAN PUMP. A.C. UNIT. PORT STEERING GEAR. Daily test of M.N. Thrust. Checked Steering E.R. Gear Pumped Bilges. Pumped up port scuttles from #7 & #8 5 PARTS. Changed & cleaned center F.O. burners & F.O. dish strainers. Made routine rounds on mach & eng. spaces. Complied with Comsts Inst 4700.7

WATCH ENGR'S SIGNATURE-

Henry Bunnay

1600-2000 WATCH

Underway 16 Nozzles machinery in operation as before. Blow Tubes on Port & stbd. Boilers @ 1600. Changed & cleaned F.O. Burners & scut. strainers. Checked steering Eng. Rm. Complied with Comsts. 4700.7. Pumped Bilges. Reduced speed from 16 Nozzles to 72 RPM @ 1930 B/o Bridge.

WATCH ENGR'S SIGNATURE-

L. Hurns

2000-2400 WATCH

Underway, Steaming 72 RPM, @ 0815 split plant, put #1 aux air ejector in operation, aux Circulator, aux cond pump, Shift & Clean F.O. dish strainers, Shift & Clean L.C. strainers #1 & 2 Turbo Generators. Pumped bilges, Made Rounds & Insp of mach & Eng. spaces. Complied with Comsts Inst. 4700-7

WATCH ENGR'S SIGNATURE-

R. Summers

2400-0400 WATCH

Underway on 10 Nozz 72 RPM Changed & cleaned center F.O. burners & dish strainers. Inspected & cleaned main L.C. dish strainers. Daily test of stbd. L.C. Pump. Reduced speed to 62 RPM B/o Bridge. Pumped up port scuttles from #5-SRB. Held Eng's Casualty drill B-20-STACK UP TAKE FIRE. Watch inst. & Bridge notified vice versa. Flashed & Pumped E.R. Bilges. Checked Steering E.R. Gear. Made routine rounds on mach & Eng. spaces. Added 1 Gal Lc each to 1 & 2 M.N. F.W. PUMPS. Complied with Comsts 4700.7

WATCH ENGR'S SIGNATURE-

Henry Bunnay

0400-0800 WATCH

Underway 10 Nozzles @ 72 RPM. Stbd @ 0400. Steaming Eng. manual. Arrival @ 0450. GPR. 27534610 FOM. P-7518060 S-4142940 Bolls AS Pa Boll Book. F.W.R. @ 0535 GPR. 27538070 FOM. P-7518280 S-4143080. Sec. Stm TB m.n. unit @ 0537 same on T-4000. 2020 @ 0538. Lit. off M.U.F. ^{Exp} @ 0600.

WATCH ENGR'S SIGNATURE-

L. Hurns

0800-1200 WATCH

In port, Inlet Bay P.E. Shift & Clean F.O. Dish strainers P & S Shift & Clean L.C. strainers #1 & 2 Generators. Made Rounds & Insp of mach & Eng. spaces. Comp with Comsts Inst 4700-7
-Refueling Ship-

WATCH ENGR'S SIGNATURE-

R. Summers

CHIEF ENGINEER

Order-Queen 744 towards Refuel-Mission. Received 11,023 BALS H.S.F.O. SVBIC BAP P.T.

BOILER WATER READINGS

STB'D	PORT
HOURS 1513	HOURS 414
AKL 11.10	AKL 9.34
T-15 15.18	T-AKL 12.85
SAL. 4.56	SAL. 4.56
PHOS. 30	PHOS. 30
R.ph #1	R.ph 10
S.O. 40	35
ph cond. 8.0	

CHIEF ENGR'S SIGNATURE-

[Signature]

USNS GEN John POPE-TAP-116 VOYAGE NO. Subic Bay PI TO Qui/Hon TYPE OF VESSEL P2-52-R2 DATE 4-27-28-67

WATCH							WATCH						
1200 TO 1600							1200 TO 1600						
1600 TO 2000							1600 TO 2000						
2000 TO 2400							2000 TO 2400						
2400 TO 0400							2400 TO 0400						
0400 TO 0800							0400 TO 0800						
0800 TO 1200							0800 TO 1200						
RUNNING TIME							AFT. H. P. ROTOR BEARING						
DETENTION TIME							FORWARD L. P. ROTOR BEARING						
REVOLUTION COUNTER (END OF WATCH)							AFT. L. P. ROTOR BEARING						
TOTAL REVOLUTIONS (FOR WATCH)							HOTTEST GEAR BEARING FORWARD						
AVERAGE RPM							HOTTEST GEAR BEARING AFT						
F.O. METER (END OF WATCH)							AUX. COND. CONDENSATE						
F.O. CONSUMED							1ST STAGE FEED WATER HEATER						
MACHINERY PARTICULARS	THROTTLE	440	440	440	440	440	MACHINERY PARTICULARS (CONT'D)	TEMPERATURES (CONT'D)					
	H.P. AHEAD		440	440	440	440		F.O. TO BURNERS					
	L.P. AHEAD		28	28	28	28		F.O. BACK PRESSURE					
	VACUUM	27.3"	27.8	27.5	27.8	28.0		AIR TO FURNACE					
	L.O. TO TURBINES	12	12	12	12	12		SAFETY UPTAKE					
	AUX. STEAM	150	150	150	150	150		MAIN STEAM					
	BACK PRESSURE	9	9	9	9	9		SUPER HEAT					
	GLAND STEAM	2.0	1.0	1.0	1.0	1.0		F.O. TO BURNERS					
	H.P. BLEEDER		70	70	70	70		F.O. TEMP. IN SETTLING TANKS					
	L.P. BLEEDER		6	6	6	6		PORT BOILER UPTAKE					
PRESSURES	L.P. BLEEDER		9"	9"	9"	9"	BOILER PARTICULARS	STBD. BOILER UPTAKE					
	STEAM AT THROTTLE		700	695	685	640		ENGINE ROOM TEMPERATURE					
	L.P. EXHAUST	110	116	116	115	117		FIRE ROOM TEMPERATURE					
	CONDENSATE	105	110	113	112	111		NOZZLES IN USE					
	CIRC. WATER IN	89	88	88	87	87		NO. OF BURNERS IN USE					
	CIRC. WATER OUT	99	96	98	98	98		BURNER TIP SIZE					
	L.O. TO COOLERS	112		129	128	127		CO ₂ % PORT BOILER					
	L.O. FROM COOLERS	110		110	110	110		CO ₂ % STBD. BOILER					
	TEMPERATURE THRUST BEARING			120	118	120		OIL LEVEL MAIN SUMP					
	FORWARD H.P. ROTOR BEARING			125	125	124							
TEMPERATURES							MISCELLANEOUS						

GENERATORS											
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE
1200 TO 1600	1	1200	440	620	9	125	115		62	700	700
	2	1200	440	620	7	140	130		63	750	750
1600 TO 2000	1	1200	440	700	9	124	112		62	750	750
	2	1200	440	700	7	140	128		63	750	750
2000 TO 2400	1	1200	440	695	9	124	113		62	750	750
	2	1200	440	695	7	140	129		63	750	750
2400 TO 0400	1	1200	440	685	9	125	115		62	800	800
	2	1200	440	685	7	141	131		63	850	800
0400 TO 0800	1	1200	440	690	9	124	115		62	800	800
	2	1200	440	690	7	140	124		63	700	700
0800 TO 1200	1	1200	440	685	9	124	114		62	750	750
	2	1200	440	695	7	140	128		63	750	750

FUEL - WATER AND LUBE OIL			
FUEL OIL	METER AT NOON	11678210	ON HAND AT START OF DAY
	METER PREVIOUS NOON	11662440	EVAPORATED OR RECEIVED
	CONSUMED BY METER	15770	ON HAND
	ON HAND AT START OF DAY	12173	CONSUMED
	RECEIVED DURING DAY	- 0 -	ON HAND AT START OF DAY
LUBE OIL	EXPENDED DURING DAY	600	RECEIVED
	REMAINING ON BOARD	16573	ON HAND
	ON HAND AT START OF DAY	843	CONSUMED
	EVAPORATED OR RECEIVED	417	DIESEL OIL
	ON HAND	950	ON HAND
DOMESTIC WATER	CONSUMED	310	CONSUMED
	LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gal.)		
	4	4	4
	L.O. CENTRIFUGE - HOURS OPERATED		
	1200 TO 1600	1600 TO 2000	2000 TO 0400
SUMMARY	4	4	4
	RUNNING TIME	1152	PERCENT OF SLIP
	DETENTION TIME	- 0 -	BBL FUEL/MI
	TOTAL REVOLUTIONS	105475	WIND DIRECTION
	AVERAGE R.P.M.	93.2	STATE OF SEA
	TOTAL MILES BY ENGINE	393	STATE OF WEATHER
	TOTAL MILES BY OBSERVATION	356	

REMARKS

1200-1600 WATCH

PORT WATCH MACH IN OPERATION #1+2 BLOWERS 1+2 F.D. BLOWERS 1+2 F.W. PUMPS 1+2 M.H. FEED PUMPS. MAIN A.R. COMP. M.H. AIR EXTRACTOR. M.H. CIRC. COND PUMPS. L.O. PURIFIER L.O. PUMP. A.C. UNIT. FIRE-SON PUMP 1+2 AUX GENERATORS AUX A.R. EXTRACTOR. AUX CIRC. COND PUMPS. MAIN UNIT IN JACKING GEAR WITH VACUUM UP. Secured Fueling Ship & Secured TAKING ON FUEL @ 1410 TIME CHECK @ 1434. Wheel Clearance @ 1458 Disengaged JACKING GEAR @ 1459 OPEN M.S. & B.S. @ 1501 Started WARMING UP M.H. UNIT @ 1503 TESTED TELEGRAPH 1505. Stby @ 1517 FEM-7519310-S-4143770-CIR-27538420 MADE ROUTINE ROUNDS ON MACH & ENGR'S SPACES Complied With Comsts 4700-7

WATCH ENGR'S SIGNATURE-

George Bunney

1600-2000 WATCH

MACHINERY IN OPERATION AS BEFORE DEPT. 1648. @ 17.27538420 FEM P-7519380 S-4144290. Bolls AS PER BOLL BOOK SPOON 18 NOZZLES. Checked STEERING ENG. ROOM. Complied with Comsts. 4700-7 Pumped Bilges. Spent M.W.F. B.V. @ 1600.

WATCH ENGR'S SIGNATURE-

L. Harris

2000-2400 WATCH

Underway, Steaming 18 Kts. Cleaned & Changed top burners #1+2 Boilers Shift & Clean 70. Disch strainers #1+5. Shift & Clean L.O. strainers #1+2 turbo Generators. Made Rounds & Insp of Mach & Eng. spaces. Pumped bilges. Complied With Comsts Inst 4700-7

WATCH ENGR'S SIGNATURE-

R. Summers

2400-0400 WATCH

Underway ON 18 NOZZ MACH AS BEFORE. Changed & CLEANED CENTER F.C. burners & 1/2 disch STRAINERS. Pumped up PORT SUTTLERS FROM #5 1/2 LB TR. INSPECTED & CLEANED MAIN L.O. DISCH STRAINERS. POWER FAILURE TO #2 EVAP BARGE PUMP @ 0030 CALLED OUT ELECT 1/2 CIE REPAIRS COMPLETED & BACK IN SERVICE @ 0100 DAILY test of stby 20 pump. Pumped Bilges. Checked STEERING ENG. GEAR. MADE ROUTINE ROUNDS ON MACH & ENGR'S SPACES Complied With COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

George Bunney

0400-0800 WATCH

Underway 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. Changed & CLEANED F.C. BURNERS & SUCT. STRAINERS. Checked STEERING ENG. RM. Complied with Comsts 4700-7 Pumped Bilges. Changed Spare BURNER BARREL.

WATCH ENGR'S SIGNATURE-

L. Harris

0800-1200 WATCH

Underway, Steaming 18 Kts. 0800 to 0830 Blew tubes on #1+2 Boilers Shift & Clean 70. Disch strainers, Shift & Clean L.O. strainers #1+2 turbo Generators. Cleaned & Changed top burners #1+2 Boilers. @ 0830 shift 70. suction to Inboard suttler. Made Rounds & Insp of Mach & Eng spaces. Complied With Comsts Inst 4700-7 Pumped Bilges.

WATCH ENGR'S SIGNATURE-

R. Summers

CHIEF ENGINEER

BURN

BOILER WATER READINGS

STB'D

PORT

HOURS 1537 HOURS 439

AKL 11.10 AKL 9.34

T-AVL 15.18 T-AKL 12.85

SAL. 456 SAL. 456

PHOS. 30 PHOS. 30

R.ph 11 R.ph 10

So 33 30

Ph. 0.00 8.0

CHIEF ENGR'S SIGNATURE-

C. Harris

REMARKS

1200-1600 WATCH

UNDERWAY ON 18 NOZZ MACH IN OPERATION #1+2 BOILERS 1+2 F.W. BLOWERS 1+2 F.O.S. PUMPS. 1+2 MAIN F.W. PUMPS. MAIN AIR EJECTOR. MIN CIRC COND PUMPS L.O. PURIFIER L.O. PUMP. MIN AIR COMPRESSOR. 1+2 AUX GENERATORS. AUX CIRC. PUMP. AUX AIR EJECTOR + COND. PUMP OVER TO MAIN F.O. UNIT FIREMAN PUMP. PORT STEERING GEAR. DAILY TEST OF MAIN THROT. PUMPED UP PORT SETTLERS FROM #5 P% DB TKS. SECURED A.C. UNIT @ 1245 DOTO POWER FAILURE. BACK ON THE LINE @ 1255. CHANGED & CLEANED CENTER F.O. BURNERS & P% DISCH STRAINERS. PUMPED BILGES. CHECKED STEERING E.R. GEAR. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH COMSTS INST

WATCH ENGR'S SIGNATURE-

4700-7

1600-2000 WATCH

UNDERWAY 18 NOZZLES MACHINERY IN OPERATION AS BEFORE. BLOWN TUBES ON PORT & STBD. BILGES @ 1600. CHANGED & CLEANED F.O. BURNERS & SUCT. STRAINERS. COMPLIED WITH COMSTS 4700-7. PUMPED BILGES. CHECKED STEERING ENG. DISASSEMBLE TWO SPARE BURNERS CHECKED & REPACKED SAME

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

UNDERWAY, STEAMING 18 NOZZ, @ 2000 REDUCED SPEED TO 16 NOZZ B/O. CHANGED & CLEANED TOP FURNERS #1+2 BOILERS, SHIFT & CLEAN 70 DISCH STRAINERS P/S, SHIFT & CLEAN L.O. STRAINERS #1+2 GENERATORS. MADE ROUNDS & INSPECTION OF MACH & ENG SPACES, PUMPED BILGES, COMPLIED WITH COMSTS INST. 4700-7

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

UNDERWAY REDUCED SPEED TO 60 RPM 10 NOZZ @ 0000 B/O BRIDGE MACH AS BEFORE. CHANGED & CLEANED CENTER F.O. BURNERS P% DISCH STRAINERS. INSPECTED & CLEANED MAIN L.O. STRAINERS. DAILY TEST OF STBY L.O. PUMP. SECURED L.O. PURIFIER @ 0100 CLEANED & BACK IN SERVICE @ 0130 PUMPED UP PORT SETTLERS FROM #9 & DB F.O. TK. CHECKED STEERING E.R. GEAR. PUMPED BILGES. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

UNDERWAY 60 RPM INCREASED SPEED TO 72 RPM @ 0542 B/O BRIDGE MACHINERY AS BEFORE. STBY @ 0556 ARRIVED @ 0600 ATU. 27742596 FORM P-7532850 S-4156370 BILLS AS PER BILL BOOK MANEUVERING TO A NEW F.W.F. @ 0652 ATU. 27744420 FORM. P-7532980 S-4156480. SEC. STR. TO MAIN UNIT @ 0652 SAME ON TACKLING @ 0630 @ 0653. ROTOR CLEANING AT 0640 L.P. 090 H.R. 040.

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

AT ANCHOR, QUL NHON, @ 0845 SECURED AIR COND UNIT. FOR REPAIRS 0905 A.C. UNIT BACK IN SERVICE. CLEANED & CHG F.O. DISCH STRAINERS P/S. SHIFT & CLEAN L.O. STRAINERS #1+2 GENERATOR. PUMPED BILGES. MADE ROUNDS & INSPECTION OF MACH & ENG SPACES, COMPLIED WITH COMSTS INST 4700-7

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

Order Lovell, F.W. Sowards, Reefer-MAYN. WEEKLY TEST OF EMERGENCY EQUIPMENT SAFETY DEVICES.

BOILER WATER READINGS 2000-2400 MADE WEEKLY INSP. OF FIRE FIGHTING EQUIP.

STE'D PORT ALL IN GOOD WORKING ORDER C/O2 CYLINDERS UP TO WEIGHT, ALL SEALS IN TACT.

HOURS 1561 HOURS 463

AXL 11.10 AXL 9.34

T-AP 14.02 T-AXL 12.85

SAL. 4.56 SAL. 4.56

PHOS. 30 PHOS. 30

R.ph 11 R.ph 10

S0232 30

PH. COND 8.0

CHIEF ENGR'S SIGNATURE-

REMARKS

1200-1600 WATCH

AT ANCHOR PORT OF QUI NHON VIETNAM. MACH IN OPERATION #1+2 Boilers. 1+2 F.D. Blowers 1+2 F.O.S. PUMPS. 1+2 M.N. F.D. PUMPS. MAIN AIR COMPRESSOR. M.N. AIR Ejector. M.N. CIRC & COND. PUMPS. L.O. PURIFIER. L.O.S. PUMP. 1+2 AUX GENERATORS. AUX AIR Ejector. AUX CIRC & COND PUMPS. AC UNIT FIRE & SAN PUMP. MAIN UNIT ON JACKING GEAR WITH VACUUM UP. CHANGED & CLEANED F.O. BURNERS & P/S DISCH STRAINERS. Bilges AT A SAFE LEVEL. POWER FAILURE TO #2 EVAP BRINE PUMP @ 1525 ELECT MAKING REPAIRS. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH COMSTS INST 4700.7

PILOT BURN FWT MORGAN REFER GINTEL

WATCH ENGR'S SIGNATURE- Henry Burrey

1600-2000 WATCH

Port watch AT ANCHOR machinery IN operation AS BEFORE EXCEPT L.O. Purifier STOP @ 1900. Sea. STM TO 5443. Repacked Lums 6292 & 6255 ON PORT Boiler. Complied with COMSTS. 4700.7. Pumped Bilges.

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

At Anchor, Qui Nhon, Machinery in operation as before, Started L.O. Purifier @ 2000. Pumped bilges, Made Rounds & Insp of Mach & Eng spaces. Cleaned & Changed burners, & F.D. Disch strainers P+S. Shift & Chon L.O. strainers #1+2 Generators, Complied With Comsts Inst 4700-7.

Duty Elect-Jenkins

Oiler Lowell, 24 Jowards, Refer Eng, Mornin

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

AT ANCHOR MACH IN OPERATION AS BEFORE. Pumped up PORT SETTLERS FROM #9 & F.O. TK. Daily test of stby L.O. pump. Shifted & CLEANED MAIN L.O. DISCH STRAINER. Secured L.O. purifier @ 0200 FOR REPAIRS. Checked steering E.R. Bilges AT SAFE LEVEL. MADE ROUTINE ROUNDS ON MACH & ENGS SPACES. COMPLIED WITH COMSTS 4700.7

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

Port watch AT ANCHOR machinery AS BEFORE CHANGED & CLEANED F.O. Burners & Soot. Strainers. Pumped #3 hold Port & stbd. Pumped Bilges Time back @ 0700. Tested Tele @ 0703. Talking 6220 DISCHARGE @ 0658 STM. TO M.N. UNIT @ 0700. ROLLING SAME @ 0702. Complied with COMSTS. 4700.7. stby. STM. L.O. Pump Idling.

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

Departing port, Qui Nhon, Manoeuvring falls as per bell loop @ 0800. 34 By @ 0818 Departure, @ 0818 44 16 Ngg By Phone, @ 0845 #1+2 Eng Room to Full Speed 16 Ngg, @ 1100 put L.O. purifier in service, Made Rounds & Insp. of Mach & Eng spaces. Pumped bilges & Cargo holds. Complied With Comsts Inst 4700-7.

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

STBY 0800		Departure - 0818	
BOILER WATER READINGS	Ctr 27745070	Ctr	- 27746030
STB'D PORT	FOM-P-7535270	FOM-P-	7535300
ECURS 15.85 HOURS 487	FOM-S-4158930	FOM-S-	4158950
AKL 8.18 AKL 8.18			
T-AKL 11.08 T-AKL 11.08			
SAL. 3.73 SAL. 4.14			
PHOS. 30 PHOS. 30			
R.ph 10 R.ph 10			
503 30 25			
Ph. Cond. 8.10			

CHIEF ENGR'S SIGNATURE-

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME	240						MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING	142				
DETENTION TIME								FORWARD L. P. ROTOR BEARING	153				
REVOLUTION COUNTER (END OF WATCH)	2778							AFT. L. P. ROTOR BEARING	130				
TOTAL REVOLUTIONS (FOR WATCH)	21740							HOTTEST GEAR BEARING FORWARD	150				
AVERAGE RPM	90.6							HOTTEST GEAR BEARING AFT	145				
F.O. METER (END OF WATCH)	1169	1169	1170					AUX. COND. CONDENSATE	116	115	115		
F.O. CONSUMED	2690	800	750					1ST STAGE FEED WATER HEATER	163	105	108		
MACHINERY PARTICULARS	THROTTLE	430	430 ^{4H}					D. C. FEED WATER HEATER	240	240	240		
	H.P. AHEAD	430	430 ^{4H}					3RD STAGE FEED HP WATER HEATER	050				
	L.P. AHEAD	22						F.O. TO BURNERS	160	110	110		
	VACUUM	28.2"	28.0"	27.8				F.O. BACK PRESSURE	170	166	116		
	L.O. TO TURBINES	12	13	13				AIR TO FURNACE	5.2	11.5	1.5		
	AUX. STEAM	150	125	125				SALINITY UPTAKE	5.6	1.5	1.5		
	BACK PRESSURE	9	9	9				MAIN STEAM	441	41	41		
	GLAND STEAM	1.5	1.5	1.5				SUPER HEAT	430	430	430		
	H.P. BLEEDER	70						F.O. TO BURNERS	685	610	600		
	I.P. BLEEDER	6						F.O. TEMP. IN SETTLING TANKS	190	190	190		
TEMPERATURES	L.P. BLEEDER	10"					BOILER PARTICULARS	PORT BOILER UPTAKE	107	110	110		
	STEAM AT THROTTLE	685						STBD. BOILER UPTAKE	348	320	325		
	L.P. EXHAUST	111	135	123				ENGINE ROOM TEMPERATURE	348	265	270		
	CONDENSATE	107	98	94				FIRE ROOM TEMPERATURE	96	95	93		
	CIRC. WATER IN	85	85	84				NOZZLES IN USE	96	95	93		
	CIRC. WATER OUT	96	89	86				NO. OF BURNERS IN USE	10				
	L.O. TO COOLERS	129	112	112				BURNER TIP SIZE	2	2	2		
	L.O. FROM COOLERS	110	110	110				CO ₂ % PORT BOILER	51/55	51/55	51/55		
	TEMPERATURE THRUST BEARING	118						CO ₂ % STBD. BOILER					
	FORWARD H.P. ROTOR BEARING	125						OIL LEVEL MAIN SUMP	1'2"	1'2"	1'2"		

GENERATORS													FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL	
1200 TO 1600	1	1200	430	685	9	125	115		62	700	700	235	METER AT NOON	11700410		ON HAND AT START OF DAY	126	
	2	1200	430	685	7	140	130		63	750	750	235	METER PREVIOUS NOON	11696270		EVAPORATED OR RECEIVED		
													CONSUMED BY METER	4140		ON HAND		
1600 TO 2000	1	1200	430	610	4	124	112		62	600	600	235	ON HAND AT START OF DAY	15837		CONSUMED		
	2	1200	430	610	7	138	125		63	700	700	235	RECEIVED DURING DAY			ON HAND AT START OF DAY	1920	
													EXPENDED DURING DAY			RECEIVED		
2000 TO 2400	1	1200	430	600	9	122	112		62	600	600	235	REMAINING ON BOARD			ON HAND		
	2	1200	430	600	7	138	126		63	600	600	235	ON HAND AT START OF DAY	877		CONSUMED		
													EVAPORATED OR RECEIVED			DIESEL OIL	1135	
2400 TO 0400													ON HAND			ON HAND		
													CONSUMED			CONSUMED		
													LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)					
0400 TO 0800													4	4	4			
													L.O. CENTRIFUGE - HOURS OPERATED					
													1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
0800 TO 1200													4	4	4			
													SUMMARY					
													RUNNING TIME		PERCENT OF SLIP			
												DETENTION TIME		BBL FUEL/MI				
												TOTAL REVOLUTIONS		WIND DIRECTION				
												AVERAGE R.P.M.		STATE OF SEA				
												TOTAL MILES BY ENGINE		STATE OF WEATHER				
												TOTAL MILES BY OBSERVATION						

REMARKS

1200-1600 WATCH

UNDERWAY ON 16 NOZZ MACH OPERATION #1+2 Boilers 1+2 F.D. Blowers 1+2 F.O.S. PUMPS. 1+2 M.H.F.D. PUMPS. M.N. AIR COMPRESSOR. M.N. AIR EJECTOR. M.N. CIRC. COND. PUMPS. L.O. PURIFIER. L.O.S. PUMP. A.G. UNIT. 1+2 AUX GENERATORS. AUX AIR EJECTOR. AUX CIRC. COND. PUMPS. FIRST SAN PUMP. PORT STEERING GEAR. DAILY test of M.N. Thrott. Shifted & Cleaned $\frac{1}{2}$ F.O. disch. STRAINERS. Checked steering ER. Gear. Pumped ALL Cargo holds Bilge. Reduced speed to 72 RPM 10 NOZZ $\frac{1}{2}$ Bridge @ 1530 Stry @ 1530 17 RR @ 60 RPM @ 1542 CTR 27786180 Fom P-7537760 - S-4161260 MADE ROUTING ROUNDS ON MACH & ENG. SPACES. Complied with Comsts 4700-7

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

Machinery as before maneuvering water. F.W.B. @ 1645 CTR. Fom. P. 7537910 S-4161400. Bolls AS FOR Ball 300K. AT ANCHOR. See. Str. TO M.N. unit @ 1646 same as Tackling Quau @ 1647. Pumped #3 hold P+S & Bubbler ship. Complied with Comsts. 4700-7.

OILCO Morris F.W.T. MEDUARDS Reefing Boats

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

At Anchor, Com Rahn Bay. Machinery in operation as before. Shift & Clean 70 Disch. strainers, P+S. Shift & Clean L.O. strainers #1+2 Generators. Bilges at Safe level. Made Rounds & Insp of Mach & Eng. spaces. Complied with Comsts Inst. 4700-7.

Coles-Lowell 74. Towards. Refer, Marwin

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

SEAL	PORT
HOURS	HOURS
AKL	AKL
T-APL	T-AKL
SAL.	SAL.
PEOS.	PEOS.
R.ph	R.ph

CHIEF ENGR'S SIGNATURE-

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE													
		WATCH						WATCH															
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200								
RUNNING TIME								MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING														
DETENTION TIME									FORWARD L. P. ROTOR BEARING														
REVOLUTION COUNTER (END OF WATCH)									AFT. L.P. ROTOR BEARING														
TOTAL REVOLUTIONS (FOR WATCH)									HOTTEST GEAR BEARING FORWARD														
AVERAGE RPM									HOTTEST GEAR BEARING AFT														
F.O. METER (END OF WATCH)									AUX. COND. CONDENSATE														
F.O. CONSUMED								1ST STAGE FEED WATER HEATER															
MACHINERY PARTICULARS	PRESSURES	THROTTLE						MACHINERY PARTICULARS (CONT'D)	D. C. FEED WATER HEATER														
		H.P. AHEAD							3RD STAGE FEED WATER HEATER														
		L.P. AHEAD							F.O. TO BURNERS														
		VACUUM							F. O. BACK PRESSURE														
		L.O. TO TURBINES							AIR TO FURNACE														
		AUX. STEAM							UPTAKE														
		BACK PRESSURE							MAIN STEAM														
		GLAND STEAM							SUPER HEAT														
		H.P. BLEEDER							F.O. TO BURNERS														
	TEMPERATURES	I.P. BLEEDER						BOILER PARTICULARS	F.O. TEMP. IN SETTLING TANKS														
		L.P. BLEEDER							PORT BOILER UPTAKE														
		STEAM AT THROTTLE							STBD. BOILER UPTAKE														
		L.P. EXHAUST							ENGINE ROOM TEMPERATURE														
		CONDENSATE							FIRE ROOM TEMPERATURE														
		CIRC. WATER IN							NOZZLES IN USE														
		CIRC. WATER OUT							NO. OF BURNERS IN USE														
		L.O. TO COOLERS							BURNER TIP SIZE														
		L.O. FROM COOLERS							CO ₂ % PORT BOILER														
TEMPERATURES	TEMPERATURE THRUST BEARING						MISCELLANEOUS	CO ₂ % STBD. BOILER															
	FORWARD H.P. ROTOR BEARING							OIL LEVEL MAIN SUMP															
GENERATORS												FUEL - WATER AND LUBE OIL											
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL						
1200 TO 1600													METER AT NOON 8000		ON HAND AT START OF DAY		ON HAND						
													METER PREVIOUS NOON 0000	470000	EVAPORATED OR RECEIVED		CONSUMED						
													CONSUMED BY METER		ON HAND		CONSUMED						
													ON HAND AT START OF DAY		ON HAND AT START OF DAY		RECEIVED						
													RECEIVED DURING DAY		RECEIVED		ON HAND						
													EXPENDED DURING DAY		ON HAND		CONSUMED						
													REMAINING ON BOARD		CONSUMED								
													ON HAND AT START OF DAY		DIESEL OIL								
													EVAPORATED OR RECEIVED		ON HAND		CONSUMED						
													ON HAND		CONSUMED								
													CONSUMED										
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gain.)																							
L.O. CENTRIFUGE - HOURS OPERATED																							
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200																
SUMMARY																							
RUNNING TIME						PERCENT OF SLIP																	
DETENTION TIME						BBL FUEL/MI																	
TOTAL REVOLUTIONS						WIND DIRECTION																	
AVERAGE R.P.M.						STATE OF SEA																	
TOTAL MILES BY ENGINE						STATE OF WEATHER																	
TOTAL MILES BY OBSERVATION																							

4-27-28-67

Checked 0800 - 4
Brown Chaper

REMARKS

TIME	PRESSURE										TEMPERATURE						SPEED R.P.M.	REMARKS
	STEAM TO THROTTLE	STEAM TO NOZZLE	STEAM TO EXHAUST	TURB. LUB OIL PRESS.	COMPRESSOR SUCTION	COMPRESSOR LUBE OIL	COMPRESSOR DISCHARGE	COND. WATER	CHILLED WATER	TURBINE L.O. TEMP.	FREON IN CONDENSER	COND. WATER	CHILLED WATER	BEARING LINE	BEARING THRUST			
1200	425	320	12	13	18	13	10	15-4	47-45	115	104	82-90	47-45	140	84	3500	Brown	
1300	425	330	13	13	18	13	10.5	84-	47-45	115	104	82-90	47-45	140	84	3500		
1400	420	340	13.5	13	18	13	11	15-4	48-46	115	104	82-90	48-46	140	84	3600		
1500	435	350	14	13	18	13	11	15-4	48-46	115	105	82-90	48-46	140	84	3500	Brown for Linton 1511A	
1600	420	350	12	11	18	13	11.5	18-4	25-46	118	107	86-91	49-45	138	82	3650		
1700	420	340	12	11	18	13	11	15-4	26-46	119	107	86-91	49-45	138	82	3650		
1800	420	370	13	11	18	13	12	15-5	26-46	121	109	86-91	52-47	138	68	3800	B.C.A.	
1900	440	380	13	11	18	13	13	15-5	26-46	126	110	88-93	49-44	137	63	3900		
2000	440	380	13	11	18	13	12	15-5	26-46	121	110	86-90	47-44	137	64	3900		
2100	440	380	13	11	18	13	12	15-5	26-46	121	109	86-90	47-44	137	64	3900	Marine	
2200	440	380	13	11	18	13	12	15-5	26-46	120	109	86-90	47-44	137	64	3900		
2300	440	380	13	11	18	13	12	15-5	26-46	120	109	86-90	47-44	137	64	3900		
2400	440	380	13	11	18	13	12	15-5	26-46	120	104	86-90	47-43	134	72	3900	Bentley	
0100	440	380	13	11	18	13	12	15-5	26-46	120	109	86-90	47-43	140	80	3900		
0200	430	370	13	11	18	13	12	15-5	26-46	120	109	86-90	47-43	140	80	3900		
0300	430	370	13	11	18.5	13	12	15-5	26-46	120	109	86-90	47-43	140	80	3925	Bentley	
0400	430	390	13	11	18	13	11	15-5	26-46	120	106	86-91	47-43	140	80	3800		
0500	440	340	13	11	18	13	11	15-5	26-46	119	106	86-91	48-44	139	81	3800		
0600	430	350	13	11	18	13	11.5	15-5	26-46	119	107	86-91	48-44	139	82	3850	Bentley	
0700	430	350	13	11	18	13	11.5	15-5	26-46	119	107	86-91	49-44	139	82	3850		
0800	430	350	13	11	18	13	12	15-5	26-46	120	108	86-90	48-44	139	82	3850		
0900	430	350	13	11	18.5	13	12	15-5	26-46	120	109	86-90	49-44	139	82	3850	Marine	
1000	440	350	13	11	18	13	12	15-5	26-46	120	109	85-90	48-44	140	82	3850		
1100	440	350	13	11	18	13	12	15-5	26-46	120	109	85-90	48-44	140	82	3850		

4/26/67
REMARKS

TIME	PRESSURE										TEMPERATURE						SPEED R.P.M.	REMARKS
	STEAM TO THROTTLE	STEAM TO NOZZLE	STEAM TO EXHAUST	TURB. LUB OIL PRESS.	COMPRESSOR SUCTION	COMPRESSOR LUBE OIL	COMPRESSOR DISCHARGE	COND, WATER	CHILLED WATER	TURBINE L.O. TEMP.	FREON IN CONDENSER	COND. WATER	CHILLED WATER	BEARING LINE	BEARING THRUST			
1200	420	330	13	11	18	13	10	14-5	25-46	118	106	85-88	48-45	136	79	4200	1200-1600	Bintef
1300	420	340	13	11	18	13	10	14-5	25-46	118	106	85-88	48-45	136	80	4000		
1400	420	340	13	11	18	13	11	14-5	26-46	118	106	85-88	48-45	137	80	4000		
1500	440	340	13	11	18	13	11	14-5	26-46	118	108	85-88	48-44	138	82	3800		
1600	410	330	12.5	11	18	13	11	14-5	26-46	120	107	87-92	49-44	138	82	3800	1600-2000	B. Lane
1700	430	350	13	11	18	13	11.5	14-5	26-46	120	107	87-92	49-44	138	82	3850		
1800	440	350	13	11	18	13	11	14-5	26-46	121	107	86-92	48-44	138	81	3850		
1900	440	350	13	11	18	13	11	14-5	26-46	120	106	85-91	48-44	138	80	3850		
2000	440	350	13	11	18	13	11	14-5	26-46	119	105	85-90	47-43	138	80	3800	2000-2400	Marion
2100	440	350	13	11	18	13	11	14-5	26-46	119	105	85-90	47-43	138	80	3800		
2200	440	350	13	11	18	13	10	14-5	26-46	118	104	84-88	47-43	137	81	3800		
2300	440	350	13	11	18	13	10	14-5	26-46	117	104	84-88	47-43	137	82	3800		
2400	440	330	13	11	18	13	10	14-5	26-46	117	100	84-88	47-43	138	83	3800	2400-2800	Bintef
0100	440	330	13	11	18	13	10	14-5	26-46	117	100	84-88	47-43	138	83	3800		
0200	440	340	13	11	18	13	10	14-5	26-46	117	104	84-88	47-43	138	83	3800		
0300	440	330	13	11	18	13	10	14-5	26-46	117	104	84-88	47-43	138	83	3800		
0400	410	320	12	11	18	13	10	14-5	26-46	117	104	85-90	47-43	138	84	3750	2800-3200	B. Lane
0500	410	320	12.5	11	18	13	10	14-5	26-46	117	104	85-90	47-43	138	84	3750		
0600	440	320	13	11	18	13	10	14-5	26-46	116	104	84-90	46-42	138	84	3800		
0700	410	300	12	11	18	13	9	14-5	26-46	115	103	84-89	47-44	136	84	3650		
0800	420	320	12	11	18	13	10	14-5	26-46	115	102	84-88	47-44	138	84	3700	3200-3600	Zilairin
0900	420	310	12	11	18	13	10	14-5	26-46	115	103	84-88	48-44	138	84	3650		
1000	420	310	12	11	18	13	10	14-5	26-46	115	104	84-88	48-44	138	84	3650		
1100	420	310	12	11	18	13	10	14-5	26-46	116	104	84-88	48-44	138	84	3650		

Bintef

Beane

Martin

Bintef

Beane

Martin

Fwd. 4/19/67

	TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1.	L.P. EXHAUST TEMP	101	102	105	104	105	105	105	103	106	106	106	102	103	105	105	105	104	104	104	103	104	103	103	102
2.	MN COND STE TEMP	92	93	94	98	100	100	100	100	102	102	103	93	95	95	95	100	100	100	100	100	100	99	100	93
3.	MN INJ TEMP	67	67	68	68	68	68	68	66	68	68	70	67	69	69.3	70	70	68	68	68	68	68	66	66	66
4.	MN OVBD TEMP	80	79	81	80	80	80	80	78	80	80	82	80	82	82	82	82	82	82	80	80	80	78	78	80
5.	L.O. TO COOLERS	126	128	130	128	128	128	129	129	129	129	129	129	129	130	129	128	128	128	124	128	129	129	129	130
6.	L.O. FROM COOLERS	109	110	111	110	110	110	110	110	110	110	110	109	111	112	110	110	110	110	108	110	110	110	111	
7.	THRUST BRG TEMP	118	118	118	120	120	120	120	118	118	118	118	118	120	120	120	118	118	118	115	118	118	118	118	120
8.	FWD H.P. ROTOR BRG	123	123	125	124	124	124	124	123	123	123	123	125	125	126	124	124	124	124	122	123	123	126	126	125
9.	AFT H.P. ROTOR BRG	137	138	140	140	140	140	140	135	137	136	136	139	139	140	140	140	140	139	139	136	136	136	136	140
10.	FWD L.P. ROTOR BRG	132	133	135	133	133	135	135	132	132	133	133	133	134	135	133	133	132	132	130	132	132	132	132	134
11.	AFT L.P. ROTOR BRG	128	129	130	130	130	130	130	128	128	128	128	130	130	130	129	129	129	129	128	127	128	128	128	130
12.	HOT GEAR BRG FWD	159	160	160	160	160	160	160	156	157	157	157	160	160	160	160	160	160	160	160	156	156	156	156	160
13.	HOT GEAR BRG AFT	146	147	148	148	148	148	148	145	146	146	146	146	148	148	146	148	147	147	147	145	146	146	146	146
14.	AUX COND STE TEMP	106	106	108	109	110	110	110	110	110	112	112	110	108	111	112	104	110	104	110	110	110	108	108	106
15.	1ST STAGE AIR TEMP	154	154	154	154	154	158	158	152	152	156	158	156	158	158	158	158	158	158	158	158	154	154	154	153
16.	D.C. HEATER TEMP	246	240	239	240	240	240	240	238	236	238	240	240	240	240	240	240	240	240	240	240	240	238	236	241
17.	SUPRHT TEMP PORT	670	665	670	690	690	690	695	670	670	670	670	660	660	660	660	675	700	695	700	660	660	660	660	660
18.	SUPRHT TEMP STBD	670	680	670	690	690	690	695	660	660	660	660	670	665	660	660	675	700	695	700	680	680	680	680	680
19.	F.O. SETT TEMP P	105	105	126	120	120	120	120	105	105	110	110	95	90	90	100	100	100	95	100	100	100	100	100	105
20.	F.O. SETT TEMP S	100	102	105	105	105	105	105	115	115	115	115	95	100	99	100	100	100	100	105	105	105	105	105	102
21.	UPTAKE PORT	345	348	350	345	345	350	350	325	325	335	335	335	333	335	335	335	335	330	330	340	340	340	340	347
22.	UPTAKE STBD	346	347	340	340	325	340	345	315	315	325	325	325	328	335	335	335	325	325	335	340	340	335	335	343
23.	F.O. PUMP SUCT TEMP	110	112	114	112	112	112	112	110	110	124	124	108	100	108	107	110	110	110	110	110	110	110	110	110
24.	MN FD PMP L.O PORT	31	31	32	31	28	29	28	26	26	32	33	29	29	29	29	31	29	29	29	28	28	30	28	30
25.	MN FD PMP L.O STBD	20	20	21	23	25	24	20	20	20	26	26	20	20	27	27	20	20	20	20	26	26	22	20	20
26.	L.O. TO GEARS	112	113	114	114	114	114	114	114	114	114	114	113	114	114	112	112	111	111	108	114	114	114	114	114
27.	AIR CONTR L.O. PRESS	30	30	30	30	30	30	30	28	28	28	28	30	30	30	30	30	30	30	30	28	28	28	28	30

4/17/18/67

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
28. L.O. PRES #2																								
31. L.O. TO COOLER #1	120	120	121	118	118	120	120	120	120	120	120	120	120	121	120	120	118	120	120	120	120	120	120	120
34. L.O. TO COOLER #2																								
33. L.O. FROM COOLER #1	110	110	112	110	110	110	110	110	110	110	110	110	110	111	110	110	110	110	110	110	110	110	110	111
32. L.O. FROM COOLER #2																								
35. L.O. GOV PRES #1	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62	62
34. L.O. GOV PRES #2																								
37. AMPS POS #1	1200	1200	1250	1250	1350	1350	1350	1400	1400	1400	1500	1350	1350	1300	1350	1450	1350	1360	1300	1200	1200	1300	1300	1350
36. AMPS POS #2																								
39. AMPS NEG #1	1200	1250	1300	1300	1400	1400	1400	1500	1500	1500	1600	1400	1400	1400	1400	1500	1400	1400	1350	1300	1200	1350	1300	1400
38. AMPS NEG #2																								
41. HP HIGH SPEED PIN. AFT	146	147	148	148	148	148	148	145	146	146	146					148	147	147	147	145	146	146	146	146
42. HP INTER SPEED PIN FWD	143	143	143	143	143	143	143	142	142	143	143	144	144	144	143	143	143	143	143	143	143	143	143	143
43. HP INTER SPEED PIN AFT	146	147	148	148	148	148	148	145	146	145	145	147	147	147	147	147	147	147	147	145	146	146	146	147
44. L.P. THRUST BEARING	131	132	133	132	132	132	131	131	131	132	132	132	133	133	132	130	130	132	129	131	131	131	131	132
45. H.P. THRUST BEARING	148	148	133	148	148	148	148	146	146	146	146	148	149	150	147	147	147	147	147	146	145	146	146	148
46. LP INTER SPEED PIN. FWD	131	132	134	134	134	130	130	131	132	131	132	132	132	134	132	132	132	132	130	131	132	132	132	133
47. LP HIGH SPEED PIN. AFT	129	130	130	130	130	128	128	128	128	128	128	130	130	131	130	130	130	130	125	128	129	128	128	130
48. LP INTER SPEED PIN FWD	151	151	153	151	151	151	151	152	152	152	152	152	152	154	154	150	150	150	148	152	153	152	152	152
49. LP INTER SPEED PIN. AFT	135	133	137	133	133	133	133	133	133	132	133	136	136	136	136	130	130	130	130	131	135	133	133	135
50. MAIN GEAR ROTOR FWD	115	115	115	115	115	1																		

14ft 4/14/67

April 17th 1967

	TIME	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
1.	L.P. EXHAUST TEMP	101	102	102	240	240	240	238	102	102	103	103	103	103	104	104	235	240	240	240	102	102	102	102	100
2.	MN COND TEMP	79	100	100	100	100	98	98	98	98	48	98	98	100	100	100	100	100	100	98	100	100	98	98	98
3.	MN INJ TEMP	69	70	70	69	69	69	68	68	68	68	68	69	70	72	72	72	72	72	70	70	70	68	68	69
4.	MN OVBD TEMP	79	81	81	80	80	78	78	78	78	78	78	78	80	83	83	82	82	82	80	80	80	78	78	78
5.	L.O. TO COOLERS	127	127	127	126	126	126	126	126	126	126	126	127	127	127	127	126	126	126	126	126	126	127	127	127
6.	L.O. FROM COOLERS	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110	110
7.	THRUST BRG TEMP	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113	113
8.	FWD H.P. ROTOR BRG	123	123	123	120	120	120	120	123	123	120	120	122	122	122	122	120	120	120	122	122	122	122	122	122
9.	AFT H.P. ROTOR BRG	132	132	132	130	130	130	130	130	130	130	130	132	132	132	132	130	130	130	130	130	130	130	130	130
10.	FWD L.P. ROTOR BRG	129	129	129	127	128	127	127	128	128	128	128	128	128	128	128	127	127	127	127	128	128	128	128	128
11.	AFT L.P. ROTOR BRG	125	126	126	124	124	124	124	126	126	125	125	125	125	125	125	125	125	125	125	125	125	125	125	125
12.	HOT GEAR BRG FWD	147	147	147	142	142	142	142	145	145	145	145	147	147	147	147	142	142	142	142	147	147	147	147	148
13.	HOT GEAR BRG AFT	137	137	137	136	136	136	136	135	135	135	135	137	137	137	137	136	136	136	136	137	137	137	137	138
14.	AUX COND TEMP	100	102	103	104	104	104	104	101	101	103	103	101	102	103	103	106	106	106	106	103	103	103	103	103
15.	1ST STAGE AIR TEMP	168	168	168	165	165	165	165	165	165	165	165	167	167	168	168	165	165	165	165	167	167	170	170	168
16.	D.C. HEATER TEMP	237	237	237	236	236	236	236	238	238	238	238	237	237	237	237	236	236	236	238	238	238	238	238	236
17.	SUPRHT TEMP PORT	715	710	710	720	720	720	720	720	720	720	720	720	720	720	720	730	730	730	725	725	730	730	725	725
18.	SUPRHT TEMP STBD	715	710	710	720	720	720	720	720	720	720	720	720	720	720	720	730	725	730	730	725	725	730	730	725
19.	F.O. SETT TEMP P	90	90	90	102	106	106	106	110	110	110	110	100	100	95	95	94	94	102	108	108	108	108	108	105
20.	F.O. SETT TEMP S	100	85	85	85	95	98	100	104	104	106	106	105	105	105	105	106	106	100	104	106	106	104	104	110
21.	UPTAKE PORT	305	310	310	305	310	310	310	300	300	300	300	300	300	300	305	305	310	300	300	305	305	305	310	310
22.	UPTAKE STBD	310	315	315	310	310	310	310	305	305	305	305	305	305	310	310	310	305	310	310	310	310	315	315	315
23.	F.O. PUMP SUCT TEMP	78	100	103	102	112	112	114	116	116	116	116	116	116	116	116	84	84	104	108	116	116	120	120	124
24.	MN FD PMP L.O PORT	32	32	32	32	32	32	32	33	33	33	33	32	32	32	32	32	32	32	32	33	33	33	33	33
25.	MN FD PMP L.O STBD	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28	28
26.	L.O. TO GEARS	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112	112
27.	AIR CONTR L.O. PRESS	29	29	29	29	29	29	29	27	27	28	28	28	28	28	28	29	29	29	29	28	28	28	28	28

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
29. L.O. PRES #1	3	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
28. L.O. PRES #2	4	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
31. L.O. TO COOLER #1	3	133	133	133	132	132	132	132	132	132	132	132	133	133	133	133	132	132	132	130	132	132	132	132	132
34. L.O. TO COOLER #2	4	137	137	137	135	136	137	137	138	138	137	137	137	137	137	137	137	137	137	135	137	137	136	136	136
33. L.O. FROM COOLER #1	3	110	110	110	108	108	108	108	110	110	110	110	110	110	110	110	108	108	108	108	110	110	110	110	110
32. L.O. FROM COOLER #2	4	113	116	116	116	116	116	116	116	116	117	117	117	117	116	116	114	114	114	114	116	116	116	116	117
35. L.O. GOV PRES #1	3	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64	64
34. L.O. GOV PRES #2	4	44	44	44	44	44	44	44	45	45	45	45	44	44	44	44	44	44	44	44	45	45	45	45	44
37. AMS POS #1	3	1050	1100	1100	1250	1150	1100	1200	1150	1150	1200	1200	1150	1150	1150	1150	1200	1200	1250	1200	1150	1150	1050	1050	1000
36. AMS POS #2	4	1000	1050	1050	1050	1000	1100	1500	1200	1200	1100	1100	1100	1100	1100	1100	1200	1250	1150	1150	1050	1050	1100	1100	1000
39. AMS NEG #1	3	1050	1100	1100	1250	1150	1100	1200	1150	1150	1250	1150	1150	1150	1150	1150	1200	1250	1150	1150	1050	1050	1050	1050	1000
38. AMS NEG #2	4	1000	1050	1050	1050	1000	1100	1200	1200	1200	1100	1100	1100	1100	1100	1100	1200	1250	1150	1150	1050	1050	1050	1050	1000
41. HP HIGH SPEED PIN. LET		132	137	137	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136	136
42. HP INTER SPEED PIN FWD		144	144	144	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142	142
43. HP INTER SPEED PIN AFT		136	136	136	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135	135
44. L.P. THRUST BEARING		133	133	133	130	132	130	130	132	132	130	130	132	132	132	132	130	130	130	130	130	130	130	130	132
45. H.P. THRUST BEARING		143	143	143	142	142	142	142	142	142	142	142	143	143	143	143	142	142	142	142	142	142	143	143	143
46. LP HIGH SPEED PIN. FWD		126	126	126	124	124	124	124	125	125	126	126	125	126	126	126	125	125	125	125	126	126	126	126	126
47. LP HIGH SPEED PIN																									

TIME	CIRC WATER	COMPRESSOR 1			COMPRESSOR 2			COMPRESSOR 3			COMPRESSOR 4			COMPRESSOR 5		
	INLET TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP
12:00	82	0	120	95	0	115	94							8	110	94
14:00	83	0	120	95	0	115	93							15	110	94
16:00	84	0	115	98	0	115	95							19	115	95
18:00	82	0	120	97	0	115	93							11	110	94
20:00	82	0	120	97	0	115	94							15	115	94
22:00	83	0	120	98	0	115	95							20	115	95
24:00	83	0	120	97	0	115	93							15	110	96
26:00	84	0	120	98	0	115	94							20	115	96
28:00	83	0	120	97	0	115	94							24	110	94
30:00	83	0	120	98	0	115	94							24	110	94
32:00	83	0	120	97	0	115	93							20	115	94
34:00	84	0	120	98	0	115	95							20	115	94

MAIN REEFER LOG: USNS GEN JOHN POPE (T-AP110)

DATE

COLD STORAGE BOX TEMPERTURES												REMARKS
TIME	ICE CREAM	DAIRY	MEAT	FROZ FOOD	THAW	MEAT	THAW	MEAT	VEG.	BUTT. EGGS	FRUIT	
	1	2	3	4	5	6	7	8	9	10	11	
1200	2	36	2	-2	34	-2	34	5	36	35	36	1200-1600 <i>Intel</i>
1400	3	36	2	-2	30	-4	34	5	37	34	36	1600-2000 <i>Beans</i>
1600	5	36	2	-2	30	-2	34	6	37	35	37	
1800	3	35	3	-2	32	-2	34	5	37	34	37	
2000	3	38	3	-3	26	-4	34	3	37	36	37	2000-2400 <i>Marin</i>
2200	3	36	3	-3	26	-3	34	4	37	36	36	
2400	0	36	3	-3	26	-4	34	3	37	35	36	
0200	0	37	3	-3	27	-4	34	2	37	37	39	0200-0600 <i>Intel</i>
0400	0	36	5	-1	36	-4	36	2	38	39	40	
0600	2	36	4	-1	34	0	37	3	38	39	38	
0800	5	36	4	-2	35	-4	34	10	37	39	39	0800-1200 <i>Beans</i>
1000	3	35	4	-3	35	-3	34	9	37	38	36	1200-1600 <i>Marin</i>
 CHIEF ENGINEER												1800-2400 <i>Marin</i>


 CHIEF ENGINEER

TIME	CIRC WATER	COMPRESSOR 1			COMPRESSOR 2			COMPRESSOR 3			COMPRESSOR 4			COMPRESSOR 5		
	INLET TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP	SUCT PRESS	DISCH PRESS	WATER OUT TEMP
12:00	80	0	120	97	0	115	95							15	110	95
14:00	80	0	115	97	0	115	92							20	110	96
16:00	80	0	115	96	0	115	95							21	115	95
18:00	79	0	110	94	0	115	94							20	110	94
20:00	79	0	115	95	0	115	94							18	110	93
22:00	81	0	115	95	0	115	93							15	115	93
24:00	82	0	120	95	0	115	94							12	110	95
26:00	82	0	115	95	0	115	93							18	115	95
28:00	82	0	120	97	0	115	94							21	115	95
30:00	82	0	120	98	0	115	94							20	115	95
32:00	82	0	115	96	0	115	94							10	110	94
34:00	82	0	120	99	0	115	94							20	110	95

MAIN REEFER LOG: USNS GEN JOHN POPE (T-AP110)

DATE

4/23/67

COLD STORAGE BOX TEMPERATURES											
	ICE CREAM	DAIRY	MEAT	FROZ FOOD	THAW	MEAT	THAW	MEAT	VEG.	BUTT. EGGS	FRUIT
TIME	1	2	3	4	5	6	7	8	9	10	11
1200	0	35	3	-2	32	-2	38	3	37	39	37
1400	0	36	4	-3	35	-3	38	3	37	40	36
1600	10	35	4	-4	32	-3	35	4	37	40	37
1800	0	35	3	-2	30	-3	35	5	37	39	37
2000	0	35	2	-2	28	-2	35	4	37	39	37
2200	1	36	4	-2	28	0	35	3	37	36	37
2400	0	36	4	-2	28	0	34	0	37	36	36
2600	0	36	3	-3	26	-2	34	0	37	34	36
2800	0	36	4	-3	26	-2	34	1	37	36	37
3000	2	35	3	-2	26	-2	34	1	37	36	37
3200	1	36	4	0	32	-2	37	3	37	36	37
3400	2	36	3	-2	32	-2	34	4	36	37	36
3600	2	36	4	-2	36	-1	35	2	36	37	37

REMARKS

1200-1600

Bintef

1600-2000

Beans

2000-2400

Marmos

RETARDED CLOCK 1HR @ 0100

Bintef

1400-1800 Replaced After Solenoid on #3 Walk in BOX

Beans

1800-1200

Marmos

CHIEF ENGINEER

3ND-P&PO 9546

U. S. S.

PLANT NO.

TIME: ZONE DESCRIPTION

SET CLOCKS OR BACK

MINUTES AT

DATE 2-26-67

	HOUR ENDING																							
	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
STEAM TO REG. VALVE, PRESSURE #G	10	10	10	10	10	10	8	8	4	9	9	10	10	10	10	10	10	9	10	10	10	10	10	10
STEAM FROM REG. VALVE, PRESSURE #G	2	2	2	2	2	7	2	3	2	2	2	2	2	2	1	2	2	2	2	2	2	2	2	2
STEAM TO 1ST EFFECT, PRESSURE, "HG OR #G	2	2	2	2"	2"	1"	1"	1	1	1	1	0	0	1	0	2"	2"	2"	2"	✓	✓	✓	✓	✓
STEAM TO 1ST EFFECT, TEMPERATURE, °F	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240
1ST EFFECT COIL DRAIN, TEMPERATURE, °F	195	195	195	200	200	200	200	200	200	200	200	195	195	195	195	200	200	200	198	195	195	195	195	195
1ST EFFECT SHELL PRESSURE, "HG	12	12	12	12"	12"	12"	12"	12	12	12	12	11	11	11	11	13"	13"	13"	13"	12	12	12	12	12
2D EFFECT COIL DRAIN, TEMPERATURE, °F	166	166	166	166	166	166	168	168	168	168	168	170	170	168	168	168	168	168	168	166	166	166	166	166
2D EFFECT SHELL PRESSURE, "HG	15	15	15	15"	15"	15"	15"	15	15	15	15	14	14	14	14	15"	15"	15"	15"	15	15	15	15	15
3D EFFECT COIL DRAIN, TEMPERATURE, °F	156	156	156	156	156	156	158	158	158	158	158	162	162	160	160	156	156	156	158	156	156	156	156	156
3D EFFECT SHELL PRESSURE, "HG	22	22	22	22"	22"	22"	22"	22	22	22	22	22	22	22	22	22"	22"	22"	22"	22	22	22	22	22
CONDENSATE TO COOLER, TEMPERATURE, °F	142	142	142	142	140	140	140	140	140	140	140	140	140	142	142	142	142	142	142	140	140	140	140	140
CONDENSATE FROM COOLER, TEMPERATURE, °F	100	100	100	102	102	102	100	100	100	100	100	100	100	102	102	102	102	102	102	100	100	100	100	100
BRINE OVERBOARD, TEMPERATURE, °F	136	136	136	136	136	136	132	132	132	132	132	136	136	136	136	136	136	136	136	136	136	136	136	136
STEAM TO AIR EJECTOR, PRESSURE, #G	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92
AIR EJECTOR DRAINS, TEMPERATURE, °F																								
CIRC. WATER INJECTION, TEMPERATURE, °F	83	83	83	83	84	84	83	83	83	83	83	84	85	85	85	85	85	85	85	84	82	82	82	82
CIRC. WATER TO CONDENSATE COOLER, TEMPERATURE, °F	83	83	83	83	84	84	83	83	83	83	83	84	85	85	85	85	85	85	85	84	82	82	82	82
CIRC. WATER TO DISTILLER CONDENSER, TEMPERATURE, °F																								
FEED TO AIR EJECTOR CONDENSER, TEMPERATURE, °F																								
FEED TO 2D EFFECT VAP. FD. HEATER, TEMPERATURE, °F																								
FEED TO 1ST EFFECT VAP. FD. HEATER, TEMPERATURE, °F																								
FEED TO 1ST EFFECT, TEMPERATURE, °F	164	164	164	164	166	168	170	170	170	170	170	170	170	170	170	164	164	162	162	164	164	164	164	164
CIRC. WATER OVERBOARD, TEMPERATURE, °F	108	108	108	108	106	104	104	104	104	104	104	108	108	108	108	108	108	108	106	106	108	108	108	108
CIRC. PUMP SUCTION PRESSURE, #G	5	5	5	5	5	4	4	4	4	4	4	5	5	5	5	5	5	5	5	5	5	5	5	5
CIRC. PUMP DISCHARGE PRESSURE, #G	18	18	18	18	18	17	17	17	17	17	17	18	18	18	18	18	18	18	18	18	18	18	18	18
BRINE PUMP SUCTION PRESSURE, #G	22	22	22	23"	23"	22"	23"	23	23	23	23	22	22	22	22	22"	22"	12"	12"	22	22	22	22	22
BRINE PUMP DISCHARGE PRESSURE, #G	34	34	34	40	36	38	35	30	30	30	30	30	30	30	30	42	42	44	44	36	36	36	36	36
FEED PUMP SUCTION PRESSURE, #G																								
FEED PUMP DISCHARGE PRESSURE, #G																								
1ST EFFECT DRAIN PUMP SUCTION PRESSURE, #G	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
1ST EFFECT DRAIN PUMP DISCHARGE PRESSURE, #G	60	60	60	62	60	60	60	60	60	60	64	60	60	60	60	60	60	60	60	60	60	60	60	60
F. W. PUMP DISCHARGE PRESSURE	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
FEED DENSITY, 32NDS																								
BRINE OVERBOARD DENSITY, 32NDS	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.04	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05
AIR EJECTOR DRAINS, SALINITY—E. P. M.	20	20	20	30	30	26	20	20	20	20	20	20	20	20	20	30	20	30	30	20	20	20	20	20
1ST EFFECT DRAINS, SALINITY—E. P. M.	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
CONDENSATE FROM COOLER, SALINITY—E. P. M.																								

4-27-67

#1

4-26-67

DISTILLED WATER RECORD

REMARKS

HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS*	FEED TANKS*
	10831800		
0000			
0100	10842000	1000	
0200	10846000	1000	
0300	10847000	1000	
0400	10848000	1000	
0500	10849700	1100	
0600	10850700	1000	
0700	10851700	1000	1000
0800	10852800		1000
0900	10853200		400
1000	10854100		900
1100	10855000		900
1200	10832800	1000	
1300	10833800	1000	
1400	10834800	1000	
1500	10835800	1000	
1600	10836800	1000	
1700	10837600	800	3
1800	10838600	1000	
1900	10839600	1000	
2000	10840600	1000	
2100	10841600	14,900	1000
2200	10842600		1000
2300	10843600		1000
2400	10844600	→	1000
			8,200

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD

	EFFECT		
	NO. 1	NO. 2	NO. 3
DATE LAST SCALED			
HOURS BROUGHT FORWARD	338		
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	302300		
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			
APPROVED			
(Engineer Officer, U. S. N.)			

0000-0400

#1 - EVAP DIST TO

#3 PORT

ADDED 8 OZ CHLORINE PER 1000 GALS

SIGNED McRoy Hill

0400-0800

#1 Evap. Dist. TO #3 port
 Filled #1 No. 1 Evap. tank, 3/4 can
 @ 0545 Shifted Dist. TO #1 stbd. feed

@ 0745
 #1 port - 2 - Test Drops
 #1 stbd - 2 - Test Drops
 #2 port - 6 - Test Drops
 #2 stbd - 7 - Test Drops

SIGNED R. Sheppard

0800-1200

#1 - EVAP DIST TO

#1 STBD FEED

SIGNED McRoy Hill

1200-1600

#1 - EVAP DIST TO

#3 PORT

ADDED 8 OZ CHLORINE PER 1000 GALS

SIGNED McRoy Hill

1600-2000

#1 Evap. Dist. TO #3 stbd
 Added 8 OZ chlorine per 1000 gals Dist.

SIGNED R. Sheppard

2000-2400

#1 & 2 EVAPS. DIST
 TO #1 STBD FEED

@ 22:00 Shifted Dist
 TO #2 STBD FEED

SIGNED E. A. Magallanes

3ND-P&PO 0546

U.S.S.

PLANT NO.

TIME: ZONE DESCRIPTION

SET CLOCKS BACK

MINUTES AT

DATE _____

SECTION	HOUR ENDING																							
	27-67												26-67											
	0100	0200	0300	0400	0500	0600	0700	0800	0900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400
STEAM TO REG. VALVE, PRESSURE #G	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
STEAM FROM REG. VALVE, PRESSURE #G	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
STEAM TO 1ST EFFECT, PRESSURE, "HG OR #G	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
STEAM TO 1ST EFFECT, TEMPERATURE, °F	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240	240
1ST EFFECT COIL DRAIN, TEMPERATURE, °F	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
1ST EFFECT SHELL PRESSURE, "HG	10	10	10	9"	10"	9"	9"	9	9	9	9	10	10	10	10	10"	10"	10	10"	10	10	10	10	10
2D EFFECT COIL DRAIN, TEMPERATURE, °F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2D EFFECT SHELL PRESSURE, "HG	13	13	13	13"	13"	13"	13"	13	13	13	13	12	12	12	12	13"	13"	13"	13"	13	13	13	13	13
2D EFFECT COIL DRAIN, TEMPERATURE, °F	148	148	148	152	152	152	152	152	152	152	152	148	148	148	148	152	152	152	152	152	152	152	152	152
2D EFFECT SHELL PRESSURE, "HG	18	18	18	18"	18"	18"	18"	18	18	18	18	18	18	18	18	18"	18"	18"	18"	18	18	18	18	18
CONDENSATE TO COOLER, TEMPERATURE, °F	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134	134
CONDENSATE FROM COOLER, TEMPERATURE, °F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BRINE OVERBOARD, TEMPERATURE, °F	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132	132
STEAM TO AIR EJECTOR, PRESSURE, #G	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92	92
AIR EJECTOR DRAINS, TEMPERATURE, °F																								
CIRC. WATER INJECTION, TEMPERATURE, °F	83	83	83	83	84	84	83	83	83	83	83	84	85	85	85	85	85	85	84	82	82	82	82	82
CIRC. WATER TO CONDENSATE COOLER, TEMPERATURE, °F	83	83	83	83	84	84	83	83	83	83	83	84	85	85	85	85	85	85	84	82	82	82	82	82
CIRC. WATER TO DISTILLER CONDENSER, TEMPERATURE, °F																								
FEED TO AIR EJECTOR CONDENSER, TEMPERATURE, °F																								
FEED TO 2D EFFECT VAP. FD. HEATER, TEMPERATURE, °F																								
FEED TO 1ST EFFECT VAP. FD. HEATER, TEMPERATURE, °F	140	140	140	156	140	140	140	140	140	140	140	152	152	152	152	140	140	140	140	140	140	140	140	140
FEED TO 1ST EFFECT, TEMPERATURE, °F	160	160	160	170	160	160	160	160	160	160	160	136	136	136	136	160	160	160	160	160	160	160	160	160
CIRC. WATER OVERBOARD, TEMPERATURE, °F	106	106	106	106	104	104	104	104	104	104	104	108	106	106	106	106	106	106	108	108	108	108	108	106
CIRC. PUMP SUCTION PRESSURE, #G	3	3	3	2	2	2	2	2	2	2	2	3	3	3	3	3	3	3	2	3	3	3	3	3
CIRC. PUMP DISCHARGE PRESSURE, #G	22	22	22	21	20	20	20	20	20	20	20	22	22	22	22	22	22	22	22	22	22	22	22	22
BRINE PUMP SUCTION PRESSURE, #G	23	23	23	20"	20"	24"	25"	25	25	25	25	20	20	20	20	23"	23"	23"	23"	23	23	23	23	23
BRINE PUMP DISCHARGE PRESSURE, #G	30	30	30	30	34	30	30	30	30	30	30	34	34	34	34	30	30	30	30	35	35	35	35	30
FEED PUMP SUCTION PRESSURE, #G	16	16	16	12	14	14	14	14	14	14	14					16	16	16	16	16	16	16	16	16
FEED PUMP DISCHARGE PRESSURE, #G	18	18	18	20	25	23	22	22	22	22	22					22	22	30	25	18	18	18	18	18
1ST EFFECT DRAIN PUMP SUCTION PRESSURE, #G	1	1	1	2	2	2	2	2	2	2	2	0	0	0	0	1	1	1	1	1	1	1	1	1
1ST EFFECT DRAIN PUMP DISCHARGE PRESSURE, #G	52	52	52	52	52	52	52	52	52	52	52	50	50	50	50	52	52	52	52	52	52	52	52	52
F. W. PUMP DISCHARGE PRESSURE	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
FEED DENSITY, 32NDS	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02
BRINE OVERBOARD DENSITY, 32NDS	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02	1.02
AIR EJECTOR DRAINS, SALINITY—E. P. M.	0.2	0.2	0.2	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
1ST EFFECT DRAINS, SALINITY—E. P. M.	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
CONDENSATE FROM COOLER, SALINITY—E. P. M.																								

4/20-67

2

4-26-67

DISTILLED WATER RECORD

REMARKS

HOUR ENDING	METER READING	GALLONS	
		SHIPS TANKS*	FEED TANKS*
	05897700		
0000			
0100	05914800	1200	
0200	05916100	1300	
0300	05917300	1200	
0400	05918600	1300	
0500	05919900	1300	
0600	05921100	1200	
0700	05922300	1200	1200
0800	05923100		800
0900	05923700		600
1000	05924900		1200
1100	05925900		1000
1200	05899000	1300	
1300	05900300	1300	
1400	05901600	1300	
1500	05902700	1100	
1600	05903900	1200	
1700	05905000	1100	?
1800	05906200	1200	
1900	05907400	1200	
2000	05908600	1200	
2100	05909800	18400	1200
2200	05911000		1200
2300	05912300		1300
2400	05913600		1300
			2,800

* Indicate under REMARKS number of tanks being filled.

SCALING RECORD			
DATE LAST SCALED	EFFECT		
	NO. 1	NO. 2	NO. 3
HOURS BROUGHT FORWARD	338		
HOURS THIS DATE			
HOURS TO DATE			
GALLONS BROUGHT FORWARD	404700		
GALLONS THIS DATE			
GALLONS TO DATE			
CHECKED (Signature)			
APPROVED			
(Engineer Officer, U. S. N.)			

0000-0400
1 - EVAP DIST TO
3 PORT
ADDED 102 CHLORINE PER 1000 GALS
SIGNED McRoy Hill

1200-1600
-2- EVAP DIST TO
3 PORT
ADDED 802 CHLORINE PER 1000 GALS
SIGNED McRoy Hill

0400-0800
2 Evap. Dist. to # 3 port
Filled # 2 Hg. Evap Tank, 3/4 can
00545 shift & Dist. to # 1 stbd feed
SIGNED R. Shoppard

1600-2000
2 Evap. Dist. to # 3 stbd
Add. 802 chlorine per 1000 gals dist.
SIGNED R. Shoppard

0800-1200
2 - EVAP DIST TO
1 STBD FEED
SIGNED McRoy Hill

2000-2400
1 & 2 Evaps Dist.
to # - 1 STBD FEED
@ 2200 Shifted Dist.
to # - 2 STBD FEED
SIGNED E. S. Magallan