

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
MACHINERY PARTICULARS							MACHINERY PARTICULARS (CONT'D)						
PRESSURES							TEMPERATURES (CONT'D)						
THROTTLE							AFT. H. P. ROTOR BEARING						
H.P. AHEAD							FORWARD L. P. ROTOR BEARING						
L.P. AHEAD							AFT. L.P. ROTOR BEARING						
VACUUM							HOTTEST GEAR BEARING FORWARD						
L.O. TO TURBINES							HOTTEST GEAR BEARING AFT						
AUX. STEAM							AUX. COND. CONDENSATE						
BACK PRESSURE							1ST STAGE FEED WATER HEATER						
GLAND STEAM							D. C. FEED WATER HEATER						
H.P. BLEEDER							3RD STAGE FEED WATER HEATER						
I.P. BLEEDER													
L.P. BLEEDER													
STEAM AT THROTTLE													
L.P. EXHAUST													
CONDENSATE													
CIRC. WATER IN													
CIRC. WATER OUT													
L.O. TO COOLERS													
L.O. FROM COOLERS													
TEMPERATURE THRUST BEARING													
FORWARD H.P. ROTOR BEARING													

GENERATORS												FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	METER AT NOON	METER PREVIOUS NOON	CONSUMED BY METER	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND
1200 TO 1600	3	1200	440	718	8	158	118		65	1500	1500	2973610	2953680				
1600 TO 2000	4	1200	440	718	9.5	145	122		40	1450	1450						
2000 TO 2400	3	1200	440	722	8	137	118		64	1400	1400						
2400 TO 0400	4	1200	440	722	9.5	145	125		40	1350	1350						
0400 TO 0800	3	1200	440	722	8	137	118		64	1300	1300						
0800 TO 1200	4	1200	440	722	9.5	145	124		40	1500	1500						
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)												L.O. CENTRIFUGE - HOURS OPERATED					
												1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
												4	4	4	4	4	4
												SUMMARY					
												RUNNING TIME	PERCENT OF SLIP				
												DETENTION TIME	BBL FUEL/MI				
												TOTAL REVOLUTIONS	WIND DIRECTION				
												AVERAGE R.P.M.	STATE OF SEA				
												TOTAL MILES BY ENGINE	STATE OF WEATHER				
												TOTAL MILES BY OBSERVATION					

1200-1600 WATCH

Underway, Machinery in service: Boilers: B-3 and 4; Generator, G-3, G-4; Feed Pumps P-3, P-4; F.O. Service Pumps F-3, F-4; Main, Circ, Cond.-MC-3; L.O. Pumps L.O. Purifier Main Air ejector ME-R, D-3 and 4; F.W. Pump W-3, Aux Circ Pump. Pumped settler, Fuel Oil Suction from Outboard settler; Made routine watch tests and inspections of engine room machinery spaces, Changed and cleaned Burners and F.O. Strainers; Added 1 Gal. each to Feed Pumps P-3-P-4; Cond. tested = - .41

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

Underway 18 Nozzles. Machinery as before. Changed & cleaned, burners, F.O. Strainers; Shifted F.O. Settler @ 2245. Made rounds, Tests & Inspections of Machinery & Machinery space. All conditions normal & satisfactory. Pumped bilges & Shaft Alley's Retarded Clock 30 min. at 2300. Complied with Night Standing order's & COMST Instr. 4700.7

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

Underway 18 Nozzles. Machinery as before. Changed & cleaned, burners, F.O. Strainers; Shifted F.O. Settler @ 2245. Made rounds, Tests & Inspections of Machinery & Machinery space. All conditions normal & satisfactory. Pumped bilges & Shaft Alley's Retarded Clock 30 min. at 2300. Complied with Night Standing order's & COMST Instr. 4700.7

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

Underway, Recorded machinery in service; at 0100 Retarded Clock 20 min. Pumped settler Fuel Oil Suction from Outboard settler; Changed and cleaned Burners, Fuel Oil and Lub. Oil strainers; Made routine watch tests and inspections of engine room machinery spaces.

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

Underway 18 Nozzles. Machinery in operation as before. Changed & cleaned F.O. Burner. Retard Clock 20 min. at 0700. Open W.T. Inboard 12 5447. 3-4 on bottom pump that had been pump out waste to bilge. Run bilge purifier to pump to remove water from tank.

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

Underway 18 Nozzles - Mach. as before - Blew tubes P's Boilers @ 0800-0815. Changed and cleaned F.O. Burners F.O. and L.O. Strainers - Tested Fire Alarm @ 1050 - Shifted F.O. Settler to In'bd. @ 1055 - Pumped E.R. and Shaft Alley Bilges - Made rounds tests and inspections of Mach. and space - Complied with Standing and Night orders - COMST Instr. 4700.7. Regular Steaming Watch Routine Mr. Burney, D³/_E Transferring F.O. from #4 P's DB to #4 & DP. Approx. 2000 barl. starting @ 1100. 1st 1/2 ins. space @ 0840. Tested Ahead & Rev. Throttle. Cond. .83 Port B. 6.63 Starb'd B. 7.87

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

F-516 F-526
STB'D W-516 PORT W-526

HOURS HOURS

AKL 3.15 AKL 11.10

T-AKL 11.07 T-AKL 15.12

SAL. 6.63 SAL. 6.63

PHOS. 30 PHOS. 50

R-ph 10.5 R-ph 10.5

SULFITE 30 SULFITE 37.5

CHIEF ENGR'S SIGNATURE-

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
MACHINERY PARTICULARS													
TEMPERATURES													
PRESSURES													
TEMPERATURES													
PRESSURES													
MISCELLANEOUS													
MACHINERY PARTICULARS (CONT'D)													
TEMPERATURES (CONT'D)													
PRESSURES													
MISCELLANEOUS													

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL					
	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL	WATER	BOILER WATER	LUBE OIL	DIESEL OIL	
1200 TO 1600	3	1200	440	728	8	138	118		64	1500	1500	240	METER AT NOON	2992360		ON HAND AT START OF DAY		
	4	1200	440	728	9.5	148	128		40	1450	1450	240	METER PREVIOUS NOON	2973610		EVAPORATED OR RECEIVED		
1600 TO 2000	3	1200	440	730	8	140	121		64	1500	1500	240	CONSUMED BY METER			ON HAND		
	4	1200	440	730	9.5	146	128		40	1450	1450	240	ON HAND AT START OF DAY			CONSUMED		
2000 TO 2400	3	1200	440	730	8	140	120		64	350	1350	240	RECEIVED DURING DAY			ON HAND AT START OF DAY		
	4	1200	440	730	9.5	145	127		40	1350	1350	240	EXPENDED DURING DAY			RECEIVED		
2400 TO 0400	3	1200	440	718	8	138	118		64	1500	1500	240	REMAINING ON BOARD			ON HAND		
	4	1200	440	718	9	148	128		40	1400	1400	240	ON HAND AT START OF DAY			CONSUMED		
0400 TO 0800	3	1200	440	725	8	140	123		64	1600	1600	240	EVAPORATED OR RECEIVED			DIESEL OIL		
	4	1200	440	725	9.5	146	127		40	1550	1550	24	ON HAND			ON HAND		
0800 TO 1200	3	1200	440	725	8	140	122		64	1600	1600	240	CONSUMED			CONSUMED		
	4	1200	440	725	9.5	148	131		40	1600	1600	240	LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)					
L.O. CENTRIFUGE - HOURS OPERATED																		
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200												
	4	4	4	4	4	4												
SUMMARY																		
RUNNING TIME												PERCENT OF SLIP						
DETENTION TIME												BBL FUEL/MI						
TOTAL REVOLUTIONS												WIND DIRECTION						
AVERAGE R.P.M.												STATE OF SEA						
TOTAL MILES BY ENGINE												STATE OF WEATHER						
TOTAL MILES BY OBSERVATION																		

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers-B-3, B-4 and aux.; Generators-G-3-G-4; and aux.; Main, Circ. Cond. A-3, Lub. Oil, and Air ejector ME-R; Lub Oil Purifier Portable water Pump W-3; Changed and cleaned Burner and Fuel Oil Strainer; Added 1 gal each Feed Pumps R-3 and P-4; Made routine watch tests and inspections of engine room machinery spaces

Cond tested = .41

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES. MACHINERY IN OPERATION AS BEFORE. PUMPED TUBES IN B-3 & B-4 - P-3 ON BOTTOM BLOW THRU M.U.F. EVAP. CHANGED & CLEANED F.O. BURNER. CLEAN F.O. FUEL STRAINER. B-4 ON BOTTOM BLOW THRU M.U.F. EVAP. ADD COMPOUND TO B-3 & B-4. COMPLIED WITH NIGHT STANDING ORDERS & HANST'S INSTR.

#2 M.F.P. = 151-0

FUEL ON P-3

#2 M.F.P. = 22-0

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

Underway 18 Nozzles. Machinery in operation as before. Changed Change Burner's, F.O. discharge strainers, Gen L.O. strainers, Pumped Bilges & Shaft Alloys. Made rounds tests & inspect. of machinery & watch space conditions. Retarded clock 20 min. at 2300, pump in board & outbd. F.O. Settler's from #5 P/B AB & #5 & Tanks. Complied with night standing orders & HANST'S INSTR. 4700-7. Cond. 141 SB. 8.29 PB 7.87

Regular Underway Steaming Watch Routine

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

Underway, Recorded machinery in service; at 0100 retarded clock 20 min., Pumped settlers, Fuel Oil Suction from In board settler, Changed and cleaned Burner F.O. and Lub. Oil strainers. Made routine watch tests and inspections of engine room machinery spaces

Cond tested = -.41

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. W.T. DOORS OPEN. RETARD CLOCK 20 MIN @ 0500. CHANGE & CLEAN #5 F.O. BURNER. CLEAN F.O. FUEL STRAINER. B-4 ON BOTTOM BLOW THRU M.U.F. EVAP. ADD COMPOUND TO B-3 & B-4. COMPLIED WITH NIGHT STANDING ORDERS & HANST'S INSTR.

#2 M.F.P. = 151-0 - .41% MAIN COND = .41%

#2 M.F.P. = 22-0 - .41% FUEL ON P-3

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

UNDERWAY 18 NOZZLES - MACH. AS BEFORE - CHANGED & CLEANED F.O. BURNERS - BLEW TUBES P/B @ 0800-0818 - 1ST/AE IN SPACE @ 0835 - FIRE ALARM TESTED @ 0915 - CHANGED AND CLEANED L.O. STRAINERS ON #3 & #4 GEN. - SHIFTED F.O. SETTLER TO OUTBD @ 0948 - SMOKE DETECTOR TESTED @ 0955 - 1010 BOTTOM BLOW FROM PORT BOILER THRU M.U.F. EVAP. SECURED PORT BOILER BLOW @ 1130 (5.349/6) - PUT STARBD BOILER ON BOTTOM BLOW @ 1130 - PUMPED E.R. AND SHAFT ALLEY BILGES - MADE ROUNDS AND INSPECTIONS OF MACH. & SPACE - COMPLIED WITH NIGHT STANDING ORDERS & HANST'S INSTR. 4700-7

COND. 83 P.B. 12.01 STRB B. 11.19

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
P-540	W-520
HOURS 4-540	HOURS W-120
AKL 6.42	AKL 7.01
T-AKL 11.10	T-AKL 11.67
SAL. 7.87	SAL. 7.46
PHOS. 30	PHOS. 50
R.ph 10	R.ph 10.5
SULFITE 12.5	SULFITE 26

CHIEF ENGR'S SIGNATURE-

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME	240	240	240	240	240	240	MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING	138	137	136	136	136
DETENTION TIME								FORWARD L. P. ROTOR BEARING	125	125	132	125	133
REVOLUTION COUNTER (END OF WATCH)	3042	3044	3046	3049	3051	3053	TEMPERATURES (CONT'D)	AFT. L.P. ROTOR BEARING	130	137	130	130	130
TOTAL REVOLUTIONS (FOR WATCH)	21710	21860	22060	22010	22010	22090		HOTTEST GEAR BEARING FORWARD	146	145	148	148	146
AVERAGE RPM	905	910	920	917	917	920	PRESSURES	HOTTEST GEAR BEARING AFT	135	140	140	140	140
F.O. METER (END OF WATCH)	1499	1299	1900	1300	1300	1301		AUX. COND. CONDENSATE	164	122	122	120	120
F.O. CONSUMED	3070	3050	3030	3050	3040	3040	TEMPERATURES	1ST STAGE FEED WATER HEATER	175	175	178	175	178
PRESSURES	THROTTLE	422	425	425	424	425		O. C. FEED WATER HEATER	238	238	238	238	238
	H.P. AHEAD	418	420	420	420	420	PRESSURES	3RD STAGE FEED WATER HEATER	135	135	135	135	135
	L.P. AHEAD	26	26.5	26.5	26.5	26.5		F.O. TO BURNERS	182	175	170	178	180
	VACUUM	27.8	27.1	28.5	28.2	28		F. O. BACK PRESSURE					
	L.O. TO TURBINES	12.5	12.5	12.5	12.5	12.5	TEMPERATURES	AIR TO FURNACE	5.7	5.7	5.8	6.6	6.6
	AUX. STEAM	140	140	145	145	145		UPTAKE					
	BACK PRESSURE	9	9	9	9	9	PRESSURES	MAIN STEAM	440	440	440	440	440
	GLAND STEAM	2	1.8	2.0	2	2		SUPER HEAT	720	725	725	725	725
	H.P. BLEEDER	60	60	60	60	60	TEMPERATURES	F.O. TO BURNERS	180	180	180	180	180
	I.P. BLEEDER	5.2		5.5	5.2			F.O. TEMP. IN SETTLING TANKS	116	116	116	112	112
TEMPERATURES	L.P. BLEEDER		5.8	10		5.8	PRESSURES	PORT BOILER UPTAKE	315	320	320	320	315
	STEAM AT THROTTLE	720	725	725	723	725		STBO. BOILER UPTAKE	320	325	310	310	305
	L.P. EXHAUST	120	120	118	118	118	TEMPERATURES	ENGINE ROOM TEMPERATURE	100	97	97	97	99
	CONDENSATE	110	112	114	110	112		FIRE ROOM TEMPERATURE	100	97	97	97	99
	CIRC. WATER IN	80	85	84	84	84	TEMPERATURES	NOZZLES IN USE	18	18	18	18	18
	CIRC. WATER OUT	92	93	94	92	94		NO. OF BURNERS IN USE	6	6	6	6	6
	L.O. TO COOLERS	126	128	128	126	127	TEMPERATURES	BURNER TIP SIZE	5/55	5/55	5/55	5/55	5/55
	L.O. FROM COOLERS	110	110	110	110	110		CO2 % PORT BOILER					13.5
	TEMPERATURE THRUST BEARING	118	118	118	115	118	TEMPERATURES	CO2 % STBD. BOILER					14.0
	FORWARD H.P. ROTOR BEARING	135	125	123	123	124		OIL LEVEL MAIN SUMP	1.4	1.5	1.4	1.4	1.4

GENERATORS													FUEL - WATER AND LUBE OIL									
WATCH	GENERATOR NUMBER	R. P. M.	STEAM PRESSURE	STEAM TEMP.	L. O. PRESSURE	L. O. TO COOLER	L. O. FROM COOLER	TEMP. OF HOTTEST BEARING	L. O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		DOMESTIC WATER		LUBE OIL		ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND	CONSUMED
													METER AT NOON	METER PREVIOUS NOON	CONSUMED BY METER	ON HAND AT START OF DAY	RECEIVED DURING DAY	EXPENDED DURING DAY				
1200 TO 1600	3	1200	440	710	8	140	120		65	1500	1500	240										
	4	1200	440	710	9.5	148	132		40	1450	1450	240										
1600 TO 2000	3	1200	440	725	8	141	124		64	1450	1450	240										
	4	1200	440	725	9.5	148	131		40	1350	1350	240										
2000 TO 2400	3	1200	440	725	8	140	122		64	1350	1350	240										
	4	1200	440	725	9.5	147	130		40	1350	1350	240										
2400 TO 0400	3	1200			8	140	120		65	1350	1350	240										
	4	1200			9.5	148	128		40	1300	1300	240										
0400 TO 0800	3	1200	440	725	8	140	122		64	1450	1450	240										
	4	1200	440	725	9.5	147	130		40	1400	1400	240										
0800 TO 1200	3	1200	440	725	8	140	122		64	1500	1500	240										
	4	1200	440	725	9.5	147	129		40	1500	1500	240										

L. O. CENTRIFUGE - HOURS OPERATED					
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
4	4	4	4	4	4

SUMMARY		
RUNNING TIME		PERCENT OF SLIP
DETENTION TIME		BBL FUEL/MI
TOTAL REVOLUTIONS		WIND DIRECTION
AVERAGE R. P. M.		STATE OF SEA
TOTAL MILES BY ENGINE		STATE OF WEATHER
TOTAL MILES BY OBSERVATION		

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers B-3-B4 and aux.; Generator-G-3-G-4 and aux.; Main Circ. Cond. MC-3; Lub. Oil Pumps and Air Ejector. ME-R; Aux. Circ. Pump; Lub. Oil Purifier. Changed and cleaned Burner and F.O. Strainer. at 1515 A.B.C. Drill Stand by at 1527 Secured from Drill and from Standby. Pumped settlers. Fuel Oil Suction from inboard settler. Made routine watch tests and inspections of engine room machinery spaces.

Cond tested = -.41

WATCH ENGR'S SIGNATURE-

Harold F. DuMond

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. BLANK TESTS IN B-3 & B-4. CLEANED & TESTED STRAINER. CLEAN #5 F.O. BURNER. CLOSURE #1 & #2 W.T. DOORS. CLOSURE FROM BRIDGE. BLOW P-3 B-TL. BLOW THRU M.U. EVAP. CLEARED MAKES ROUNDS EVERY 15 MIN. P-4 CO. P-TL. BLOW THRU M.U. EVAP. ADD COND. TO B-4. COND. WITH LEASTS 4700.7. PUMP BILGES.

M.U. EVAP. = 5-1-10 - 1-1-10

M.U. EVAP. = 5-1-10 - 1-1-10

WATCH ENGR'S SIGNATURE-

H. R. R. R.

2000-2400 WATCH

Underway 18 Nozzles in oper. as before. Changed & cleaned burners. Re-discharge strainer's. Re-w. L.O. Strainer's. Shifted F.O. Settler's at 2300. Made rounds every half hr. on spring bearings. Make round tests & inspections of mach. space & mach. All conditions normal. Broke cooling water union on #6 spring bearing to bring down bearing temp. Complied with Night & Steaming order's & COMST Instr. 4700.7. Cond. #1 F.O. 6.21 Star. B. 5.80. Regular Routine Steaming Watch.

WATCH ENGR'S SIGNATURE-

H. R. R. R.

2400-0400 WATCH

Underway, Recorded Machinery in service: Pumped settlers. Fuel Oil Suction from outboard settler. Changed and cleaned burner, Fuel Oil and Lub. Oil Strainers. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested = .41

WATCH ENGR'S SIGNATURE-

Harold F. DuMond

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. CHANGE & CLEAN #5 F.O. BURNER. CLEAN F.O. SETT. STRAINER. MAKE ROUNDS ON SPRING BEARINGS EVERY 15 MIN. - P-4 CO. P-TL. BLOW THRU M.U. EVAP. ADD COND. TO B-4. COND. WITH LEASTS 4700.7. PUMP BILGES.

M.U. EVAP. = 21-0 - 1-1-10

M.U. EVAP. = 22-0 - 1-1-10 MAIN COND. = 41/10

WATCH ENGR'S SIGNATURE-

H. R. R. R.

0800-1200 WATCH

Underway 18 Nozzles mach. as before. Changed & cleaned burners. Strains L.O. & F.O. Chg'd 4 1/2" 1/2" ins. proc. 0855. Tested Ship's Fire Alarm. 0915, 0925 Tested Smoke detector, made rounds, tests & inspections all-normal. made half-hourly rounds on all spring bearing, all OK.

Cond. #1 R. 7.57 S. 5.87

Regular Routine Steaming Watch Routine

WATCH ENGR'S SIGNATURE-

H. R. R. R.

CHIEF ENGINEER

BOILER WATER READINGS

STB'D

PORT

HOURS

HOURS

AKL

AKL

T-AKL

T-AKL

SAL.

SAL.

PHOS.

PHOS.

R.ph

R.ph

SUMP 42.5

CHIEF ENGR'S SIGNATURE-

H. R. R. R.

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers B-3-B-4 and aux. Generator G-3-4 and aux.; Main Circ., Cond. M.C-3, Lub. Oil Pumps, and Air Ejector M.E-R; Pot. Water Pump W-3; Lub. Oil Purifier, Pumped Aux Circ. Pump; Pumped Settlers, Fuel Oil Suction from inboard settler. Added 3 gals. lub. Oil to Port, and 1 gal. to Stbd. Feed Pumps. Made routine watch tests and inspections of engine room machinery spaces. Changed and cleaned Burner and F.O. Strainer.

Cond tested = .41

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. BLOW TUBES IN B-3 + B-4. CHANGED + CLEANED F.O. BURNER. CHANGED F.O. SUCT. STRAINER. B-3 ON BOIL. BLOW THRU M.E. VALVE - MADE HALF HR. ROUNDS ON SIGNAL. PAINT. CLOSE. #2 W.T. PUMP @ 1254 P. ORDERED TERRAPIN. ADD LUB. OIL TO CHY. TANK.

MUF #2-S = 21'-5" N19°E

MUF #2-P = 22'-0" N19°E

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

Underway 18 Nozz. MACH. AS BEFORE Shifted F.O. Settlers at 2000 Shifted F.W. Suction at 2030 F.W. Suction on #3 P, distilling to #34. Changed + cleaned Burner's, F.O. discharge strainer's, Gen. L.O. strainer's, Made half-hourly rounds on Spring bearing, OK; made rounds, tests + inspections all conditions normal. Complied with Night + Standing order + COMSTS Instr. #700.7 Carried out Regular underway steaming watch Routine. Retired Clock 20 min @ 2300

Cond. 41 P.B. 8.70 S.B. 8.70

WATCH ENGR'S SIGNATURE

2400-0400 WATCH

Underway, Recorded machinery in service; Pumped settlers, Fuel Oil suction from Outboard settler, Added 1 gal. each P's Feed Pumps. Changed and cleaned burner, F.O. and Lub. Oil Strainers, Made routine watch tests and inspections of engine room machinery spaces

Cond tested = .41

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. CHANGED + CLEANED F.O. BURNER. CLEAN F.O. SUCT. STRAINER. RETARD CLOCK 20 MIN @ 0500. F.O. SPILL ON DECK OUTSIDE MAIN DIVISION. P.M. @ 0520. MIDJOURNEY TOOK HEAD OFF TO TANK #1 P. CALLED MEERS TO CLEAN DECK. THERE. SCUM IN BOWL OF SPRING BEARING. CHANGED OIL ON POT. WATER TO STBD. P. FILL TO #3 PORT. COMPLY WITH COMSTS #700.7 PUMP BILGES.

MUF #2-S = 22'-0" N19°E

MUF #2-P = 22'-0" N19°E

MAIN COND. 41

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

Underway 18 Nozz. Machinery as before Blow tubes 0800-0820 Changed + cleaned L.O. Gen. strainer's, Changed + cleaned F.O. discharge strainer's + Burner's. Tested smoke detector system @ 0901, + fire alarm at 0859. P. Boiler on cautious Bottom blow from 0900-1015 thru M.U.F.E. and switched to Stbd. Boiler at 1016. Made half-hourly rounds of Spring bearing, and rounds, Tests + inspections of mach. + spaces. Conditions normal. Complied with Standing orders + COMSTS Instr. #700.7 1st Lt. inspection at 0900. Carried out Reg. underway steaming watch Routine

CHIEF ENGINEER

Cond. 41 P.B. 6.63 S.B. 7.11

WATCH ENGR'S SIGNATURE

BOILER WATER READINGS

STB'D	PORT
HOURS 5:58	HOURS 5:16
AKL 8.76	AKL 7.68
T-AKL 11.65	T-AKL 17.52
SAL. 2.29	SAL. 2.29
PHOS. 30	PHOS. 30
R.ph 11	R.ph 11
S. F. 40	S. F. 40

CHIEF ENGR'S SIGNATURE

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers B-3-B4 and aux.; Generator-G-3-G-4 and aux.; Main Circ. Cond. MC-3; Lub. Oil Pumps and Air Ejector. ME-R; Aux. Circ. Pump; Lub. Oil Purifier. Changed and cleaned Burner and F.O. Strainer. at 1515 A.B.C. Drill Stand by at 1527 Secured from Drill and from Standby. Pumped settlers. Fuel Oil Suction from inboard settler. Made routine watch tests and inspections of engine room machinery spaces.

Cond tested = -.41

WATCH ENGR'S SIGNATURE-

Harold F. DeMond

1600-2000 WATCH

UNDERWAY ON 12 NOZZLES. MACH. IN OPERATION AS BEFORE. MADE TESTS IN B-3 & B-4. CLEANED #5 F.O. PUMP. CLEAN #1 & #2 W.T. DOORS ORDER FROM BRIDGE. BLOW #3 B.T. PUMP TANK. M.U. EVAP. CYLER MAKES ROUNDS ON SPRING BEARINGS EVERY HALF HR. B-3 SAL = 4.97 - B-4 SAL = 5.31 - ADD COND. V2 TO B3. MUF #2 = 3 - 22 - 0 - 4.95

WATCH ENGR'S SIGNATURE-

H. R. Sten

2000-2400 WATCH

Underway 18 Nozzles in op. as before. Changed & cleaned burners, Re-discharge strainers, Re-w L.O. Strainer's, Shifted F.O. Settler's at 2300 made rounds every half hr. on spring bearings. Made round tests & inspections of mach. space & mach. All conditions normal. Brake cooling water union on #6 Spring bearing to bring down bearing temp. Complied with slight & standing orders & COMST'S Instr 4700.7. Cond. #1 F.B. 6.21 Star. B. 5.80 Regular Routine Steaming Watch.

WATCH ENGR'S SIGNATURE-

D. L. Puckett

2400-0400 WATCH

Underway, Recorded Machinery in service. Pumped settlers. Fuel Oil Suction from outboard settler. Changed and cleaned burner, Fuel Oil and Lub. Oil Strainers. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested = .41

WATCH ENGR'S SIGNATURE-

Harold F. DeMond

0400-0800 WATCH

UNDERWAY ON 12 NOZZLES. MACH. IN OPERATION AS BEFORE. CHANGED & CLEANED #5 F.O. PUMP. CLEANED F.O. SUMP STRAINER. MADE ROUNDS ON SPRING BEARINGS EVERY HALF HR. - B-4 ON B.T. PUMP TANK. M.U. EVAP. AND COND. TO B-4. COMPLY WITH COND. 4700.7. P.S.P. B-3.

MUF #2 = 3 - 21 - 0 - 4.95

MUF #2 = 3 - 22 - 0 - 4.95 MAIN COND = 4.95

WATCH ENGR'S SIGNATURE-

H. R. Sten

0800-1200 WATCH

Underway 18 Nozzles mach. as before. Changed & cleaned burners. Strainers L.O. & F.O. Checked 12" 1/2" inspection at 0835. Tested Ship's Fire Alarm at 0915, 0925 Tested Smoke detector, made rounds, Tests & inspections all-normal. made half hourly rounds on all spring bearing, all ok.

Cond. #1 P. 7.57 S. 5.29

Regular Underway Steaming Watch Routine

WATCH ENGR'S SIGNATURE-

D. L. Puckett

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS F-564	HOURS F-344
N-564	N-344
AKL 11.68	AKL 7.57
T-AKL 12.42	T-AKL 12.35
SAL. 4.61	SAL. 6.03
PHOS. 30	PHOS. 30
R.ph 11.6	R.ph 11.6

Submer 42.5 SURFITE 2.8

CHIEF ENGR'S SIGNATURE-

D. L. Puckett

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers B-3-4 and aux.; Generators G-3-4 and aux.; Main. Circ. M-2; Cond. M.C-3, Lub. Oil Pumps and Air Ejector ME-R; Aux Circ. Pump. F.W. Pump W-3; Lub. Oil Purifier. Pump Settlers. Fuel Oil suction from in board settler. Cleaned and changed Burners and F.O. Strainers. Abandon Fire and Emery Drill, Stand by 1515. 1520 Fire Pump on line; 1525 secured Fire and Emery Drill, Abandon Ship Drill, secured Fire Pump. 1532 Secured from all Drills and secured from standby. Made routine watch tests and inspections of engine room Cond tested. .41 Boiler both. H. 14. machinery spaces. WATCH ENGR'S SIGNATURE: *Harold J. Du Mond*

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES. MACHINERY IN OPERATION AS BEFORE. BLOW TUBES IN B-3 + B-4. CLEAN F.O. SUCT. STRAINER CHANGE + CLEAN #5 F.O. BURNER. B-3 + B-4 ON BOTTOM BLOW THRU M.V. EVAP. ADD COMPOUND TO B-3 + B-4. CLOSE #1 + #2 W.T. DOORS, ORDERS FROM BRIDGE. MAKE ROUTINE INSPECTIONS COMPLY WITH COMSTS #4700.7 KEEP BILGES IN SAFE LEVEL. SAL. TEST @ 1930 = S. 4.44 % P. 4.56 % MUF #2 S = 22'-0" = .41 F.O. SUCT. ON D.B.

2000-2400 WATCH

MUF #2 - P = 22'-0" = .41. MAIN COND. .41 WATCH ENGR'S SIGNATURE: *J. Karsten*
UNDERWAY 18 NOZZLES - MACH. AS BEFORE - CHANGED AND CLEANED F.O. BURNERS - CHANGED AND CLEANED L.O. STRAINERS ON #3 AND #4 AUX. GEN. SHIFTED F.W. SUCTION FR. #3 PORT TO #3 STARBOARD - SHIFTED F.W. DISTILLED FR. #3 STARBOARD TO #3 PORT @ 2000 - HELD ENG. CASUALTY DRILL B-3 (LOSS OF FEED PUMP SUCTION) - BRIDGE INFORMED - 4 MEN PRESENT - PUMPED E.R. BILGES AND SHAFT ALLEY - MADE ROUTINE TESTS AND INSPECTIONS OF MACH. SPACE - COMPLIED WITH STANDING AND NIGHT ORDERS - COMSTS INSTR. 4700.7 - REG. STEAMING WATCH ROUTINE - COND. .41 P. 4.21 S. 5.39 Shifted F.O. Strainers @ 2132 WATCH ENGR'S SIGNATURE: *D. L. Prickett*

2400-0400 WATCH

Underway, Recorded machinery in service; Held Eng. Casualty Drill instruction B-3 Loss of Feed Pump suction, 4 Men Present 0130-0200; Pumped settlers, Fuel Oil Suction from Outboard settler. Changed and cleaned Burner, F.O. and Lub. Oil strainers; Made routine watch tests and inspections of engine room machinery spaces. Added 1 gal. each #1's Feed Pumps.

Cond tested .41

WATCH ENGR'S SIGNATURE: *Harold J. Du Mond*

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. HELD CASUALTY DRILL (LOSS OF FEED PUMP SUCT.) B-3. - BRIDGE INFORMED 0500-0530. - 4 MEN PRESENT. CHANGE + CLEAN #6 F.O. BURNER CLEAN F.O. SUCT. STRAINER. TEST STAY F.O. Pump. COMPLIED WITH STANDING AND NIGHT ORDERS - COMSTS INSTR. #4700.7.

MUF #2 S = 23'-0" = .41 % SUCT. ON D.B.

MUF #2 P = 23'-0" = .41 % MAIN COND. = .41

WATCH ENGR'S SIGNATURE: *J. Karsten*

0800-1200 WATCH

Underway 18 NOZZLES machinery as before. Blew tubes 1st boiler's 0800-0820, tested fire & smoke detecting systems from bridge and fire alarm from 0900-0920. Changed & cleaned burner's F.O. discharge strainer, L.O. (gen.) strainer's. Shifted Potable water section at 0800 to 3P distilling to #3 ^{PORT} ~~STARBOARD~~ pump. Made half hourly check of spring bearings. Made rounds, tests & inspection of machinery & space. pumped bilges & shaft alley's. All conditions normal. Add (4) four gal L.O. to #8 feed Pump. Carried Out Reg. underway steaming watch Routine.

COND. .41 P. B. 5.80 SB 5.34

WATCH ENGR'S SIGNATURE: *D. L. Prickett*

CHIEF ENGINEER

BOILER WATER READINGS

STB'D PORT
HOURS # - 412 F - 392
W - 412 HOURS W - 392

AKL 10.51 AKL 11.68

T-AKL 16.35 T-AKL 18.69

SAL. 4.14 SAL. 4.56

PHOS. 40 PHOS. 50

R. ph 11 R. ph 11

SULFITE 45 SULFITE 50

CHIEF ENGR'S SIGNATURE: *L. L. Clemens*

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers - B-3-4 and aux., Generator G-3-4 and aux.; Main Circ M-2, Cond. MC-3, Lub Oil pumps and Air ejector. ME-R. Aux. Circ Pump; Lub Oil Purifier. Pumped settlor, Out board settlor is F.O. Suction. Added 1 gal. each P/O Feed Pumps. Changed and cleaned Burners and F.O. strainer. Made routine watch tests and inspections of engine room machinery space - also F.W. Pump W-3 in service. Secured No 2 Evap at 1540.

Cond. tested = .41

WATCH ENGR'S SIGNATURE

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. BLOW TUBES IN B-3 + B-4. CHANGE + CLEAN #5 F.O. BURNER. CLEAN F.O. SUCT. STRAINER 1735 START AIR COMPRESSOR. SECURE #1. MAKE HALF HR. ROUND ON SPRING BEARINGS. SAL. TESTS: B-3 = 7.0 % + B-4 = 5.8 %. CLOSE #1 & #2 W.T. DOORS. ORDERS FROM BRIDGE.

MUF #2 - S = 21'-0" SUCT. ON PB.

MUF #2 - P = 22'-0"

WATCH ENGR'S SIGNATURE

2000-2400 WATCH

Underway 18 NOZZ. Machinery as before except as follows split out main Aux. plant's. at 2200 ON TIC line Aux. Air ejector's, Aux. Condensate pump. made half-hourly checks of spring bearings, Changed burner's + F.O. discharge strainer's + L.O. strainer's pumped bilges + shaft alley's. Complied with night distilling order's + comets 4700.7. All conditions normal & satisfactory. Shifted F.W. Suct. to #3 Purifier to #3 S.

Cond. 41 PB. 7.87 SB. 7.04

2400-0400 WATCH

Underway, Recorded machinery in service: S.S. Air Compressor operated by hand will not start on auto.; Pumped settlers, Fuel Oil Suction from inboard settler. Changed and cleaned burner & Fuel Oil and Lub Oil strainers. Made routine watch tests and inspections of engine room machinery spaces. Added 3 gals. each P/O Feed Pumps - Lub Oil.

Cond. tested = .41

WATCH ENGR'S SIGNATURE

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES. MACH. IN OPERATION AS BEFORE. CLOSE W.T. DOORS 0437 ARRIVAL @ 0630 F.O.M.P. = 4591500 CNTR. P = 30908070
BELLS PER BELL BOCK. F.O.M.S. = 8470340 CNTR. S = 32124050
F.W.E. @ 0741 F.O.M.P. = 4591810 CNTR. P = 30910440
F.O.M.S. = 8470640 CNTR. S = 32126570

WATCH ENGR'S SIGNATURE

0800-1200 WATCH

IN PORT WATCH BUNKER BAY OKINAWA - CHANGED AND CLEANED F.O. BURNERS AND DISCHARGE STRAINERS - SHIFTED F.W. SUCTION AND DISTILLING @ 0800 - SUCTION ON #3 PORT - DISTILLED TO #3 STBD. TAKING F.W. FROM PIER @ 0805. OPENED HIGH AND SEC'D L.O. SEA INJECTION. Pumped Bilges down to a safe level - MADE ROUNDS TESTS AND INSPECTIONS OF MACH. AND SPACE - REG. ROUTINE SEA WATCH IN PORT - Complied with COMSTS INSTE. 4700.7.

FUT - McLeod Oiler - Taitague

WATCH ENGR'S SIGNATURE

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS F-636	HOURS F-416
M-436	M-416
AKL 9.34	AKL 11.10
T-AKL 14.60	T-AKL 16.95
SAL. 6.43	SAL. 7.04
PHOS. 30	PHOS. 50
R.ph 11	R.ph 11

SULFITE - 37.5 SULFITE

CHIEF ENGR'S SIGNATURE

USNS Gen John Pope (TAP 110) VOYAGE NO. FROM San Diego, Calif. TO Okinawa TYPE OF VESSEL DATE 7-22-67

		WATCH								WATCH						
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200	
RUNNING TIME			46	260	260	240	240	MACHINERY PARTICULARS (CONT'D)	TEMPERATURES (CONT'D)	AFT. H. P. ROTOR BEARING						
DETENTION TIME										FORWARD L. P. ROTOR BEARING						
REVOLUTION COUNTER (END OF WATCH)			3091	3094	3096	3098	3100			AFT. L. P. ROTOR BEARING						
TOTAL REVOLUTIONS (FOR WATCH)			6890	0146	3740	7410	9350			HOTTEST GEAR BEARING FORWARD						
AVERAGE RPM			77.6	89.4	90.8	91.0	91.4			HOTTEST GEAR BEARING AFT						
F.O. METER (END OF WATCH)		1306	1306	1306	1307	1307	1307			AUX. COND. CONDENSATE						
F.O. CONSUMED		620	1670	3050	3060	3160	2990			1ST STAGE FEED WATER HEATER						
										D. C. FEED WATER HEATER						
										3RD STAGE FEED WATER HEATER						
MACHINERY PARTICULARS	PRESSURES	THROTTLE		430	420	418	420	420	BOILER PARTICULARS	TEMPERATURES	F.O. TO BURNERS					
		H.P. AHEAD		425	418	414	415	415			F. O. BACK PRESSURE					
		L.P. AHEAD		21	25	25	25	25			AIR TO FURNACE					
		VACUUM	26.5	28	28.25	27.7	27.7	27.5			UPTAKE					
		L.O. TO TURBINES	13.5	12.75	12.7	12.6	12.7	12.7			MAIN STEAM					
		AUX. STEAM	150	150	150	150	150	152			SUPER HEAT					
		BACK PRESSURE	9	9	9	9	9	9			F.O. TO BURNERS					
		GLAND STEAM	2	2	1.5	1.5	1.5	1.5			F.O. TEMP. IN SETTLING TANKS					
		H.P. BLEEDER		70	70	70		60			PORT BOILER UPTAKE					
		I.P. BLEEDER		5.5	5.5	5.5	5.8	5.2			STBD. BOILER UPTAKE					
L.P. BLEEDER			10"			10"	ENGINE ROOM TEMPERATURE									
MACHINERY PARTICULARS	TEMPERATURES	STEAM AT THROTTLE			735	722	722	720	MISCELLANEOUS	FIRE ROOM TEMPERATURE						
		L.P. EXHAUST		5	120	120	121	120		NOZZLES IN USE						
		CONDENSATE	98		116	116	118	118		NO. OF BURNERS IN USE						
		CIRC. WATER IN	86	150	88	88	88.9	88		BURNER TIP SIZE						
		CIRC. WATER OUT	88		98	100	99	100		CO ₂ % PORT BOILER						
		L.O. TO COOLERS	115		128	128	128	128		CO ₂ % STBD. BOILER						
		L.O. FROM COOLERS	110		110	110	110	110		OIL LEVEL MAIN SUMP						
		TEMPERATURE THRUST BEARING			120	120	118	120								
		FORWARD H.P. ROTOR BEARING			127	127	127	128								

GENERATORS										
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE
1200 TO 1600	3	1200	440	720	8	140	120		60	1300
	4	1200	440	720	9.5	148	132		40	1200
1600 TO 2000	3	1200	440	720	8	140	120		60	1300
	4	1200	440	720	9.5	148	132		40	1300
2000 TO 2400	3	1200	440	735	8	142	124		60	1300
	4	1200	440	735	9.5	148	132		40	1300
2400 TO 0400	3	1200	440	722	8	142	124		60	1250
	4	1200	440	722	9.5	148	133		40	1200
0400 TO 0800	3	1200	440	720	8	142	125		60	1550
	4	1200	440	720	9.5	150	124		40	1500
0800 TO 1200	3	1200	440	720	8	144	125		60	1600
	4	1200	440	720	9.5	152	134		40	1550

FUEL - WATER AND LUBE OIL			
METER AT NOON	1307.780	ON HAND AT START OF DAY	
METER PREVIOUS NOON	1306.300	EVAPORATED OR RECEIVED	
CONSUMED BY METER		ON HAND	
ON HAND AT START OF DAY		CONSUMED	
EXPENDED DURING DAY		ON HAND AT START OF DAY	
REMAINING ON BOARD		RECEIVED	
ON HAND AT START OF DAY		ON HAND	
EVAPORATED OR RECEIVED		CONSUMED	
ON HAND		DIESEL OIL	
CONSUMED		ON HAND	

L.O. CENTRIFUGE - HOURS OPERATED					
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
4	4	4	4	4	4

SUMMARY	
RUNNING TIME	PERCENT OF SLIP
DETENTION TIME	BBL FUEL/MI
TOTAL REVOLUTIONS	WIND DIRECTION
AVERAGE R.P.M.	STATE OF SEA
TOTAL MILES BY ENGINE	STATE OF WEATHER
TOTAL MILES BY OBSERVATION	

REMARKS

1200-1600 WATCH

In Port. Machinery in service: Boilers B-3-4 and aux.; Generators G-3-4 and aux.; Jacking gear engaged; Main Circ. M-2; Cond. MC-3, L.O. Pumps Air ejector. ME-R, Aux Cond and Circ. Pumps Lub Oil Purifier. Added packing Bal. Valve Ahead Throttle. Fuel Oil Suction from inboard settler. Added 1 gal Lub Oil to P. Feed Pump Made routine watch tests and inspections of engine room machinery spaces

Oiler Mr. Meckon K.W.T. M+Trapp. Conducted -41

WATCH ENGR'S SIGNATURE

Harold J. DuMond

1600-2000 WATCH

PORT WATCH TILL 1800.

STBY @ 1748 FOM P-4592170 - CNTR. P-30910560

BELLS PER BELL BOOK.

FOM-S-2472160 - CNTR. S-32126790

DEPT. @ 1854 FOM-P-4592470 - CNTR. P-30913330

FOM-S-8472420 - CNTR. S-32129390

UNDERWAY ON 16 NOZZLES MACH. IN OPERATION AS BEFORE. ELECT. WORKING ON AIR COMP.

WATCH ENGR'S SIGNATURE

A. Karsten

2000-2400 WATCH

Underway 16 Nozzles machinery as before shifted to low sea suet at 2010. Call out Electrician to work on pump on #2 EVAP. Chief Electrician working on Air Compressor. #2 EVAP secured to repair pump. Added 10 gal. L.O. to #4 Feed pump at 2000 hrs and again at 2100 (2) gal at 2300 hrs. Retarded Clock 20 min at 2300 hrs. made half-hourly rounds of Steaming bearings, made rounds of Space + mach. All conditions Normal. Cond. 41 S.D. & Box 9.11% sal. @ 2300 M's went up to 18 Nozzles by 0600 hrs.

Carried out Reg. Underway Steaming Watch Routine

WATCH ENGR'S SIGNATURE

D. J. Penkett

2400-0400 WATCH

Underway, Recorded machinery in service. at 0100 Retarded clocks 20 min added 1 gal. Lub. Oil each to Feed Pump's; Made routine watch tests and inspection of engine room machinery spaces. Pumped settlers, Fuel Oil suction from catboard settler.

Cond. tested -41

WATCH ENGR'S SIGNATURE

Harold J. DuMond

0400-0800 WATCH

UNDERWAY ON 18 NOZZLES - MACHINERY IN OPERATION AS BEFORE. RETARD CLOCK 20 MIN. @ 0500. CHANGE & CLEAN #5 & #6 F.O. ~~BURNERS~~ BURNERS. CLEAN F.O. SUCT. STRAINER. OPEN W.T. DOORS @ 0500. - B-4 ON BOTTOM BLOW THRU M.U. EVAP. - CHANGE LUB. OIL ON #25 SPRING BEARING. COMPLY WITH COMSTS. INSTR. #4700.7

M.U.F. #2-S-3 21'-0" - SUCT. ON DB.

M.U.F. #2-P = 23'-0"

MAIN COND. 41

WATCH ENGR'S SIGNATURE

A. Karsten

0800-1200 WATCH

UNDERWAY 18 NOZZLES - MACH. AS BEFORE - CHANGED AND CLEANED F.O. BURNERS & DISCHARGE STRAINERS - BLEW TUBES P/S BOILERS @ 0800-0816 - 151/AE IN SPACE @ 0830 - CHANGED AND CLEANED L.O. STRAINERS ON #3 & #4 AUX. GEN. SHIFTED F.O. SETTLER TO INBD. @ 1000 - TESTED FIRE ALARM @ 1132 - SHIFTED FW ~~SUCT~~ SUCTION TO #2 STBD. @ 1135 Pumped E.R. & SHAFT ALLEY BILGES - MADE ROUNDS TESTS AND INSPECTIONS OF MACH. AND SPACE. Complied with STANDING & NIGHT ORDERS - COMSTS INSTR. 4700.7 - REG. STEAMING WATCH ROUTINE.

Cond. 41 PR 7.04 SR 8.29

WATCH ENGR'S SIGNATURE

D. J. Penkett

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS F-660	HOURS F-440
W-660	W-440
AKL 9.39	AKL 11.10
T-AKL 11.10	T-AKL 19.27
SAL. 7.87	SAL. 8.29
PECS. 30	PHOS. 50
R-ph 11	R-ph 11
30.5	11

SULFITE 36 Sulfite -45

CHIEF ENGR'S SIGNATURE

H. L. Clemens

		WATCH								WATCH							
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		
RUNNING TIME		240	240	240	240	240	240			AFT. H. P. ROTOR BEARING	130	136	134	135	135	134	
DETENTION TIME							3113			FORWARD L. P. ROTOR BEARING	130	133	130	130	130	130	
REVOLUTION COUNTER (END OF WATCH)		3103	3105	3107	3109	3111	3113			AFT. L.P. ROTOR BEARING	130	130	127	130	128	132	
TOTAL REVOLUTIONS (FOR WATCH)		21680	21770	21860	21950	22040	22130			HOTTEST GEAR BEARING FORWARD	148	147	140	140	144	138	
AVERAGE RPM		90.3	90.7	91.1	91.5	91.9	92.3			HOTTEST GEAR BEARING AFT	144	140	135	135	135	132	
F.O. METER (END OF WATCH)		1308	1308	1308	1308	1308	1309			AUX. COND. CONDENSATE	128	128	130	126	129	133	
F.O. CONSUMED		2020	2030	2040	2050	2060	2070			1ST STAGE FEED WATER HEATER	175	179	175	175	174	170	
PRESSURES		THROTTLE	414	414	420	420	415	418			O. C. FEED WATER HEATER	238	239	238	238	239	238
		H.P. AHEAD	410	410	415	416	410	418			3RD STAGE FEED WATER HEATER	135	135	135	135	135	135
		L.P. AHEAD	24.5	24.5	21	21	20	16.25			F.O. TO BURNERS	160	160	150	155	155	150
		VACUUM	27.7	27.7	28	28.2	28	28.5			F.O. BACK PRESSURE						
		L.O. TO TURBINES	12.8	12.8	12.7	12.7	12.7	12.7			AIR TO FURNACE	6.5	6.5	6.5	4.6	4.4	4.2
		AUX. STEAM	150	150	150	156	150	150			UPTAKE						
		BACK PRESSURE	9	9	9	9	9	9			MAIN STEAM	440	440	440	446	440	440
		GLAND STEAM	1.8	1.8	.5	.5	1.2	1.7			SUPER HEAT	728	730	715	713	715	720
		H.P. BLEEDER	60	60	60	60	60	60			F.O. TO BURNERS	160	172	180	180	180	180
		I.P. BLEEDER	5.2	5.2	5.5	5.4	5.5	5.5			F.O. TEMP. IN SETTLING TANKS	102	109	114	113	110	111
L.P. BLEEDER			11.4			13			PORT BOILER UPTAKE	310	300	295	295	300	295		
TEMPERATURES		STEAM AT THROTTLE	728	730	715	713	715	720			STBD. BOILER UPTAKE	310	300	295	295	300	295
		L.P. EXHAUST	120	121	118	116	115	116			ENGINE ROOM TEMPERATURE	105	100	99	99	99	97
		CONDENSATE	118	117	114	114	113	110			FIRE ROOM TEMPERATURE			99			97
		CIRC. WATER IN	90	90	89	88	88	88			NOZZLES IN USE	18	18	16	16	16	14
		CIRC. WATER OUT	98	98	98	94	96	96			NO. OF BURNERS IN USE	6	6	6	6	6	6
		L.O. TO COOLERS	128	128	126	125	126	124			BURNER TIP SIZE	51	51	51	51	51	51
		L.O. FROM COOLERS	110	110	110	110	110	110			CO ₂ % PORT. BOILER			13.5			12.5
		TEMPERATURE THRUST BEARING	120	118	117	118	116	115			CO ₂ % STBD. BOILER			14.5			13.0
		FORWARD H.P. ROTOR BEARING	126	127	125	125	127	125			OIL LEVEL MAIN SUMP	1" 3/4"	1" 3/4"	1" 3/4"	1" 3/4"	1" 3/4"	1" 3/4"

WATCH	GENERATORS												FUEL - WATER AND LUBE OIL					
	GENERATOR NUMBER	R. P. M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		DOMESTIC WATER		LUBE OIL	
1200 TO 1600	3	1200	440	728	8	144	120	26.6	60	1350	1350	240	METER AT NOON	13094.340	ON HAND AT START OF DAY		ON HAND	
													METER PREVIOUS NOON	13077.550	EVAPORATED OR RECEIVED		CONSUMED	
1600 TO 2000	4	1200	440	728	9.5	100	134	26.2	40	1300	1300	240	CONSUMED BY METER		ON HAND		ON HAND	
													ON HAND AT START OF DAY		CONSUMED		CONSUMED	
2000 TO 2400	3	1200	440	730	8	142	126	27	60	1500	1500	240	RECEIVED DURING DAY		ON HAND AT START OF DAY		RECEIVED	
													EXPENDED DURING DAY		ON HAND		ON HAND	
2400 TO 0400	4	1200	440	730	9.5	150	134	26.2	40	1350	1350	240	REMAINING ON BOARD		CONSUMED		CONSUMED	
													ON HAND AT START OF DAY		DIESEL OIL		ON HAND	
0400 TO 0800	3	1200	440	715	8	142	123	27	64	1250	1250	240	EVAPORATED OR RECEIVED		ON HAND		CONSUMED	
													ON HAND		CONSUMED		CONSUMED	
0800 TO 1200	4	1200	440	715	9.5	148	132	26.5	90	1300	1300	240	CONSUMED		CONSUMED		CONSUMED	
													CONSUMED		CONSUMED		CONSUMED	
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)																		
L.O. CENTRIFUGE - HOURS OPERATED																		
1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200								
3		4		4		4		4		4								
SUMMARY																		
RUNNING TIME												PERCENT OF SLIP						
DETENTION TIME												BBL FUEL/MI						
TOTAL REVOLUTIONS												WIND DIRECTION						
AVERAGE R.P.M.												STATE OF SEA						
TOTAL MILES BY ENGINE												STATE OF WEATHER						
TOTAL MILES BY OBSERVATION																		

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boiler B-3-4 and aux.; Generator G-3-4 and aux.; Main Cond. M-2, Cond. M.C.-3, L.O. Pumps and Air ejector. ME-R; Aux. Circ. Lub. Oil Purifier, Cleaned and changed Burner and F.O. Strainers. Pumped settlers, Fuel Oil Suction From inboard settler. Added 2 gals. L.O. each to $\frac{1}{2}$ Feed Pumps. Electrician working on S.S. Air Comp. 59-100 PSIG. Cleaned L.O. Purifier Bowl, suet and disch. str. Made routine watch tests and inspections of engine room machinery spaces.

Cond. Main and Aux tested Hourly: 41

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

1600-2000 WATCH

UNDERWAY ON 18 NOZZLES MACH. IN OPERATION AS BEFORE. BLOW TUBES IN B-3 & B-4. CHANGE & CLEAN #5 F.O. BURNER B-3 ON BOTTOM BLOW THRU M.V. EVAP. MADE ROUTINE ROUNDS COMPLY WITH COMSTS WITH ENGINE ROOM & SHAFT ALLEY INSPECTIONS.

M.U.F. #2-S = 21 SUCT ON DB.

M.U.F. #2-P = 23

WATCH ENGR'S SIGNATURE-

H. Karsten

2000-2400 WATCH

Underway 18 Nozz. Machinery as before except at 2000 hrs. $\frac{5}{8}$ B Reduced speed to 16 Nozzles. Shifted F.O. Settler's to outbid at 2020. Changed & cleaned F.O. discharge & Gen L.O. Strainer's. changed burner's. At 2110 Mr. Barney D2 $\frac{1}{2}$ took a drag on #7 $\frac{1}{5}$ to Tanks to relieve head psi. made half-hourly check on all spring bearing's. Made rounds, Tests, & Inspect. of Mach. & space. All condition's Normal. Pumped Bilges & Shaft Alley's. Complied with night & standing orders & Comsts Instr. 4700.7 M. Cond. .41 Aux. Cond. .41 B3 7.46 B3-6.21

Carried out Reg. Underway steaming watch Routine

WATCH ENGR'S SIGNATURE-

D. J. Puckett

2400-0400 WATCH

Underway, Recorded machinery in service; Changed and cleaned burners, Fuel Oil and Lub. Oil strainers; Pumped settlers, Fuel oil Suction From Outboard settler. Added 1 gal. L.O. each $\frac{1}{2}$ Feed Pumps Made routine watch tests and inspections of engine room machinery spaces

Cond tested -.41

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

0400-0800 WATCH

UNDERWAY ON 16 NOZZELS MACHINERY IN OPERATION AS BEFORE. CHANGE & CLEAN #6 F.O. BURNER. CLEAN SUCT. STRAINER. B-3 ON BOTTOM BLOW THRU M.V. EVAP. ADD COMPOUND TO B-3 & B-4. OPEN W.T. DOORS ORDERS FROM BRIDGE. SAL TEST @ 0730 = B-3 = 5.2% - B-4 = 6.2%

#2-S M.U.F. = 22-0 SUCT. ON DB.

#2-P M.U.F. = 22-0 MAIN COND. .41

WATCH ENGR'S SIGNATURE-

H. Karsten

0800-1200 WATCH

Underway 16 Nozz. Machinery in operation as before, except at 0800 reduced speed to 80 RPM's $\frac{5}{8}$ B. Blew tubes $\frac{1}{2}$ boiler's 0805-0830 tested fire & smoke detector & fire Alarm 0908-0914 from the bridge. Changed & cleaned Gen. L.O. & F.O. discharge strainer's & burner's. made half-hourly rounds on spring bearing's, machinery & space. All condition's Normal. Pumped Bilges & Shaft Alley's. Complied with standing orders & comstr instr. 4700.7 Cond. .41 Aux cond. .41 B3 7.04 B4 6.63

Carried out Reg. Underway steaming watch Routine

WATCH ENGR'S SIGNATURE-

D. J. Puckett

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS 7-00	HOURS 7-00
AKL 5.84	AKL 8.76
T-AKL 10.51	T-AKL 11.48
SAL. 5.39	SAL. 7.04
PHOS. 20	PHOS. 30
R.ph 11	R.ph 11

SULFITE 25 SULFITE 25

CHIEF ENGR'S SIGNATURE-

L. L. Clemens

		WATCH								WATCH							
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		
RUNNING TIME		240	240	240	240	240	240	MACHINERY PARTICULARS (CONT'D)	TEMPERATURES (CONT'D)	AFT. H. P. ROTOR BEARING	136	131	138	138	140	130	
DETENTION TIME										FORWARD L. P. ROTOR BEARING	125	129	131	131	133	127	
REVOLUTION COUNTER (END OF WATCH)		3115	3117	3119	3121	3123	3125			AFT. L. P. ROTOR BEARING	135	130	130	130	130	127	
TOTAL REVOLUTIONS (FOR WATCH)		19580	19640	19700	19760	19820	19880			HOTTEST GEAR BEARING FORWARD	135	140	140	135	141	140	
AVERAGE RPM		81.5	82.0	82.1	81.9	81.9	81.6			HOTTEST GEAR BEARING AFT	138	133	133	138	133	130	
F.O. METER (END OF WATCH)		1309	1309	1310	1310	1310	1310			AUX. COND. CONDENSATE	129	129	129	118	122	124	
F.O. CONSUMED		2540	2530	2420	2456	2470	2430			1ST STAGE FEED WATER HEATER	165	170	170	170	171	171	
PRESSURES	THROTTLE	418	420	420	418	420	418			D. C. FEED WATER HEATER	238	239	238	239	239	238	
	H.P. AHEAD	416	415	420	416	420	418			3RD STAGE FEED WATER HEATER	185	185	185	185	185	185	
	L.P. AHEAD	16.5	16.5	16.5	16.5	16.5	16.0			F.O. TO BURNERS	135	150	120	125	125	130	
	VACUUM	28.4	28.5	28.5	28.4	28.5	28.4			F. O. BACK PRESSURE							
	L.O. TO TURBINES	12.25	12.75	12.75	12.7	12.75	12.7			AIR TO FURNACE	4.5	4.5	4.0	4.5	4.5	3.8	3.6
	AUX. STEAM	150	150	150	150	150	150			UPTAKE							
	BACK PRESSURE	9	9	9	9	9	9			MAIN STEAM	440	440	440	446	440	440	
	GLAND STEAM	1.8	1.8	1.0	1.6	1.5	1.5			SUPER HEAT	715	720	715	722	720	720	
	H.P. BLEEDER	60	60	60	60	60	60			F.O. TO BURNERS	180	180	180	182	182	180	
	L.P. BLEEDER	5.2	5.2	5.2	5.2	5.2	5.5			F.O. TEMP. IN SETTLING TANKS	110	110	113	108	110	110	110
TEMPERATURES	L.P. BLEEDER			13			13			PORT BOILER UPTAKE	290	295	295	290	295	290	
	STEAM AT THROTTLE	715	720	715	722	720	720			STBD. BOILER UPTAKE	290	290	290	300	300	290	
	L.P. EXHAUST	116	115	116	116	116	116			ENGINE ROOM TEMPERATURE	100	98	98	99	99	101	
	CONDENSATE	112	111	110	110	110	112			FIRE ROOM TEMPERATURE		98	98	99	99	101	
	CIRC. WATER IN	89	88	87	86	88	89			NOZZLES IN USE	14	14	14	14	14	14	
	CIRC. WATER OUT	96	95	95	96	95	97			NO. OF BURNERS IN USE	6	6	6	6	6	6	
	L.O. TO COOLERS	124	124	125	125	125	126			BURNER TIP SIZE	51/55	51/55	51/55	51/55	51/55	51/55	
	L.O. FROM COOLERS	110	110	110	110	110	110			CO ₂ % PORT BOILER			12.0			13.0	
	TEMPERATURE THRUST BEARING	118	115	116	118	116	117			CO ₂ % STBD. BOILER			13.5			14.0	
	FORWARD H.P. ROTOR BEARING	125	126	125	125	126	125			OIL LEVEL MAIN SUMP	1.4"	1.4"	1.4	1.4"	1.4"	1.5'	

GENERATORS												FUEL - WATER AND LUBE OIL									
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL	METER AT NOON	METER PREVIOUS NOON	CONSUMED BY METER	ON HAND AT START OF DAY	EVAPORATED OR RECEIVED	ON HAND	CONSUMED	RECEIVED
1200 TO 1600	3	1200	440	715	8	142	124	26.8	65	1400	1400	236	FUEL OIL	13109180	13094340						
	4	1200	440	715	9.5	149	133	26.2	40	1300	1300	240	BOILER WATER								
1600 TO 2000	3	1200	440	720	8	148	124	27.5	64	1150	1150	240	DOMESTIC WATER								
	4	1200	440	720	9.5	124	132	26.2	40	1050	1050	240									
2000 TO 2400	3	1200	440	715	8	142	122	26.3	64	1100	1100	240									
	4	1200	440	715	9.5	147	132	26.3	40	1100	1100	240									
2400 TO 0400	3	1200	440	722	8	140	120	27.6	64	1050	1050	240									
	4	1200	440	722	9.5	148	132	27.2	40	1000	1000	240									
0400 TO 0800	3	1200	440	720	8	141	124	27.2	64	1150	1150	240									
	4	1200	440	720	9.5	149	133	27.2	40	1150	1150	240									
0800 TO 1200	3	1200	440	720	8	142	124	27.0	64	1400	1400	240									
	4	1200	440	720	9.5	148	132	27.0	40	1400	1400	240									

L.O. CENTRIFUGE - HOURS OPERATED					
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
4	4	4	4	4	4

SUMMARY			
RUNNING TIME		PERCENT OF SLIP	
DETENTION TIME		BBL FUEL/MI	
TOTAL REVOLUTIONS		WIND DIRECTION	
AVERAGE R.P.M.		STATE OF SEA	
TOTAL MILES BY ENGINE		STATE OF WEATHER	
TOTAL MILES BY OBSERVATION			

Underway:

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux.; Generator - G-3-4 and aux; Main Circ. - M-2, Cond. - MC-3, Lub Oil Pumps Air Ejector. ME - R. Aux Circ and Cond. pumps, F.W. Pump - W-3, L.O. Purifier. Pumped settlers. Fuel Oil suction from inboard settlers. Cleaned, changed burner and F.O. Strainer. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - .41

1600-2000 WATCH

WATCH ENGR'S SIGNATURE-

Harold F. DuMond

UNDERWAY ON 14 NOZZLES MACHINERY IN OPERATION AS BEFORE BLOW TUBES IN B-3 + B-4. CHANGE + CLEAN #5 F.O. BURNER. CLEAN F.O. SUCT. STRAINER. B-4 ON BOTTOM BLOW THRU. M.U. EVAP. MADE ROUTINE INSPECTIONS + COMPLIED WITH COMSTS. STANDING ORDERS #4700.7. CLOSE #1 + #2 W.T. DOORS - BARGE SAL TEST @ 1900 B-3 = 5.8% B-4 = 5.4%

#2 MUF - P = 22'-0" SUCT. ON D.B.

#2 MUF - S =

2000-2400 WATCH

WATCH ENGR'S SIGNATURE-

A. Karsten

UNDERWAY 14 NOZZLES - MACH AS BEFORE - CHANGED + CLEANED F.O. BURNERS + STRAINERS - CHANGED + CLEANED L.O. STRAINERS CO #3 + #4 AUX. GENERATORS - Pumped E.R. AND SHAFT ALLEY - MADE ROUNDS TESTS AND INSPECTIONS OF MACH. AND SPACE - REG. STEAMING WATCH ROUTINE - COMPLIED WITH STANDING AND NIGHT ORDERS - COMSTS INTR. 4700.7

Cond. .41 P 5.80 S 6.63

2400-0400 WATCH

WATCH ENGR'S SIGNATURE-

Underway. Recorded machinery in service; Added 1 gal. Lub oil each to #1's Feed Pumps; Pumped settlers. Fuel Oil suction from outboard settlers; Changed and cleaned burners, Fuel Oil and Lub. Oil strainers; Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - .41

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

Harold F. DuMond

UNDERWAY ON 14 NOZZLES. MACHINERY IN OPERATION AS BEFORE B-3 ON BOTTOM BLOW THRU. M.U. EVAP - CHANGE + CLEAN #6 F.O. BURNER. CLEAN SUCT. F.O. STRAINER. PUMPED E.R. + SHAFT ALLEY PILGES. MADE ROUTINE INSPECTS. OF E.R. + SHAFT ALLEY. COMPLY WITH COMSTS. #4700.7

SAL TEST 0700 = B-3 - 4.14% - B-4 - 4.97% MAIN COND. .41

MUF #2 - S = 22'-0" SUCT. ON DB

MUF #2 - P = 22'-0"

0800-1200 WATCH

WATCH ENGR'S SIGNATURE-

A. Karsten

Underway 14 nozzles, mach. as before Blew tubes #1's boiler's 0800-0824 + Tested from the bridge, smoke & fire detection & fire alarm systems. 0845-0905. Cleaned & changed L.O., gen. strainer's, F.O. discharge strainer's & burner's. Tested Thrust And Gov. throttle's. Changed oil & cleaned sump's of #2 + #4 starboard spring bearing's. Made half-hourly check of all spring bearing's. Pumped bilges & shaft alley's. Made rounds, tests & inspection of mach. & space. Cond. .41 Aux Cond. .41 B3. 4.56% B4 5.39%

Carried out regular underway steaming watch routine
Complied with standing orders & Comsts Instr. 4700.7

WATCH ENGR'S SIGNATURE-

D. J. Puckett

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS F-768	HOURS F-468
W-768	W-468

AKL 10.51 AKL 2.76

T-AKL 17.52 T-AKL 15.18

SAL. 5.5 SAL. 4.97

PHOS. 40 PHOS. 30

R.ph R.ph

SULFITE 37.5

CHIEF ENGR'S SIGNATURE-

L. H. Clemens

WATCH							WATCH						
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME	240	240	240	240	98	-							
DETENTION TIME													
REVOLUTION COUNTER (END OF WATCH)	3127 2790	3129 0460	3130 4280	3131 6840	3132 0310								
TOTAL REVOLUTIONS (FOR WATCH)	19490	17070	13770	12610	3470								
AVERAGE RPM	81.2	73.6	57.3	52.5	55.4								
F.O. METER (END OF WATCH)	1311 1630	1311 3070	1311 5120	1311 6490	1311 7850	1311 8500							
F.O. CONSUMED	2450	2060	1430	1370	1300	650							
PRESSURES	THROTTLE	414	420	420	418		MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING	134	128	120	120	
	H.P. AHEAD	410	420	218	185			FORWARD L. P. ROTOR BEARING	125	123	115	115	
	L.P. AHEAD	16	7.5	4"	7.6"			AFT. L.P. ROTOR BEARING	125	124	120	120	
	VACUUM	28.4	28.5	29.0	29			HOTTEST GEAR BEARING FORWARD	135	136	126	115	
	L.O. TO TURBINES	12.7	12.75	13.5	13.			HOTTEST GEAR BEARING AFT	140	132	124	124	
	AUX. STEAM	150	150	140	140			AUX. COND. CONDENSATE	124	121	118	114	114
	BACK PRESSURE	9	9	9	9			1ST STAGE FEED WATER HEATER	170	162	105	105	160
	GLAND STEAM	1.5	1.5	1.7	1.8			D. C. FEED WATER HEATER	238	239	238	238	238
	H.P. BLEEDER	60	60	58	58			3RD STAGE FEED WATER HEATER	1051 1135	1051 1135	105 113	105 113	
	L.P. BLEEDER	5.2	5.2	5.5	5.2			F.O. TO BURNERS	125	80	100	105	100
TEMPERATURES	STEAM AT THROTTLE	720	710	650	648		BOILER PARTICULARS	F.O. BACK PRESSURE					
	L.P. EXHAUST	117	114	110	110	130		AIR TO FURNACE	4.5 4.4	2.5 2.5	1.5 1.5	1.4 2.4	2.0 2.2
	CONDENSATE	112	106	107	96	92		UPTAKE					
	CIRC. WATER IN	88	90	88	86	81		MAIN STEAM	440	440	440	440	440
	CIRC. WATER OUT	96	95	90	88	82		SUPER HEAT	720	710	650	648	
	L.O. TO COOLERS	126	122	118	116	112		F.O. TO BURNERS	182	180	180	180	180
	L.O. FROM COOLERS	110	110	110	110	109		F.O. TEMP. IN SETTLING TANKS	104 104	112 105	110 105	104 108	110 106
	TEMPERATURE THRUST BEARING	115	115	112	115			PORT BOILER UPTAKE	300	285	270	270	270
	FORWARD H.P. ROTOR BEARING	125	124	118	115			STBD. BOILER UPTAKE	295	275	270	265	270
								ENGINE ROOM TEMPERATURE	101	99	98	98	90
								FIRE ROOM TEMPERATURE			98	98	100
MISCELLANEOUS	NOZZLES IN USE	14	0	10	10	3.00K		NOZZLES IN USE	14	0	10	10	3.00K
	NO. OF BURNERS IN USE	6	6	4	4	2		NO. OF BURNERS IN USE	6	6	4	4	2
	BURNER TIP SIZE	5'5.5	5'5.5	5'5.5	5'5.5	5'5.5		BURNER TIP SIZE	5'5.5	5'5.5	5'5.5	5'5.5	5'5.5
	CO ₂ % PORT BOILER					5.0		CO ₂ % PORT BOILER					5.0
	CO ₂ % STBD. BOILER					8.0		CO ₂ % STBD. BOILER					8.0
	OIL LEVEL MAIN SUMP	1'4"	1'4"	1.5'	1'4"	1.2		OIL LEVEL MAIN SUMP	1'4"	1'4"	1.5'	1'4"	1.2

GENERATORS													FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL	
1200 TO 1600	3	1200	440	720	9	142	123	27"	65	1250	1250	240	METER AT NOON	13118500	ON HAND AT START OF DAY			
	4	1200	440	720	9.5	156	134	26.6"	40	1150	1150	240	METER PREVIOUS NOON	31109180	EVAPORATED OR RECEIVED			
1600 TO 2000	3	1200	440	710	8	141	123	27.5	64	1150	1150	240	CONSUMED BY METER		ON HAND			
	4	1200	440	710	9.5	148	132	27	40	1050	1050	240	ON HAND AT START OF DAY		CONSUMED			
2000 TO 2400	3	1200	440	650	8	140	122	28	64	1000	1000	240	RECEIVED DURING DAY		ON HAND AT START OF DAY			
	4	1200	440	650	9.5	147	132	27.5	40	1000	1000	240	EXPENDED DURING DAY		RECEIVED			
2400 TO 0400	3	1200	440	648	8	138	118	27.4	65	1100	1100	240	REMAINING ON BOARD		ON HAND			
	4	1200	440	648	9.5	145	128	27.2	40	1050	1050	240	ON HAND AT START OF DAY		CONSUMED			
0400 TO 0800	3	1200	440		8	140	118	27	65	1100	1100	240	EVAPORATED OR RECEIVED		DIESEL OIL			
	4	1200	440		9.5	145	125	27	40	1100	1100	240	ON HAND		ON HAND			
0800 TO 1200	3	1200	440		8	136	118	26.4	64	1100	1100	240	CONSUMED		CONSUMED			
	4	1200	440		9.5	145	125	27.0	40	1100	1100	240						
LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)																		
L.O. CENTRIFUGE - HOURS OPERATED																		
1200 TO 1600		1600 TO 2000		2000 TO 2400		2400 TO 0400		0400 TO 0800		0800 TO 1200								
4		4		4		4		4		4								
SUMMARY																		
RUNNING TIME												PERCENT OF SLIP						
DETENTION TIME												BBL FUEL/MI						
TOTAL REVOLUTIONS												WIND DIRECTION						
AVERAGE R.P.M.												STATE OF SEA						
TOTAL MILES BY ENGINE												STATE OF WEATHER						
TOTAL MILES BY OBSERVATION																		

Underway.

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux.; Generators - G-3-4 and aux.; Main Circ: M-1, Cond - M.C.-3, Lub. Oil Pumps and Air Ejector - ME-R. Aux. Circ and cond. Pumps; Lub Oil Purifier F-W-3-Pump. Pumped Settlers, Fuel Oil suction from inboard settler. Added 2 gals. Lub Oil each P's Feed Pumps. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - 41

1600-2000 WATCH

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

UNDERWAY ON 10 NOZZLES. MACHINERY IN OPERATION AS BEFORE.

REDUCE SPEED TO 70 R.P.M. @ 1400. - BLOW TUBES IN B-3 + B-4. - B-4 ON BOTTOM BLOW THRU MV EVAR. ADD COND. TO B-3 - SAL. TEST: B-3-4.14% + B-4 = 4.14%. MADE ROUTINE ROUNDS OF E.R. 1/2 HR. ROUNDS OF SPRING BEARINGS COMPLY WITH COMSTS #4700.7. CLOSE #1 + #2 W.T. DOORS (AS REQD).

M.U.F. #2 S = 2.50 - 2.50 - 2.50 - 2.50 - 2.50 - 2.50 - 2.50 - 2.50 - 2.50 - 2.50

M.U.F. #2 P = 22.00 - 22.00 - 22.00 - 22.00 - 22.00 - 22.00 - 22.00 - 22.00 - 22.00 - 22.00

2000-2400 WATCH

WATCH ENGR'S SIGNATURE-

J. H. Hinton

Underway 10 Nozzles. 70 R.P.M. Machinery as before. At 2000 hrs Reduced speed to 50 R.P.M. B.O.B. Changed & cleaned, burners, F.O. drain strainers, Gen. L.O. strainers. Made half-hourly rounds on all spring bearings. Made rounds of Mach. & Space. Pump bilges & shaft alley's. All W.T. doors closed for War Zone conditions. Complied with Night & standing orders & Comsts Instr. 4700.7.

Cond. 9.60 Cond. 14.00 E.R. 2.50 2.50 2.50 2.50 2.50 2.50 2.50 2.50 2.50 2.50

Carried out inspection of machinery spaces during watch routine

WATCH ENGR'S SIGNATURE-

J. H. Hinton

2400-0400 WATCH

Underway 50 R.P.M. Recorded Machinery in service. Pumped settlers, Outboard settler's Fuel Oil suction. Added 1 gal. Lub. Oil each P's Feed Pumps. Changed and cleaned Fuel Oil and lub. Oil strainers. Made routine watch tests and inspections of engine room machinery spaces.

Cond. test - 41

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

UNDERWAY 30 R.P.M. MACHINERY IN OPERATION AS BEFORE. REDUCE SPEED TO 30 R.P.M. @ 0400. BELLS PER BELL BOOK. F.W.E. @ 0512.

ARRIVAL @ 0512. FOM. P = 4617690 CNTR. P = 31320310 PLE MAIN UNIT ON

FOM. S = 8499280 CNTR. S = 32538170 JACKING GEAR.

F.W.E. @ 0714 FOM. P = 4618210 CNTR. P = 31324880

FOM. S = 8499610 CNTR. S = 32543250

DISCHARGE - F.W.E. ALIVE TO F.W.E. FROM B.O.B.

WATCH ENGR'S SIGNATURE-

J. H. Hinton

0800-1200 WATCH

IN ANCHORAGE DANANG, VIETNAM - MACH AS BEFORE - CHANGED & CLEANED F.O. BURNERS AND DISCHARGE STRAINERS - CHANGED & CLEANED L.O. STRAINERS ON #3 & #4 AUX. GEN. Pumped Bilges down to a safe level - MADE ROUNDS TESTS AND INSPECTIONS OF MACH. AND SPACE. Complied with standing and night orders Comsts INSTR. 4700.7

COND. 1.41 P 5.80 S 4.97 - JACKING GEAR ENGAGED

OILER TAITAGUE FWT McLEOD JR. ENGR. FRANK

CHIEF ENGINEER

WATCH ENGR'S SIGNATURE-

D. L. Clement

ARRIVAL @ 0512

BOILER WATER READINGS

FOM. P = 4617690 CNTR. P = 31320310

STB'D PORT

FOM. S = 8499280 CNTR. S = 32538170

HOURS F 732 W 732 HOURS F 732 W 732

AKL 6.42 AKL 13.43

F.W.E. @ 0714

T-AKL 7.76 T-AKL 13.55

FOM. P = 4618210 CNTR. S = 32543250

SAL. 4.14 SAL. 5.39

FOM. S = 8499610 CNTR. P = 31324880

PHOS. 30 PHOS. 30

R.ph 11 R.ph 11

SAL. 20 INLET 41.5

CHIEF ENGR'S SIGNATURE-

D. L. Clement

REMARKS

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux.; Generators - G-3-4 and aux.; Main Air ejector FLE-R, Cond-3, Circ-M-A, Lub Oil Pumps, Lub Oil Purifier, Aux. Circ. and cond pumps F-W-3, 1315 secured jacking gear cut M. Steam and bld. Stops. 1328 Bolls as per Bell Book. 1359 FWE 1359 secured Steam stops engaged jacking gear. Pumped settlers F.O. section from inboard settler.

Cond tested .41

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

PORT WATCH MAINTAINED IN POSITION AS BEFORE SET CLOCK @ 1700. TEST TELEGR. REMOVED FROM HEAD - WHEN STOP @ 1815 PERMITTED TO PULL IN. 1000. SET @ 1814 Bolls per Bell Book. DEPT. @ 1912 UNDERWAY ON 14 NOZZLES.

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

UNDERWAY 14 NOZZLES - MACH. AS BEFORE - CHANGED & CLEANED F.O. BURNERS AND DISCHARGE STRAINERS - CHANGED AND CLEANED L.O. STRAINERS ON #3 & #4 AUX. GEN. PUMPED F.R. AND SHAFT ALLEY BILGES - MADE RUNDS TESTS AND INSPECTIONS OF MACH. AND SPACE - COMPLIED WITH STANDING AND NIGHT ORDERS, COMSTS INSTRUCTION #700.7. REGULAR STEAMING WATCH ROUTINE.

COND. .41 P-7.37 S-5.34

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

Underway. Recorded machinery in service. Changed and cleaned burner. Fuel Oil and Lub Oil strainers. unable to pump settlers. Fuel Oil suction from outboard settler. Made routine watch tests and inspections of engine room machinery spaces. Added 1 gal each Lub Oil to P-S Feed Pumps.

WATCH ENGR'S SIGNATURE-

Cond tested .41

0400-0800 WATCH

UNDERWAY ON 14 NOZZLES. MACHINERY IN OPERATION AS BEFORE. B-4 ON REEL. FUEL OIL CLAR - VENTURATED BURNER OUT OF FUEL. BOLLERS STOPPED. CHIEFT. @ 0445. APP. COND. NO TO 3-3. MADE RUNDS. & INSPECTIONS. COMPLY WITH COMSTS #4700.7. MAINTAINED UNDERWAY.

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

Underway as before. Machinery in operation as before. WT doors closed for W3 Zone cruising conditions. Blue Tubes 13 knots @ 0825 130 10.8 - B-3534 OK F.O. S&B. Tested H-15 smoke alarm & indicator at 0918. From bridge, pumped bilges & shaft alley. made oil bolls hourly rounds. on spring bearing & mach. & mach. space oil condition. maintained. 1148. Cond. .41 P-5.93 S-5.04. COMPLIED WITH STANDING AND NIGHT ORDERS (COMSTS #700.7). Maintained regular underway steaming watch routine.

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

STBY @ 1234

FOM P = 4619280 - CNTR = 31325160

STB'D

PORT

FOM S = 2500670 - CNTR = 32544940

HOURS P-756 F-576

HOURS W-534

DEPT @ 1412

FOM P = 4619490 - CNTR = 31325160

AKL 142 AKL 1110

FOM S = 2500740 - CNTR = 32544940

T-AKL 276 T-AKL 1115

SAL. 5.20 SAL. 6.21

PHOS. .30 PHOS. .40

R.ph 11 R.ph 1

SULFITE-11 SULFITE-11

CHIEF ENGR'S SIGNATURE-

L. L. Clement

	WATCH							WATCH					
	1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME	240	240	240	240	132		MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING	120	122	122	122	
DETENTION TIME								FORWARD L. P. ROTOR BEARING	125	120	120	120	
REVOLUTION COUNTER (END OF WATCH)	3142	3144	3146	3147	3148			AFT. L. P. ROTOR BEARING	125	127	120	120	
TOTAL REVOLUTIONS (FOR WATCH)	20040	20040	14140	13330	7240			HOTTEST GEAR BEARING FORWARD	135	137	130	130	
AVERAGE RPM	83.5	83.5	58.9	55.5	71.0			HOTTEST GEAR BEARING AFT	138	132	128	128	
F.O. METER (END OF WATCH)	1919	1919	1313	1313	1314			AUX. COND. CONDENSATE	114	114	112	110	118
F.O. CONSUMED	2450	2500	1460	1430	1610	800		1ST STAGE FEED WATER HEATER	170	169	110	110	108
MACHINERY PARTICULARS	THROTTLE	424	425	430	430			D. C. FEED WATER HEATER	238	237	238	238	238
	H.P. AHEAD	424	425	220	215			3RD STAGE FEED WATER HEATER	HP 1051 LP 126	1051 126	1051 126	1051 126	
	L.P. AHEAD	15	15	—	—5			F.O. TO BURNERS	125	110	100	108	65
	VACUUM	28.6	28.5	29.5	29.4	28		F.O. BACK PRESSURE					
	L.O. TO TURBINES	12.7	12.7	13	13	13.2		AIR TO FURNACE	4.5	4.3	4.5	2.6	2.0
	AUX. STEAM	150	150	150	150	150		UPTAKE					
	BACK PRESSURE	9	9	9	9	9		MAIN STEAM	440	440	440	440	440
	GLAND STEAM	2.	2.	1.2	1.	1.8		SUPER HEAT	726	725	650	644	465
	H.P. BLEEDER	60	60	60	60	58		F.O. TO BURNERS	180	180	180	182	180
	L.P. BLEEDER	185"	15"	25"	—	25"		F.O. TEMP. IN SETTLING TANKS	112	116	115	112	114
PRESSURES	L.P. BLEEDER	185"	15"	25"	—	25"	BOILER PARTICULARS	PORT BOILER UPTAKE	300	295	275	270	275
	STEAM AT THROTTLE	726	725	650	644			STBD. BOILER UPTAKE	290	280	275	270	275
	L.P. EXHAUST	112	113	107	108	133		ENGINE ROOM TEMPERATURE	98	97	95	95	98
	CONDENSATE	106	115	92	92	93		FIRE ROOM TEMPERATURE			95		98
	CIRC. WATER IN	82	82	83	83	84		NOZZLES IN USE	14	14	Block 10	Block 10	
	CIRC. WATER OUT	90	90	86	86	86		NO. OF BURNERS IN USE	6	4	4	4	2
	L.O. TO COOLERS	129	126	118	119	112		BURNER TIP SIZE	5' 55"	5' 55"	5' 55"	5' 55"	5' 55"
	L.O. FROM COOLERS	110	110	110	110	110		CO ₂ % PORT BOILER			10.5		
	TEMPERATURE THRUST BEARING	115	114	112	112	110		CO ₂ % STBD. BOILER			12.5		
	FORWARD H.P. ROTOR BEARING	130	134	117	115			OIL LEVEL MAIN SUMP	1' 3"	1' 3"	1' 2"	1' 2"	1'
TEMPERATURES							MISCELLANEOUS						

GENERATORS													FUEL - WATER AND LUBE OIL					
WATCH	GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL		BOILER WATER		LUBE OIL	
1200 TO 1600	3	1200	440	726	8	136	116	100	65	1200	1200	240	METER AT NOON	13140430	METER PREVIOUS NOON	13130100	ON HAND AT START OF DAY	ON HAND
1600 TO 2000	4	1200	440	726	9.5	145	125		40	1100	1100	240	CONSUMED BY METER		ON HAND AT START OF DAY	ON HAND	CONSUMED	CONSUMED
2000 TO 2400	3	1200	440	650	8	138	118		64	1050	1050	240	RECEIVED DURING DAY		ON HAND AT START OF DAY	ON HAND	CONSUMED	CONSUMED
2400 TO 0400	4	1200	440	644	9.5	144	124		40	1050	1050	240	EXPENDED DURING DAY		ON HAND AT START OF DAY	ON HAND	CONSUMED	CONSUMED
0400 TO 0800	3	1200	440	644	8	136	116	28.2	64	1050	1050	240	REMAINING ON BOARD		ON HAND AT START OF DAY	ON HAND	CONSUMED	CONSUMED
0800 TO 1200	4	1200	440	644	9.5	144	124	28.2	46	950	950	240	EVAPORATED OR RECEIVED		ON HAND AT START OF DAY	ON HAND	CONSUMED	CONSUMED
LOW PRESS. EVAPORATORS (No. of hrs. operated)(Fresh water made gals.)																		
L.O. CENTRIFUGE - HOURS OPERATED																		
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200													
4	7	4	4	4	4													
SUMMARY																		
RUNNING TIME													PERCENT OF SLIP					
DETENTION TIME													BBL FUEL/MI					
TOTAL REVOLUTIONS													WIND DIRECTION					
AVERAGE R.P.M.													STATE OF SEA					
TOTAL MILES BY ENGINE													STATE OF WEATHER					
TOTAL MILES BY OBSERVATION																		

Underway.

REMARKS

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux.; Generator - G-3-4 and aux.; Main Circ-M-1, Cond.-MC-3, Lub Oil-L-3, Pumps, Lub Oil Purifier, Aux. Circ and cond. Pumps; F.W.-3, S.S. Air Comp. No. 2; Pumped settlers, Fuel Oil suction from Inboard Settler, Changed and cleaned Burner and F.O. Strainer, Fire and Emerg. Drill stand by 1515; 1624 secured from Fire and Emerg. Drill; Abandon ship Drill 1526; 1531 Secured from all Drills, Secured Stand by. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - 41

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

1600-2000 WATCH

Underway 14 nryles mach. as before. at 1900 hrs. reduced speed to 54 R.P.M. B.O.B. C&C F.O. discharge 54B; C&C L.O.S. G.3&G.4. Made rounds, tests & inspections of mach. & mach. space all conditions normal & satisfactory. Made 1/2 hourly checks on all spring bearings, pumped bilges & shaft allkts. Complied with night & standing orders and COMSTS Instr. 4700.7. Major & Aux. cond. 44 B4-6.21; B3 7.24

M.F.P. 2 = 21'-0" - 41 1/2

M.F.P. 2 = 21'-0" - 41 1/2

WATCH ENGR'S SIGNATURE-

H. Kasten

2000-2400 WATCH

Underway 14 nryles mach. as before. at 2000 hrs. reduced speed to 54 R.P.M. B.O.B. C&C F.O. discharge 54B; C&C L.O.S. G.3&G.4. Made rounds, tests & inspections of mach. & mach. space all conditions normal & satisfactory. Made 1/2 hourly checks on all spring bearings, pumped bilges & shaft allkts. Complied with night & standing orders and COMSTS Instr. 4700.7. Major & Aux. cond. 44 B4-6.21; B3 7.24

2400-0400 WATCH

Underway 54 R.P.M. Recorded machinery in service; Pumped Settlers, outboard settler Fuel Oil Suction, Changed, Cleaned burners, F.O. and Lub Oil strainers. Made routine tests and inspections of engine room machinery spaces. Added 1 gal Lub Oil each to 1/2 Feed Pump.

Cond. tested - 41

WATCH ENGR'S SIGNATURE-

Harold J. DuMond

0400-0800 WATCH

Underway 54 R.P.M. Machinery in operation as before. Time check 0412. Reduce speed to 48 R.P.M. C&C F.O. discharge 54B; C&C L.O.S. G.3&G.4. Made rounds, tests & inspections of mach. & mach. space all conditions normal & satisfactory. Made 1/2 hourly checks on all spring bearings, pumped bilges & shaft allkts. Complied with night & standing orders and COMSTS Instr. 4700.7. Major & Aux. cond. 44 B4-6.21; B3 7.24

WATCH ENGR'S SIGNATURE-

H. Kasten

0800-1200 WATCH

Anchored VANG TAU - ENGAGED JACKING GEAR @ 0830 - MACH. AS BEFORE - C&C F.O. B&S - C&C L.O.S. - G.3&G.4. ALL BILGES SAFE LEVEL - MADE ROUNDS TESTS AND INSPECTION OF MACH. AND SPACE - ALL W.T.D. AND HATCH EMERGENCY ESCAPE SECURED - REG. SEA WATCH IN PORT - Complied with Standing and Night Orders - COMSTS Instr. 4700.7

OILER TAITAGUE FWT MCLEOD

WATCH ENGR'S SIGNATURE-

D. J. Duckett

CHIEF ENGINEER

BOILER WATER READINGS

ARRIVAL 13 0012

STB'D PORT

FOM P 4628720 CNTR P - 3145440

HOURS F-78 HOURS W-540

FOM S - 8510250 CNTR S - 3270810

AKL 8.76 AKL 9.23

FWE @ 0817

T-AKL 12.20 T-AKL 13.43

SAL. 6.21 SAL. 6.21

FOM P 462 9380 CNTR P 3148 6910

PHOS. 40 PHOS. 40

FOM S 851 0590 CNTR S 3270 6270

R.ph 11 R.ph 11

SL-FITE-25 SL-FITE 29.5

CHIEF ENGR'S SIGNATURE-

L. L. Clemens

Anchored.

REMARKS

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux; Generators - G-3-4 and aux; Main Circ. M-2, Cond-MC-3, Lub Oil Pumps Air Ejector - A-ME-R, Aux. Circ. and Cond. Pumps S.S. Air Comp. F.W-3 Pump, Jacking gear engaged. Changed burners. Jn Eng Repaired Flange gasket. Master Controller Steam line. Made routine watch tests and inspections of engine

Cond. tested .41

WATCH ENGR'S SIGNATURE-

1600-2000 WATCH

PORT WATCH MACHINERY IN OPERATION AS BEFORE B-4 ON BOTTOM BACK THRU M.E. PUMP. DIESEL OIL PUMPED TO 1000 DEEP BILGES AT SAFE LEVEL. COMPLY WITH COMST 4700.7

SAL. TEST. B-4 = 5.11% B-3 = 6.21%

OILER - BURN - FWT. KLINT

WATCH ENGR'S SIGNATURE-

2000-2400 WATCH

ANCHORAGED VUNG TAU, VIETNAM - MACH. AS BEFORE - CHANGED & CLEANED F.O. BURNERS & STRAINERS SHAFT EMERGENCY HATCH AND ALL W.T.D. SECURED - E.R. & SHAFT ALLEY BILGES AT SAFE LEVEL - MADE ROUTINE TESTS AND INSPECTIONS OF MACH. AND SPACE - REGULAR SEA WATCH IN PORT ROUTINE - COMPLIED WITH STANDING AND NIGHT ORDERS - COMST INSTRUCTION 4700.7 Secured 1st stage to main air ejector.

OILER TAITAGUE FWT MCLEOD

WATCH ENGR'S SIGNATURE-

2400-0400 WATCH

Port watch. Anchored. Recorded Machinery in service: Diesel Fuel Purifier Leaking Fuel in bilged secured sump Pumped bilgas. Cleaned burners. Made routine watch tests and inspections of engine room machinery spaces Added 1 gal each L.O. #1s Feed Pumps

Oiler - Mcchem - FWT - Trapp Cond tested -.41

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

PORT WATCH MACHINERY IN OPERATION AS BEFORE B-3 ON BOTTOM BLOW THRU M.E. PUMP. ADD LUB. OIL TO MAIN ENG. PUMP. CHECK EJECTOR & HATCH COMPLY WITH COMST INSTRUCTION 4700.7

SAL. TEST. B-3 = 4.97% B-4 = 5.10%

OILER - BURN - FWT. KLINT

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

In port watch Machinery as before at 0900, set spring bearing for underway operations, disengaged jacking gear, opened main steam stops, started 1st stage main air ejector. Wheel clearance received from bridge. @ 0952, set clock at 0847, tested engine order telegraph 0900, tested steering motor's at 0900 started in operation. Set special sea detail at 1012. Steady at 1012. Report man & ready at that time. Jn. Eng. on watch at 1000 hrs. Oiler Taitague. FWT. McLeod. 1st stage in space for maneuvering. Carried out Reg. maneuvering & underway steaming watch Routine.

Main & Aux Cond. - .41; B-4 5.8 B-3 5.39.

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

STE'D

PORT

HOURS

HOURS

AKL

AKL

T-AKL

T-AKL

SAL.

SAL.

PHOS.

PHOS.

R.ph

R.ph

SULFITE 22.5 SULFITE 21

Steady at 1012

deft: at 1100

Fom-P 463 1100

Fom-P 463 1350

Fom-S 851 1930

Fom-S 851 2140

Total 1314 3030

Total 1314 3190

ctr. P 3148 7140

ctr. -P 3148 9150

ctr. S 3270 6930

ctr. S 3270 8880

CHIEF ENGR'S SIGNATURE-

Underway

1200-1600 WATCH

Machinery in service: Boilers - B-3-4 and aux. Generator - G-3-4 and aux.; Main Cond. MC-3, Circ. - M-2, Lub Oil Pumps and Air Ejector. ME-R, S.S. Air. 400 Comp.; Lub Oil Purifier; Pumped settlers, suction from in board settler. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - 41

1600-2000 WATCH

WATCH ENGR'S SIGNATURE -

Harold J. DeMond

UNDERWAY ON 12 NOZZLES. MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. D. S. STRAINER. PUT B-4 ON BOTTOM BLOW. THRU MC BLANK. COMPLIED WITH ORD. 4700.7. MADE ROUTINE INSPECTIONS. F.O. D. S. 4700.7

MUF #2 S = 21'-0" - 1476

SAL. TO. B-3-S-30 - 4.47-6.41

MUF #2 P = 23'-0" - 1496

MAIN COND. IN

WATCH ENGR'S SIGNATURE -

H. J. DeMond

2000-2400 WATCH

Underway 18 Nozzles Machinery as before C&C LOS-63-64 C&C F.O. D. S. 6.15 Shifted F.O. Sett. to Outbd. at 2235. Made half-hourly check on all spring bearings. Made rounds, tests & inspect. of Mach & Mach space. Pumped bilges & shaft alley's. Complied with night & standing orders & C&C 4700.7 Instr. 4700.7

Main & Aux Cond. .41, B4-6.63, B3-6.21

Carried out Reg. Underway Steaming Watch Routine

WATCH ENGR'S SIGNATURE -

D. L. Brinkett

2400-0400 WATCH

Underway Machinery in service as before. Pump Settlers. Fuel Oil suction from outboard settler. Changed and cleaned burner; Fuel Oil and Lub Oil Strainer. Made routine watch tests and inspections of engine room machinery spaces.

Cond. tested - 41

0400-0800 WATCH

WATCH ENGR'S SIGNATURE -

Harold J. DeMond

UNDERWAY ON 12 NOZZLES. MACHINERY IN OPERATION AS BEFORE. CHANGED & CLEANED F.O. D. S. STRAINER. PUT B-4 ON BOTTOM BLOW. THRU MC BLANK. COMPLIED WITH ORD. 4700.7. MADE ROUTINE INSPECTIONS. F.O. D. S. 4700.7

SAL. TO. B-4 - 4.50-7.5 - B-3-S-30

MUF #2 S = 21'-0" - 1476

MUF #2 P = 23'-0" - 1496

WATCH ENGR'S SIGNATURE -

H. J. DeMond

0800-1200 WATCH

Underway 18 nozzles machinery as before Blew tubes for boilers 0800-0812 1st & 2nd inspace 0820. C&C LOS-63-64 C&C F.O. D. S. & burners. Made continuous check of all spring bearings. made rounds, tests & inspections of mach & mach space all conditions normal. pumped bilges & shaft alley's. Complied with standing orders & comsts instr. 4700.7 Shifted to settlers at 1133.

Main & Aux Cond. .41 B4 5.39, B-3 6.21

Carried Out Regular Underway Steaming Watch Routine

WATCH ENGR'S SIGNATURE -

D. L. Brinkett

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS	HOURS
AKL	AKL
T-AKL	T-AKL
SAL.	SAL.
PHOS.	PHOS.
R.ph	R.ph

SULFITE 40 SULFITE 25

CHIEF ENGR'S SIGNATURE -

L. D. O'Leary

REMARKS

1200-1600 WATCH

Underway, Machinery in service: Boilers - B-3-4- and aux.; Generator - G-3-4 and aux.; Main. Circ., Cond. and Lub Oil Pumps Air ejector. ME-R. Lub Oil Purifier F.W. Pump. Pumped settlers Fuel Oil suction from in board settler. at 1545 secured Mn. Steam stops and blhd. stops in good Jacking gear. at 1300 slowed to Block 10 Noz, 74 R.P.M.

Cond. tested -.41

WATCH ENGR'S SIGNATURE

Harold J. DeMond

1600-2000 WATCH

Port Watch Machinery in operation as before. Main engine in service. Made routine inspections of engine room machinery spaces. Fuel Oil suction from in board settler. at 1545 secured Mn. Steam stops and blhd. stops in good Jacking gear. at 1300 slowed to Block 10 Noz, 74 R.P.M.

SAL. T-4 = 4.50 % P-3 = 5.39 % MAIN COND. = .41 %

JR. ENGR. - CROW - OILER - MORR - FWT ALINT.

WATCH ENGR'S SIGNATURE

H. J. DeMond

2000-2400 WATCH

Port Watch machinery as before water tight doors closed for war zone conditions. Made rounds, tests, & inspect. of mach. & space. all condition Normal & sat. pumped bilges & shaft alley's to safe level. Slit to high sea suction at 2020 hrs. #1 Evap distilling to #3 & at 2300.

Oiler - Taitague; FWT - Malcod Jr. Eng - Frink

Carried out Regular Aux. Steaming Watch Routine.

WATCH ENGR'S SIGNATURE

D. L. Fickert

2400-0400 WATCH

Port. watch. Recorded machinery in service; Jr. Eng Repaired Reach rod to bal. Valve stem - Throttle Valve. Made routine watch tests and inspections of engine room machinery spaces. Fuel Oil suction from in board settler. Nipple - cooling water. line No. 6 Sp. bearing needs replacing.

Cond. tested -.41

Jr. Eng. Wetherald, Oiler - Mechem, FWT. Trapp

WATCH ENGR'S SIGNATURE

Harold J. DeMond

0400-0800 WATCH

Port Watch Machinery in operation as before - B-3 ON BOTTOM SLOW - ADD COMPRESSOR TO P-3 CHECK SHAFT ALLEY & COOL WATER (NOTED) ENGINE ROOM B-3: B-4 TO 2/3 CHANGING OVER TO 3 + 5 FOR BURNER.

SAL. T-4 = 4.50 % P-3 = 5.39 % MAIN COND. = .41 %

JR. ENGR. - CROW - OILER - MORR - FWT ALINT.

WATCH ENGR'S SIGNATURE

H. J. DeMond

0800-1200 WATCH

Port Watch mach. as before ship conducted manoeuvre board drill at 0800. C & C LOS. 3-3 B-4; C & C F.O.D.S. & Burners. Tested Fire & smoke detecting system 0900 - 0920. made rounds, tests, & inspections of mach. & mach space. all Conditions Normal & satisfactory. Main & Aux. Cond. .41 B-4 - 5.39 B-3 - 5.39 bilges & shaft alley's at safe level.

Carried Out Regular Aux. Steaming Watch Routine

Oiler - Taitague FWT - Malcod Jr. Eng. Frink

WATCH ENGR'S SIGNATURE

D. L. Fickert

CHIEF ENGINEER

BOILER WATER READINGS

STE'D	PORT
HOURS F-132	HOURS F-132
AKL 5.34	AKL 5.34
T-AKL 5.34	T-AKL 5.34
SAL. 5.39	SAL. 4.97
PHOS. 20	PHOS. 40
R.ph 11	R.ph 11

SULFITE IS SULFITE 42

Arrival - F.O.M. - P-4640710-S-8521340

F.W.E. F.O.M. - P-4641110-S-8521520

Arrival Cntr - P-3163750470

Cntr - P-31637950 P-31637950

S-32860740

FWE-Cntr - P-31640010

S-32862560

CHIEF ENGR'S SIGNATURE

USNS		VOYAGE NO.		FROM		TO		TYPE OF VESSEL		DATE	
Gen John Pope (Tap-110)				Da Nang						7-31-67	

		WATCH								WATCH					
		1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200			1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
RUNNING TIME															
DETENTION TIME															
REVOLUTION COUNTER (END OF WATCH)															
TOTAL REVOLUTIONS (FOR WATCH)															
AVERAGE RPM															
F.O. METER (END OF WATCH)		1316	1316	1316											
F.O. CONSUMED		370	370	370											
MACHINERY PARTICULARS	THROTTLE							MACHINERY PARTICULARS (CONT'D)	AFT. H. P. ROTOR BEARING						
	H.P. AHEAD								FORWARD L. P. ROTOR BEARING						
	L.P. AHEAD								AFT. L.P. ROTOR BEARING						
	VACUUM	22.6	22.5	22.5					HOTTEST GEAR BEARING FORWARD						
	L.O. TO TURBINES								HOTTEST GEAR BEARING AFT						
	AUX. STEAM	145	145	150					AUX. COND. CONDENSATE	118	118	120			
	BACK PRESSURE	9	1	9					1ST STAGE FEED WATER HEATER	100	105	105			
	GLAND STEAM	1.6	1.7	1.5					D. C. FEED WATER HEATER	238	235	238			
	H.P. BLEEDER								3RD STAGE FEED WATER HEATER						
	L.P. BLEEDER														
PRESSURES	STEAM AT THROTTLE							PRESSURES	F.O. TO BURNERS	160	155	150			
	L.P. EXHAUST	126	126	126					F.O. BACK PRESSURE						
	CONDENSATE	96	96	97					AIR TO FURNACE	0.8	0.8	0.8			
	CIRC. WATER IN	86	86	88					UPTAKE						
	CIRC. WATER OUT	86	85	85					MAIN STEAM	440	440	440			
	L.O. TO COOLERS	114		104					SUPER HEAT						
	L.O. FROM COOLERS	110		102					F.O. TO BURNERS	186	180	180			
	TEMPERATURE THRUST BEARING	115							F.O. TEMP. IN SETTLING TANKS	114	111	111			
	FORWARD H.P. ROTOR BEARING								PORT BOILER UPTAKE	255	260	260			
									STBD. BOILER UPTAKE	320	320	325			
TEMPERATURES								TEMPERATURES	ENGINE ROOM TEMPERATURE	99	97	97			
									FIRE ROOM TEMPERATURE		77	77			
									NOZZLES IN USE						
									NO. OF BURNERS IN USE	2	2	2			
									BURNER TIP SIZE	50	50	50			
									CO ₂ % PORT BOILER						
									CO ₂ % STBD. BOILER						
									OIL LEVEL MAIN SUMP	1'5"	1'5"	1'5"			

		GENERATORS											FUEL - WATER AND LUBE OIL											
		GENERATOR NUMBER	R.P.M.	STEAM PRESSURE	STEAM TEMP.	L.O. PRESSURE	L.O. TO COOLER	L.O. FROM COOLER	TEMP. OF HOTTEST BEARING	L.O. GOVERNOR PRESSURE	AMPS POSITIVE	AMPS NEGATIVE	VOLTS	FUEL OIL				DOMESTIC WATER				LUBE OIL		
1200 TO 1600	3	1200	440			9	140	120	65	65	1050	1050	240	METER AT NOON		ON HAND AT START OF DAY		ON HAND		ON HAND		ON HAND		
	4	1200	440			9.5	145	130	40	40	1000	1000	240	METER PREVIOUS NOON	13164710	EVAPORATED OR RECEIVED		CONSUMED		CONSUMED		CONSUMED		
1600 TO 2000	3	1200	440			9	140	124	27.5	65	960	960	240	CONSUMED BY METER		ON HAND		ON HAND		ON HAND		ON HAND		
	4	1200	440			9.5	147	132	27.5	40	950	950	240	ON HAND AT START OF DAY		CONSUMED		CONSUMED		CONSUMED		CONSUMED		
2000 TO 2400	3	1200	440			9	140	124	27.5	65	960	960	240	RECEIVED DURING DAY		ON HAND AT START OF DAY		ON HAND		ON HAND		ON HAND		
	4	1200	440			10	147	132	27.5	40	950	950	240	EXPENDED DURING DAY		ON HAND		ON HAND		ON HAND		ON HAND		
2400 TO 0400														REMAINING ON BOARD		ON HAND		ON HAND		ON HAND		ON HAND		
														ON HAND AT START OF DAY		ON HAND		ON HAND		ON HAND		ON HAND		
0400 TO 0800														EVAPORATED OR RECEIVED		ON HAND		ON HAND		ON HAND		ON HAND		
														CONSUMED		ON HAND		ON HAND		ON HAND		ON HAND		
0800 TO 1200														LOW PRESS. EVAPORATORS (No. of hrs. operated) (Fresh water made gals.)		ON HAND		ON HAND		ON HAND		ON HAND		
														L.O. CENTRIFUGE - HOURS OPERATED		ON HAND		ON HAND		ON HAND		ON HAND		

L.O. CENTRIFUGE - HOURS OPERATED					
1200 TO 1600	1600 TO 2000	2000 TO 2400	2400 TO 0400	0400 TO 0800	0800 TO 1200
4	4	4			

SUMMARY			
RUNNING TIME		PERCENT OF SLIP	
DETENTION TIME		BBL FUEL/MI	
TOTAL REVOLUTIONS		WIND DIRECTION	
AVERAGE R.P.M.		STATE OF SEA	
TOTAL MILES BY ENGINE		STATE OF WEATHER	
TOTAL MILES BY OBSERVATION			

In Port.

REMARKS

1200-1600 WATCH

Machinery in service: Boilers B-3-4 and aux.; Generators-G-3-4 and aux.; Main Circ. M-2, Cond. MC-3, Lub Oil Pumps and Air ejector ME-R; F.W. Pump W-3, Lub. Oil Purifier. at 1330 secured F.W. at 1400 cut in F.W. - secured for repairs on line. Pumped settlers, F.O. suction from outboard settlor. Made routine watch tests and inspections of engine room machinery spaces

Cond tested--41

Jr. Eng - Wetherald, Oiler - Mechem, F.W.T. Trapp

WATCH ENGR'S SIGNATURE-

Harold J. DeMond

1600-2000 WATCH

PORT WATCH. MACHINERY IN OPERATION AS BEFORE. START DENSE LL. RE-STARTED TO RE-START DENSE LL. (34RS) KEEN. 1400 1/2 AIRP. 2. WATCH TESTS AND INSPECTIONS. MADE. 1400 1/2 AIRP. 2. WATCH TESTS AND INSPECTIONS. MADE. 1400 1/2 AIRP. 2. WATCH TESTS AND INSPECTIONS. MADE.

MEF #2 3. 22-01

SHA. TIT B-3-0.34 1/2 - P-4 = 4.17%

MEF #2 1. 22-01

Jr. Eng - G. H. - Oiler - B. - F.W.T. - M. L. T.

WATCH ENGR'S SIGNATURE-

TH. M. L. T.

2000-2400 WATCH

In Port watch. Machinery as before. Made rounds Tests & inspections. Pumped bilges & shaft alley's to safe level.

carried out Reg. Aux. steaming watch Routine.

Oil - T. T. T. F.W.T. - M. L. T. Jr. Eng. Frank Elect. C. Brooks

WATCH ENGR'S SIGNATURE-

D. J. Guckett

2400-0400 WATCH

WATCH ENGR'S SIGNATURE-

0400-0800 WATCH

WATCH ENGR'S SIGNATURE-

0800-1200 WATCH

WATCH ENGR'S SIGNATURE-

CHIEF ENGINEER

BOILER WATER READINGS

STB'D	PORT
HOURS	HOURS
AKL	AKL
T-AKL	T-AKL
SAL.	SAL.
PHOS.	PHOS.
R-ph	R-ph

CHIEF ENGR'S SIGNATURE-